

Stan Functions Reference

Version 2.36

Stan Development Team



Table of Contents

Overview 1

I Built-in Functions

2

1. **Void Functions** 4
 - 1.1 Print statement 4
 - 1.2 Reject statement 4
 - 1.3 Fatal error statement 5
2. **Integer-Valued Basic Functions** 6
 - 2.1 Integer-valued arithmetic operators 6
 - 2.2 Absolute functions 8
 - 2.3 Bound functions 9
 - 2.4 Size functions 9
 - 2.5 Casting functions 10
3. **Real-Valued Basic Functions** 11
 - 3.1 Vectorization of real-valued functions 11
 - 3.2 Mathematical constants 16
 - 3.3 Special values 17
 - 3.4 Log probability function 17
 - 3.5 Logical functions 18
 - 3.6 Real-valued arithmetic operators 22
 - 3.7 Step-like functions 24
 - 3.8 Power and logarithm functions 26
 - 3.9 Trigonometric functions 28
 - 3.10 Hyperbolic trigonometric functions 29
 - 3.11 Link functions 29
 - 3.12 Probability-related functions 30
 - 3.13 Combinatorial functions 31

- 3.14 Composed functions 38
- 3.15 Special functions 41
- 4. Complex-Valued Basic Functions 42**
 - 4.1 Complex assignment and promotion 42
 - 4.2 Complex constructors and accessors 42
 - 4.3 Complex arithmetic operators 43
 - 4.4 Complex comparison operators 45
 - 4.5 Complex (compound) assignment operators 46
 - 4.6 Complex special functions 46
 - 4.7 Complex exponential and power functions 48
 - 4.8 Complex trigonometric functions 49
 - 4.9 Complex hyperbolic trigonometric functions 50
- 5. Array Operations 52**
 - 5.1 Reductions 52
 - 5.2 Array size and dimension function 56
 - 5.3 Array broadcasting 57
 - 5.4 Array concatenation 59
 - 5.5 Sorting functions 59
 - 5.6 Reversing functions 61
- 6. Matrix Operations 62**
 - 6.1 Integer-valued matrix size functions 62
 - 6.2 Matrix arithmetic operators 63
 - 6.3 Transposition operator 67
 - 6.4 Elementwise functions 67
 - 6.5 Dot products and specialized products 70
 - 6.6 Reductions 73
 - 6.7 Broadcast functions 77
 - 6.8 Diagonal matrix functions 78
 - 6.9 Container construction functions 79
 - 6.10 Slicing and blocking functions 81
 - 6.11 Matrix concatenation 83
 - 6.12 Special matrix functions 85

- 6.13 Gaussian Process Covariance Functions 86
- 6.14 Linear algebra functions and solvers 93
- 6.15 Sort functions 101
- 6.16 Reverse functions 102
- 7. Complex Matrix Operations 103**
 - 7.1 Complex promotion 103
 - 7.2 Integer-valued complex matrix size functions 104
 - 7.3 Complex matrix arithmetic operators 105
 - 7.4 Complex Transposition Operator 109
 - 7.5 Complex elementwise functions 110
 - 7.6 Dot products and specialized products for complex matrices 112
 - 7.7 Complex reductions 114
 - 7.8 Vectorized accessor functions 115
 - 7.9 Complex broadcast functions 116
 - 7.10 Diagonal complex matrix functions 117
 - 7.11 Slicing and blocking functions for complex matrices 117
 - 7.12 Complex matrix concatenation 119
 - 7.13 Complex special matrix functions 121
 - 7.14 Complex linear algebra functions 122
 - 7.15 Reverse functions for complex matrices 126
- 8. Sparse Matrix Operations 127**
 - 8.1 Compressed row storage 127
 - 8.2 Conversion functions 128
 - 8.3 Sparse matrix arithmetic 129
- 9. Mixed Operations 130**
- 10. Compound Arithmetic and Assignment 138**
 - 10.1 Compound addition and assignment 138
 - 10.2 Compound subtraction and assignment 138
 - 10.3 Compound multiplication and assignment 138
 - 10.4 Compound division and assignment 139

10.5	Compound elementwise multiplication and assignment	139
10.6	Compound elementwise division and assignment	139
11.	Higher-Order Functions	140
11.1	Algebraic equation solvers	140
11.2	Ordinary differential equation (ODE) solvers	143
11.3	Differential-Algebraic equation (DAE) solver	148
11.4	1D integrator	150
11.5	Reduce-sum function	153
11.6	Map-rect function	155
12.	Deprecated Functions	156
12.1	Integer division with operator/	156
12.2	integrate_ode_rk45, integrate_ode_adams, integrate_ode_bdf ODE Integrators	156
12.3	algebra_solver, algebra_solver_newton algebraic solvers	159
13.	Removed Functions	162
13.1	multiply_log and binomial_coefficient_log functions	162
13.2	get_lp() function	162
13.3	fabs function	162
13.4	Exponentiated quadratic covariance functions	162
13.5	Real arguments to logical operators operator&&, operator , and operator!	163
14.	Conventions for Probability Functions	164
14.1	Suffix marks type of function	164
14.2	Argument order and the vertical bar	164
14.3	Sampling notation	164
14.4	Finite inputs	165
14.5	Boundary conditions	165
14.6	Pseudorandom number generators	165
14.7	Cumulative distribution functions	165
14.8	Vectorization	166

II	Discrete Distributions	170
15.	Binary Distributions	172
15.1	Bernoulli distribution	172
15.2	Bernoulli distribution, logit parameterization	173
15.3	Bernoulli-logit generalized linear model (Logistic Regression)	174
16.	Bounded Discrete Distributions	177
16.1	Binomial distribution	177
16.2	Binomial distribution, logit parameterization	178
16.3	Binomial-logit generalized linear model (Logistic Regression)	179
16.4	Beta-binomial distribution	182
16.5	Hypergeometric distribution	183
16.6	Categorical distribution	184
16.7	Categorical logit generalized linear model (softmax regression)	186
16.8	Discrete range distribution	188
16.9	Ordered logistic distribution	189
16.10	Ordered logistic generalized linear model (ordinal regression)	190
16.11	Ordered probit distribution	192
17.	Unbounded Discrete Distributions	194
17.1	Negative binomial distribution	194
17.2	Negative binomial distribution (alternative parameterization)	195
17.3	Negative binomial distribution (log alternative parameterization)	197
17.4	Negative-binomial-2-log generalized linear model (negative binomial regression)	198
17.5	Poisson distribution	200
17.6	Poisson distribution, log parameterization	201
17.7	Poisson-log generalized linear model (Poisson regression)	202
17.8	Beta negative binomial distribution	204

18. Multivariate Discrete Distributions	206
18.1 Multinomial distribution	206
18.2 Multinomial distribution, logit parameterization	207
18.3 Dirichlet-multinomial distribution	208
III Continuous Distributions	210
19. Unbounded Continuous Distributions	212
19.1 Normal distribution	212
19.2 Normal-id generalized linear model (linear regression)	215
19.3 Exponentially modified normal distribution	218
19.4 Skew normal distribution	220
19.5 Student-t distribution	221
19.6 Cauchy distribution	222
19.7 Double exponential (Laplace) distribution	224
19.8 Logistic distribution	225
19.9 Gumbel distribution	227
19.10 Skew double exponential distribution	228
20. Positive Continuous Distributions	230
20.1 Lognormal distribution	230
20.2 Chi-square distribution	231
20.3 Inverse chi-square distribution	232
20.4 Scaled inverse chi-square distribution	233
20.5 Exponential distribution	234
20.6 Gamma distribution	235
20.7 Inverse gamma Distribution	237
20.8 Weibull distribution	238
20.9 Frechet distribution	239
20.10 Rayleigh distribution	240
20.11 Log-logistic distribution	241
21. Positive Lower-Bounded Distributions	243
21.1 Pareto distribution	243

21.2	Pareto type 2 distribution	244
21.3	Wiener First Passage Time Distribution	245
22.	Continuous Distributions on $[0, 1]$	249
22.1	Beta distribution	249
22.2	Beta proportion distribution	250
23.	Circular Distributions	252
23.1	Von Mises distribution	252
24.	Bounded Continuous Distributions	255
24.1	Uniform distribution	255
25.	Distributions over Unbounded Vectors	257
25.1	Multivariate normal distribution	257
25.2	Multivariate normal distribution, precision parameterization	259
25.3	Multivariate normal distribution, Cholesky parameterization	261
25.4	Multivariate Gaussian process distribution	263
25.5	Multivariate Gaussian process distribution, Cholesky parameterization	264
25.6	Multivariate Student-t distribution	265
25.7	Multivariate Student-t distribution, Cholesky parameterization	267
25.8	Gaussian dynamic linear models	269
26.	Simplex Distributions	271
26.1	Dirichlet distribution	271
27.	Correlation Matrix Distributions	274
27.1	LKJ correlation distribution	274
27.2	Cholesky LKJ correlation distribution	275
28.	Covariance Matrix Distributions	277
28.1	Wishart distribution	277
28.2	Wishart distribution, Cholesky Parameterization	278

- 28.3 Inverse Wishart distribution 279
- 28.4 Inverse Wishart distribution, Cholesky Parameterization 280

IV Additional Distributions 282

- 29. Hidden Markov Models 284**
 - 29.1 Stan functions 284

V Appendix 286

- 30. Mathematical Functions 288**
 - 30.1 Beta 288
 - 30.2 Incomplete beta 288
 - 30.3 Gamma 288
 - 30.4 Digamma 289

References 290

Overview

This is the reference for the functions defined in the [Stan math library](#) and available in the [Stan](#) programming language.

For more information the Stan language and inference engines and how to use Stan for Bayesian inference, see

- the **Stan User's Guide**. The Stan user's guide provides example models and programming techniques for coding statistical models in Stan. It also serves as an example-driven introduction to Bayesian modeling and inference:
- the **Stan Reference Manual**. Stan's modeling language is shared across all of its interfaces. The Stan Language Reference Manual provides a concise definition of the language syntax for all elements in the language together with an overview of the inference algorithms and posterior inference tools.

Copyright and trademark

- Copyright 2011–2024, Stan Development Team and their assignees.
- The Stan name and logo are registered trademarks of NumFOCUS.

Licensing

- *Text content*: [CC-BY ND 4.0 license](#)
- *Computer code*: [BSD 3-clause license](#)
- *Logo*: [Stan logo usage guidelines](#)

Part I

Built-in Functions

1. Void Functions

Stan supports a few special statements for printing or for signaling an issue with the program.

Although `print`, `reject`, and `fatal_error` appear to have the syntax of functions, they are actually special kinds of statements with slightly different form and behavior than other functions. First, they are the constructs that allow a variable number of arguments. Second, they are the only constructs to accept string literals (e.g., "hello world") as arguments. Third, they have no effect on the log density function and operate solely through side effects.

The special keyword `void` is used for their return type because they behave like variadic functions with `void` return type, even though they are special kinds of statements built in to the language.

1.1. Print statement

Printing has no effect on the model's log probability function. Its sole purpose is the side effect (i.e., an effect not represented in a return value) of arguments being printed to whatever the standard output stream is connected to (e.g., the terminal in command-line Stan or the R console in RStan).

```
void print(T1 x1, ..., TN xN)
```

Print the values denoted by the arguments `x1` through `xN` on the output message stream. There are no spaces between items in the print, but a line feed (LF; Unicode U+000A; C++ literal `'\n'`) is inserted at the end of the printed line. The types `T1` through `TN` can be any of Stan's built-in numerical types or double quoted strings of characters (bytes).

Available since 2.1

1.2. Reject statement

The `reject` statement has the same syntax as the `print` statement, accepting an arbitrary number of arguments of any type (including string literals). The effect of executing a `reject` statement is to throw an exception internally that terminates the current iteration with a rejection (the behavior of which will depend on the algorithmic context in which it occurs).

```
void reject(T1 x1, ..., TN xN)
```

Reject the current iteration and print the values denoted by the arguments x_1 through x_N on the output message stream. There are no spaces between items in the print, but a line feed (LF; Unicode U+000A; C++ literal `'\n'`) is inserted at the end of the printed line. The types T_1 through T_N can be any of Stan's built-in numerical types or double quoted strings of characters (bytes).

Available since 2.18

1.3. Fatal error statement

The fatal error statement has the same syntax as the print and reject statements, accepting an arbitrary number of arguments of any type (including string literals). The effect of executing a `fatal_error` statement is to throw an exception internally that terminates the algorithm completely. It can be viewed as an unrecoverable version of `reject`, and as such should be used only when exiting the algorithm is the only option.

```
void fatal_error(T1 x1, ..., TN xN)
```

Print the values denoted by the arguments x_1 through x_N on the output message stream and then exit the currently running algorithm. There are no spaces between items in the print, but a line feed (LF; Unicode U+000A; C++ literal `'\n'`) is inserted at the end of the printed line. The types T_1 through T_N can be any of Stan's built-in numerical types or double quoted strings of characters (bytes).

Available since 2.35

2. Integer-Valued Basic Functions

This chapter describes Stan's built-in function that take various types of arguments and return integer values.

2.1. Integer-valued arithmetic operators

Stan's arithmetic is based on standard double-precision C++ integer and floating-point arithmetic. If the arguments to an arithmetic operator are both integers, as in $2 + 2$, integer arithmetic is used. If one argument is an integer and the other a floating-point value, as in $2.0 + 2$ and $2 + 2.0$, then the integer is promoted to a floating point value and floating-point arithmetic is used.

Integer arithmetic behaves slightly differently than floating point arithmetic. The first difference is how overflow is treated. If the sum or product of two integers overflows the maximum integer representable, the result is an undesirable wraparound behavior at the bit level. If the integers were first promoted to real numbers, they would not overflow a floating-point representation. There are no extra checks in Stan to flag overflows, so it is up to the user to make sure it does not occur.

Secondly, because the set of integers is not closed under division and there is no special infinite value for integers, integer division implicitly rounds the result. If both arguments are positive, the result is rounded down. For example, $1 / 2$ evaluates to 0 and $5 / 3$ evaluates to 1.

If one of the integer arguments to division is negative, the latest C++ specification (C++11), requires rounding toward zero. This would have $1 / 2$ and $-1 / 2$ evaluate to 0, $-7 / 2$ evaluate to -3, and $7 / 2$ evaluate to 3. Before the C++11 specification, the behavior was platform dependent, allowing rounding up or down. All compilers recent enough to be able to deal with Stan's templating should follow the C++11 specification, but it may be worth testing if you are not sure and plan to use integer division with negative values.

Unlike floating point division, where $1.0 / 0.0$ produces the special positive infinite value, integer division by zero, as in $1 / 0$, has undefined behavior in the C++ standard. For example, the clang++ compiler on Mac OS X returns 3764, whereas the g++ compiler throws an exception and aborts the program with a warning. As with overflow, it is up to the user to make sure integer divide-by-zero does not occur.

Binary infix operators

Operators are described using the C++ syntax. For instance, the binary operator of addition, written $X + Y$, would have the Stan signature `int operator+(int, int)` indicating it takes two real arguments and returns a real value. As noted previously, the value of integer division is platform-dependent when rounding is platform dependent before C++11; the descriptions below provide the C++11 definition.

`int operator+(int x, int y)`

The sum of the addends x and y

$$\text{operator+}(x, y) = (x + y)$$

Available since 2.0

`int operator-(int x, int y)`

The difference between the minuend x and subtrahend y

$$\text{operator-}(x, y) = (x - y)$$

Available since 2.0

`int operator*(int x, int y)`

The product of the factors x and y

$$\text{operator*}(x, y) = (x \times y)$$

Available since 2.0

`int operator/(int x, int y)`

The integer quotient of the dividend x and divisor y

$$\text{operator/}(x, y) = \begin{cases} \lfloor x/y \rfloor & \text{if } x/y \geq 0 \\ -\lfloor \text{floor}(-x/y) \rfloor & \text{if } x/y < 0. \end{cases}$$

deprecated; - use `operator%/%` instead.

Available since 2.0, deprecated in 2.24

`int operator%/%(int x, int y)`

The integer quotient of the dividend x and divisor y

$$\text{operator\%/\%}(x, y) = \begin{cases} \lfloor x/y \rfloor & \text{if } x/y \geq 0 \\ -\lfloor \text{floor}(-x/y) \rfloor & \text{if } x/y < 0. \end{cases}$$

Available since 2.24

int **operator%**(int x, int y)

x modulo y, which is the positive remainder after dividing x by y. If both x and y are non-negative, so is the result; otherwise, the sign of the result is platform dependent.

$$\text{operator}\%(x, y) = x \bmod y = x - y * \lfloor x/y \rfloor$$

Available since 2.13

Unary prefix operators

int **operator-**(int x)

The negation of the subtrahend x

$$\text{operator-}(x) = -x$$

Available since 2.0

T **operator-**(T x)

Vectorized version of operator-. If T x is a (possibly nested) array of integers, -x is the same shape array where each individual integer is negated.

Available since 2.31

int **operator+**(int x)

This is a no-op.

$$\text{operator+}(x) = x$$

Available since 2.0

2.2. Absolute functions

T **abs**(T x)

The absolute value of x.

This function works elementwise over containers such as vectors. Given a type T which is int, or an array of ints, abs returns the same type where each element has had its absolute value taken.

Available since 2.0, vectorized in 2.30

int **int_step**(int x)

int **int_step**(real x)

Return the step function of x as an integer,

$$\text{int_step}(x) = \begin{cases} 1 & \text{if } x > 0 \\ 0 & \text{if } x \leq 0 \text{ or } x \text{ is NaN} \end{cases}$$

Warning: `int_step(0)` and `int_step(NaN)` return 0 whereas `step(0)` and `step(NaN)` return 1.

See the warning in section [step functions](#) about the dangers of step functions applied to anything other than data.

Available since 2.0

2.3. Bound functions

int **min**(int x, int y)

Return the minimum of x and y.

$$\min(x, y) = \begin{cases} x & \text{if } x < y \\ y & \text{otherwise} \end{cases}$$

Available since 2.0

int **max**(int x, int y)

Return the maximum of x and y.

$$\max(x, y) = \begin{cases} x & \text{if } x > y \\ y & \text{otherwise} \end{cases}$$

Available since 2.0

2.4. Size functions

int **size**(int x)

int **size**(real x)

Return the size of x which for scalar-valued x is 1

Available since 2.26

2.5. Casting functions

It is possible to cast real numbers to integers as long as the real value is data. See [data only qualifiers](#) in the Stan Reference Manual.

```
int to_int(data real x)
```

Return the value x truncated to an integer. This will throw an error if the value of x is too big to represent as a 32-bit signed integer.

This is similar to `trunc` (see [Rounding functions](#)) but the return type is of type `int`. For example, `to_int(3.9)` is 3, and `to_int(-3.9)` is -3.

Available since 2.31

```
I to_int(data T x)
```

The vectorized version of `to_int`. This function accepts a (possibly nested) array of reals and returns an array of the same shape where each element has been truncated to an integer.

Available since 2.31

3. Real-Valued Basic Functions

This chapter describes built-in functions that take zero or more real or integer arguments and return real values.

3.1. Vectorization of real-valued functions

Although listed in this chapter, many of Stan's built-in functions are vectorized so that they may be applied to any argument type. The vectorized form of these functions is not any faster than writing an explicit loop that iterates over the elements applying the function—it's just easier to read and write and less error prone.

Unary function vectorization

Many of Stan's unary functions can be applied to any argument type. For example, the exponential function, `exp`, can be applied to real arguments or arrays of real arguments. Other than for integer arguments, the result type is the same as the argument type, including dimensionality and size. Integer arguments are first promoted to real values, but the result will still have the same dimensionality and size as the argument.

Real and real array arguments

When applied to a simple real value, the result is a real value. When applied to arrays, vectorized functions like `exp()` are defined elementwise. For example,

```
// declare some variables for arguments
real x0;
array[5] real x1;
array[4, 7] real x2;
// ...
// declare some variables for results
real y0;
array[5] real y1;
array[4, 7] real y2;
// ...
// calculate and assign results
y0 = exp(x0);
y1 = exp(x1);
y2 = exp(x2);
```

When `exp` is applied to an array, it applies elementwise. For example, the statement above,

```
y2 = exp(x2);
```

produces the same result for `y2` as the explicit loop

```
for (i in 1:4) {
  for (j in 1:7) {
    y2[i, j] = exp(x2[i, j]);
  }
}
```

Vector and matrix arguments

Vectorized functions also apply elementwise to vectors and matrices. For example,

```
vector[5] xv;
row_vector[7] xrv;
matrix[10, 20] xm;

vector[5] yv;
row_vector[7] yrv;
matrix[10, 20] ym;

yv = exp(xv);
yrv = exp(xrv);
ym = exp(xm);
```

Arrays of vectors and matrices work the same way. For example,

```
array[12] matrix[17, 93] u;

array[12] matrix[17, 93] z;

z = exp(u);
```

After this has been executed, $z[i, j, k]$ will be equal to $\exp(u[i, j, k])$.

Integer and integer array arguments

Integer arguments are promoted to real values in vectorized unary functions. Thus if `n` is of type `int`, `exp(n)` is of type `real`. Arrays work the same way, so that if `n2` is a one dimensional array of integers, then `exp(n2)` will be a one-dimensional array of reals with the same number of elements as `n2`. For example,

```
array[23] int n1;
array[23] real z1;
z1 = exp(n1);
```

It would be illegal to try to assign `exp(n1)` to an array of integers; the return type is a real array.

Binary function vectorization

Like the unary functions, many of Stan's binary functions have been vectorized, and can be applied elementwise to combinations of both scalars or container types.

Scalar and scalar array arguments

When applied to two scalar values, the result is a scalar value. When applied to two arrays, or combination of a scalar value and an array, vectorized functions like `pow()` are defined elementwise. For example,

```
// declare some variables for arguments
real x00;
real x01;
array[5] real x10;
array[5] real x11;
array[4, 7] real x20;
array[4, 7] real x21;
// ...
// declare some variables for results
real y0;
array[5] real y1;
array[4, 7] real y2;
// ...
// calculate and assign results
y0 = pow(x00, x01);
y1 = pow(x10, x11);
y2 = pow(x20, x21);
```

When `pow` is applied to two arrays, it applies elementwise. For example, the statement above,

```
y2 = pow(x20, x21);
```

produces the same result for `y2` as the explicit loop

```

for (i in 1:4) {
  for (j in 1:7) {
    y2[i, j] = pow(x20[i, j], x21[i, j]);
  }
}

```

Alternatively, if a combination of an array and a scalar are provided, the scalar value is broadcast to be applied to each value of the array. For example, the following statement:

```
y2 = pow(x20, x00);
```

produces the same result for `y2` as the explicit loop:

```

for (i in 1:4) {
  for (j in 1:7) {
    y2[i, j] = pow(x20[i, j], x00);
  }
}

```

Vector and matrix arguments

Vectorized binary functions also apply elementwise to vectors and matrices, and to combinations of these with scalar values. For example,

```

real x00;
vector[5] xv00;
vector[5] xv01;
row_vector[7] xrv;
matrix[10, 20] xm;

```

```

vector[5] yv;
row_vector[7] yrv;
matrix[10, 20] ym;

```

```

yv = pow(xv00, xv01);
yrv = pow(xrv, x00);
ym = pow(x00, xm);

```

Arrays of vectors and matrices work the same way. For example,

```

array[12] matrix[17, 93] u;

```

```
array[12] matrix[17, 93] z;

z = pow(u, x00);
```

After this has been executed, $z[i, j, k]$ will be equal to $\text{pow}(u[i, j, k], x00)$.

Input & return types

Vectorised binary functions require that both inputs, unless one is a real, be containers of the same type and size. For example, the following statements are legal:

```
vector[5] xv;
row_vector[7] xrv;
matrix[10, 20] xm;

vector[5] yv = pow(xv, xv)
row_vector[7] yrv = pow(xrv, xrv)
matrix[10, 20] = pow(xm, xm)
```

But the following statements are not:

```
vector[5] xv;
vector[7] xv2;
row_vector[5] xrv;

// Cannot mix different types
vector[5] yv = pow(xv, xrv)

// Cannot mix different sizes of the same type
vector[5] yv = pow(xv, xv2)
```

While the vectorized binary functions generally require the same input types, the only exception to this is for binary functions that require one input to be an integer and the other to be a real (e.g., `bessel_first_kind`). For these functions, one argument can be a container of any type while the other can be an integer array, as long as the dimensions of both are the same. For example, the following statements are legal:

```
vector[5] xv;
matrix[5, 5] xm;
array[5] int xi;
array[5, 5] int xii;
```



```
vector[5] yv = bessel_first_kind(xi, xv);
matrix[5, 5] ym = bessel_first_kind(xii, xm);
```

Whereas these are not:

```
vector[5] xv;
matrix[5, 5] xm;
array[7] int xi;

// Dimensions of containers do not match
vector[5] yv = bessel_first_kind(xi, xv);

// Function requires first argument be an integer type
matrix[5, 5] ym = bessel_first_kind(xm, xm);
```

3.2. Mathematical constants

Constants are represented as functions with no arguments and must be called as such. For instance, the mathematical constant π must be written in a Stan program as `pi()`.

real **pi**()

π , the ratio of a circle's circumference to its diameter

Available since 2.0

real **e**()

e , the base of the natural logarithm

Available since 2.0

real **sqrt2**()

The square root of 2

Available since 2.0

real **log2**()

The natural logarithm of 2

Available since 2.0

real **log10**()

The natural logarithm of 10

Available since 2.0

3.3. Special values

real **not_a_number**()

Not-a-number, a special non-finite real value returned to signal an error

Available since 2.0

real **positive_infinity**()

Positive infinity, a special non-finite real value larger than all finite numbers

Available since 2.0

real **negative_infinity**()

Negative infinity, a special non-finite real value smaller than all finite numbers

Available since 2.0

real **machine_precision**()

The smallest number x such that $(x + 1) \neq 1$ in floating-point arithmetic on the current hardware platform

Available since 2.0

3.4. Log probability function

The basic purpose of a Stan program is to compute a log probability function and its derivatives. The log probability function in a Stan model outputs the log density on the unconstrained scale. A log probability accumulator starts at zero and is then incremented in various ways by a Stan program. The variables are first transformed from unconstrained to constrained, and the log Jacobian determinant added to the log probability accumulator. Then the model block is executed on the constrained parameters, with each sampling statement (\sim) and log probability increment statement (`increment_log_prob`) adding to the accumulator. At the end of the model block execution, the value of the log probability accumulator is the log probability value returned by the Stan program.

Stan provides a special built-in function `target()` that takes no arguments and returns the current value of the log probability accumulator. This function is primarily useful for debugging purposes, where for instance, it may be used with a print statement to display the log probability accumulator at various stages of execution to see where it becomes ill defined.

real **target**()

Return the current value of the log probability accumulator.

Available since 2.10

target acts like a function ending in `_lp`, meaning that it may only be used in the model block.

3.5. Logical functions

Like C++, BUGS, and R, Stan uses 0 to encode false, and 1 to encode true. Stan supports the usual boolean comparison operations and boolean operators. These all have the same syntax and precedence as in C++; for the full list of operators and precedences, see the reference manual.

Comparison operators

All comparison operators return boolean values, either 0 or 1. Each operator has two signatures, one for integer comparisons and one for floating-point comparisons. Comparing an integer and real value is carried out by first promoting the integer value.

int **operator**<(int x, int y)

int **operator**<(real x, real y)

Return 1 if x is less than y and 0 otherwise.

$$\text{operator}<(x, y) = \begin{cases} 1 & \text{if } x < y \\ 0 & \text{otherwise} \end{cases}$$

Available since 2.0

int **operator**<=(int x, int y)

int **operator**<=(real x, real y)

Return 1 if x is less than or equal y and 0 otherwise.

$$\text{operator}<=(x, y) = \begin{cases} 1 & \text{if } x \leq y \\ 0 & \text{otherwise} \end{cases}$$

Available since 2.0

int **operator**>(int x, int y)

int **operator**>(real x, real y)

Return 1 if x is greater than y and 0 otherwise.

$$\text{operator}>(x, y) = \begin{cases} 1 & \text{if } x > y \\ 0 & \text{otherwise} \end{cases}$$

Available since 2.0

int **operator**>=(int x , int y)

int **operator**>=(real x , real y)

Return 1 if x is greater than or equal to y and 0 otherwise.

$$\text{operator}>=(x, y) = \begin{cases} 1 & \text{if } x \geq y \\ 0 & \text{otherwise} \end{cases}$$

Available since 2.0

int **operator**==(int x , int y)

int **operator**==(real x , real y)

Return 1 if x is equal to y and 0 otherwise.

$$\text{operator}==(x, y) = \begin{cases} 1 & \text{if } x = y \\ 0 & \text{otherwise} \end{cases}$$

Available since 2.0

int **operator**!=(int x , int y)

int **operator**!=(real x , real y)

Return 1 if x is not equal to y and 0 otherwise.

$$\text{operator}!=(x, y) = \begin{cases} 1 & \text{if } x \neq y \\ 0 & \text{otherwise} \end{cases}$$

Available since 2.0

Boolean operators

Boolean operators return either 0 for false or 1 for true. Inputs may be any real or integer values, with non-zero values being treated as true and zero values treated as false. These operators have the usual precedences, with negation (not) binding the most tightly, conjunction the next and disjunction the weakest; all of the operators bind more tightly than the comparisons. Thus an expression such as `!a && b` is interpreted as `(!a) && b`, and `a < b || c >= d && e != f` as `(a < b) || ((c >= d) && (e != f))`.

int **operator!**(int x)

Return 1 if x is zero and 0 otherwise.

$$\text{operator!}(x) = \begin{cases} 0 & \text{if } x \neq 0 \\ 1 & \text{if } x = 0 \end{cases}$$

Available since 2.0

int **operator!**(real x)

Return 1 if x is zero and 0 otherwise.

$$\text{operator!}(x) = \begin{cases} 0 & \text{if } x \neq 0.0 \\ 1 & \text{if } x = 0.0 \end{cases}$$

deprecated; - use `operator==` instead.

Available since 2.0, deprecated in 2.31

int **operator&&**(int x, int y)

Return 1 if x is unequal to 0 and y is unequal to 0.

$$\text{operator&&}(x, y) = \begin{cases} 1 & \text{if } x \neq 0 \text{ and } y \neq 0 \\ 0 & \text{otherwise} \end{cases}$$

Available since 2.0

int **operator&&**(real x, real y)

Return 1 if x is unequal to 0.0 and y is unequal to 0.0.

$$\text{operator&&}(x, y) = \begin{cases} 1 & \text{if } x \neq 0.0 \text{ and } y \neq 0.0 \\ 0 & \text{otherwise} \end{cases}$$

deprecated*Available since 2.0, deprecated in 2.31*`int operator ||(int x, int y)`

Return 1 if x is unequal to 0 or y is unequal to 0.

$$\text{operator } ||(x, y) = \begin{cases} 1 & \text{if } x \neq 0 \text{ or } y \neq 0 \\ 0 & \text{otherwise} \end{cases}$$

Available since 2.0`int operator ||(real x, real y)`

Return 1 if x is unequal to 0.0 or y is unequal to 0.0.

$$\text{operator } ||(x, y) = \begin{cases} 1 & \text{if } x \neq 0.0 \text{ or } y \neq 0.0 \\ 0 & \text{otherwise} \end{cases}$$

deprecated*Available since 2.0, deprecated in 2.31**Boolean operator short circuiting*

Like in C++, the boolean operators `&&` and `||` and are implemented to short circuit directly to a return value after evaluating the first argument if it is sufficient to resolve the result. In evaluating `a || b`, if `a` evaluates to a value other than zero, the expression returns the value 1 without evaluating the expression `b`. Similarly, evaluating `a && b` first evaluates `a`, and if the result is zero, returns 0 without evaluating `b`.

Logical functions

The logical functions introduce conditional behavior functionally and are primarily provided for compatibility with BUGS and JAGS.

`real step(real x)`

Return 1 if x is positive and 0 otherwise.

$$\text{step}(x) = \begin{cases} 0 & \text{if } x < 0 \\ 1 & \text{otherwise} \end{cases}$$

Warning: `int_step(0)` and `int_step(NaN)` return 0 whereas `step(0)` and `step(NaN)` return 1.

The step function is often used in BUGS to perform conditional operations. For instance, `step(a-b)` evaluates to 1 if `a` is greater than `b` and evaluates to 0 otherwise. `step` is a step-like functions; see the warning in section [step functions](#) applied to expressions dependent on parameters.

Available since 2.0

int **is_inf**(real x)

Return 1 if `x` is infinite (positive or negative) and 0 otherwise.

Available since 2.5

int **is_nan**(real x)

Return 1 if `x` is NaN and 0 otherwise.

Available since 2.5

Care must be taken because both of these indicator functions are step-like and thus can cause discontinuities in gradients when applied to parameters; see section [step-like functions](#) for details.

3.6. Real-valued arithmetic operators

The arithmetic operators are presented using C++ notation. For instance `operator+(x,y)` refers to the binary addition operator and `operator-(x)` to the unary negation operator. In Stan programs, these are written using the usual infix and prefix notations as `x + y` and `-x`, respectively.

Binary infix operators

real **operator+**(real x, real y)

Return the sum of `x` and `y`.

$$(x + y) = \text{operator+}(x, y) = x + y$$

Available since 2.0

real **operator-**(real x, real y)

Return the difference between `x` and `y`.

$$(x - y) = \text{operator-}(x, y) = x - y$$

Available since 2.0

real **operator***(real x, real y)

Return the product of x and y.

$$(x * y) = \text{operator}^*(x, y) = xy$$

Available since 2.0

real **operator/**(real x, real y)

Return the quotient of x and y.

$$(x / y) = \text{operator}/(x, y) = \frac{x}{y}$$

Available since 2.0

real **operator^**(real x, real y)

Return x raised to the power of y.

$$(x ^ y) = \text{operator}^\wedge(x, y) = x^y$$

Available since 2.5

Unary prefix operators

real **operator-**(real x)

Return the negation of the subtrahend x.

$$\text{operator-}(x) = (-x)$$

Available since 2.0

T **operator-**(T x)

Vectorized version of operator-. If T x is a (possibly nested) array of reals, -x is the same shape array where each individual number is negated.

Available since 2.31

real **operator+**(real x)

Return the value of x.

$$\text{operator+}(x) = x$$

Available since 2.0

3.7. Step-like functions

Warning: These functions can seriously hinder sampling and optimization efficiency for gradient-based methods (e.g., NUTS, HMC, BFGS) if applied to parameters (including transformed parameters and local variables in the transformed parameters or model block). The problem is that they break gradients due to discontinuities coupled with zero gradients elsewhere. They do not hinder sampling when used in the data, transformed data, or generated quantities blocks.

Absolute value functions

T **abs**(T x)

The absolute value of x.

This function works elementwise over containers such as vectors. Given a type T which is `real`, `vector`, `row_vector`, `matrix`, or an array of those types, `abs` returns the same type where each element has had its absolute value taken.

Available since 2.0, vectorized in 2.30

real **fdim**(real x, real y)

Return the positive difference between x and y, which is $x - y$ if x is greater than y and 0 otherwise; see warning above.

$$\text{fdim}(x, y) = \begin{cases} x - y & \text{if } x \geq y \\ 0 & \text{otherwise} \end{cases}$$

Available since 2.0

R **fdim**(T1 x, T2 y)

Vectorized implementation of the `fdim` function

Available since 2.25

Bounds functions

real **fmin**(real x, real y)

Return the minimum of x and y; see warning above.

$$\text{fmin}(x, y) = \begin{cases} x & \text{if } x \leq y \\ y & \text{otherwise} \end{cases}$$

Available since 2.0

R **fmin**(T1 x, T2 y)

Vectorized implementation of the `fmin` function

Available since 2.25

real **fmax**(real x, real y)

Return the maximum of x and y; see warning above.

$$\text{fmax}(x, y) = \begin{cases} x & \text{if } x \geq y \\ y & \text{otherwise} \end{cases}$$

Available since 2.0

R **fmax**(T1 x, T2 y)

Vectorized implementation of the fmax function

Available since 2.25

Arithmetic functions

real **fmod**(real x, real y)

Return the real value remainder after dividing x by y; see warning above.

$$\text{fmod}(x, y) = x - \left\lfloor \frac{x}{y} \right\rfloor y$$

The operator $\lfloor u \rfloor$ is the floor operation; see below.

Available since 2.0

R **fmod**(T1 x, T2 y)

Vectorized implementation of the fmod function

Available since 2.25

Rounding functions

Warning: Rounding functions convert real values to integers. Because the output is an integer, any gradient information resulting from functions applied to the integer is not passed to the real value it was derived from. With MCMC sampling using HMC or NUTS, the MCMC acceptance procedure will correct for any error due to poor gradient calculations, but the result is likely to be reduced acceptance probabilities and less efficient sampling.

The rounding functions cannot be used as indices to arrays because they return real values. For operations over data or in the generated quantities block, the `to_int()` function can be used.

R **floor**(T x)

The floor of x, which is the largest integer less than or equal to x, converted to a real value; see warning at start of section [step-like functions](#)

Available since 2.0, vectorized in 2.13

R `ceil`(T x)

The ceiling of x , which is the smallest integer greater than or equal to x , converted to a real value; see warning at start of section [step-like functions](#)

Available since 2.0, vectorized in 2.13

R `round`(T x)

The nearest integer to x , converted to a real value; see warning at start of section [step-like functions](#)

Available since 2.0, vectorized in 2.13

R `trunc`(T x)

The integer nearest to but no larger in magnitude than x , converted to a double value; see warning at start of section [step-like functions](#)

Available since 2.0, vectorized in 2.13

3.8. Power and logarithm functions

R `sqrt`(T x)

The square root of x

Available since 2.0, vectorized in 2.13

R `cbrt`(T x)

The cube root of x

Available since 2.0, vectorized in 2.13

R `square`(T x)

The square of x

Available since 2.0, vectorized in 2.13

R `exp`(T x)

The natural exponential of x

Available since 2.0, vectorized in 2.13

R `exp2`(T x)

The base-2 exponential of x

Available since 2.0, vectorized in 2.13

R **log**(T x)

The natural logarithm of x

Available since 2.0, vectorized in 2.13

R **log2**(T x)

The base-2 logarithm of x

Available since 2.0, vectorized in 2.13

R **log10**(T x)

The base-10 logarithm of x

Available since 2.0, vectorized in 2.13

real **pow**(real x, real y)

Return x raised to the power of y.

$$\text{pow}(x, y) = x^y$$

Available since 2.0

R **pow**(T1 x, T2 y)

Vectorized implementation of the pow function

Available since 2.25

R **inv**(T x)

The inverse of x

Available since 2.0, vectorized in 2.13

R **inv_sqrt**(T x)

The inverse of the square root of x

Available since 2.0, vectorized in 2.13

R **inv_square**(T x)

The inverse of the square of x

Available since 2.0, vectorized in 2.13

3.9. Trigonometric functions

real **hypot**(real x , real y)

Return the length of the hypotenuse of a right triangle with sides of length x and y .

$$\text{hypot}(x, y) = \begin{cases} \sqrt{x^2 + y^2} & \text{if } x, y \geq 0 \\ \text{NaN} & \text{otherwise} \end{cases}$$

Available since 2.0

R **hypot**(T1 x , T2 y)

Vectorized implementation of the hypot function

Available since 2.25

R **cos**(T x)

The cosine of the angle x (in radians)

Available since 2.0, vectorized in 2.13

R **sin**(T x)

The sine of the angle x (in radians)

Available since 2.0, vectorized in 2.13

R **tan**(T x)

The tangent of the angle x (in radians)

Available since 2.0, vectorized in 2.13

R **acos**(T x)

The principal arc (inverse) cosine (in radians) of x

Available since 2.0, vectorized in 2.13

R **asin**(T x)

The principal arc (inverse) sine (in radians) of x

Available since 2.0

R **atan**(T x)

The principal arc (inverse) tangent (in radians) of x , with values from $-\pi/2$ to $\pi/2$

Available since 2.0, vectorized in 2.13

R atan2(T y, T x)

Return the principal arc (inverse) tangent (in radians) of y divided by x,

$$\text{atan2}(y, x) = \arctan\left(\frac{y}{x}\right)$$

Available since 2.0, vectorized in 2.34

3.10. Hyperbolic trigonometric functions

R cosh(T x)

The hyperbolic cosine of x (in radians)

*Available since 2.0, vectorized in 2.13***R sinh**(T x)

The hyperbolic sine of x (in radians)

*Available since 2.0, vectorized in 2.13***R tanh**(T x)

The hyperbolic tangent of x (in radians)

*Available since 2.0, vectorized in 2.13***R acosh**(T x)

The inverse hyperbolic cosine (in radians)

*Available since 2.0, vectorized in 2.13***R asinh**(T x)

The inverse hyperbolic cosine (in radians)

*Available since 2.0, vectorized in 2.13***R atanh**(T x)

The inverse hyperbolic tangent (in radians) of x

Available since 2.0, vectorized in 2.13

3.11. Link functions

The following functions are commonly used as link functions in generalized linear models. The function Φ is also commonly used as a link function (see section [probability-related functions](#)).

R logit(T x)

The log odds, or logit, function applied to x

Available since 2.0, vectorized in 2.13

R `inv_logit`(T x)

The logistic sigmoid function applied to x

Available since 2.0, vectorized in 2.13

R `inv_cloglog`(T x)

The inverse of the complementary log-log function applied to x

Available since 2.0, vectorized in 2.13

3.12. Probability-related functions

Normal cumulative distribution functions

The error function `erf` is related to the standard normal cumulative distribution function Φ by scaling. See section [normal distribution](#) for the general normal cumulative distribution function (and its complement).

R `erf`(T x)

The error function, also known as the Gauss error function, of x

Available since 2.0, vectorized in 2.13

R `erfc`(T x)

The complementary error function of x

Available since 2.0, vectorized in 2.13

R `inv_erfc`(T x)

The inverse of the complementary error function of x

Available since 2.29, vectorized in 2.29

R `Phi`(T x)

The standard normal cumulative distribution function of x

Available since 2.0, vectorized in 2.13

R `inv_Phi`(T x)

Return the value of the inverse standard normal cdf Φ^{-1} at the specified quantile x. The details of the algorithm can be found in (Wichura 1988). Quantile arguments below $1e-16$ are untested; quantiles above 0.999999999 result in increasingly large errors.

Available since 2.0, vectorized in 2.13

R **Phi_approx**(T x)

The fast approximation of the unit (may replace Phi for probit regression with maximum absolute error of 0.00014, see (Bowling et al. 2009) for details)

Available since 2.0, vectorized in 2.13

Other probability-related functions

real **binary_log_loss**(int y, real y_hat)

Return the log loss function for predicting $\hat{y} \in [0, 1]$ for boolean outcome $y \in \{0, 1\}$.

$$\text{binary_log_loss}(y, \hat{y}) = \begin{cases} -\log \hat{y} & \text{if } y = 1 \\ -\log(1 - \hat{y}) & \text{otherwise} \end{cases}$$

Available since 2.0

R **binary_log_loss**(T1 x, T2 y)

Vectorized implementation of the `binary_log_loss` function

Available since 2.25

real **owens_t**(real h, real a)

Return the Owen's T function for the probability of the event $X > h$ and $0 < Y < aX$ where X and Y are independent standard normal random variables.

$$\text{owens_t}(h, a) = \frac{1}{2\pi} \int_0^a \frac{\exp(-\frac{1}{2}h^2(1+x^2))}{1+x^2} dx$$

Available since 2.25

R **owens_t**(T1 x, T2 y)

Vectorized implementation of the `owens_t` function

Available since 2.25

3.13. Combinatorial functions

real **beta**(real alpha, real beta)

Return the beta function applied to alpha and beta. The beta function, $B(\alpha, \beta)$, computes the normalizing constant for the beta distribution, and is defined for $\alpha > 0$ and $\beta > 0$. See section [appendix](#) for definition of $B(\alpha, \beta)$.

Available since 2.25

R **beta**(T1 x, T2 y)

Vectorized implementation of the beta function

Available since 2.25

real **inc_beta**(real alpha, real beta, real x)

Return the regularized incomplete beta function up to x applied to alpha and beta. See section [appendix](#) for a definition.

Available since 2.10

real **inv_inc_beta**(real alpha, real beta, real p)

Return the inverse of the regularized incomplete beta function. The return value x is the value that solves $p = \text{inc_beta}(\text{alpha}, \text{beta}, x)$. See section [appendix](#) for a definition of the `inc_beta`.

Available since 2.30

real **lbeta**(real alpha, real beta)

Return the natural logarithm of the beta function applied to alpha and beta. The beta function, $B(\alpha, \beta)$, computes the normalizing constant for the beta distribution, and is defined for $\alpha > 0$ and $\beta > 0$.

$$\text{lbeta}(\alpha, \beta) = \log \Gamma(\alpha) + \log \Gamma(\beta) - \log \Gamma(\alpha + \beta)$$

See section [appendix](#) for definition of $B(\alpha, \beta)$.

Available since 2.0

R **lbeta**(T1 x, T2 y)

Vectorized implementation of the `lbeta` function

Available since 2.25

R **tgamma**(T x)

The gamma function applied to x. The gamma function is the generalization of the factorial function to continuous variables, defined so that $\Gamma(n + 1) = n!$. See for a full definition of $\Gamma(x)$. The function is defined for positive numbers and non-integral negative numbers,

Available since 2.0, vectorized in 2.13

R **lgamma**(T x)

The natural logarithm of the gamma function applied to x,

Available since 2.0, vectorized in 2.15

R **digamma**(T x)

The digamma function applied to x. The digamma function is the derivative of

the natural logarithm of the Gamma function. The function is defined for positive numbers and non-integral negative numbers

Available since 2.0, vectorized in 2.13

R `trigamma`(T x)

The trigamma function applied to x. The trigamma function is the second derivative of the natural logarithm of the Gamma function

Available since 2.0, vectorized in 2.13

real **lmgamma**(int n, real x)

Return the natural logarithm of the multivariate gamma function Γ_n with n dimensions applied to x.

$$\text{lmgamma}(n, x) = \begin{cases} \frac{n(n-1)}{4} \log \pi + \sum_{j=1}^n \log \Gamma \left(x + \frac{1-j}{2} \right) & \text{if } x \notin \{\dots, -3, -2, -1, 0\} \\ \text{error} & \text{otherwise} \end{cases}$$

Available since 2.0

R `lmgamma`(T1 x, T2 y)

Vectorized implementation of the lmgamma function

Available since 2.25

real **gamma_p**(real a, real z)

Return the normalized lower incomplete gamma function of a and z defined for positive a and nonnegative z.

$$\text{gamma}_p(a, z) = \begin{cases} \frac{1}{\Gamma(a)} \int_0^z t^{a-1} e^{-t} dt & \text{if } a > 0, z \geq 0 \\ \text{error} & \text{otherwise} \end{cases}$$

Available since 2.0

R `gamma_p`(T1 x, T2 y)

Vectorized implementation of the gamma_p function

Available since 2.25

real **gamma_q**(real a, real z)

Return the normalized upper incomplete gamma function of a and z defined for

positive a and nonnegative z .

$$\text{gamma_q}(a, z) = \begin{cases} \frac{1}{\Gamma(a)} \int_z^\infty t^{a-1} e^{-t} dt & \text{if } a > 0, z \geq 0 \\ \text{error} & \text{otherwise} \end{cases}$$

Available since 2.0

R gamma_q(T1 x, T2 y)

Vectorized implementation of the gamma_q function

Available since 2.25

int **choose**(int x, int y)

Return the binomial coefficient of x and y . For non-negative integer inputs, the binomial coefficient function is written as $\binom{x}{y}$ and pronounced “ x choose y .” In its the antilog of the lchoose function but returns an integer rather than a real number with no non-zero decimal places. For $0 \leq y \leq x$, the binomial coefficient function can be defined via the factorial function

$$\text{choose}(x, y) = \frac{x!}{(y!)(x-y)!}$$

Available since 2.14

R choose(T1 x, T2 y)

Vectorized implementation of the choose function

Available since 2.25

real **bessel_first_kind**(int v, real x)

Return the Bessel function of the first kind with order v applied to x .

$$\text{bessel_first_kind}(v, x) = J_v(x),$$

where

$$J_v(x) = \left(\frac{1}{2}x\right)^v \sum_{k=0}^{\infty} \frac{\left(-\frac{1}{4}x^2\right)^k}{k! \Gamma(v+k+1)}$$

Available since 2.5

R bessel_first_kind(T1 x, T2 y)

Vectorized implementation of the bessel_first_kind function

Available since 2.25

real **bessel_second_kind**(int v, real x)

Return the Bessel function of the second kind with order v applied to x defined for positive x and v. For $x, v > 0$,

$$\text{bessel_second_kind}(v, x) = \begin{cases} Y_v(x) & \text{if } x > 0 \\ \text{error} & \text{otherwise} \end{cases}$$

where

$$Y_v(x) = \frac{J_v(x) \cos(v\pi) - J_{-v}(x)}{\sin(v\pi)}$$

Available since 2.5

R **bessel_second_kind**(T1 x, T2 y)

Vectorized implementation of the `bessel_second_kind` function

Available since 2.25

real **modified_bessel_first_kind**(int v, real z)

Return the modified Bessel function of the first kind with order v applied to z defined for all z and integer v.

$$\text{modified_bessel_first_kind}(v, z) = I_v(z)$$

where

$$I_v(z) = \left(\frac{1}{2}z\right)^v \sum_{k=0}^{\infty} \frac{\left(\frac{1}{4}z^2\right)^k}{k! \Gamma(v+k+1)}$$

Available since 2.1

R **modified_bessel_first_kind**(T1 x, T2 y)

Vectorized implementation of the `modified_bessel_first_kind` function

Available since 2.25

real **log_modified_bessel_first_kind**(real v, real z)

Return the log of the modified Bessel function of the first kind. v does not have to be an integer.

Available since 2.26

R **log_modified_bessel_first_kind**(T1 x, T2 y)

Vectorized implementation of the `log_modified_bessel_first_kind` function

Available since 2.26

real **modified_bessel_second_kind**(int v , real z)

Return the modified Bessel function of the second kind with order v applied to z defined for positive z and integer v .

$$\text{modified_bessel_second_kind}(v, z) = \begin{cases} K_v(z) & \text{if } z > 0 \\ \text{error} & \text{if } z \leq 0 \end{cases}$$

where

$$K_v(z) = \frac{\pi}{2} \cdot \frac{I_{-v}(z) - I_v(z)}{\sin(v\pi)}$$

Available since 2.1

R **modified_bessel_second_kind**(T1 x , T2 y)

Vectorized implementation of the `modified_bessel_second_kind` function

Available since 2.25

real **falling_factorial**(real x , real n)

Return the falling factorial of x with power n defined for positive x and real n .

$$\text{falling_factorial}(x, n) = \begin{cases} (x)_n & \text{if } x > 0 \\ \text{error} & \text{if } x \leq 0 \end{cases}$$

where

$$(x)_n = \frac{\Gamma(x+1)}{\Gamma(x-n+1)}$$

Available since 2.0

R **falling_factorial**(T1 x , T2 y)

Vectorized implementation of the `falling_factorial` function

Available since 2.25

real **lchoose**(real x , real y)

Return the natural logarithm of the generalized binomial coefficient of x and y . For non-negative integer inputs, the binomial coefficient function is written as $\binom{x}{y}$ and pronounced “ x choose y .” This function generalizes to real numbers using the gamma function. For $0 \leq y \leq x$,

$$\text{binomial_coefficient_log}(x, y) = \log \Gamma(x+1) - \log \Gamma(y+1) - \log \Gamma(x-y+1).$$

Available since 2.10

R lchoose(T1 x, T2 y)

Vectorized implementation of the lchoose function

Available since 2.29

real **log_falling_factorial**(real x, real n)

Return the log of the falling factorial of x with power n defined for positive x and real n.

$$\log_falling_factorial(x, n) = \begin{cases} \log(x)_n & \text{if } x > 0 \\ \text{error} & \text{if } x \leq 0 \end{cases}$$

Available since 2.0

real **rising_factorial**(real x, int n)

Return the rising factorial of x with power n defined for positive x and integer n.

$$\text{rising_factorial}(x, n) = \begin{cases} x^{(n)} & \text{if } x > 0 \\ \text{error} & \text{if } x \leq 0 \end{cases}$$

where

$$x^{(n)} = \frac{\Gamma(x+n)}{\Gamma(x)}$$

Available since 2.20

R rising_factorial(T1 x, T2 y)

Vectorized implementation of the rising_factorial function

Available since 2.25

real **log_rising_factorial**(real x, real n)

Return the log of the rising factorial of x with power n defined for positive x and real n.

$$\log_rising_factorial(x, n) = \begin{cases} \log x^{(n)} & \text{if } x > 0 \\ \text{error} & \text{if } x \leq 0 \end{cases}$$

Available since 2.0

R log_rising_factorial(T1 x, T2 y)

Vectorized implementation of the log_rising_factorial function

Available since 2.25

3.14. Composed functions

The functions in this section are equivalent in theory to combinations of other functions. In practice, they are implemented to be more efficient and more numerically stable than defining them directly using more basic Stan functions.

R **expm1**(T x)

The natural exponential of x minus 1

Available since 2.0, vectorized in 2.13

real **fma**(real x, real y, real z)

Return z plus the result of x multiplied by y.

$$\text{fma}(x, y, z) = (x \times y) + z$$

Available since 2.0

real **ldexp**(real x, int y)

Return the product of x and two raised to the y power.

$$\text{ldexp}(x, y) = x2^y$$

Available since 2.25

R **ldexp**(T1 x, T2 y)

Vectorized implementation of the ldexp function

Available since 2.25

real **lmultiply**(real x, real y)

Return the product of x and the natural logarithm of y.

$$\text{lmultiply}(x, y) = \begin{cases} 0 & \text{if } x = y = 0 \\ x \log y & \text{if } x, y \neq 0 \\ \text{NaN} & \text{otherwise} \end{cases}$$

Available since 2.10

R **lmultiply**(T1 x, T2 y)

Vectorized implementation of the lmultiply function

Available since 2.25

R **log1p**(T x)

The natural logarithm of 1 plus x

Available since 2.0, vectorized in 2.13

R **log1m**(T x)

The natural logarithm of 1 minus x

Available since 2.0, vectorized in 2.13

R **log1p_exp**(T x)

The natural logarithm of one plus the natural exponentiation of x

Available since 2.0, vectorized in 2.13

R **log1m_exp**(T x)

The logarithm of one minus the natural exponentiation of x

Available since 2.0, vectorized in 2.13

real **log_diff_exp**(real x, real y)

Return the natural logarithm of the difference of the natural exponentiation of x and the natural exponentiation of y.

$$\log_diff_exp(x, y) = \begin{cases} \log(\exp(x) - \exp(y)) & \text{if } +\infty > x \geq y \\ \text{NaN} & \text{otherwise} \end{cases}$$

When x is equal to y, `log_diff_exp(x, y)` returns $-\infty$, consistent with `log(0)` returning $-\infty$. This includes the case in which x and y are both equal to $-\infty$, which corresponds to `log(0 - 0)` because `exp(negative_infinity())` returns 0.

Available since 2.0

R **log_diff_exp**(T1 x, T2 y)

Vectorized implementation of the `log_diff_exp` function

Available since 2.25

real **log_mix**(real theta, real lp1, real lp2)

Return the log mixture of the log densities lp1 and lp2 with mixing proportion theta, defined by

$$\begin{aligned} \log_mix(\theta, \lambda_1, \lambda_2) &= \log(\theta \exp(\lambda_1) + (1 - \theta) \exp(\lambda_2)) \\ &= \log_sum_exp(\log(\theta) + \lambda_1, \log(1 - \theta) + \lambda_2). \end{aligned}$$

Available since 2.6

R `log_mix`(T1 thetas, T2 lps)

Calculates the log mixture density given thetas, mixing proportions which should be between 0 and 1 and sum to 1, and lps, log densities. The lps variable must be either a 1-d container of the same length as thetas, or an array of such.

$$\begin{aligned}\log_mix(\theta, \lambda) &= \log\left(\sum_{n=1}^N \theta_n * \exp(\lambda_n)\right) \\ &= \log_sum_exp(\log(\theta) + \lambda).\end{aligned}$$

This is a generalization of the above signature of three arguments to more than two densities. For example, `log_mix(lambda, lp1, lp2) == log_mix({lambda, 1 - lambda}, {lp1, lp2})`.

Available since 2.26

R `log_sum_exp`(T1 x, T2 y)

Return the natural logarithm of the sum of the natural exponentiation of x and the natural exponentiation of y.

$$\log_sum_exp(x, y) = \log(\exp(x) + \exp(y))$$

Available since 2.0, vectorized in 2.33

R `log_inv_logit`(T x)

The natural logarithm of the inverse logit function of x

Available since 2.0, vectorized in 2.13

R `log_inv_logit_diff`(T1 x, T2 y)

The natural logarithm of the difference of the inverse logit function of x and the inverse logit function of y

Available since 2.25

R `log1m_inv_logit`(T x)

The natural logarithm of 1 minus the inverse logit function of x

Available since 2.0, vectorized in 2.13

3.15. Special functions

R **lambert_w0**(T x)

Implementation of the W_0 branch of the Lambert W function, i.e., solution to the function $W_0(x) \exp^{W_0(x)} = x$

Available since 2.25

R **lambert_wm1**(T x)

Implementation of the W_{-1} branch of the Lambert W function, i.e., solution to the function $W_{-1}(x) \exp^{W_{-1}(x)} = x$

Available since 2.25

4. Complex-Valued Basic Functions

This chapter describes built-in functions that operate on complex numbers, either as an argument type or a return type. This includes the arithmetic operators generalized to complex numbers.

4.1. Complex assignment and promotion

Just as integers may be assigned to real variables, real variables may be assigned to complex numbers, with the result being a zero imaginary component.

```
int n = 5;           // n = 5
real x = a;         // x = 5.0
complex z1 = n;     // z = 5.0 + 0.0i
complex z2 = x;     // z = 5.0 + 0.0i
```

Complex function arguments

Function arguments of type `int` or `real` may be promoted to type `complex`. The complex version of functions in this chapter are only used if one of the arguments is complex. For example, if `z` is complex, then `pow(z, 2)` will call the complex version of the power function and the integer `2` will be promoted to a complex number with a real component of `2` and an imaginary component of `0`. The same goes for binary operators like addition and subtraction, where `z + 2` will be legal and produce a complex result. Functions such as `arg` and `conj` that are only available for complex numbers can accept integer or real arguments, promoting them to `complex` before applying the function.

4.2. Complex constructors and accessors

Complex constructors

Variables and constants of type `complex` are constructed from zero, one, or two real numbers.

```
complex z1 = to_complex();           // z1 = 0.0 + 0.0i
real re = -2.9;
complex z2 = to_complex(re);        // z2 = -2.9 + 0.0i
real im = 1.3;
complex z3 = to_complex(re, im);    // z3 = -2.9 + 1.3i
```

`complex to_complex()`

Return complex number with real part 0.0 and imaginary part 0.0.

Available since 2.28

`complex to_complex(real re)`

Return complex number with real part `re` and imaginary part 0.0.

Available since 2.28

`complex to_complex(real re, real im)`

Return complex number with real part `re` and imaginary part `im`.

Available since 2.28

`Z to_complex(T1 re, T2 im)`

Vectorized implementation of the `to_complex` function.

`T1` and `T2` can either be real containers of the same size, or a real container and a real, in which case the real value is used for the corresponding component in all elements of the output.

Available since 2.30

Complex accessors

Given a complex number, its real and imaginary parts can be extracted with the following functions.

`real get_real(complex z)`

Return the real part of the complex number `z`.

Available since 2.28

`real get_imag(complex z)`

Return the imaginary part of the complex number `z`.

Available since 2.28

4.3. Complex arithmetic operators

The arithmetic operators have the same precedence for complex and real arguments. The complex form of an operator will be selected if at least one of its argument is of type `complex`. If there are two arguments and only one is of type `complex`, then the other will be promoted to type `complex` before performing the operation.

Unary operators

complex **operator+**(complex z)

Return the complex argument z ,

$$+z = z.$$

Available since 2.28

complex **operator-**(complex z)

Return the negation of the complex argument z , which for $z = x + yi$ is

$$-z = -x - yi.$$

Available since 2.28

T operator-(\mathbb{T} x)

Vectorized version of **operator-**. If \mathbb{T} x is a (possibly nested) array of complex numbers, $-x$ is the same shape array where each individual value is negated.

Available since 2.31

Binary operators

complex **operator+**(complex x , complex y)

Return the sum of x and y ,

$$(x + y) = \text{operator+}(x, y) = x + y.$$

Available since 2.28

complex **operator-**(complex x , complex y)

Return the difference between x and y ,

$$(x - y) = \text{operator-}(x, y) = x - y.$$

Available since 2.28

complex **operator***(complex x , complex y)

Return the product of x and y ,

$$(x * y) = \text{operator*}(x, y) = x \times y.$$

Available since 2.28

complex **operator**/(complex x, complex y)

Return the quotient of x and y,

$$(x/y) = \text{operator}/(x, y) = \frac{x}{y}$$

Available since 2.28

complex **operator**^(complex x, complex y)

Return x raised to the power of y,

$$(x^y) = \text{operator}^\wedge(x, y) = \exp(y \log(x)).$$

Available since 2.28

4.4. Complex comparison operators

Complex numbers are equal if and only if both their real and imaginary components are equal. That is, the conditional

```
z1 == z2
```

is equivalent to

```
get_real(z1) == get_real(z2) && get_imag(z1) == get_imag(z2)
```

As with other complex functions, if one of the arguments is of type `real` or `int`, it will be promoted to type `complex` before comparison. For example, if `z` is of type `complex`, then `z == 0` will be true if `z` has real component equal to 0.0 and complex component equal to 0.0.

Warning: As with real values, it is usually a mistake to compare complex numbers for equality because their parts are implemented using floating-point arithmetic, which suffers from precision errors, rendering algebraically equivalent expressions not equal after evaluation.

int **operator**==(complex x, complex y)

Return 1 if x is equal to y and 0 otherwise,

$$(x == y) = \text{operator}==(x, y) = \begin{cases} 1 & \text{if } x = y, \text{ and} \\ 0 & \text{otherwise.} \end{cases}$$

Available since 2.28

`int operator!=(complex x, complex y)`
 Return 1 if x is not equal to y and 0 otherwise,

$$(x \neq y) = \text{operator}!=(x, y) = \begin{cases} 1 & \text{if } x \neq y, \text{ and} \\ 0 & \text{otherwise.} \end{cases}$$

Available since 2.28

4.5. Complex (compound) assignment operators

The assignment operator only serves as a component in the assignment statement and is thus not technically a function in the Stan language. With that caveat, it is documented here for completeness.

Assignment of complex numbers works elementwise. If an expression of type `int` or `real` is assigned to a complex number, it will be promoted before assignment as if calling to `_complex()`, so that the imaginary component is 0.0.

`void operator=(complex x, complex y)`
 $y = x$; assigns a (copy of) the value of y to x .

Available since 2.28

`void operator+=(complex x, complex y)`
 $x += y$; is equivalent to $x = x + y$;

Available since 2.28

`void operator-=(complex x, complex y)`
 $x -= y$; is equivalent to $x = x - y$;

Available since 2.28

`void operator*=(complex x, complex y)`
 $x *= y$; is equivalent to $x = x * y$;

Available since 2.28

`void operator/=(complex x, complex y)`
 $x /= y$; is equivalent to $x = x / y$;

Available since 2.28

4.6. Complex special functions

The following functions are specific to complex numbers other than absolute value, which has a specific meaning for complex numbers.

real **abs**(complex *z*)

Return the absolute value of *z*, also known as the modulus or magnitude, which for $z = x + yi$ is

$$\text{abs}(z) = \sqrt{x^2 + y^2}.$$

This function works elementwise over containers, returning the same shape and kind of the input container but holding reals. For example, a `complex_vector[n]` input will return a `vector[n]` output, with each element transformed by the above equation.

Available since 2.28, vectorized in 2.30

real **arg**(complex *z*)

Return the phase angle (in radians) of *z*, which for $z = x + yi$ is

$$\text{arg}(z) = \text{atan2}(y, x) = \text{atan}(y/x).$$

Available since 2.28

real **norm**(complex *z*)

Return the Euclidean norm of *z*, which is its absolute value squared, and which for $z = x + yi$ is

$$\text{norm}(z) = \text{abs}^2(z) = x^2 + y^2.$$

Available since 2.28

complex **conj**(complex *z*)

Return the complex conjugate of *z*, which negates the imaginary component, so that if $z = x + yi$,

$$\text{conj}(z) = x - yi.$$

Available since 2.28

Z conj(Z *z*)

Vectorized version of `conj`. This will apply the `conj` function to each element of a complex array, vector, or matrix.

Available since 2.31

complex **proj**(complex *z*)

Return the projection of *z* onto the Riemann sphere, which for $z = x + yi$ is

$$\text{proj}(z) = \begin{cases} z & \text{if } z \text{ is finite, and} \\ 0 + \text{sign}(y)i & \text{otherwise,} \end{cases}$$

where $\text{sign}(y)$ is -1 if y is negative and 1 otherwise.

Available since 2.28

complex **polar**(real r , real θ)

Return the complex number with magnitude (absolute value) r and phase angle θ .

Available since 2.28

4.7. Complex exponential and power functions

The exponential, log, and power functions may be supplied with complex arguments with specialized meanings that generalize their real counterparts. These versions are only called when the argument is complex.

complex **exp**(complex z)

Return the complex natural exponential of z , which for $z = x + yi$ is

$$\exp z = \exp(x)\text{cis}(y) = \exp(x)(\cos(y) + i\sin(y)).$$

Available since 2.28

complex **log**(complex z)

Return the complex natural logarithm of z , which for $z = \text{polar}(r, \theta)$ is

$$\log z = \log r + \theta i.$$

Available since 2.28

complex **log10**(complex z)

Return the complex common logarithm of z ,

$$\log_{10} z = \frac{\log z}{\log 10}.$$

Available since 2.28

complex **pow**(complex x , complex y)

Return x raised to the power of y ,

$$\text{pow}(x, y) = \exp(y \log(x)).$$

Available since 2.28

`Z pow(T1 x, T2 y)`

Vectorized implementation of the pow function

Available since 2.30

`complex sqrt(complex x)`

Return the complex square root of x with branch cut along the negative real axis. For finite inputs, the result will be in the right half-plane.

Available since 2.28

4.8. Complex trigonometric functions

The standard trigonometric functions are supported for complex numbers.

`complex cos(complex z)`

Return the complex cosine of z , which is

$$\cos(z) = \cosh(zi) = \frac{\exp(zi) + \exp(-zi)}{2}.$$

Available since 2.28

`complex sin(complex z)`

Return the complex sine of z ,

$$\sin(z) = -\sinh(zi) i = \frac{\exp(zi) - \exp(-zi)}{2i}.$$

Available since 2.28

`complex tan(complex z)`

Return the complex tangent of z ,

$$\tan(z) = -\tanh(zi) i = \frac{(\exp(-zi) - \exp(zi)) i}{\exp(-zi) + \exp(zi)}.$$

Available since 2.28

`complex acos(complex z)`

Return the complex arc (inverse) cosine of z ,

$$\operatorname{acos}(z) = \frac{1}{2}\pi + \log(zi + \sqrt{1-z^2}) i.$$

Available since 2.28

complex **asin**(complex z)

Return the complex arc (inverse) sine of z ,

$$\operatorname{asin}(z) = -\log(zi + \sqrt{1-z^2})i.$$

Available since 2.28

complex **atan**(complex z)

Return the complex arc (inverse) tangent of z ,

$$\operatorname{atan}(z) = -\frac{1}{2}(\log(1-zi) - \log(1+zi))i.$$

Available since 2.28

4.9. Complex hyperbolic trigonometric functions

The standard hyperbolic trigonometric functions are supported for complex numbers.

complex **cosh**(complex z)

Return the complex hyperbolic cosine of z ,

$$\operatorname{cosh}(z) = \frac{\exp(z) + \exp(-z)}{2}.$$

Available since 2.28

complex **sinh**(complex z)

Return the complex hyperbolic sine of z ,

$$\operatorname{sinh}(z) = \frac{\exp(z) - \exp(-z)}{2}.$$

Available since 2.28

complex **tanh**(complex z)

Return the complex hyperbolic tangent of z ,

$$\operatorname{tanh}(z) = \frac{\operatorname{sinh}(z)}{\operatorname{cosh}(z)} = \frac{\exp(z) - \exp(-z)}{\exp(z) + \exp(-z)}.$$

Available since 2.28

complex **acosh**(complex z)

Return the complex hyperbolic arc (inverse) cosine of z ,

$$\operatorname{acosh}(z) = \log\left(z + \sqrt{(z+1)(z-1)}\right).$$

Available since 2.28

complex **asinh**(complex z)

Return the complex hyperbolic arc (inverse) sine of z ,

$$\operatorname{asinh}(z) = \log\left(z + \sqrt{1+z^2}\right).$$

Available since 2.28

complex **atanh**(complex z)

Return the complex hyperbolic arc (inverse) tangent of z ,

$$\operatorname{atanh}(z) = \frac{\log(1+z) - \log(1-z)}{2}.$$

Available since 2.28

5. Array Operations

5.1. Reductions

The following operations take arrays as input and produce single output values. The boundary values for size 0 arrays are the unit with respect to the combination operation (min, max, sum, or product).

Minimum and maximum

real **min**(array[] real x)

The minimum value in x, or $+\infty$ if x is size 0.

Available since 2.0

int **min**(array[] int x)

The minimum value in x, or error if x is size 0.

Available since 2.0

real **max**(array[] real x)

The maximum value in x, or $-\infty$ if x is size 0.

Available since 2.0

int **max**(array[] int x)

The maximum value in x, or error if x is size 0.

Available since 2.0

Sum, product, and log sum of exp

int **sum**(array[] int x)

The sum of the elements in x, or 0 if the array is empty.

Available since 2.1

real **sum**(array[] real x)

The sum of the elements in x; see definition above.

Available since 2.0

complex **sum**(array[] complex x)

The sum of the elements in x; see definition above.

Available since 2.30

real **prod**(array[] real x)

The product of the elements in x, or 1 if x is size 0.

Available since 2.0

real **prod**(array[] int x)

The product of the elements in x,

$$\text{product}(x) = \begin{cases} \prod_{n=1}^N x_n & \text{if } N > 0 \\ 1 & \text{if } N = 0 \end{cases}$$

Available since 2.0

real **log_sum_exp**(array[] real x)

The natural logarithm of the sum of the exponentials of the elements in x, or $-\infty$ if the array is empty.

Available since 2.0

Sample mean, variance, and standard deviation

The sample mean, variance, and standard deviation are calculated in the usual way. For i.i.d. draws from a distribution of finite mean, the sample mean is an unbiased estimate of the mean of the distribution. Similarly, for i.i.d. draws from a distribution of finite variance, the sample variance is an unbiased estimate of the variance.¹ The sample deviation is defined as the square root of the sample deviation, but is not unbiased.

real **mean**(array[] real x)

The sample mean of the elements in x. For an array x of size $N > 0$,

$$\text{mean}(x) = \bar{x} = \frac{1}{N} \sum_{n=1}^N x_n.$$

It is an error to call the mean function with an array of size 0.

Available since 2.0

¹Dividing by N rather than $(N - 1)$ produces a maximum likelihood estimate of variance, which is biased to underestimate variance.

real **variance**(array[] real x)

The sample variance of the elements in x. For $N > 0$,

$$\text{variance}(x) = \begin{cases} \frac{1}{N-1} \sum_{n=1}^N (x_n - \bar{x})^2 & \text{if } N > 1 \\ 0 & \text{if } N = 1 \end{cases}$$

It is an error to call the variance function with an array of size 0.

Available since 2.0

real **sd**(array[] real x)

The sample standard deviation of elements in x.

$$\text{sd}(x) = \begin{cases} \sqrt{\text{variance}(x)} & \text{if } N > 1 \\ 0 & \text{if } N = 0 \end{cases}$$

It is an error to call the sd function with an array of size 0.

Available since 2.0

Norms

real **norm1**(vector x)

The L1 norm of x, defined by

$$\text{norm1}(x) = \sum_{n=1}^N (|x_n|)$$

where N is the size of x.

Available since 2.30

real **norm1**(row_vector x)

The L1 norm of x

Available since 2.30

real **norm1**(array[] real x)

The L1 norm of x

Available since 2.30

real **norm2**(vector x)

The L2 norm of x, defined by

$$\text{norm2}(x) = \sqrt{\sum_{n=1}^N (x_n)^2}$$

where N is the size of x

Available since 2.30

real **norm2**(row_vector x)

The L2 norm of x

Available since 2.30

real **norm2**(array[] real x)

The L2 norm of x

Available since 2.30

Euclidean distance and squared distance

real **distance**(vector x, vector y)

The Euclidean distance between x and y, defined by

$$\text{distance}(x, y) = \sqrt{\sum_{n=1}^N (x_n - y_n)^2}$$

where N is the size of x and y. It is an error to call distance with arguments of unequal size.

Available since 2.2

real **distance**(vector x, row_vector y)

The Euclidean distance between x and y

Available since 2.2

real **distance**(row_vector x, vector y)

The Euclidean distance between x and y

Available since 2.2

real **distance**(row_vector x, row_vector y)

The Euclidean distance between x and y

Available since 2.2

real **squared_distance**(vector x, vector y)

The squared Euclidean distance between x and y, defined by

$$\text{squared_distance}(x, y) = \text{distance}(x, y)^2 = \sum_{n=1}^N (x_n - y_n)^2,$$

where N is the size of x and y. It is an error to call squared_distance with arguments of unequal size.

Available since 2.7

`real squared_distance(vector x, row_vector y)`

The squared Euclidean distance between x and y

Available since 2.26

`real squared_distance(row_vector x, vector y)`

The squared Euclidean distance between x and y

Available since 2.26

`real squared_distance(row_vector x, row_vector y)`

The Euclidean distance between x and y

Available since 2.26

Quantile

Produces sample quantiles corresponding to the given probabilities. The smallest observation corresponds to a probability of 0 and the largest to a probability of 1.

Implements algorithm 7 from Hyndman, R. J. and Fan, Y., Sample quantiles in Statistical Packages (R's default quantile function).

`real quantile(data array[] real x, data real p)`

The p-th quantile of x

Available since 2.27

`array[] real quantile(data array[] real x, data array[] real p)`

An array containing the quantiles of x given by the array of probabilities p

Available since 2.27

5.2. Array size and dimension function

The size of an array or matrix can be obtained using the `dims()` function. The `dims()` function is defined to take an argument consisting of any variable with up to 8 array dimensions (and up to 2 additional matrix dimensions) and returns an array of integers with the dimensions. For example, if two variables are declared as follows,

```
array[7, 8, 9] real x;
array[7] matrix[8, 9] y;
```

then calling `dims(x)` or `dims(y)` returns an integer array of size 3 containing the elements 7, 8, and 9 in that order.

The `size()` function extracts the number of elements in an array. This is just the top-level elements, so if the array is declared as

```
array[M, N] real a;
```

the size of `a` is `M`.

The function `num_elements`, on the other hand, measures all of the elements, so that the array `a` above has $M \times N$ elements.

The specialized functions `rows()` and `cols()` should be used to extract the dimensions of vectors and matrices.

```
array[] int dims(T x)
```

Return an integer array containing the dimensions of `x`; the type of the argument `T` can be any Stan type with up to 8 array dimensions.

Available since 2.0

```
int num_elements(array[] T x)
```

Return the total number of elements in the array `x` including all elements in contained arrays, vectors, and matrices. `T` can be any array type. For example, if `x` is of type `array[4, 3] real` then `num_elements(x)` is 12, and if `y` is declared as `array[5] matrix[3, 4] y`, then `size(y)` evaluates to 60.

Available since 2.5

```
int size(array[] T x)
```

Return the number of elements in the array `x`; the type of the array `T` can be any type, but the size is just the size of the top level array, not the total number of elements contained. For example, if `x` is of type `array[4, 3] real` then `size(x)` is 4.

Available since 2.0

5.3. Array broadcasting

The following operations create arrays by repeating elements to fill an array of a specified size. These operations work for all input types `T`, including reals, integers, vectors, row vectors, matrices, or arrays.

```
array[] T rep_array(T x, int n)
```

Return the `n` array with every entry assigned to `x`.

Available since 2.0

```
array [,] T rep_array(T x, int m, int n)
```

Return the m by n array with every entry assigned to x.

Available since 2.0

```
array [,,] T rep_array(T x, int k, int m, int n)
```

Return the k by m by n array with every entry assigned to x.

Available since 2.0

For example, `rep_array(1.0,5)` produces a real array (type `array[] real`) of size 5 with all values set to 1.0. On the other hand, `rep_array(1,5)` produces an integer array (type `array[] int`) of size 5 with all values set to 1. This distinction is important because it is not possible to assign an integer array to a real array. For example, the following example contrasts legal with illegal array creation and assignment

```
array[5] real y;
array[5] int x;

x = rep_array(1, 5);    // ok
y = rep_array(1.0, 5); // ok

x = rep_array(1.0, 5); // illegal
y = rep_array(1, 5);   // illegal

x = y;                 // illegal
y = x;                 // illegal
```

If the value being repeated `v` is a vector (i.e., `T` is vector), then `rep_array(v, 27)` is a size 27 array consisting of 27 copies of the vector `v`.

```
vector[5] v;
array[3] vector[5] a;

a = rep_array(v, 3); // fill a with copies of v
a[2, 4] = 9.0;      // v[4], a[1, 4], a[3, 4] unchanged
```

If the type `T` of `x` is itself an array type, then the result will be an array with one, two, or three added dimensions, depending on which of the `rep_array` functions is called. For instance, consider the following legal code snippet.

```
array[5, 6] real a;
array[3, 4, 5, 6] real b;

b = rep_array(a, 3, 4); // make (3 x 4) copies of a
b[1, 1, 1, 1] = 27.9; // a[1, 1] unchanged
```

After the assignment to `b`, the value for `b[j, k, m, n]` is equal to `a[m, n]` where it is defined, for `j` in `1:3`, `k` in `1:4`, `m` in `1:5`, and `n` in `1:6`.

5.4. Array concatenation

`T append_array(T x, T y)`

Return the concatenation of two arrays in the order of the arguments. `T` must be an `N`-dimensional array of any Stan type (with a maximum `N` of 7). All dimensions but the first must match.

Available since 2.18

For example, the following code appends two three dimensional arrays of matrices together. Note that all dimensions except the first match. Any mismatches will cause an error to be thrown.

```
array[2, 1, 7] matrix[4, 6] x1;
array[3, 1, 7] matrix[4, 6] x2;
array[5, 1, 7] matrix[4, 6] x3;

x3 = append_array(x1, x2);
```

5.5. Sorting functions

Sorting can be used to sort values or the indices of those values in either ascending or descending order. For example, if `v` is declared as a real array of size 3, with values

$$v = (1, -10.3, 20.987),$$

then the various sort routines produce

$$\begin{aligned} \text{sort_asc}(v) &= (-10.3, 1, 20.987) \\ \text{sort_desc}(v) &= (20.987, 1, -10.3) \\ \text{sort_indices_asc}(v) &= (2, 1, 3) \\ \text{sort_indices_desc}(v) &= (3, 1, 2) \end{aligned}$$

array[] real **sort_asc**(array[] real v)

Sort the elements of v in ascending order

Available since 2.0

array[] int **sort_asc**(array[] int v)

Sort the elements of v in ascending order

Available since 2.0

array[] real **sort_desc**(array[] real v)

Sort the elements of v in descending order

Available since 2.0

array[] int **sort_desc**(array[] int v)

Sort the elements of v in descending order

Available since 2.0

array[] int **sort_indices_asc**(array[] real v)

Return an array of indices between 1 and the size of v, sorted to index v in ascending order.

Available since 2.3

array[] int **sort_indices_asc**(array[] int v)

Return an array of indices between 1 and the size of v, sorted to index v in ascending order.

Available since 2.3

array[] int **sort_indices_desc**(array[] real v)

Return an array of indices between 1 and the size of v, sorted to index v in descending order.

Available since 2.3

array[] int **sort_indices_desc**(array[] int v)

Return an array of indices between 1 and the size of v, sorted to index v in descending order.

Available since 2.3

int **rank**(array[] real v, int s)

Number of components of v less than v[s]

Available since 2.0

`int rank(array[] int v, int s)`
Number of components of `v` less than `v[s]`

Available since 2.0

5.6. Reversing functions

Stan provides functions to create a new array by reversing the order of elements in an existing array. For example, if `v` is declared as a real array of size 3, with values

$$v = (1, -10.3, 20.987),$$

then

$$\text{reverse}(v) = (20.987, -10.3, 1).$$

`array[] T reverse(array[] T v)`

Return a new array containing the elements of the argument in reverse order.

Available since 2.23

6. Matrix Operations

6.1. Integer-valued matrix size functions

int **num_elements**(vector x)

The total number of elements in the vector x (same as function rows)

Available since 2.5

int **num_elements**(row_vector x)

The total number of elements in the vector x (same as function cols)

Available since 2.5

int **num_elements**(matrix x)

The total number of elements in the matrix x. For example, if x is a 5×3 matrix, then `num_elements(x)` is 15

Available since 2.5

int **rows**(vector x)

The number of rows in the vector x

Available since 2.0

int **rows**(row_vector x)

The number of rows in the row vector x, namely 1

Available since 2.0

int **rows**(matrix x)

The number of rows in the matrix x

Available since 2.0

int **cols**(vector x)

The number of columns in the vector x, namely 1

Available since 2.0

int **cols**(row_vector x)

The number of columns in the row vector x

Available since 2.0

int **cols**(matrix x)

The number of columns in the matrix x

Available since 2.0

int **size**(vector x)

The size of x, i.e., the number of elements

Available since 2.26

int **size**(row_vector x)

The size of x, i.e., the number of elements

Available since 2.26

int **size**(matrix x)

The size of the matrix x. For example, if x is a 5×3 matrix, then `size(x)` is 15

Available since 2.26

6.2. Matrix arithmetic operators

Stan supports the basic matrix operations using infix, prefix and postfix operations. This section lists the operations supported by Stan along with their argument and result types.

Negation prefix operators

vector **operator-**(vector x)

The negation of the vector x.

Available since 2.0

row_vector **operator-**(row_vector x)

The negation of the row vector x.

Available since 2.0

matrix **operator-**(matrix x)

The negation of the matrix x.

Available since 2.0

T **operator-**(T x)

Vectorized version of `operator-`. If T x is a (possibly nested) array of matrix types, -x is the same shape array where each individual value is negated.

Available since 2.31

Infix matrix operators

vector **operator+**(vector x, vector y)

The sum of the vectors x and y.

Available since 2.0

row_vector **operator+**(row_vector x, row_vector y)

The sum of the row vectors x and y.

Available since 2.0

matrix **operator+**(matrix x, matrix y)

The sum of the matrices x and y

Available since 2.0

vector **operator-**(vector x, vector y)

The difference between the vectors x and y.

Available since 2.0

row_vector **operator-**(row_vector x, row_vector y)

The difference between the row vectors x and y

Available since 2.0

matrix **operator-**(matrix x, matrix y)

The difference between the matrices x and y

Available since 2.0

vector **operator***(real x, vector y)

The product of the scalar x and vector y

Available since 2.0

row_vector **operator***(real x, row_vector y)

The product of the scalar x and the row vector y

Available since 2.0

matrix **operator***(real x, matrix y)

The product of the scalar x and the matrix y

Available since 2.0

vector **operator***(vector x, real y)

The product of the scalar y and vector x

Available since 2.0

matrix **operator***(vector x, row_vector y)

The product of the vector x and row vector y

Available since 2.0

row_vector **operator***(row_vector x, real y)

The product of the scalar y and row vector x

Available since 2.0

real **operator***(row_vector x, vector y)

The product of the row vector x and vector y

Available since 2.0

row_vector **operator***(row_vector x, matrix y)

The product of the row vector x and matrix y

Available since 2.0

matrix **operator***(matrix x, real y)

The product of the scalar y and matrix x

Available since 2.0

vector **operator***(matrix x, vector y)

The product of the matrix x and vector y

Available since 2.0

matrix **operator***(matrix x, matrix y)

The product of the matrices x and y

Available since 2.0

Broadcast infix operators

vector **operator+**(vector x, real y)

The result of adding y to every entry in the vector x

Available since 2.0

vector **operator+**(real x, vector y)

The result of adding x to every entry in the vector y

Available since 2.0

row_vector **operator+**(row_vector x, real y)

The result of adding y to every entry in the row vector x

Available since 2.0

row_vector **operator+**(real x, row_vector y)

The result of adding x to every entry in the row vector y

Available since 2.0

matrix **operator+**(matrix x, real y)

The result of adding y to every entry in the matrix x

Available since 2.0

matrix **operator+**(real x, matrix y)

The result of adding x to every entry in the matrix y

Available since 2.0

vector **operator-**(vector x, real y)

The result of subtracting y from every entry in the vector x

Available since 2.0

vector **operator-**(real x, vector y)

The result of adding x to every entry in the negation of the vector y

Available since 2.0

row_vector **operator-**(row_vector x, real y)

The result of subtracting y from every entry in the row vector x

Available since 2.0

row_vector **operator-**(real x, row_vector y)

The result of adding x to every entry in the negation of the row vector y

Available since 2.0

matrix **operator-**(matrix x, real y)

The result of subtracting y from every entry in the matrix x

Available since 2.0

matrix **operator-**(real x, matrix y)

The result of adding x to every entry in negation of the matrix y

Available since 2.0

vector **operator/**(vector x, real y)

The result of dividing each entry in the vector x by y

Available since 2.0

row_vector **operator/**(row_vector x, real y)

The result of dividing each entry in the row vector x by y

Available since 2.0

matrix **operator/**(matrix x, real y)

The result of dividing each entry in the matrix x by y

Available since 2.0

6.3. Transposition operator

Matrix transposition is represented using a postfix operator.

matrix **operator'**(matrix x)

The transpose of the matrix x, written as x'

Available since 2.0

row_vector **operator'**(vector x)

The transpose of the vector x, written as x'

Available since 2.0

vector **operator'**(row_vector x)

The transpose of the row vector x, written as x'

Available since 2.0

6.4. Elementwise functions

Elementwise functions apply a function to each element of a vector or matrix, returning a result of the same shape as the argument. There are many functions that are vectorized in addition to the ad hoc cases listed in this section; see section [function vectorization](#) for the general cases.

vector **operator.***(vector x, vector y)

The elementwise product of y and x

Available since 2.0

row_vector **operator.***(row_vector x, row_vector y)

The elementwise product of y and x

Available since 2.0

matrix **operator.***(matrix x, matrix y)

The elementwise product of y and x

Available since 2.0

vector **operator./**(vector x, vector y)

The elementwise quotient of y and x

Available since 2.0

vector **operator./**(vector x, real y)

The elementwise quotient of y and x

Available since 2.4

vector **operator./**(real x, vector y)

The elementwise quotient of y and x

Available since 2.4

row_vector **operator./**(row_vector x, row_vector y)

The elementwise quotient of y and x

Available since 2.0

row_vector **operator./**(row_vector x, real y)

The elementwise quotient of y and x

Available since 2.4

row_vector **operator./**(real x, row_vector y)

The elementwise quotient of y and x

Available since 2.4

matrix **operator./**(matrix x, matrix y)

The elementwise quotient of y and x

Available since 2.0

matrix **operator./**(matrix x, real y)

The elementwise quotient of y and x

Available since 2.4

matrix **operator./**(real x, matrix y)

The elementwise quotient of y and x

Available since 2.4

vector **operator.**^(vector x, vector y)

The elementwise power of y and x

Available since 2.24

vector **operator.**^(vector x, real y)

The elementwise power of y and x

Available since 2.24

vector **operator.**^(real x, vector y)

The elementwise power of y and x

Available since 2.24

row_vector **operator.**^(row_vector x, row_vector y)

The elementwise power of y and x

Available since 2.24

row_vector **operator.**^(row_vector x, real y)

The elementwise power of y and x

Available since 2.24

row_vector **operator.**^(real x, row_vector y)

The elementwise power of y and x

Available since 2.24

matrix **operator.**^(matrix x, matrix y)

The elementwise power of y and x

Available since 2.24

matrix **operator.**^(matrix x, real y)

The elementwise power of y and x

Available since 2.24

matrix **operator.**^(real x, matrix y)

The elementwise power of y and x

Available since 2.24

6.5. Dot products and specialized products

real **dot_product**(vector x, vector y)

The dot product of x and y

Available since 2.0

real **dot_product**(vector x, row_vector y)

The dot product of x and y

Available since 2.0

real **dot_product**(row_vector x, vector y)

The dot product of x and y

Available since 2.0

real **dot_product**(row_vector x, row_vector y)

The dot product of x and y

Available since 2.0

row_vector **columns_dot_product**(vector x, vector y)

The dot product of the columns of x and y

Available since 2.0

row_vector **columns_dot_product**(row_vector x, row_vector y)

The dot product of the columns of x and y

Available since 2.0

row_vector **columns_dot_product**(matrix x, matrix y)

The dot product of the columns of x and y

Available since 2.0

vector **rows_dot_product**(vector x, vector y)

The dot product of the rows of x and y

Available since 2.0

vector **rows_dot_product**(row_vector x, row_vector y)

The dot product of the rows of x and y

Available since 2.0

vector **rows_dot_product**(matrix x, matrix y)

The dot product of the rows of x and y

Available since 2.0

real **dot_self**(vector x)

The dot product of the vector x with itself

Available since 2.0

real **dot_self**(row_vector x)

The dot product of the row vector x with itself

Available since 2.0

row_vector **columns_dot_self**(vector x)

The dot product of the columns of x with themselves

Available since 2.0

row_vector **columns_dot_self**(row_vector x)

The dot product of the columns of x with themselves

Available since 2.0

row_vector **columns_dot_self**(matrix x)

The dot product of the columns of x with themselves

Available since 2.0

vector **rows_dot_self**(vector x)

The dot product of the rows of x with themselves

Available since 2.0

vector **rows_dot_self**(row_vector x)

The dot product of the rows of x with themselves

Available since 2.0

vector **rows_dot_self**(matrix x)

The dot product of the rows of x with themselves

Available since 2.0

Specialized products

matrix **tcrossprod**(matrix x)

The product of x postmultiplied by its own transpose, similar to the `tcrossprod(x)` function in R. The result is a symmetric matrix xx^T .

Available since 2.0

matrix **crossprod**(matrix x)

The product of x premultiplied by its own transpose, similar to the `crossprod(x)` function in R. The result is a symmetric matrix $x^T x$.

Available since 2.0

The following functions all provide shorthand forms for common expressions, which are also much more efficient.

matrix **quad_form**(matrix A, matrix B)

The quadratic form, i.e., $B' * A * B$.

Available since 2.0

real **quad_form**(matrix A, vector B)

The quadratic form, i.e., $B' * A * B$.

Available since 2.0

matrix **quad_form_diag**(matrix m, vector v)

The quadratic form using the column vector v as a diagonal matrix, i.e., $\text{diag_matrix}(v) * m * \text{diag_matrix}(v)$.

Available since 2.3

matrix **quad_form_diag**(matrix m, row_vector rv)

The quadratic form using the row vector rv as a diagonal matrix, i.e., $\text{diag_matrix}(rv) * m * \text{diag_matrix}(rv)$.

Available since 2.3

matrix **quad_form_sym**(matrix A, matrix B)

Similarly to `quad_form`, gives $B' * A * B$, but additionally checks if A is symmetric and ensures that the result is also symmetric.

Available since 2.3

real **quad_form_sym**(matrix A, vector B)

Similarly to `quad_form`, gives $B' * A * B$, but additionally checks if A is symmetric and ensures that the result is also symmetric.

Available since 2.3

real **trace_quad_form**(matrix A, matrix B)

The trace of the quadratic form, i.e., $\text{trace}(B' * A * B)$.

Available since 2.0

real **trace_gen_quad_form**(matrix D, matrix A, matrix B)

The trace of a generalized quadratic form, i.e., $\text{trace}(D * B' * A * B)$.

Available since 2.0

matrix **multiply_lower_tri_self_transpose**(matrix x)

The product of the lower triangular portion of x (including the diagonal) times its own transpose; that is, if L is a matrix of the same dimensions as x with $L(m, n)$ equal to $x(m, n)$ for $n \leq m$ and $L(m, n)$ equal to 0 if $n > m$, the result is the symmetric matrix LL^T . This is a specialization of `tcrossprod(x)` for lower-triangular matrices. The input matrix does not need to be square.

Available since 2.0

matrix **diag_pre_multiply**(vector v, matrix m)

Return the product of the diagonal matrix formed from the vector v and the matrix m, i.e., $\text{diag_matrix}(v) * m$.

Available since 2.0

matrix **diag_pre_multiply**(row_vector rv, matrix m)

Return the product of the diagonal matrix formed from the vector rv and the matrix m, i.e., $\text{diag_matrix}(rv) * m$.

Available since 2.0

matrix **diag_post_multiply**(matrix m, vector v)

Return the product of the matrix m and the diagonal matrix formed from the vector v, i.e., $m * \text{diag_matrix}(v)$.

Available since 2.0

matrix **diag_post_multiply**(matrix m, row_vector rv)

Return the product of the matrix m and the diagonal matrix formed from the the row vector rv, i.e., $m * \text{diag_matrix}(rv)$.

Available since 2.0

6.6. Reductions

Log sum of exponents

real **log_sum_exp**(vector x)

The natural logarithm of the sum of the exponentials of the elements in x

Available since 2.0

real **log_sum_exp**(row_vector x)

The natural logarithm of the sum of the exponentials of the elements in x

Available since 2.0

real **log_sum_exp**(matrix x)

The natural logarithm of the sum of the exponentials of the elements in x

Available since 2.0

Minimum and maximum

real **min**(vector x)

The minimum value in x, or $+\infty$ if x is empty

Available since 2.0

real **min**(row_vector x)

The minimum value in x, or $+\infty$ if x is empty

Available since 2.0

real **min**(matrix x)

The minimum value in x, or $+\infty$ if x is empty

Available since 2.0

real **max**(vector x)

The maximum value in x, or $-\infty$ if x is empty

Available since 2.0

real **max**(row_vector x)

The maximum value in x, or $-\infty$ if x is empty

Available since 2.0

real **max**(matrix x)

The maximum value in x, or $-\infty$ if x is empty

Available since 2.0

Sums and products

real **sum**(vector x)

The sum of the values in x, or 0 if x is empty

Available since 2.0

```
real sum(row_vector x)
```

The sum of the values in x , or 0 if x is empty

Available since 2.0

```
real sum(matrix x)
```

The sum of the values in x , or 0 if x is empty

Available since 2.0

```
real prod(vector x)
```

The product of the values in x , or 1 if x is empty

Available since 2.0

```
real prod(row_vector x)
```

The product of the values in x , or 1 if x is empty

Available since 2.0

```
real prod(matrix x)
```

The product of the values in x , or 1 if x is empty

Available since 2.0

Sample moments

Full definitions are provided for sample moments in section [array reductions](#).

```
real mean(vector x)
```

The sample mean of the values in x ; see section [array reductions](#) for details.

Available since 2.0

```
real mean(row_vector x)
```

The sample mean of the values in x ; see section [array reductions](#) for details.

Available since 2.0

```
real mean(matrix x)
```

The sample mean of the values in x ; see section [array reductions](#) for details.

Available since 2.0

```
real variance(vector x)
```

The sample variance of the values in x ; see section [array reductions](#) for details.

Available since 2.0

real **variance**(row_vector x)

The sample variance of the values in x; see section [array reductions](#) for details.

Available since 2.0

real **variance**(matrix x)

The sample variance of the values in x; see section [array reductions](#) for details.

Available since 2.0

real **sd**(vector x)

The sample standard deviation of the values in x; see section [array reductions](#) for details.

Available since 2.0

real **sd**(row_vector x)

The sample standard deviation of the values in x; see section [array reductions](#) for details.

Available since 2.0

real **sd**(matrix x)

The sample standard deviation of the values in x; see section [array reductions](#) for details.

Available since 2.0

Quantile

Produces sample quantiles corresponding to the given probabilities. The smallest observation corresponds to a probability of 0 and the largest to a probability of 1.

Implements algorithm 7 from Hyndman, R. J. and Fan, Y., Sample quantiles in Statistical Packages (R's default quantile function).

real **quantile**(data vector x, data real p)

The p-th quantile of x

Available since 2.27

array[] real **quantile**(data vector x, data array[] real p)

An array containing the quantiles of x given by the array of probabilities p

Available since 2.27

real **quantile**(data row_vector x, data real p)

The p-th quantile of x

Available since 2.27

array[] real **quantile**(data row_vector x, data array[] real p)
An array containing the quantiles of x given by the array of probabilities p

Available since 2.27

6.7. Broadcast functions

The following broadcast functions allow vectors, row vectors and matrices to be created by copying a single element into all of their cells. Matrices may also be created by stacking copies of row vectors vertically or stacking copies of column vectors horizontally.

vector **rep_vector**(real x, int m)
Return the size m (column) vector consisting of copies of x.

Available since 2.0

row_vector **rep_row_vector**(real x, int n)
Return the size n row vector consisting of copies of x.

Available since 2.0

matrix **rep_matrix**(real x, int m, int n)
Return the m by n matrix consisting of copies of x.

Available since 2.0

matrix **rep_matrix**(vector v, int n)
Return the m by n matrix consisting of n copies of the (column) vector v of size m.

Available since 2.0

matrix **rep_matrix**(row_vector rv, int m)
Return the m by n matrix consisting of m copies of the row vector rv of size n.

Available since 2.0

Unlike the situation with array broadcasting (see section [array broadcasting](#)), where there is a distinction between integer and real arguments, the following two statements produce the same result for vector broadcasting; row vector and matrix broadcasting behave similarly.

```
vector[3] x;
x = rep_vector(1, 3);
x = rep_vector(1.0, 3);
```

There are no integer vector or matrix types, so integer values are automatically promoted.

Symmetrization

matrix **symmetrize_from_lower_tri**(matrix A)

Construct a symmetric matrix from the lower triangle of A.

Available since 2.26

6.8. Diagonal matrix functions

matrix **add_diag**(matrix m, row_vector d)

Add row_vector d to the diagonal of matrix m.

Available since 2.21

matrix **add_diag**(matrix m, vector d)

Add vector d to the diagonal of matrix m.

Available since 2.21

matrix **add_diag**(matrix m, real d)

Add scalar d to every diagonal element of matrix m.

Available since 2.21

vector **diagonal**(matrix x)

The diagonal of the matrix x

Available since 2.0

matrix **diag_matrix**(vector x)

The diagonal matrix with diagonal x

Available since 2.0

Although the `diag_matrix` function is available, it is unlikely to ever show up in an efficient Stan program. For example, rather than converting a diagonal to a full matrix for use as a covariance matrix,

```
y ~ multi_normal(mu, diag_matrix(square(sigma)));
```

it is much more efficient to just use a univariate normal, which produces the same density,

```
y ~ normal(mu, sigma);
```

Rather than writing `m * diag_matrix(v)` where `m` is a matrix and `v` is a vector, it is much more efficient to write `diag_post_multiply(m, v)` (and similarly for pre-multiplication). By the same token, it is better to use `quad_form_diag(m, v)` rather than `quad_form(m, diag_matrix(v))`.

```
matrix identity_matrix(int k)
Create an identity matrix of size  $k \times k$ 
```

Available since 2.26

6.9. Container construction functions

```
array[] real linspaced_array(int n, data real lower, data real upper)
Create a real array of length n of equidistantly-spaced elements between lower and upper
```

Available since 2.24

```
array[] int linspaced_int_array(int n, int lower, int upper)
Create a regularly spaced, increasing integer array of length n between lower and upper, inclusively. If  $(upper - lower) / (n - 1)$  is less than one, repeat each output  $(n - 1) / (upper - lower)$  times. If neither  $(upper - lower) / (n - 1)$  or  $(n - 1) / (upper - lower)$  are integers, upper is reduced until one of these is true.
```

Available since 2.26

```
vector linspaced_vector(int n, data real lower, data real upper)
Create an n-dimensional vector of equidistantly-spaced elements between lower and upper
```

Available since 2.24

```
row_vector linspaced_row_vector(int n, data real lower, data real upper)
Create an n-dimensional row-vector of equidistantly-spaced elements between lower and upper
```

Available since 2.24

```
array[] int one_hot_int_array(int n, int k)
Create a one-hot encoded int array of length n with array[k] = 1
```


Available since 2.26

array[] real **one_hot_array**(int n, int k)

Create a one-hot encoded real array of length n with array[k] = 1

Available since 2.24

vector **one_hot_vector**(int n, int k)

Create an n-dimensional one-hot encoded vector with vector[k] = 1

Available since 2.24

row_vector **one_hot_row_vector**(int n, int k)

Create an n-dimensional one-hot encoded row-vector with row_vector[k] = 1

Available since 2.24

array[] int **ones_int_array**(int n)

Create an int array of length n of all ones

Available since 2.26

array[] real **ones_array**(int n)

Create a real array of length n of all ones

Available since 2.26

vector **ones_vector**(int n)

Create an n-dimensional vector of all ones

Available since 2.26

row_vector **ones_row_vector**(int n)

Create an n-dimensional row-vector of all ones

Available since 2.26

array[] int **zeros_int_array**(int n)

Create an int array of length n of all zeros

Available since 2.26

array[] real **zeros_array**(int n)

Create a real array of length n of all zeros

Available since 2.24

vector **zeros_vector**(int n)

Create an n-dimensional vector of all zeros

Available since 2.24

row_vector **zeros_row_vector**(int n)
Create an n-dimensional row-vector of all zeros

Available since 2.24

vector **uniform_simplex**(int n)
Create an n-dimensional simplex with elements $\text{vector}[i] = 1 / n$ for all $i \in 1, \dots, n$

Available since 2.24

6.10. Slicing and blocking functions

Stan provides several functions for generating slices or blocks or diagonal entries for matrices.

Columns and rows

vector **col**(matrix x, int n)
The n-th column of matrix x

Available since 2.0

row_vector **row**(matrix x, int m)
The m-th row of matrix x

Available since 2.0

The row function is special in that it may be used as an lvalue in an assignment statement (i.e., something to which a value may be assigned). The row function is also special in that the indexing notation $x[m]$ is just an alternative way of writing $\text{row}(x, m)$. The col function may **not**, be used as an lvalue, nor is there an indexing based shorthand for it.

Block operations

Matrix slicing operations

Block operations may be used to extract a sub-block of a matrix.

matrix **block**(matrix x, int i, int j, int n_rows, int n_cols)
Return the submatrix of x that starts at row i and column j and extends n_rows rows and n_cols columns.

Available since 2.0

The sub-row and sub-column operations may be used to extract a slice of row or column from a matrix

vector **sub_col**(matrix x, int i, int j, int n_rows)

Return the sub-column of x that starts at row i and column j and extends n_rows rows and 1 column.

Available since 2.0

row_vector **sub_row**(matrix x, int i, int j, int n_cols)

Return the sub-row of x that starts at row i and column j and extends 1 row and n_cols columns.

Available since 2.0

Vector and array slicing operations

The head operation extracts the first n elements of a vector and the tail operation the last. The segment operation extracts an arbitrary subvector.

vector **head**(vector v, int n)

Return the vector consisting of the first n elements of v.

Available since 2.0

row_vector **head**(row_vector rv, int n)

Return the row vector consisting of the first n elements of rv.

Available since 2.0

array[] T **head**(array[] T sv, int n)

Return the array consisting of the first n elements of sv; applies to up to three-dimensional arrays containing any type of elements T.

Available since 2.0

vector **tail**(vector v, int n)

Return the vector consisting of the last n elements of v.

Available since 2.0

row_vector **tail**(row_vector rv, int n)

Return the row vector consisting of the last n elements of rv.

Available since 2.0

array[] T **tail**(array[] T sv, int n)

Return the array consisting of the last n elements of sv ; applies to up to three-dimensional arrays containing any type of elements T .

Available since 2.0

vector **segment**(vector v , int i , int n)

Return the vector consisting of the n elements of v starting at i ; i.e., elements i through $i + n - 1$.

Available since 2.0

row_vector **segment**(row_vector rv , int i , int n)

Return the row vector consisting of the n elements of rv starting at i ; i.e., elements i through $i + n - 1$.

Available since 2.10

array[] T **segment**(array[] T sv , int i , int n)

Return the array consisting of the n elements of sv starting at i ; i.e., elements i through $i + n - 1$. Applies to up to three-dimensional arrays containing any type of elements T .

Available since 2.0

6.11. Matrix concatenation

Stan's matrix concatenation operations `append_col` and `append_row` are like the operations `cbind` and `rbind` in R.

Horizontal concatenation

matrix **append_col**(matrix x , matrix y)

Combine matrices x and y by column. The matrices must have the same number of rows.

Available since 2.5

matrix **append_col**(matrix x , vector y)

Combine matrix x and vector y by column. The matrix and the vector must have the same number of rows.

Available since 2.5

matrix **append_col**(vector x , matrix y)

Combine vector x and matrix y by column. The vector and the matrix must have the same number of rows.

Available since 2.5

matrix **append_col**(vector x, vector y)

Combine vectors x and y by column. The vectors must have the same number of rows.

Available since 2.5

row_vector **append_col**(row_vector x, row_vector y)

Combine row vectors x and y of any size into another row vector by appending y to the end of x.

Available since 2.5

row_vector **append_col**(real x, row_vector y)

Append x to the front of y, returning another row vector.

Available since 2.12

row_vector **append_col**(row_vector x, real y)

Append y to the end of x, returning another row vector.

Available since 2.12

Vertical concatenation

matrix **append_row**(matrix x, matrix y)

Combine matrices x and y by row. The matrices must have the same number of columns.

Available since 2.5

matrix **append_row**(matrix x, row_vector y)

Combine matrix x and row vector y by row. The matrix and the row vector must have the same number of columns.

Available since 2.5

matrix **append_row**(row_vector x, matrix y)

Combine row vector x and matrix y by row. The row vector and the matrix must have the same number of columns.

Available since 2.5

matrix **append_row**(row_vector x, row_vector y)

Combine row vectors x and y by row. The row vectors must have the same number of columns.

Available since 2.5

vector **append_row**(vector x , vector y)

Concatenate vectors x and y of any size into another vector.

Available since 2.5

vector **append_row**(real x , vector y)

Append x to the top of y , returning another vector.

Available since 2.12

vector **append_row**(vector x , real y)

Append y to the bottom of x , returning another vector.

Available since 2.12

6.12. Special matrix functions

Softmax

The softmax function maps¹ $y \in \mathbb{R}^K$ to the K -simplex by

$$\text{softmax}(y) = \frac{\exp(y)}{\sum_{k=1}^K \exp(y_k)},$$

where $\exp(y)$ is the componentwise exponentiation of y . Softmax is usually calculated on the log scale,

$$\begin{aligned} \log \text{softmax}(y) &= y - \log \sum_{k=1}^K \exp(y_k) \\ &= y - \log_sum_exp(y). \end{aligned}$$

where the vector y minus the scalar $\log_sum_exp(y)$ subtracts the scalar from each component of y .

Stan provides the following functions for softmax and its log.

vector **softmax**(vector x)

The softmax of x

Available since 2.0

vector **log_softmax**(vector x)

The natural logarithm of the softmax of x

¹The softmax function is so called because in the limit as $y_n \rightarrow \infty$ with y_m for $m \neq n$ held constant, the result tends toward the “one-hot” vector θ with $\theta_n = 1$ and $\theta_m = 0$ for $m \neq n$, thus providing a “soft” version of the maximum function.

Available since 2.0

Cumulative sums

The cumulative sum of a sequence x_1, \dots, x_N is the sequence y_1, \dots, y_N , where

$$y_n = \sum_{m=1}^n x_m.$$

`array[] int cumulative_sum(array[] int x)`

The cumulative sum of x

Available since 2.30

`array[] real cumulative_sum(array[] real x)`

The cumulative sum of x

Available since 2.0

`vector cumulative_sum(vector v)`

The cumulative sum of v

Available since 2.0

`row_vector cumulative_sum(row_vector rv)`

The cumulative sum of rv

Available since 2.0

6.13. Gaussian Process Covariance Functions

The Gaussian process covariance functions compute the covariance between observations in an input data set or the cross-covariance between two input data sets.

For one dimensional GPs, the input data sets are arrays of scalars. The covariance matrix is given by $K_{ij} = k(x_i, x_j)$ (where x_i is the i^{th} element of the array x) and the cross-covariance is given by $K_{ij} = k(x_i, y_j)$.

For multi-dimensional GPs, the input data sets are arrays of vectors. The covariance matrix is given by $K_{ij} = k(\mathbf{x}_i, \mathbf{x}_j)$ (where \mathbf{x}_i is the i^{th} vector in the array x) and the cross-covariance is given by $K_{ij} = k(\mathbf{x}_i, \mathbf{y}_j)$.

Exponentiated quadratic kernel

With magnitude σ and length scale l , the exponentiated quadratic kernel is:

$$k(\mathbf{x}_i, \mathbf{x}_j) = \sigma^2 \exp\left(-\frac{|\mathbf{x}_i - \mathbf{x}_j|^2}{2l^2}\right)$$

matrix **gp_exp_quad_cov**(array[] real x, real sigma, real length_scale)

Gaussian process covariance with exponentiated quadratic kernel in one dimension.

Available since 2.20

matrix **gp_exp_quad_cov**(array[] real x1, array[] real x2, real sigma, real length_scale)

Gaussian process cross-covariance of x1 and x2 with exponentiated quadratic kernel in one dimension.

Available since 2.20

matrix **gp_exp_quad_cov**(vectors x, real sigma, real length_scale)

Gaussian process covariance with exponentiated quadratic kernel in multiple dimensions.

Available since 2.20

matrix **gp_exp_quad_cov**(vectors x, real sigma, array[] real length_scale)

Gaussian process covariance with exponentiated quadratic kernel in multiple dimensions with a length scale for each dimension.

Available since 2.20

matrix **gp_exp_quad_cov**(vectors x1, vectors x2, real sigma, real length_scale)

Gaussian process cross-covariance of x1 and x2 with exponentiated quadratic kernel in multiple dimensions.

Available since 2.20

matrix **gp_exp_quad_cov**(vectors x1, vectors x2, real sigma, array[] real length_scale)

Gaussian process cross-covariance of x1 and x2 with exponentiated quadratic kernel in multiple dimensions with a length scale for each dimension.

Available since 2.20

Dot product kernel

With bias σ_0 the dot product kernel is:

$$k(\mathbf{x}_i, \mathbf{x}_j) = \sigma_0^2 + \mathbf{x}_i^T \mathbf{x}_j$$

matrix **gp_dot_prod_cov**(array[] real x, real sigma)

Gaussian process covariance with dot product kernel in one dimension.

Available since 2.20

matrix **gp_dot_prod_cov**(array[] real x1, array[] real x2, real sigma)

Gaussian process cross-covariance of x1 and x2 with dot product kernel in one dimension.

Available since 2.20

matrix **gp_dot_prod_cov**(vectors x, real sigma)

Gaussian process covariance with dot product kernel in multiple dimensions.

Available since 2.20

matrix **gp_dot_prod_cov**(vectors x1, vectors x2, real sigma)

Gaussian process cross-covariance of x1 and x2 with dot product kernel in multiple dimensions.

Available since 2.20

Exponential kernel

With magnitude σ and length scale l , the exponential kernel is:

$$k(\mathbf{x}_i, \mathbf{x}_j) = \sigma^2 \exp\left(-\frac{|\mathbf{x}_i - \mathbf{x}_j|}{l}\right)$$

matrix **gp_exponential_cov**(array[] real x, real sigma, real length_scale)

Gaussian process covariance with exponential kernel in one dimension.

Available since 2.20

matrix **gp_exponential_cov**(array[] real x1, array[] real x2, real sigma, real length_scale)

Gaussian process cross-covariance of x1 and x2 with exponential kernel in one dimension.

Available since 2.20

matrix **gp_exponential_cov**(vectors x, real sigma, real length_scale)

Gaussian process covariance with exponential kernel in multiple dimensions.

Available since 2.20

matrix **gp_exponential_cov**(vectors x, real sigma, array[] real length_scale)

Gaussian process covariance with exponential kernel in multiple dimensions with a length scale for each dimension.

Available since 2.20

matrix **gp_exponential_cov**(vectors x1, vectors x2, real sigma, real length_scale)

Gaussian process cross-covariance of x1 and x2 with exponential kernel in multiple dimensions.

Available since 2.20

matrix **gp_exponential_cov**(vectors x1, vectors x2, real sigma, array[] real length_scale)

Gaussian process cross-covariance of x1 and x2 with exponential kernel in multiple dimensions with a length scale for each dimension.

Available since 2.20

Matern 3/2 kernel

With magnitude σ and length scale l , the Matern 3/2 kernel is:

$$k(\mathbf{x}_i, \mathbf{x}_j) = \sigma^2 \left(1 + \frac{\sqrt{3}|\mathbf{x}_i - \mathbf{x}_j|}{l} \right) \exp \left(-\frac{\sqrt{3}|\mathbf{x}_i - \mathbf{x}_j|}{l} \right)$$

matrix **gp_matern32_cov**(array[] real x, real sigma, real length_scale)

Gaussian process covariance with Matern 3/2 kernel in one dimension.

Available since 2.20

matrix **gp_matern32_cov**(array[] real x1, array[] real x2, real sigma, real length_scale)

Gaussian process cross-covariance of x1 and x2 with Matern 3/2 kernel in one dimension.

Available since 2.20

matrix **gp_matern32_cov**(vectors x, real sigma, real length_scale)

Gaussian process covariance with Matern 3/2 kernel in multiple dimensions.

Available since 2.20

matrix **gp_matern32_cov**(vectors x, real sigma, array[] real length_scale)

Gaussian process covariance with Matern 3/2 kernel in multiple dimensions with a length scale for each dimension.

Available since 2.20

matrix **gp_matern32_cov**(vectors x1, vectors x2, real sigma, real length_scale)

Gaussian process cross-covariance of x1 and x2 with Matern 3/2 kernel in multiple dimensions.

Available since 2.20

matrix **gp_matern32_cov**(vectors x1, vectors x2, real sigma, array[] real length_scale)

Gaussian process cross-covariance of x1 and x2 with Matern 3/2 kernel in multiple dimensions with a length scale for each dimension.

Available since 2.20

Matern 5/2 kernel

With magnitude σ and length scale l , the Matern 5/2 kernel is:

$$k(\mathbf{x}_i, \mathbf{x}_j) = \sigma^2 \left(1 + \frac{\sqrt{5}|\mathbf{x}_i - \mathbf{x}_j|}{l} + \frac{5|\mathbf{x}_i - \mathbf{x}_j|^2}{3l^2} \right) \exp \left(-\frac{\sqrt{5}|\mathbf{x}_i - \mathbf{x}_j|}{l} \right)$$

matrix **gp_matern52_cov**(array[] real x, real sigma, real length_scale)

Gaussian process covariance with Matern 5/2 kernel in one dimension.

Available since 2.20

matrix **gp_matern52_cov**(array[] real x1, array[] real x2, real sigma, real length_scale)

Gaussian process cross-covariance of x1 and x2 with Matern 5/2 kernel in one dimension.

Available since 2.20

matrix **gp_matern52_cov**(vectors x, real sigma, real length_scale)

Gaussian process covariance with Matern 5/2 kernel in multiple dimensions.

Available since 2.20

matrix **gp_matern52_cov**(vectors x, real sigma, array[] real length_scale)

Gaussian process covariance with Matern 5/2 kernel in multiple dimensions with a length scale for each dimension.

Available since 2.20

matrix **gp_matern52_cov**(vectors x1, vectors x2, real sigma, real length_scale)

Gaussian process cross-covariance of x1 and x2 with Matern 5/2 kernel in multiple dimensions.

Available since 2.20

matrix **gp_matern52_cov**(vectors x1, vectors x2, real sigma, array[] real length_scale)

Gaussian process cross-covariance of x1 and x2 with Matern 5/2 kernel in multiple dimensions with a length scale for each dimension.

Available since 2.20

Periodic kernel

With magnitude σ , length scale l , and period p , the periodic kernel is:

$$k(\mathbf{x}_i, \mathbf{x}_j) = \sigma^2 \exp\left(-\frac{2 \sin^2\left(\pi \frac{|\mathbf{x}_i - \mathbf{x}_j|}{p}\right)}{l^2}\right)$$

matrix **gp_periodic_cov**(array[] real x, real sigma, real length_scale, real period)

Gaussian process covariance with periodic kernel in one dimension.

Available since 2.20

matrix **gp_periodic_cov**(array[] real x1, array[] real x2, real sigma, real length_scale, real period)

Gaussian process cross-covariance of x1 and x2 with periodic kernel in one dimension.

Available since 2.20

matrix **gp_periodic_cov**(vectors x, real sigma, real length_scale, real period)

Gaussian process covariance with periodic kernel in multiple dimensions.

Available since 2.20

matrix **gp_periodic_cov**(vectors x1, vectors x2, real sigma, real length_scale, real period)

Gaussian process cross-covariance of x1 and x2 with periodic kernel in multiple dimensions with a length scale for each dimension.

Available since 2.20

6.14. Linear algebra functions and solvers

Matrix division operators and functions

In general, it is much more efficient and also more arithmetically stable to use matrix division than to multiply by an inverse. There are specialized forms for lower triangular matrices and for symmetric, positive-definite matrices.

Matrix division operators

row_vector **operator/**(row_vector b, matrix A)

The right division of b by A; equivalently $b * \text{inverse}(A)$

Available since 2.0

matrix **operator/**(matrix B, matrix A)

The right division of B by A; equivalently $B * \text{inverse}(A)$

Available since 2.5

vector **operator**\(matrix A, vector b)

The left division of A by b; equivalently $\text{inverse}(A) * b$

Available since 2.18

matrix **operator**\(matrix A, matrix B)

The left division of A by B; equivalently $\text{inverse}(A) * B$

Available since 2.18

Lower-triangular matrix division functions

There are four division functions which use lower triangular views of a matrix. The lower triangular view of a matrix $\text{tri}(A)$ is used in the definitions and defined by

$$\text{tri}(A)[m, n] = \begin{cases} A[m, n] & \text{if } m \geq n, \text{ and} \\ 0 & \text{otherwise.} \end{cases}$$

When a lower triangular view of a matrix is used, the elements above the diagonal are ignored.

vector **mdivide_left_tri_low**(matrix A, vector b)

The left division of b by a lower-triangular view of A; algebraically equivalent to the less efficient and stable form $\text{inverse}(\text{tri}(A)) * b$, where $\text{tri}(A)$ is the lower-triangular portion of A with the above-diagonal entries set to zero.

Available since 2.12

matrix **mdivide_left_tri_low**(matrix A, matrix B)

The left division of B by a triangular view of A; algebraically equivalent to the less efficient and stable form $\text{inverse}(\text{tri}(A)) * B$, where $\text{tri}(A)$ is the lower-triangular portion of A with the above-diagonal entries set to zero.

Available since 2.5

row_vector **mdivide_right_tri_low**(row_vector b, matrix A)

The right division of b by a triangular view of A; algebraically equivalent to the less efficient and stable form $b * \text{inverse}(\text{tri}(A))$, where $\text{tri}(A)$ is the lower-triangular portion of A with the above-diagonal entries set to zero.

Available since 2.12

matrix **mdivide_right_tri_low**(matrix B, matrix A)

The right division of B by a triangular view of A; algebraically equivalent to the less efficient and stable form $B * \text{inverse}(\text{tri}(A))$, where $\text{tri}(A)$ is the lower-triangular portion of A with the above-diagonal entries set to zero.

Available since 2.5

Symmetric positive-definite matrix division functions

There are four division functions which are specialized for efficiency and stability for symmetric positive-definite matrix dividends. If the matrix dividend argument is not symmetric and positive definite, these will reject and print warnings.

matrix **mdivide_left_spd**(matrix A, vector b)

The left division of b by the symmetric, positive-definite matrix A; algebraically equivalent to the less efficient and stable form `inverse(A) * b`.

Available since 2.12

vector **mdivide_left_spd**(matrix A, matrix B)

The left division of B by the symmetric, positive-definite matrix A; algebraically equivalent to the less efficient and stable form `inverse(A) * B`.

Available since 2.12

row_vector **mdivide_right_spd**(row_vector b, matrix A)

The right division of b by the symmetric, positive-definite matrix A; algebraically equivalent to the less efficient and stable form `b * inverse(A)`.

Available since 2.12

matrix **mdivide_right_spd**(matrix B, matrix A)

The right division of B by the symmetric, positive-definite matrix A; algebraically equivalent to the less efficient and stable form `B * inverse(A)`.

Available since 2.12

Matrix exponential

The exponential of the matrix *A* is formally defined by the convergent power series:

$$e^A = \sum_{n=0}^{\infty} \frac{A^n}{n!}$$

matrix **matrix_exp**(matrix A)

The matrix exponential of A

Available since 2.13

matrix **matrix_exp_multiply**(matrix A, matrix B)

The multiplication of matrix exponential of A and matrix B; algebraically equivalent to the less efficient form `matrix_exp(A) * B`.

Available since 2.18

matrix **scale_matrix_exp_multiply**(real t, matrix A, matrix B)

The multiplication of matrix exponential of tA and matrix B; algebraically equivalent to the less efficient form `matrix_exp(t * A) * B`.

Available since 2.18

Matrix power

Returns the nth power of the specific matrix:

$$M^n = M_1 * \dots * M_n$$

matrix **matrix_power**(matrix A, int B)

Matrix A raised to the power B.

Available since 2.24

Linear algebra functions

Trace

real **trace**(matrix A)

The trace of A, or 0 if A is empty; A is not required to be diagonal

Available since 2.0

Determinants

real **determinant**(matrix A)

The determinant of A

Available since 2.0

real **log_determinant**(matrix A)

The log of the absolute value of the determinant of A

Available since 2.0

real **log_determinant_spd**(matrix A)

The log of the absolute value of the determinant of the symmetric, positive-definite matrix A.

Available since 2.30

Inverses

It is almost never a good idea to use matrix inverses directly because they are both inefficient and arithmetically unstable compared to the alternatives. Rather

than inverting a matrix m and post-multiplying by a vector or matrix a , as in `inverse(m) * a`, it is better to code this using matrix division, as in `m \ a`. The pre-multiplication case is similar, with `b * inverse(m)` being more efficiently coded as `as b / m`. There are also useful special cases for triangular and symmetric, positive-definite matrices that use more efficient solvers.

Warning: The function `inv(m)` is the elementwise inverse function, which returns `1 / m[i, j]` for each element.

`matrix inverse(matrix A)`

Compute the inverse of A

Available since 2.0

`matrix inverse_spd(matrix A)`

Compute the inverse of A where A is symmetric, positive definite. This version is faster and more arithmetically stable when the input is symmetric and positive definite.

Available since 2.0

`matrix chol2inv(matrix L)`

Compute the inverse of the matrix whose cholesky factorization is L . That is, for $A = LL^T$, return A^{-1} .

Available since 2.26

Generalized Inverse

The generalized inverse M^+ of a matrix M is a matrix that satisfies $MM^+M = M$. For an invertible, square matrix M , M^+ is equivalent to M^{-1} . The dimensions of M^+ are equivalent to the dimensions of M^T . The generalized inverse exists for any matrix, so the M may be singular or less than full rank.

Even though the generalized inverse exists for any arbitrary matrix, the derivatives of this function only exist on matrices of locally constant rank (Golub and Pereyra 1973), meaning, the derivatives do not exist if small perturbations make the matrix change rank. For example, considered the rank of the matrix A as a function of ϵ :

$$A = \begin{pmatrix} 1 + \epsilon & 2 & 1 \\ 2 & 4 & 2 \end{pmatrix}$$

When $\epsilon = 0$, A is rank 1 because the second row is twice the first (and so there is only one linearly independent row). If $\epsilon \neq 0$, the rows are no longer linearly dependent, and the matrix is rank 2. This matrix does not have locally constant

rank at $\epsilon = 0$, and so the derivatives do not exist at zero. Because HMC depends on the derivatives existing, this lack of differentiability creates undefined behavior.

matrix **generalized_inverse**(matrix A)

The generalized inverse of A

Available since 2.26

Eigendecomposition

complex_vector **eigenvalues**(matrix A)

The complex-valued vector of eigenvalues of the matrix A. The eigenvalues are repeated according to their algebraic multiplicity, so there are as many eigenvalues as rows in the matrix. The eigenvalues are not sorted in any particular order.

Available since 2.30

complex_matrix **eigenvectors**(matrix A)

The matrix with the complex-valued (column) eigenvectors of the matrix A in the same order as returned by the function `eigenvalues`

Available since 2.30

tuple(complex_matrix, complex_vector) **eigendecompose**(matrix A)

Return the matrix of (column) eigenvectors and vector of eigenvalues of the matrix A. This function is equivalent to `(eigenvectors(A), eigenvalues(A))` but with a lower computational cost due to the shared work between the two results.

Available since 2.33

vector **eigenvalues_sym**(matrix A)

The vector of eigenvalues of a symmetric matrix A in ascending order

Available since 2.0

matrix **eigenvectors_sym**(matrix A)

The matrix with the (column) eigenvectors of symmetric matrix A in the same order as returned by the function `eigenvalues_sym`

Available since 2.0

tuple(matrix, vector) **eigendecompose_sym**(matrix A)

Return the matrix of (column) eigenvectors and vector of eigenvalues of the symmetric matrix A. This function is equivalent to `(eigenvectors_sym(A), eigenvalues_sym(A))` but with a lower computational cost due to the shared work between the two results.

Available since 2.33

Because multiplying an eigenvector by -1 results in an eigenvector, eigenvectors returned by a decomposition are only identified up to a sign change. In order to compare the eigenvectors produced by Stan's eigendecomposition to others, signs may need to be normalized in some way, such as by fixing the sign of a component, or doing comparisons allowing a multiplication by -1 .

The condition number of a symmetric matrix is defined to be the ratio of the largest eigenvalue to the smallest eigenvalue. Large condition numbers lead to difficulty in numerical algorithms such as computing inverses, and thus known as "ill conditioned." The ratio can even be infinite in the case of singular matrices (i.e., those with eigenvalues of 0).

QR decomposition

`matrix qr_thin_Q(matrix A)`

The orthogonal matrix in the thin QR decomposition of A , which implies that the resulting matrix has the same dimensions as A

Available since 2.18

`matrix qr_thin_R(matrix A)`

The upper triangular matrix in the thin QR decomposition of A , which implies that the resulting matrix is square with the same number of columns as A

Available since 2.18

`tuple(matrix, matrix) qr_thin(matrix A)`

Returns both portions of the QR decomposition of A . The first element ("Q") is the orthonormal matrix in the thin QR decomposition and the second element ("R") is upper triangular. This function is equivalent to `(qr_thin_Q(A), qr_thin_R(A))` but with a lower computational cost due to the shared work between the two results.

Available since 2.33

`matrix qr_Q(matrix A)`

The orthogonal matrix in the fat QR decomposition of A , which implies that the resulting matrix is square with the same number of rows as A

Available since 2.3

`matrix qr_R(matrix A)`

The upper trapezoidal matrix in the fat QR decomposition of A , which implies that the resulting matrix will be rectangular with the same dimensions as A

Available since 2.3

`tuple(matrix, matrix) qr(matrix A)`

Returns both portions of the QR decomposition of A. The first element (“Q”) is the orthonormal matrix in the thin QR decomposition and the second element (“R”) is upper triangular. This function is equivalent to `(qr_Q(A), qr_R(A))` but with a lower computational cost due to the shared work between the two results.

Available since 2.33

The thin QR decomposition is always preferable because it will consume much less memory when the input matrix is large than will the fat QR decomposition. Both versions of the decomposition represent the input matrix as

$$A = QR.$$

Multiplying a column of an orthogonal matrix by -1 still results in an orthogonal matrix, and you can multiply the corresponding row of the upper trapezoidal matrix by -1 without changing the product. Thus, Stan adopts the normalization that the diagonal elements of the upper trapezoidal matrix are strictly positive and the columns of the orthogonal matrix are reflected if necessary. Also, these QR decomposition algorithms do not utilize pivoting and thus may be numerically unstable on input matrices that have less than full rank.

Cholesky decomposition

Every symmetric, positive-definite matrix (such as a correlation or covariance matrix) has a Cholesky decomposition. If Σ is a symmetric, positive-definite matrix, its Cholesky decomposition is the lower-triangular vector L such that

$$\Sigma = LL^T.$$

`matrix cholesky_decompose(matrix A)`

The lower-triangular Cholesky factor of the symmetric positive-definite matrix A

Available since 2.0

Singular value decomposition

The matrix A can be decomposed into a diagonal matrix of singular values, D, and matrices of its left and right singular vectors, U and V,

$$A = UDV^T.$$

The matrices of singular vectors here are thin. That is for an N by P input A, $M = \min(N, P)$, U is size N by M and V is size P by M .

vector **singular_values**(matrix A)
The singular values of A in descending order

Available since 2.0

matrix **svd_U**(matrix A)
The left-singular vectors of A

Available since 2.26

matrix **svd_V**(matrix A)
The right-singular vectors of A

Available since 2.26

tuple(matrix, vector, matrix) **svd**(matrix A)
Returns a tuple containing the left-singular vectors of A, the singular values of A in descending order, and the right-singular values of A. This function is equivalent to `(svd_U(A), singular_values(A), svd_V(A))` but with a lower computational cost due to the shared work between the different components.

Available since 2.33

6.15. Sort functions

See the [sorting functions section](#) for examples of how the functions work.

vector **sort_asc**(vector v)
Sort the elements of v in ascending order

Available since 2.0

row_vector **sort_asc**(row_vector v)
Sort the elements of v in ascending order

Available since 2.0

vector **sort_desc**(vector v)
Sort the elements of v in descending order

Available since 2.0

row_vector **sort_desc**(row_vector v)
Sort the elements of v in descending order

Available since 2.0

array[] int **sort_indices_asc**(vector v)

Return an array of indices between 1 and the size of v, sorted to index v in ascending order.

Available since 2.3

array[] int **sort_indices_asc**(row_vector v)

Return an array of indices between 1 and the size of v, sorted to index v in ascending order.

Available since 2.3

array[] int **sort_indices_desc**(vector v)

Return an array of indices between 1 and the size of v, sorted to index v in descending order.

Available since 2.3

array[] int **sort_indices_desc**(row_vector v)

Return an array of indices between 1 and the size of v, sorted to index v in descending order.

Available since 2.3

int **rank**(vector v, int s)

Number of components of v less than v[s]

Available since 2.0

int **rank**(row_vector v, int s)

Number of components of v less than v[s]

Available since 2.0

6.16. Reverse functions

vector **reverse**(vector v)

Return a new vector containing the elements of the argument in reverse order.

Available since 2.23

row_vector **reverse**(row_vector v)

Return a new row vector containing the elements of the argument in reverse order.

Available since 2.23

7. Complex Matrix Operations

7.1. Complex promotion

This chapter provides the details of functions that operate over complex matrices, vectors, and row vectors. These mirror the operations over real `complex_matrix` types and are defined in the usual way for complex numbers.

Promotion of complex arguments

If an expression `e` can be assigned to a variable of type `T`, then it can be used as an argument to a function that is specified to take arguments of type `T`. For instance, `sqrt(real)` is specified to take a `real` argument, but an integer expression such as `2 + 2` of type `int` can be passed to `sqrt`, so that `sqrt(2 + 2)` is well defined. This works by promoting the integer expression `2 + 2` to be of `real` type.

The rules for promotion in Stan are simple:

- `int` may be promoted to `real`,
- `real` may be promoted to `complex`,
- `vector` can be promoted to `complex_vector`,
- `row_vector` can be promoted to `complex_row_vector`,
- `matrix` can be promoted to `complex_matrix`,
- if `T` can be promoted to `U` and `U` can be promoted to `V`, then `T` can be promoted to `V` (transitive), and
- if `T` can be promoted to `U`, then `T[]` can be promoted to `U[]` (covariant).

Signature selection

When a function is called, the definition requiring the fewest number of promotions is used. For example, when calling `vector + vector`, the real-valued signature is used. When calling any of `complex_vector + vector`, `vector + complex_vector`, or `complex_vector + complex_vector`, the complex signature is used. If more than one signature matches with a the minimal number of promotions, the call is ambiguous, and an error will be raised by the compiler. Promotion ambiguity leading to ill-defined calls should never happen with Stan built-in functions.

Signatures for complex functions

Complex function signatures will only list the fully complex type. For example, with complex vector addition, we will list a single signature, `complex operator+(complex_vector, complex_vector)`. Through promotion, `operator+` may

be called with one complex vector and one real vector as well, but the documentation elides the implied signatures `operator+(complex_vector, vector)` and `operator+(vector, complex_vector)`.

Generic functions work for complex containers

Generic functions work for arrays containing complex, complex matrix, complex vector, or complex row vector types. This includes the functions `append_array`, `dims`, `head`, `num_elements`, `rep_array`, `reverse`, `segment`, `size`, and `tail`.

7.2. Integer-valued complex matrix size functions

`int num_elements(complex_vector x)`

The total number of elements in the vector `x` (same as function `rows`)

Available since 2.30

`int num_elements(complex_row_vector x)`

The total number of elements in the vector `x` (same as function `cols`)

Available since 2.30

`int num_elements(complex_matrix x)`

The total number of elements in the matrix `x`. For example, if `x` is a 5×3 matrix, then `num_elements(x)` is 15

Available since 2.30

`int rows(complex_vector x)`

The number of rows in the vector `x`

Available since 2.30

`int rows(complex_row_vector x)`

The number of rows in the row vector `x`, namely 1

Available since 2.30

`int rows(complex_matrix x)`

The number of rows in the matrix `x`

Available since 2.30

`int cols(complex_vector x)`

The number of columns in the vector `x`, namely 1

Available since 2.30

int **cols**(complex_row_vector x)

The number of columns in the row vector x

Available since 2.30

int **cols**(complex_matrix x)

The number of columns in the matrix x

Available since 2.30

int **size**(complex_vector x)

The size of x, i.e., the number of elements

Available since 2.30

int **size**(complex_row_vector x)

The size of x, i.e., the number of elements

Available since 2.30

int **size**(matrix x)

The size of the matrix x. For example, if x is a 5×3 matrix, then `size(x)` is 15.

Available since 2.30

7.3. Complex matrix arithmetic operators

Stan supports all basic complex arithmetic operators using infix, prefix and postfix operations. This section lists the operations supported by Stan along with their argument and result types.

Negation prefix operators

complex_vector **operator-**(complex_vector x)

The negation of the vector x.

Available since 2.30

complex_row_vector **operator-**(complex_row_vector x)

The negation of the row vector x.

Available since 2.30

complex_matrix **operator-**(complex_matrix x)

The negation of the matrix x.

Available since 2.30

T operator-(T x)

Vectorized version of operator-. If T x is a (possibly nested) array of matrix types, -x is the same shape array where each individual value is negated.

Available since 2.31

Infix complex_matrix operators

complex_vector **operator+**(complex_vector x, complex_vector y)

The sum of the vectors x and y.

Available since 2.30

complex_row_vector **operator+**(complex_row_vector x, complex_row_vector y)

The sum of the row vectors x and y.

Available since 2.30

complex_matrix **operator+**(complex_matrix x, complex_matrix y)

The sum of the matrices x and y

Available since 2.30

complex_vector **operator-**(complex_vector x, complex_vector y)

The difference between the vectors x and y.

Available since 2.30

complex_row_vector **operator-**(complex_row_vector x, complex_row_vector y)

The difference between the row vectors x and y

Available since 2.30

complex_matrix **operator-**(complex_matrix x, complex_matrix y)

The difference between the matrices x and y

Available since 2.30

complex_vector **operator***(complex x, complex_vector y)

The product of the scalar x and vector y

Available since 2.30

complex_row_vector **operator***(complex x, complex_row_vector y)

The product of the scalar x and the row vector y

Available since 2.30

`complex_matrix operator*(complex x, complex_matrix y)`

The product of the scalar `x` and the matrix `y`

Available since 2.30

`complex_vector operator*(complex_vector x, complex y)`

The product of the scalar `y` and vector `x`

Available since 2.30

`complex_matrix operator*(complex_vector x, complex_row_vector y)`

The product of the vector `x` and row vector `y`

Available since 2.30

`complex_row_vector operator*(complex_row_vector x, complex y)`

The product of the scalar `y` and row vector `x`

Available since 2.30

`complex operator*(complex_row_vector x, complex_vector y)`

The product of the row vector `x` and vector `y`

Available since 2.30

`complex_row_vector operator*(complex_row_vector x, complex_matrix y)`

The product of the row vector `x` and matrix `y`

Available since 2.30

`complex_matrix operator*(complex_matrix x, complex y)`

The product of the scalar `y` and matrix `x`

Available since 2.30

`complex_vector operator*(complex_matrix x, complex_vector y)`

The product of the matrix `x` and vector `y`

Available since 2.30

`complex_matrix operator*(complex_matrix x, complex_matrix y)`

The product of the matrices `x` and `y`

Available since 2.30

Broadcast infix operators

`complex_vector` **operator+**(`complex_vector` x , `complex` y)

The result of adding y to every entry in the vector x

Available since 2.30

`complex_vector` **operator+**(`complex` x , `complex_vector` y)

The result of adding x to every entry in the vector y

Available since 2.30

`complex_row_vector` **operator+**(`complex_row_vector` x , `complex` y)

The result of adding y to every entry in the row vector x

Available since 2.30

`complex_row_vector` **operator+**(`complex` x , `complex_row_vector` y)

The result of adding x to every entry in the row vector y

Available since 2.30

`complex_matrix` **operator+**(`complex_matrix` x , `complex` y)

The result of adding y to every entry in the matrix x

Available since 2.30

`complex_matrix` **operator+**(`complex` x , `complex_matrix` y)

The result of adding x to every entry in the matrix y

Available since 2.30

`complex_vector` **operator-**(`complex_vector` x , `complex` y)

The result of subtracting y from every entry in the vector x

Available since 2.30

`complex_vector` **operator-**(`complex` x , `complex_vector` y)

The result of adding x to every entry in the negation of the vector y

Available since 2.30

`complex_row_vector` **operator-**(`complex_row_vector` x , `complex` y)

The result of subtracting y from every entry in the row vector x

Available since 2.30

`complex_row_vector` **operator-**(`complex` x , `complex_row_vector` y)

The result of adding x to every entry in the negation of the row vector y

Available since 2.30

`complex_matrix operator-`(`complex_matrix x`, `complex y`)

The result of subtracting `y` from every entry in the matrix `x`

Available since 2.30

`complex_matrix operator+`(`complex x`, `complex_matrix y`)

The result of adding `x` to every entry in negation of the matrix `y`

Available since 2.30

`complex_vector operator/`(`complex_vector x`, `complex y`)

The result of dividing each entry in the vector `x` by `y`

Available since 2.30

`complex_row_vector operator/`(`complex_row_vector x`, `complex y`)

The result of dividing each entry in the row vector `x` by `y`

Available since 2.30

`complex_matrix operator/`(`complex_matrix x`, `complex y`)

The result of dividing each entry in the matrix `x` by `y`

Available since 2.30

7.4. Complex Transposition Operator

Complex `complex_matrix` transposition is represented using a postfix operator.

`complex_matrix operator'`(`complex_matrix x`)

The transpose of the matrix `x`, written as `x'`

Available since 2.30

`complex_row_vector operator'`(`complex_vector x`)

The transpose of the vector `x`, written as `x'`

Available since 2.30

`complex_vector operator'`(`complex_row_vector x`)

The transpose of the row vector `x`, written as `x'`

Available since 2.30

7.5. Complex elementwise functions

As in the real case, elementwise complex functions apply a function to each element of a vector or matrix, returning a result of the same shape as the argument.

`complex_vector` **operator.***(`complex_vector` x, `complex_vector` y)

The elementwise product of x and y

Available since 2.30

`complex_row_vector` **operator.***(`complex_row_vector` x, `complex_row_vector` y)

The elementwise product of x and y

Available since 2.30

`complex_matrix` **operator.***(`complex_matrix` x, `complex_matrix` y)

The elementwise product of x and y

Available since 2.30

`complex_vector` **operator./**(`complex_vector` x, `complex_vector` y)

The elementwise quotient of x and y

Available since 2.30

`complex_vector` **operator./**(`complex` x, `complex_vector` y)

The elementwise quotient of x and y

Available since 2.30

`complex_vector` **operator./**(`complex_vector` x, `complex` y)

The elementwise quotient of x and y

Available since 2.30

`complex_row_vector` **operator./**(`complex_row_vector` x, `complex_row_vector` y)

The elementwise quotient of x and y

Available since 2.30

`complex_row_vector` **operator./**(`complex` x, `complex_row_vector` y)

The elementwise quotient of x and y

Available since 2.30

`complex_row_vector` **operator./**(`complex_row_vector` x, `complex` y)

The elementwise quotient of x and y

Available since 2.30

`complex_matrix operator./(complex_matrix x, complex_matrix y)`

The elementwise quotient of x and y

Available since 2.30

`complex_matrix operator./(complex x, complex_matrix y)`

The elementwise quotient of x and y

Available since 2.30

`complex_matrix operator./(complex_matrix x, complex y)`

The elementwise quotient of x and y

Available since 2.30

`vector operator.^(complex_vector x, complex_vector y)`

The elementwise power of y and x

Available since 2.30

`vector operator.^(complex_vector x, complex y)`

The elementwise power of y and x

Available since 2.30

`vector operator.^(complex x, complex_vector y)`

The elementwise power of y and x

Available since 2.30

`row_vector operator.^(complex_row_vector x, complex_row_vector y)`

The elementwise power of y and x

Available since 2.30

`row_vector operator.^(complex_row_vector x, complex y)`

The elementwise power of y and x

Available since 2.30

`row_vector operator.^(complex x, complex_row_vector y)`

The elementwise power of y and x

Available since 2.30

`matrix operator.^(complex_matrix x, complex_matrix y)`

The elementwise power of y and x

Available since 2.30

matrix **operator.**^(complex_matrix x, complex y)

The elementwise power of y and x

Available since 2.30

matrix **operator.**^(complex x, complex_matrix y)

The elementwise power of y and x

Available since 2.30

7.6. Dot products and specialized products for complex matrices

complex **dot_product**(complex_vector x, complex_vector y)

The dot product of x and y

Available since 2.30

complex **dot_product**(complex_vector x, complex_row_vector y)

The dot product of x and y

Available since 2.30

complex **dot_product**(complex_row_vector x, complex_vector y)

The dot product of x and y

Available since 2.30

complex **dot_product**(complex_row_vector x, complex_row_vector y)

The dot product of x and y

Available since 2.30

complex_row_vector **columns_dot_product**(complex_vector x, complex_vector y)

The dot product of the columns of x and y

Available since 2.30

complex_row_vector **columns_dot_product**(complex_row_vector x, complex_row_vector y)

The dot product of the columns of x and y

Available since 2.30

complex_row_vector **columns_dot_product**(complex_matrix x, complex_matrix y)

The dot product of the columns of x and y

Available since 2.30

`complex_vector` **rows_dot_product**(`complex_vector` x , `complex_vector` y)

The dot product of the rows of x and y

Available since 2.30

`complex_vector` **rows_dot_product**(`complex_row_vector` x , `complex_row_vector` y)

The dot product of the rows of x and y

Available since 2.30

`complex_vector` **rows_dot_product**(`complex_matrix` x , `complex_matrix` y)

The dot product of the rows of x and y

Available since 2.30

`complex` **dot_self**(`complex_vector` x)

The dot product of the vector x with itself

Available since 2.30

`complex` **dot_self**(`complex_row_vector` x)

The dot product of the row vector x with itself

Available since 2.30

`complex_row_vector` **columns_dot_self**(`complex_vector` x)

The dot product of the columns of x with themselves

Available since 2.30

`complex_row_vector` **columns_dot_self**(`complex_row_vector` x)

The dot product of the columns of x with themselves

Available since 2.30

`complex_row_vector` **columns_dot_self**(`complex_matrix` x)

The dot product of the columns of x with themselves

Available since 2.30

`complex_vector` **rows_dot_self**(`complex_vector` x)

The dot product of the rows of x with themselves

Available since 2.30

complex_vector **rows_dot_self**(complex_row_vector x)

The dot product of the rows of x with themselves

Available since 2.30

complex_vector **rows_dot_self**(complex_matrix x)

The dot product of the rows of x with themselves

Available since 2.30

Specialized products

complex_matrix **diag_pre_multiply**(complex_vector v, complex_matrix m)

Return the product of the diagonal matrix formed from the vector v and the matrix m, i.e., $\text{diag_matrix}(v) * m$.

Available since 2.30

complex_matrix **diag_pre_multiply**(complex_row_vector v, complex_matrix m)

Return the product of the diagonal matrix formed from the vector rv and the matrix m, i.e., $\text{diag_matrix}(rv) * m$.

Available since 2.30

complex_matrix **diag_post_multiply**(complex_matrix m, complex_vector v)

Return the product of the matrix m and the diagonal matrix formed from the vector v, i.e., $m * \text{diag_matrix}(v)$.

Available since 2.30

complex_matrix **diag_post_multiply**(complex_matrix m, complex_row_vector v)

Return the product of the matrix m and the diagonal matrix formed from the the row vector rv, i.e., $m * \text{diag_matrix}(rv)$.

Available since 2.30

7.7. Complex reductions

Sums and products

complex **sum**(complex_vector x)

The sum of the values in x, or 0 if x is empty

Available since 2.30

complex **sum**(complex_row_vector x)

The sum of the values in x, or 0 if x is empty

Available since 2.30

complex **sum**(complex_matrix x)

The sum of the values in x, or 0 if x is empty

Available since 2.30

complex **prod**(complex_vector x)

The product of the values in x, or 1 if x is empty

Available since 2.30

complex **prod**(complex_row_vector x)

The product of the values in x, or 1 if x is empty

Available since 2.30

complex **prod**(complex_matrix x)

The product of the values in x, or 1 if x is empty

Available since 2.30

7.8. Vectorized accessor functions

Much like with complex scalars, two functions are defined to get the real and imaginary components of complex-valued objects.

Type “demotion”

These functions return the same shape (e.g., matrix, vector, row vector, or array) object as their input, but demoted to a real type. For example, `get_real(complex_matrix M)` yields a matrix containing the real component of each value in M.

The following table contains examples of what this notation can mean:

Type T	Type T_demoted
complex	real
complex_vector	vector
complex_row_vector	row_vector
complex_matrix	matrix
array[] complex	array[] real
array[,] complex	array[,] real

Real and imaginary component accessor functions

`T_demoted` **get_real**(`T x`)

Given an object of complex type `T`, return the same shape object but of type `real` by getting the real component of each element of `x`.

Available since 2.30

`T_demoted` **get_imag**(`T x`)

Given an object of complex type `T`, return the same shape object but of type `real` by getting the imaginary component of each element of `x`.

Available since 2.30

For example, given the Stan declaration

```
complex_vector[2] z = [3+4i, 5+6i]';
```

A call `get_real(z)` will yield the vector `[3, 5]'`, and a call `get_imag(z)` will yield the vector `[4, 6]'`.

7.9. Complex broadcast functions

The following broadcast functions allow vectors, row vectors and matrices to be created by copying a single element into all of their cells. Matrices may also be created by stacking copies of row vectors vertically or stacking copies of column vectors horizontally.

`complex_vector` **rep_vector**(`complex z`, `int m`)

Return the size `m` (column) vector consisting of copies of `z`.

Available since 2.30

`complex_row_vector` **rep_row_vector**(`complex z`, `int n`)

Return the size `n` row vector consisting of copies of `z`.

Available since 2.30

`complex_matrix` **rep_matrix**(`complex z`, `int m`, `int n`)

Return the `m` by `n` matrix consisting of copies of `z`.

Available since 2.30

`complex_matrix` **rep_matrix**(`complex_vector v`, `int n`)

Return the `m` by `n` matrix consisting of `n` copies of the (column) vector `v` of size `m`.

Available since 2.30

`complex_matrix rep_matrix(complex_row_vector rv, int m)`
Return the m by n matrix consisting of m copies of the row vector rv of size n.

Available since 2.30

Symmetrization

`complex_matrix symmetrize_from_lower_tri(complex_matrix A)`
Construct a symmetric matrix from the lower triangle of A.

Available since 2.30

7.10. Diagonal complex matrix functions

`complex_matrix add_diag(complex_matrix m, complex_row_vector d)`
Add row_vector d to the diagonal of matrix m.

Available since 2.30

`complex_matrix add_diag(complex_matrix m, complex_vector d)`
Add vector d to the diagonal of matrix m.

Available since 2.30

`complex_matrix add_diag(complex_matrix m, complex d)`
Add scalar d to every diagonal element of matrix m.

Available since 2.30

`complex_vector diagonal(complex_matrix x)`
The diagonal of the matrix x

Available since 2.30

`complex_matrix diag_matrix(complex_vector x)`
The diagonal matrix with diagonal x

Available since 2.30

7.11. Slicing and blocking functions for complex matrices

Stan provides several functions for generating slices or blocks or diagonal entries for matrices.

Columns and rows

`complex_vector col(complex_matrix x, int n)`
The n-th column of matrix x

Available since 2.30

complex_row_vector **row**(complex_matrix x, int m)

The m-th row of matrix x

Available since 2.30

Block operations

Matrix slicing operations

complex_matrix **block**(complex_matrix x, int i, int j, int n_rows, int n_cols)

Return the submatrix of x that starts at row i and column j and extends n_rows rows and n_cols columns.

Available since 2.30

complex_vector **sub_col**(complex_matrix x, int i, int j, int n_rows)

Return the sub-column of x that starts at row i and column j and extends n_rows rows and 1 column.

Available since 2.30

complex_row_vector **sub_row**(complex_matrix x, int i, int j, int n_cols)

Return the sub-row of x that starts at row i and column j and extends 1 row and n_cols columns.

Available since 2.30

Vector slicing operations.

complex_vector **head**(complex_vector v, int n)

Return the vector consisting of the first n elements of v.

Available since 2.30

complex_row_vector **head**(complex_row_vector rv, int n)

Return the row vector consisting of the first n elements of rv.

Available since 2.30

complex_vector **tail**(complex_vector v, int n)

Return the vector consisting of the last n elements of v.

Available since 2.30

complex_row_vector **tail**(complex_row_vector rv, int n)

Return the row vector consisting of the last n elements of rv.

Available since 2.30

`complex_vector` **segment**(`complex_vector` v, `int` i, `int` n)

Return the vector consisting of the n elements of v starting at i; i.e., elements i through through i + n - 1.

Available since 2.30

`complex_row_vector` **segment**(`complex_row_vector` rv, `int` i, `int` n)

Return the row vector consisting of the n elements of rv starting at i; i.e., elements i through through i + n - 1.

Available since 2.30

7.12. Complex matrix concatenation

Horizontal concatenation

`complex_matrix` **append_col**(`complex_matrix` x, `complex_matrix` y)

Combine matrices x and y by column. The matrices must have the same number of rows.

Available since 2.30

`complex_matrix` **append_col**(`complex_matrix` x, `complex_vector` y)

Combine matrix x and vector y by column. The matrix and the vector must have the same number of rows.

Available since 2.30

`complex_matrix` **append_col**(`complex_vector` x, `complex_matrix` y)

Combine vector x and matrix y by column. The vector and the matrix must have the same number of rows.

Available since 2.30

`complex_matrix` **append_col**(`complex_vector` x, `complex_vector` y)

Combine vectors x and y by column. The vectors must have the same number of rows.

Available since 2.30

`complex_row_vector` **append_col**(`complex_row_vector` x, `complex_row_vector` y)

Combine row vectors x and y (of any size) into another row vector by appending y to the end of x.

Available since 2.30

`complex_row_vector` **append_col**(`complex` x, `complex_row_vector` y)
Append x to the front of y, returning another row vector.

Available since 2.30

`complex_row_vector` **append_col**(`complex_row_vector` x, `complex` y)
Append y to the end of x, returning another row vector.

Available since 2.30

Vertical concatenation

`complex_matrix` **append_row**(`complex_matrix` x, `complex_matrix` y)
Combine matrices x and y by row. The matrices must have the same number of columns.

Available since 2.30

`complex_matrix` **append_row**(`complex_matrix` x, `complex_row_vector` y)
Combine matrix x and row vector y by row. The matrix and the row vector must have the same number of columns.

Available since 2.30

`complex_matrix` **append_row**(`complex_row_vector` x, `complex_matrix` y)
Combine row vector x and matrix y by row. The row vector and the matrix must have the same number of columns.

Available since 2.30

`complex_matrix` **append_row**(`complex_row_vector` x, `complex_row_vector` y)
Combine row vectors x and y by row. The row vectors must have the same number of columns.

Available since 2.30

`complex_vector` **append_row**(`complex_vector` x, `complex_vector` y)
Concatenate vectors x and y of any size into another vector.

Available since 2.30

`complex_vector` **append_row**(`complex` x, `complex_vector` y)
Append x to the top of y, returning another vector.

Available since 2.30

`complex_vector` **append_row**(`complex_vector` x, `complex` y)
Append y to the bottom of x, returning another vector.

Available since 2.30

7.13. Complex special matrix functions

Fast Fourier transforms

Stan's fast Fourier transform functions take the standard definition of the discrete Fourier transform (see the definitions below for specifics) and scale the inverse transform by one over dimensionality so that the following identities hold for complex vectors u and v ,

$$\text{fft}(\text{inv_fft}(u)) == u \quad \text{inv_fft}(\text{fft}(v)) == v$$

and in the 2-dimensional case for complex matrices A and B ,

$$\text{fft2}(\text{inv_fft2}(A)) == A \quad \text{inv_fft2}(\text{fft2}(B)) == B$$

Although the FFT functions only accept complex inputs, real vectors and matrices will be promoted to their complex counterparts before applying the FFT functions.

`complex_vector` **fft**(`complex_vector` v)

Return the discrete Fourier transform of the specified complex vector v . If $v \in \mathbb{C}^N$ is a complex vector with N elements and $u = \text{fft}(v)$, then

$$u_n = \sum_{m < n} v_m \cdot \exp\left(\frac{-n \cdot m \cdot 2 \cdot \pi \cdot \sqrt{-1}}{N}\right).$$

Available since 2.30

`complex_matrix` **fft2**(`complex_matrix` m)

Return the 2D discrete Fourier transform of the specified complex matrix m . The 2D FFT is defined as the result of applying the FFT to each row and then to each column.

Available since 2.30

`complex_vector` **inv_fft**(`complex_vector` u)

Return the inverse of the discrete Fourier transform of the specified complex vector u . The inverse FFT (this function) is scaled so that $\text{fft}(\text{inv_fft}(u)) == u$. If $u \in \mathbb{C}^N$ is a complex vector with N elements and $v = \text{fft}^{-1}(u)$, then

$$v_n = \frac{1}{N} \sum_{m < n} u_m \cdot \exp\left(\frac{n \cdot m \cdot 2 \cdot \pi \cdot \sqrt{-1}}{N}\right).$$

This only differs from the FFT by the sign inside the exponential and the scaling. The $\frac{1}{N}$ scaling ensures that $\text{fft}(\text{inv_fft}(u)) == u$ and $\text{inv_fft}(\text{fft}(v)) == v$ for complex vectors u and v .

Available since 2.30

`complex_matrix` **inv_fft2**(`complex_matrix` m)

Return the inverse of the 2D discrete Fourier transform of the specified complex matrix m . The 2D inverse FFT is defined as the result of applying the inverse FFT to each row and then to each column. The invertible scaling of the inverse FFT ensures $\text{fft2}(\text{inv_fft2}(A)) == A$ and $\text{inv_fft2}(\text{fft2}(B)) == B$.

Available since 2.30

Cumulative sums

The cumulative sum of a sequence x_1, \dots, x_N is the sequence y_1, \dots, y_N , where

$$y_n = \sum_{m=1}^n x_m.$$

`array[]` `complex` **cumulative_sum**(`array[]` `complex` x)

The cumulative sum of x

Available since 2.30

`complex_vector` **cumulative_sum**(`complex_vector` v)

The cumulative sum of v

Available since 2.30

`complex_row_vector` **cumulative_sum**(`complex_row_vector` rv)

The cumulative sum of rv

Available since 2.30

7.14. Complex linear algebra functions

Complex matrix division operators and functions

In general, it is much more efficient and also more arithmetically stable to use matrix division than to multiply by an inverse.

Complex matrix division operators

`complex_row_vector` **operator/**(`complex_row_vector` b, `complex_matrix` A)

The right division of b by A ; equivalently $b * \text{inverse}(A)$

Available since 2.30

complex_matrix **operator/**(complex_matrix B, complex_matrix A)
The right division of B by A; equivalently $B * \text{inverse}(A)$

Available since 2.30

Linear algebra functions

Trace

complex **trace**(complex_matrix A)

The trace of A, or 0 if A is empty; A is not required to be diagonal

Available since 2.30

Eigendecomposition

complex_vector **eigenvalues**(complex_matrix A)

The complex-valued vector of eigenvalues of the matrix A. The eigenvalues are repeated according to their algebraic multiplicity, so there are as many eigenvalues as rows in the matrix. The eigenvalues are not sorted in any particular order.

Available since 2.32

complex_matrix **eigenvectors**(complex_matrix A)

The matrix with the complex-valued (column) eigenvectors of the matrix A in the same order as returned by the function `eigenvalues`

Available since 2.32

tuple(complex_matrix, complex_vector) **eigendecompose**(complex_matrix A)

Return the matrix of (column) eigenvectors and vector of eigenvalues of the matrix A. This function is equivalent to `(eigenvectors(A), eigenvalues(A))` but with a lower computational cost due to the shared work between the two results.

Available since 2.33

complex_vector **eigenvalues_sym**(complex_matrix A)

The vector of eigenvalues of a symmetric matrix A in ascending order

Available since 2.30

complex_matrix **eigenvectors_sym**(complex_matrix A)

The matrix with the (column) eigenvectors of symmetric matrix A in the same order as returned by the function `eigenvalues_sym`

Available since 2.30

`tuple(complex_matrix, complex_vector)` **eigendecom-
pose_sym**(`complex_matrix A`)

Return the matrix of (column) eigenvectors and vector of eigenvalues of the symmetric matrix A . This function is equivalent to `(eigenvectors_sym(A), eigenvalues_sym(A))` but with a lower computational cost due to the shared work between the two results.

Available since 2.33

Because multiplying an eigenvector by -1 results in an eigenvector, eigenvectors returned by a decomposition are only identified up to a sign change. In order to compare the eigenvectors produced by Stan's eigendecomposition to others, signs may need to be normalized in some way, such as by fixing the sign of a component, or doing comparisons allowing a multiplication by -1 .

The condition number of a symmetric matrix is defined to be the ratio of the largest eigenvalue to the smallest eigenvalue. Large condition numbers lead to difficulty in numerical algorithms such as computing inverses, and thus known as "ill conditioned." The ratio can even be infinite in the case of singular matrices (i.e., those with eigenvalues of 0).

Singular value decomposition

The matrix A can be decomposed into a diagonal matrix of singular values, D , and matrices of its left and right singular vectors, U and V ,

$$A = UDV^T.$$

The matrices of singular vectors here are thin. That is for an N by P input A , $M = \min(N, P)$, U is size N by M and V is size P by M .

`vector singular_values`(`complex_matrix A`)

The singular values of A in descending order

Available since 2.30

`complex_matrix svd_U`(`complex_matrix A`)

The left-singular vectors of A

Available since 2.30

`complex_matrix svd_V`(`complex_matrix A`)

The right-singular vectors of A

Available since 2.30

`tuple(complex_matrix, vector, complex_matrix) svd(complex_matrix A)`
 Returns a tuple containing the left-singular vectors of A , the singular values of A in descending order, and the right-singular values of A . This function is equivalent to `(svd_U(A), singular_values(A), svd_V(A))` but with a lower computational cost due to the shared work between the different components.

Available since 2.33

Complex Schur Decomposition

The complex Schur decomposition of a square matrix A produces a complex unitary matrix U and a complex upper-triangular Schur form matrix T such that

$$A = U \cdot T \cdot U^{-1}$$

Since U is unitary, its inverse is also its conjugate transpose, $U^{-1} = U^*$, $U^*(i, j) = \text{conj}(U(j, i))$

`complex_matrix complex_schur_decompose_t(matrix A)`

Compute the upper-triangular Schur form matrix of the complex Schur decomposition of A .

Available since 2.31

`complex_matrix complex_schur_decompose_t(complex_matrix A)`

Compute the upper-triangular Schur form matrix of the complex Schur decomposition of A .

Available since 2.31

`complex_matrix complex_schur_decompose_u(matrix A)`

Compute the unitary matrix of the complex Schur decomposition of A .

Available since 2.31

`complex_matrix complex_schur_decompose_u(complex_matrix A)`

Compute the unitary matrix of the complex Schur decomposition of A .

Available since 2.31

`tuple(complex_matrix, complex_matrix) complex_schur_decompose(matrix A)`

Returns the unitary matrix and the upper-triangular Schur form matrix of the complex Schur decomposition of A . This function is equivalent to `(complex_schur_decompose_u(A), complex_schur_decompose_t(A))` but with a lower computational cost due to the shared work between the two results. This

overload is equivalent to `complex_schur_decompose(to_complex(A,0))` but is more efficient.

Available since 2.33

`tuple(complex_matrix, complex_matrix) complex_schur_decompose(complex_matrix A)`

Returns the unitary matrix and the upper-triangular Schur form matrix of the complex Schur decomposition of A. This function is equivalent to `(complex_schur_decompose_u(A), complex_schur_decompose_t(A))` but with a lower computational cost due to the shared work between the two results.

Available since 2.33

7.15. Reverse functions for complex matrices

`complex_vector reverse(complex_vector v)`

Return a new vector containing the elements of the argument in reverse order.

Available since 2.30

`complex_row_vector reverse(complex_row_vector v)`

Return a new row vector containing the elements of the argument in reverse order.

Available since 2.30

8. Sparse Matrix Operations

For sparse matrices, for which many elements are zero, it is more efficient to use specialized representations to save memory and speed up matrix arithmetic (including derivative calculations). Given Stan's implementation, there is substantial space (memory) savings by using sparse matrices. Because of the ease of optimizing dense matrix operations, speed improvements only arise at 90% or even greater sparsity; below that level, dense matrices are faster but use more memory.

Because of this speedup and space savings, it may even be useful to read in a dense matrix and convert it to a sparse matrix before multiplying it by a vector. This chapter covers a very specific form of sparsity consisting of a sparse matrix multiplied by a dense vector.

8.1. Compressed row storage

Sparse matrices are represented in Stan using compressed row storage (CSR). For example, the matrix

$$A = \begin{bmatrix} 19 & 27 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 52 \\ 81 & 0 & 95 & 33 \end{bmatrix}$$

is translated into a vector of the non-zero real values, read by row from the matrix A ,

$$w(A) = [19 \ 27 \ 52 \ 81 \ 95 \ 33]^\top,$$

an array of integer column indices for the values,

$$v(A) = [1 \ 2 \ 4 \ 1 \ 3 \ 4],$$

and an array of integer indices indicating where in $w(A)$ a given row's values start,

$$u(A) = [1 \ 3 \ 3 \ 4 \ 7],$$

with a padded value at the end to guarantee that

$$u(A)[n+1] - u(A)[n]$$

is the number of non-zero elements in row n of the matrix (here 2, 0, 1, and 3). Note that because the second row has no non-zero elements both the second and third

elements of $u(A)$ correspond to the third element of $w(A)$, which is 52. The values $(w(A), v(A), u(A))$ are sufficient to reconstruct A .

The values are structured so that there is a real value and integer column index for each non-zero entry in the array, plus one integer for each row of the matrix, plus one for padding. There is also underlying storage for internal container pointers and sizes. The total memory usage is roughly $12K + M$ bytes plus a small constant overhead, which is often considerably fewer bytes than the $M \times N$ required to store a dense matrix. Even more importantly, zero values do not introduce derivatives under multiplication or addition, so many storage and evaluation steps are saved when sparse matrices are multiplied.

8.2. Conversion functions

Conversion functions between dense and sparse matrices are provided.

Dense to sparse conversion

Converting a dense matrix m to a sparse representation produces a vector w and two integer arrays, u and v .

vector **csr_extract_w**(matrix a)

Return non-zero values in matrix a; see section [compressed row storage](#).

Available since 2.8

array[] int **csr_extract_v**(matrix a)

Return column indices for values in `csr_extract_w(a)`; see [compressed row storage](#).

Available since 2.8

array[] int **csr_extract_u**(matrix a)

Return array of row starting indices for entries in `csr_extract_w(a)` followed by the size of `csr_extract_w(a)` plus one; see section [compressed row storage](#).

Available since 2.8

tuple(vector, array[] int, array[] int) **csr_extract**(matrix a)

Return all three components of the CSR representation of the matrix a; see section [compressed row storage](#). This function is equivalent to `(csr_extract_w(a), csr_extract_v(a), csr_extract_u(a))`.

Available since 2.33

Sparse to dense conversion

To convert a sparse matrix representation to a dense matrix, there is a single function.

```
matrix csr_to_dense_matrix(int m, int n, vector w, array[] int v,
array[] int u)
```

Return dense $m \times n$ matrix with non-zero matrix entries w , column indices v , and row starting indices u ; the vector w and array v must be the same size (corresponding to the total number of nonzero entries in the matrix), array v must have index values bounded by m , array u must have length equal to $m + 1$ and contain index values bounded by the number of nonzeros (except for the last entry, which must be equal to the number of nonzeros plus one). See section [compressed row storage](#) for more details.

Available since 2.10

8.3. Sparse matrix arithmetic

Sparse matrix multiplication

The only supported operation is the multiplication of a sparse matrix A and a dense vector b to produce a dense vector Ab . Multiplying a dense row vector b and a sparse matrix A can be coded using transposition as

$$bA = (A^T b^T)^T,$$

but care must be taken to represent A^T rather than A as a sparse matrix.

```
vector csr_matrix_times_vector(int m, int n, vector w, array[] int
v, array[] int u, vector b)
```

Multiply the $m \times n$ matrix represented by values w , column indices v , and row start indices u by the vector b ; see [compressed row storage](#).

Available since 2.18

9. Mixed Operations

These functions perform conversions between Stan containers matrix, vector, row vector and arrays.

`matrix to_matrix(matrix m)`

Return the matrix `m` itself.

Available since 2.3

`complex_matrix to_matrix(complex_matrix m)`

Return the matrix `m` itself.

Available since 2.30

`matrix to_matrix(vector v)`

Convert the column vector `v` to a `size(v)` by 1 matrix.

Available since 2.3

`complex_matrix to_matrix(complex_vector v)`

Convert the column vector `v` to a `size(v)` by 1 matrix.

Available since 2.30

`matrix to_matrix(row_vector v)`

Convert the row vector `v` to a 1 by `size(v)` matrix.

Available since 2.3

`complex_matrix to_matrix(complex_row_vector v)`

Convert the row vector `v` to a 1 by `size(v)` matrix.

Available since 2.30

`matrix to_matrix(matrix M, int m, int n)`

Convert a matrix `A` to a matrix with `m` rows and `n` columns filled in column-major order.

Available since 2.15

`complex_matrix to_matrix(complex_matrix M, int m, int n)`

Convert a matrix `A` to a matrix with `m` rows and `n` columns filled in column-major order.

Available since 2.30

`matrix` **to_matrix**(vector v, int m, int n)

Convert a vector v to a matrix with m rows and n columns filled in column-major order.

Available since 2.15

`complex_matrix` **to_matrix**(complex_vector v, int m, int n)

Convert a vector v to a matrix with m rows and n columns filled in column-major order.

Available since 2.30

`matrix` **to_matrix**(row_vector v, int m, int n)

Convert a row_vector v to a matrix with m rows and n columns filled in column-major order.

Available since 2.15

`complex_matrix` **to_matrix**(complex_row_vector v, int m, int n)

Convert a row vector v to a matrix with m rows and n columns filled in column-major order.

Available since 2.30

`matrix` **to_matrix**(matrix A, int m, int n, int col_major)

Convert a matrix A to a matrix with m rows and n columns filled in row-major order if col_major equals 0 (otherwise, they get filled in column-major order).

Available since 2.15

`complex_matrix` **to_matrix**(complex_matrix A, int m, int n, int col_major)

Convert a matrix A to a matrix with m rows and n columns filled in row-major order if col_major equals 0 (otherwise, they get filled in column-major order).

Available since 2.30

`matrix` **to_matrix**(vector v, int m, int n, int col_major)

Convert a vector v to a matrix with m rows and n columns filled in row-major order if col_major equals 0 (otherwise, they get filled in column-major order).

Available since 2.15

`complex_matrix` **to_matrix**(complex_vector v, int m, int n, int col_major)

Convert a vector v to a matrix with m rows and n columns filled in row-major order if `col_major` equals 0 (otherwise, they get filled in column-major order).

Available since 2.30

`matrix` **to_matrix**(`row_vector` v , `int` m , `int` n , `int` `col_major`)

Convert a row vector v to a matrix with m rows and n columns filled in row-major order if `col_major` equals 0 (otherwise, they get filled in column-major order).

Available since 2.15

`complex_matrix` **to_matrix**(`complex_row_vector` v , `int` m , `int` n , `int` `col_major`)

Convert a row vector v to a matrix with m rows and n columns filled in row-major order if `col_major` equals 0 (otherwise, they get filled in column-major order).

Available since 2.30

`matrix` **to_matrix**(`array`[] `real` a , `int` m , `int` n)

Convert a one-dimensional array a to a matrix with m rows and n columns filled in column-major order.

Available since 2.15

`matrix` **to_matrix**(`array`[] `int` a , `int` m , `int` n)

Convert a one-dimensional array a to a matrix with m rows and n columns filled in column-major order.

Available since 2.15

`complex_matrix` **to_matrix**(`array`[] `complex` a , `int` m , `int` n)

Convert a one-dimensional array a to a matrix with m rows and n columns filled in column-major order.

Available since 2.30

`matrix` **to_matrix**(`array`[] `real` a , `int` m , `int` n , `int` `col_major`)

Convert a one-dimensional array a to a matrix with m rows and n columns filled in row-major order if `col_major` equals 0 (otherwise, they get filled in column-major order).

Available since 2.15

`matrix` **to_matrix**(`array`[] `int` a , `int` m , `int` n , `int` `col_major`)

Convert a one-dimensional array a to a matrix with m rows and n columns filled in

row-major order if `col_major` equals 0 (otherwise, they get filled in column-major order).

Available since 2.15

`complex_matrix` **to_matrix**(array[] complex a, int m, int n, int col_major)

Convert a one-dimensional array `a` to a matrix with `m` rows and `n` columns filled in row-major order if `col_major` equals 0 (otherwise, they get filled in column-major order).

Available since 2.30

`matrix` **to_matrix**(array[] row_vector vs)

Convert a one-dimensional array of row vectors to a matrix, where the size of the array is the number of rows of the resulting matrix and the length of row vectors is the number of columns.

Available since 2.28

`complex_matrix` **to_matrix**(array[] complex_row_vector vs)

Convert a one-dimensional array of row vectors to a matrix, where the size of the array is the number of rows of the resulting matrix and the length of row vectors is the number of columns.

Available since 2.30

`matrix` **to_matrix**(array[,] real a)

Convert the two dimensional array `a` to a matrix with the same dimensions and indexing order.

Available since 2.3

`matrix` **to_matrix**(array[,] int a)

Convert the two dimensional array `a` to a matrix with the same dimensions and indexing order. If any of the dimensions of `a` are zero, the result will be a 0×0 matrix.

Available since 2.3

`complex_matrix` **to_matrix**(array[,] complex a)

Convert the two dimensional array `a` to a matrix with the same dimensions and indexing order.

Available since 2.30

vector **to_vector**(matrix m)

Convert the matrix m to a column vector in column-major order.

Available since 2.0

complex_vector **to_vector**(complex_matrix m)

Convert the matrix m to a column vector in column-major order.

Available since 2.30

vector **to_vector**(vector v)

Return the column vector v itself.

Available since 2.3

complex_vector **to_vector**(complex_vector v)

Return the column vector v itself.

Available since 2.30

vector **to_vector**(row_vector v)

Convert the row vector v to a column vector.

Available since 2.3

complex_vector **to_vector**(complex_row_vector v)

Convert the row vector v to a column vector.

Available since 2.30

vector **to_vector**(array[] real a)

Convert the one-dimensional array a to a column vector.

Available since 2.3

vector **to_vector**(array[] int a)

Convert the one-dimensional integer array a to a column vector.

Available since 2.3

complex_vector **to_vector**(array[] complex a)

Convert the one-dimensional complex array a to a column vector.

Available since 2.30

row_vector **to_row_vector**(matrix m)

Convert the matrix m to a row vector in column-major order.

Available since 2.3

`complex_row_vector` **to_row_vector**(`complex_matrix` m)
Convert the matrix m to a row vector in column-major order.

Available since 2.30

`row_vector` **to_row_vector**(`vector` v)
Convert the column vector v to a row vector.

Available since 2.3

`complex_row_vector` **to_row_vector**(`complex_vector` v)
Convert the column vector v to a row vector.

Available since 2.30

`row_vector` **to_row_vector**(`row_vector` v)
Return the row vector v itself.

Available since 2.3

`complex_row_vector` **to_row_vector**(`complex_row_vector` v)
Return the row vector v itself.

Available since 2.30

`row_vector` **to_row_vector**(`array[]` real a)
Convert the one-dimensional array a to a row vector.

Available since 2.3

`row_vector` **to_row_vector**(`array[]` int a)
Convert the one-dimensional array a to a row vector.

Available since 2.3

`complex_row_vector` **to_row_vector**(`array[]` complex a)
Convert the one-dimensional complex array a to a row vector.

Available since 2.30

`array[,]` real **to_array_2d**(`matrix` m)
Convert the matrix m to a two dimensional array with the same dimensions and indexing order.

Available since 2.3

`array[,]` complex **to_array_2d**(`complex_matrix` m)
Convert the matrix m to a two dimensional array with the same dimensions and

indexing order.

Available since 2.30

array[] real **to_array_1d**(vector v)
Convert the column vector v to a one-dimensional array.

Available since 2.3

array[] complex **to_array_1d**(complex_vector v)
Convert the column vector v to a one-dimensional array.

Available since 2.30

array[] real **to_array_1d**(row_vector v)
Convert the row vector v to a one-dimensional array.

Available since 2.3

array[] complex **to_array_1d**(complex_row_vector v)
Convert the row vector v to a one-dimensional array.

Available since 2.30

array[] real **to_array_1d**(matrix m)
Convert the matrix m to a one-dimensional array in column-major order.

Available since 2.3

array[] real **to_array_1d**(complex_matrix m)
Convert the matrix m to a one-dimensional array in column-major order.

Available since 2.30

array[] real **to_array_1d**(array[...] real a)
Convert the array a (of any dimension up to 10) to a one-dimensional array in row-major order.

Available since 2.3

array[] int **to_array_1d**(array[...] int a)
Convert the array a (of any dimension up to 10) to a one-dimensional array in row-major order.

Available since 2.3

array[] complex **to_array_1d**(array[...] complex a)
Convert the array a (of any dimension up to 10) to a one-dimensional array in

row-major order.

Available since 2.30

10. Compound Arithmetic and Assignment

Compound arithmetic and assignment statements combine an arithmetic operation and assignment, replacing a statement such as

```
x = x op y;
```

with the more compact compound form

```
x op= y;
```

For example, `x = x + 1;` may be replaced with `x += 1;`. This works for all types that support arithmetic, including the scalar types `int`, `real`, `complex`, the real matrix types `vector`, `row_vector`, and `matrix`, and the complex matrix types, `complex_vector`, `complex_row_vector`, and `complex_matrix`.

10.1. Compound addition and assignment

Compound addition and assignment works wherever the corresponding addition and assignment would be well formed.

```
void operator+=(T x, U y)
```

`x += y` is equivalent to `x = x + y`. Defined for all types `T` and `U` where `T = T + U` is well formed.

Available since 2.17, complex signatures added in 2.30

10.2. Compound subtraction and assignment

Compound addition and assignment works wherever the corresponding subtraction and assignment would be well formed.

```
void operator--(T x, U y)
```

`x -= y` is equivalent to `x = x - y`. Defined for all types `T` and `U` where `T = T - U` is well formed.

Available since 2.17, complex signatures added in 2.30

10.3. Compound multiplication and assignment

Compound multiplication and assignment works wherever the corresponding multiplication and assignment would be well formed.

void **operator****=(T x, U y)

$x ** y$ is equivalent to $x = x * y$. Defined for all types T and U where $T = T * U$ is well formed.

Available since 2.17, complex signatures added in 2.30

10.4. Compound division and assignment

Compound division and assignment works wherever the corresponding division and assignment would be well formed.

void **operator/=**=(T x, U y)

$x /= y$ is equivalent to $x = x / y$. Defined for all types T and U where $T = T / U$ is well formed.

Available since 2.17, complex signatures added in 2.30

10.5. Compound elementwise multiplication and assignment

Compound elementwise multiplication and assignment works wherever the corresponding multiplication and assignment would be well formed.

void **operator.***=(T x, U y)

$x .* y$ is equivalent to $x = x .* y$. Defined for all types T and U where $T = T .* U$ is well formed.

Available since 2.17, complex signatures added in 2.30

10.6. Compound elementwise division and assignment

Compound elementwise division and assignment works wherever the corresponding division and assignment would be well formed.

void **operator./**=(T x, U y)

$x ./ y$ is equivalent to $x = x ./ y$. Defined for all types T and U where $T = T ./ U$ is well formed.

Available since 2.17, complex signatures added in 2.30

11. Higher-Order Functions

Stan provides a few higher-order functions that act on other functions. In all cases, the function arguments to the higher-order functions are defined as functions within the Stan language and passed by name to the higher-order functions.

11.1. Algebraic equation solvers

Stan provides two built-in algebraic equation solvers, respectively based on the Newton method and the Powell “dog leg” hybrid method. Empirically the Newton method is found to be faster and its use is recommended for most problems.

An algebraic solver is a higher-order function, i.e. it takes another function as one of its arguments. Other functions in Stan which share this feature are the differential equation solvers (see section [Ordinary Differential Equation \(ODE\) Solvers](#) and [Differential Algebraic Equation \(DAE\) solver](#)). Ordinary Stan functions do not allow functions as arguments.

Specifying an algebraic equation as a function

An algebraic system is specified as an ordinary function in Stan within the function block. The function must return a vector and takes in, as its first argument, the unknowns y we wish to solve for, also passed as a vector. This argument is followed by additional arguments as specified by the user; we call such arguments *variadic arguments* and denote them \dots . The signature of the algebraic system is then:

```
vector algebra_system (vector y, ...)
```

There is no type restriction for the variadic arguments and each argument can be passed as data or parameter. However users should use parameter arguments only when necessary and mark data arguments with the keyword `data`. In the below example, the last variadic argument, x , is restricted to being data:

```
vector algebra_system (vector y, vector theta, data vector x)
```

Distinguishing data and parameter is important for computational reasons. Augmenting the total number of parameters increases the cost of propagating derivatives through the solution to the algebraic equation, and ultimately the computational cost of evaluating the gradients.

Call to the algebraic solver

vector **solve_newton**(function algebra_system, vector y_guess, ...)
Solves the algebraic system, given an initial guess, using Newton's method.

Available since 2.31

vector **solve_newton_tol**(function algebra_system, vector y_guess, data real scaling_step, data real f_tol, int max_steps, ...)
Solves the algebraic system, given an initial guess, using Newton's method with additional control parameters for the solver.

Available since 2.31

vector **solve_powell**(function algebra_system, vector y_guess, ...)
Solves the algebraic system, given an initial guess, using Powell's hybrid method.

Available since 2.31

vector **solve_powell_tol**(function algebra_system, vector y_guess, data real rel_tol, data real f_tol, int max_steps, ...)
Solves the algebraic system, given an initial guess, using Powell's hybrid method with additional control parameters for the solver.

Available since 2.31

Arguments to the algebraic solver

The arguments to the algebraic solvers are as follows:

- *algebra_system*: function literal referring to a function specifying the system of algebraic equations with signature (vector, ...):vector. The arguments represent (1) unknowns, (2) additional parameter and/or data arguments, and the return value contains the value of the algebraic function, which goes to 0 when we plug in the solution to the algebraic system,
- *y_guess*: initial guess for the solution, type vector,
- ...: variadic arguments.

The algebraic solvers admit control parameters. While Stan provides default values, the user should be prepared to adjust the control parameters. The following controls are available:

- *scaling_step*: for the Newton solver only, the scaled-step stopping tolerance, type real, data only. If a Newton step is smaller than the scaling step tolerance, the code breaks, assuming the solver is no longer making significant progress. If set to 0, this constraint is ignored. Default value is 10^{-3} .

- *rel_tol*: for the Powell solver only, the relative tolerance, type `real`, data only. The relative tolerance is the estimated relative error of the solver and serves to test if a satisfactory solution has been found. Default value is 10^{-10} .
- *function_tol*: function tolerance for the algebraic solver, type `real`, data only. After convergence of the solver, the proposed solution is plugged into the algebraic system and its norm is compared to the function tolerance. If the norm is below the function tolerance, the solution is deemed acceptable. Default value is 10^{-6} .
- *max_num_steps*: maximum number of steps to take in the algebraic solver, type `int`, data only. If the solver reaches this number of steps, it breaks and returns an error message. Default value is 200.

The difference in which control parameters are available has to do with the underlying implementations for the solvers and the control parameters these implementations support. The Newton solver is based on KINSOL from the SUNDIAL suites, while the Powell solver uses a module from the Eigen library.

Return value

The return value for the algebraic solver is an object of type `vector`, with values which, when plugged in as y make the algebraic function go to 0 (approximately, within the specified function tolerance).

Sizes and parallel arrays

Certain sizes have to be consistent. The initial guess, return value of the solver, and return value of the algebraic function must all be the same size.

Algorithmic details

Stan offers two methods to solve algebraic equations. `solve_newton` and `solve_newton_tol` use the Newton method, a first-order derivative based numerical solver. The Stan code builds on the implementation in KINSOL from the SUNDIALS suite (Hindmarsh et al. 2005). For many problems, we find that the Newton method is faster than the Powell method. If however Newton's method performs poorly, either failing to or requiring an excessively long time to converge, the user should be prepared to switch to the Powell method.

`solve_powell` and `solve_powell_tol` are based on the Powell hybrid method (Powell 1970), which also uses first-order derivatives. The Stan code builds on the implementation of the hybrid solver in the unsupported module for nonlinear optimization problems of the Eigen library (Guennebaud, Jacob, et al. 2010). This solver is in turn based on the algorithm developed for the package MINPACK-1 (Jorge J. More 1980).

For both solvers, derivatives are propagated through the solution to the algebraic solution using the implicit function theorem and an adjoint method of automatic differentiation; for a discussion on this topic, see (Gaebler 2021) and (Margossian and Betancourt 2022).

11.2. Ordinary differential equation (ODE) solvers

Stan provides several higher order functions for solving initial value problems specified as Ordinary Differential Equations (ODEs).

Solving an initial value ODE means given a set of differential equations $y'(t, \theta) = f(t, y, \theta)$ and initial conditions $y(t_0, \theta)$, solving for y at a sequence of times $t_0 < t_1 < t_2 \cdots < t_n$. $f(t, y, \theta)$ is referred to here as the ODE system function.

$f(t, y, \theta)$ will be defined as a function with a certain signature and provided along with the initial conditions and output times to one of the ODE solver functions.

To make it easier to write ODEs, the solve functions take extra arguments that are passed along unmodified to the user-supplied system function. Because there can be any number of these arguments and they can be of different types, they are denoted below as \dots . The types of the arguments represented by \dots in the ODE solve function call must match the types of the arguments represented by \dots in the user-supplied system function.

Non-stiff solver

array[] vector **ode_rk45**(function ode, vector initial_state, real initial_time, array[] real times, ...)

Solves the ODE system for the times provided using the Dormand-Prince algorithm, a 4th/5th order Runge-Kutta method.

Available since 2.24

array[] vector **ode_rk45_tol**(function ode, vector initial_state, real initial_time, array[] real times, data real rel_tol, data real abs_tol, int max_num_steps, ...)

Solves the ODE system for the times provided using the Dormand-Prince algorithm, a 4th/5th order Runge-Kutta method with additional control parameters for the solver.

Available since 2.24

array[] vector **ode_ckrk**(function ode, vector initial_state, real initial_time, array[] real times, ...)

Solves the ODE system for the times provided using the Cash-Karp algorithm, a

4th/5th order explicit Runge-Kutta method.

Available since 2.27

array[] vector **ode_ckrk_tol**(function ode, vector initial_state, real initial_time, array[] real times, data real rel_tol, data real abs_tol, int max_num_steps, ...)

Solves the ODE system for the times provided using the Cash-Karp algorithm, a 4th/5th order explicit Runge-Kutta method with additional control parameters for the solver.

Available since 2.27

array[] vector **ode_adams**(function ode, vector initial_state, real initial_time, array[] real times, ...)

Solves the ODE system for the times provided using the Adams-Moulton method.

Available since 2.24

array[] vector **ode_adams_tol**(function ode, vector initial_state, real initial_time, array[] real times, data real rel_tol, data real abs_tol, int max_num_steps, ...)

Solves the ODE system for the times provided using the Adams-Moulton method with additional control parameters for the solver.

Available since 2.24

Stiff solver

array[] vector **ode_bdf**(function ode, vector initial_state, real initial_time, array[] real times, ...)

Solves the ODE system for the times provided using the backward differentiation formula (BDF) method.

Available since 2.24

array[] vector **ode_bdf_tol**(function ode, vector initial_state, real initial_time, array[] real times, data real rel_tol, data real abs_tol, int max_num_steps, ...)

Solves the ODE system for the times provided using the backward differentiation formula (BDF) method with additional control parameters for the solver.

Available since 2.24

Adjoint solver

```
array[] vector      ode_adjoint_tol_ctl(function ode, vector initial_state, real initial_time, array[] real times, data real rel_tol_forward, data vector abs_tol_forward, data real rel_tol_backward, data vector abs_tol_backward, int max_num_steps, int num_steps_between_checkpoints, int interpolation_polynomial, int solver_forward, int solver_backward, ...)
```

Solves the ODE system for the times provided using the adjoint ODE solver method from CVODES. The adjoint ODE solver requires a checkpointed forward in time ODE integration, a backwards in time integration that makes uses of an interpolated version of the forward solution, and the solution of a quadrature problem (the number of which depends on the number of parameters passed to the solve). The tolerances and numeric methods used for the forward solve, backward solve, quadratures, and interpolation can all be configured.

Available since 2.27

ODE system function

The first argument to one of the ODE solvers is always the ODE system function. The ODE system function must have a vector return type, and the first two arguments must be a real and vector in that order. These two arguments are followed by the variadic arguments that are passed through from the ODE solve function call:

```
vector ode(real time, vector state, ...)
```

The ODE system function should return the derivative of the state with respect to time at the time and state provided. The length of the returned vector must match the length of the state input into the function.

The arguments to this function are:

- *time*, the time to evaluate the ODE system
- *state*, the state of the ODE system at the time specified
- *...*, sequence of arguments passed unmodified from the ODE solve function call. The types here must match the types in the *...* arguments of the ODE solve function call.

Arguments to the ODE solvers

The arguments to the ODE solvers in both the stiff and non-stiff solvers are the same. The arguments to the adjoint ODE solver are different; see [Arguments to the](#)

adjoint ODE solver.

- *ode*: ODE system function,
- *initial_state*: initial state, type vector,
- *initial_time*: initial time, type real,
- *times*: solution times, type array[] real,
- ...: sequence of arguments that will be passed through unmodified to the ODE system function. The types here must match the types in the ... arguments of the ODE system function.

For the versions of the ode solver functions ending in *_tol*, these three parameters must be provided after *times* and before the ... arguments:

- data *rel_tol*: relative tolerance for the ODE solver, type real, data only,
- data *abs_tol*: absolute tolerance for the ODE solver, type real, data only, and
- *max_num_steps*: maximum number of steps to take between output times in the ODE solver, type int, data only.

Because the tolerances are data arguments, they must be defined in either the data or transformed data blocks. They cannot be parameters, transformed parameters or functions of parameters or transformed parameters.

Arguments to the adjoint ODE solver

The arguments to the adjoint ODE solver are different from those for the other functions (for those see [Arguments to the ODE solvers](#)).

- *ode*: ODE system function,
- *initial_state*: initial state, type vector,
- *initial_time*: initial time, type real,
- *times*: solution times, type array[] real,
- data *rel_tol_forward*: Relative tolerance for forward solve, type real, data only,
- data *abs_tol_forward*: Absolute tolerance vector for each state for forward solve, type vector, data only,

- data *rel_tol_backward*: Relative tolerance for backward solve, type `real`, data only,
- data *abs_tol_backward*: Absolute tolerance vector for each state for backward solve, type `vector`, data only,
- data *rel_tol_quadrature*: Relative tolerance for backward quadrature, type `real`, data only,
- data *abs_tol_quadrature*: Absolute tolerance for backward quadrature, type `real`, data only,
- data *max_num_steps*: Maximum number of time-steps to take in integrating the ODE solution between output time points for forward and backward solve, type `int`, data only,
- *num_steps_between_checkpoints*: number of steps between checkpointing forward solution, type `int`, data only,
- *interpolation_polynomial*: can be 1 for hermite or 2 for polynomial interpolation method of CVODES, type `int`, data only,
- *solver_forward*: solver used for forward ODE problem: 1=Adams (non-stiff), 2=BDF (stiff), type `int`, data only,
- *solver_backward*: solver used for backward ODE problem: 1=Adams (non-stiff), 2=BDF (stiff), type `int`, data only.
- . . . : sequence of arguments that will be passed through unmodified to the ODE system function. The types here must match the types in the . . . arguments of the ODE system function.

Because the tolerances are data arguments, they must be defined in either the data or transformed data blocks. They cannot be parameters, transformed parameters or functions of parameters or transformed parameters.

Return values

The return value for the ODE solvers is an array of vectors (type `array[] vector`), one vector representing the state of the system at every time in specified in the `times` argument.

Array and vector sizes

The sizes must match, and in particular, the following groups are of the same size:

- state variables passed into the system function, derivatives returned by the system function, initial state passed into the solver, and length of each vector

in the output,

- number of solution times and number of vectors in the output.

11.3. Differential-Algebraic equation (DAE) solver

Stan provides two higher order functions for solving initial value problems specified as Differential-Algebraic Equations (DAEs) with index-1 (Serban et al. 2021).

Solving an initial value DAE means given a set of residual functions $r(y'(t, \theta), y(t, \theta), t)$ and initial conditions $(y(t_0, \theta), y'(t_0, \theta))$, solving for y at a sequence of times $t_0 < t_1 \leq t_2, \dots \leq t_n$. The residual function $r(y', y, t, \theta)$ will be defined as a function with a certain signature and provided along with the initial conditions and output times to one of the DAE solver functions.

Similar to ODE solvers, the DAE solver function takes extra arguments that are passed along unmodified to the user-supplied system function. Because there can be any number of these arguments and they can be of different types, they are denoted below as \dots , and the types of these arguments, also represented by \dots in the DAE solver call, must match the types of the arguments represented by \dots in the user-supplied system function.

The DAE solver

```
array[] vector    dae(function residual, vector initial_state, vec-
tor initial_state_derivative, data real initial_time, data array[]
real times, ...)
```

Solves the DAE system using the backward differentiation formula (BDF) method (Serban et al. 2021).

Available since 2.29

```
array[] vector    dae_tol(function residual, vector initial_state,
vector initial_state_derivative, data real initial_time, data
array[] real times, data real rel_tol, data real abs_tol, int
max_num_steps, ...)
```

Solves the DAE system for the times provided using the backward differentiation formula (BDF) method with additional control parameters for the solver.

Available since 2.29

DAE system function

The first argument to the DAE solver is the DAE residual function. The DAE residual function must have a vector return type, and the first three arguments must be a real, vector, and vector, in that order. These three arguments are

followed by the variadic arguments that are passed through from the DAE solver function call:

```
vector residual(real time, vector state, vector state_derivative, ...)
```

The DAE residual function should return the residuals at the time and state provided. The length of the returned vector must match the length of the state input into the function.

The arguments to this function are:

- *time*, the time to evaluate the DAE system
- *state*, the state of the DAE system at the time specified
- *state_derivative*, the time derivatives of the state of the DAE system at the time specified
- *...*, sequence of arguments passed unmodified from the DAE solve function call. The types here must match the types in the *...* arguments of the DAE solve function call.

Arguments to the DAE solver

The arguments to the DAE solver are

- *residual*: DAE residual function,
- *initial_state*: initial state, type vector,
- *initial_state_derivative*: time derivative of the initial state, type vector,
- *initial_time*: initial time, type data real,
- *times*: solution times, type data array[] real,
- *...*: sequence of arguments that will be passed through unmodified to the DAE residual function. The types here must match the types in the *...* arguments of the DAE residual function.

For `dae_tol`, the following three parameters must be provided after `times` and before the *...* arguments:

- data *rel_tol*: relative tolerance for the DAE solver, type real, data only,
- data *abs_tol*: absolute tolerance for the DAE solver, type real, data only, and

- *max_num_steps*: maximum number of steps to take between output times in the DAE solver, type `int`, data only.

Because the tolerances are data arguments, they must be supplied as primitive numerics or defined in either the data or transformed data blocks. They cannot be parameters, transformed parameters or functions of parameters or transformed parameters.

Consistency of the initial conditions

The user is responsible to ensure the residual function becomes zero at the initial time, `t0`, when the arguments `initial_state` and `initial_state_derivative` are introduced as `state` and `state_derivative`, respectively.

Return values

The return value for the DAE solvers is an array of vectors (type `array[] vector`), one vector representing the state of the system at every time specified in the `times` argument.

Array and vector sizes

The sizes must match, and in particular, the following groups are of the same size:

- state variables and state derivatives passed into the residual function, the residual returned by the residual function, initial state and initial state derivatives passed into the solver, and length of each vector in the output,
- number of solution times and number of vectors in the output.

11.4. 1D integrator

Stan provides a built-in mechanism to perform 1D integration of a function via quadrature methods.

It operates similarly to the [algebraic solver](#) and the [ordinary differential equations solver](#) in that it allows as an argument a function.

Like both of those utilities, some of the arguments are limited to data only expressions. These expressions must not contain variables other than those declared in the data or transformed data blocks.

Specifying an integrand as a function

Performing a 1D integration requires the integrand to be specified somehow. This is done by defining a function in the Stan functions block with the special signature:

```
real integrand(real x, real xc, array[] real theta,
              array[] real x_r, array[] int x_i)
```

The function should return the value of the integrand evaluated at the point x .

The argument of this function are:

- x , the independent variable being integrated over
- xc , a high precision version of the distance from x to the nearest endpoint in a definite integral (for more into see section [Precision Loss](#)).
- $theta$, parameter values used to evaluate the integral
- x_r , data values used to evaluate the integral
- x_i , integer data used to evaluate the integral

Like algebraic solver and the differential equations solver, the 1D integrator separates parameter values, $theta$, from data values, x_r .

Call to the 1D integrator

```
real integrate_1d (function integrand, real a, real b, array[] real
theta, array[] real x_r, array[] int x_i)
```

Integrates the integrand from a to b .

Available since 2.23

```
real integrate_1d (function integrand, real a, real b, array[] real
theta, array[] real x_r, array[] int x_i, real relative_tolerance)
```

Integrates the integrand from a to b with the given relative tolerance.

Available since 2.23

Arguments to the 1D integrator

The arguments to the 1D integrator are as follows:

- *integrand*: function literal referring to a function specifying the integrand with signature `(real, real, array[] real, array[] real, array[] int):real`. The arguments represent
 - (1) where *integrand* is evaluated,
 - (2) distance from evaluation point to integration limit for definite integrals,
 - (3) parameters,
 - (4) real data

- (5) integer data, and the return value is the integrand evaluated at the given point,
- a : left limit of integration, may be negative infinity, type `real`,
- b : right limit of integration, may be positive infinity, type `real`,
- $theta$: parameters only, type `array[] real`,
- x_r : real data only, type `array[] real`,
- x_i : integer data only, type `array[] int`.

A `relative_tolerance` argument can optionally be provided for more control over the algorithm:

- `relative_tolerance`: relative tolerance for the 1d integrator, type `real`, data only.

Return value

The return value for the 1D integrator is a `real`, the value of the integral.

Zero-crossing integrals

For numeric stability, integrals on the (possibly infinite) interval (a, b) that cross zero are split into two integrals, one from $(a, 0)$ and one from $(0, b)$. Each integral is separately integrated to the given `relative_tolerance`.

Precision loss near limits of integration in definite integrals

When integrating certain definite integrals, there can be significant precision loss in evaluating the integrand near the endpoints. This has to do with the breakdown in precision of double precision floating point values when adding or subtracting a small number from a number much larger than it in magnitude (for instance, $1.0 - x$). `xc` (as passed to the integrand) is a high-precision version of the distance between x and the definite integral endpoints and can be used to address this issue. More information (and an example where this is useful) is given in the User's Guide. For zero crossing integrals, `xc` will be a high precision version of the distance to the endpoints of the two smaller integrals. For any integral with an endpoint at negative infinity or positive infinity, `xc` is set to `NaN`.

Algorithmic details

Internally the 1D integrator uses the double-exponential methods in the Boost 1D quadrature library. Boost in turn makes use of quadrature methods developed in (Takahasi and Mori 1974), (Mori 1978), (Bailey, Jeyabalan, and Li 2005), and (Tanaka et al. 2009).

The gradients of the integral are computed in accordance with the Leibniz integral rule. Gradients of the integrand are computed internally with Stan's automatic

differentiation.

11.5. Reduce-sum function

Stan provides a higher-order reduce function for summation. A function which returns a scalar $g: U \rightarrow \text{real}$ is mapped to every element of a list of type `array[] U, { x1, x2, ... }` and all the results are accumulated,

$$g(x_1) + g(x_2) + \dots$$

For efficiency reasons the reduce function doesn't work with the element-wise evaluated function g itself, but instead works through evaluating partial sums, $f: \text{array[] } U \rightarrow \text{real}$, where:

$$\begin{aligned} f(\{ x_1 \}) &= g(x_1) \\ f(\{ x_1, x_2 \}) &= g(x_1) + g(x_2) \\ f(\{ x_1, x_2, \dots \}) &= g(x_1) + g(x_2) + \dots \end{aligned}$$

Mathematically the summation reduction is associative and forming arbitrary partial sums in an arbitrary order will not change the result. However, floating point numerics on computers only have a limited precision such that associativity does not hold exactly. This implies that the order of summation determines the exact numerical result. For this reason, the higher-order reduce function is available in two variants:

- `reduce_sum`: Automatically choose partial sums partitioning based on a dynamic scheduling algorithm.
- `reduce_sum_static`: Compute the same sum as `reduce_sum`, but partition the input in the same way for given data set (in `reduce_sum` this partitioning might change depending on computer load). This should result in stable numerical evaluations.

Specifying the reduce-sum function

The higher-order reduce function takes a partial sum function f , an array argument x (with one array element for each term in the sum), a recommended `grainsize`, and a set of shared arguments. This representation allows parallelization of the resultant sum.

```
real reduce_sum(F f, array[] T x, int grainsize, T1 s1, T2 s2, ...)
real reduce_sum_static(F f, array[] T x, int grainsize, T1 s1, T2 s2, ...)
```

Returns the equivalent of $f(x, 1, \text{size}(x), s_1, s_2, \dots)$, but computes the

result in parallel by breaking the array x into independent partial sums. s_1 , s_2 , \dots are shared between all terms in the sum.

Available since 2.23

- f : function literal referring to a function specifying the partial sum operation. Refer to the [partial sum function](#).
- x : array of T , one for each term of the reduction, T can be any type,
- $grainsize$: For `reduce_sum`, $grainsize$ is the recommended size of the partial sum ($grainsize = 1$ means pick totally automatically). For `reduce_sum_static`, $grainsize$ determines the maximum size of the partial sums, type `int`,
- s_1 : first (optional) shared argument, type T_1 , where T_1 can be any type
- s_2 : second (optional) shared argument, type T_2 , where T_2 can be any type,
- \dots : remainder of shared arguments, each of which can be any type.

The partial sum function

The partial sum function must have the following signature where the type T , and the types of all the shared arguments (T_1 , T_2 , \dots) match those of the original `reduce_sum` (`reduce_sum_static`) call.

```
(array[] T x_subset, int start, int end, T1 s1, T2 s2, ...):real
```

The partial sum function returns the sum of the `start` to `end` terms (inclusive) of the overall calculations. The arguments to the partial sum function are:

- x_subset , the subset of x a given partial sum is responsible for computing, type `array[] T`, where T matches the type of x in `reduce_sum` (`reduce_sum_static`)
- $start$, the index of the first term of the partial sum, type `int`
- end , the index of the last term of the partial sum (inclusive), type `int`
- s_1 , first shared argument, type T_1 , matching type of s_1 in `reduce_sum` (`reduce_sum_static`)
- s_2 , second shared argument, type T_2 , matching type of s_2 in `reduce_sum` (`reduce_sum_static`)
- \dots , remainder of shared arguments, with types matching those in `reduce_sum` (`reduce_sum_static`)

11.6. Map-rect function

Stan provides a higher-order map function. This allows map-reduce functionality to be coded in Stan as described in the user's guide.

Specifying the mapped function

The function being mapped must have a signature identical to that of the function `f` in the following declaration.

```
vector f(vector phi, vector theta,
         data array[] real x_r, data array[] int x_i);
```

The map function returns the sequence of results for the particular shard being evaluated. The arguments to the mapped function are:

- *phi*, the sequence of parameters shared across shards
- *theta*, the sequence of parameters specific to this shard
- *x_r*, sequence of real-valued data
- *x_i*, sequence of integer data

All input for the mapped function must be packed into these sequences and all output from the mapped function must be packed into a single vector. The vector of output from each mapped function is concatenated into the final result.

Rectangular map

The rectangular map function operates on rectangular (not ragged) data structures, with parallel data structures for job-specific parameters, job-specific real data, and job-specific integer data.

```
vector      map_rect(F f, vector phi, array[] vector theta, data ar-
array[,] real x_r, data array[,] int x_i)
```

Return the concatenation of the results of applying the function `f`, of type `(vector, vector, array[] real, array[] int):vector` elementwise, i.e., `f(phi, theta[n], x_r[n], x_i[n])` for each `n` in `1:N`, where `N` is the size of the parallel arrays of job-specific/local parameters `theta`, real data `x_r`, and integer data `x_i`. The shared/global parameters `phi` are passed to each invocation of `f`.

Available since 2.18

12. Deprecated Functions

This appendix lists currently deprecated functionality along with how to replace it.

Starting in Stan 2.29, deprecated functions with drop in replacements (such as the renaming of `get_lp` or `multiply_log`) will be removed 3 versions later e.g., functions deprecated in Stan 2.20 will be removed in Stan 2.23 and placed in [Removed Functions](#). The Stan compiler can [automatically update](#) these on the behalf of the user for the entire deprecation window and at least one version following the removal.

12.1. Integer division with operator /

Deprecated: Using `/` with two integer arguments is interpreted as integer floor division, such that

$$1/2 = 0$$

This is deprecated due to its confusion with real-valued division, where

$$1.0/2.0 = 0.5$$

Replacement: Use the integer division operator `operator%%` instead.

12.2. `integrate_ode_rk45`, `integrate_ode_adams`, `integrate_ode_bdf` ODE Integrators

These ODE integrator functions have been replaced by those described in [Ordinary Differential Equation \(ODE\) Solvers](#).

Specifying an ordinary differential equation as a function

A system of ODEs is specified as an ordinary function in Stan within the functions block. The ODE system function must have this function signature:

```
array[] real ode(real time, array[] real state, array[] real theta,  
                array[] real x_r, array[] int x_i);
```

The ODE system function should return the derivative of the state with respect to time at the time provided. The length of the returned real array must match the length of the state input into the function.

The arguments to this function are:

- *time*, the time to evaluate the ODE system
- *state*, the state of the ODE system at the time specified
- *theta*, parameter values used to evaluate the ODE system
- *x_r*, data values used to evaluate the ODE system
- *x_i*, integer data values used to evaluate the ODE system.

The ODE system function separates parameter values, *theta*, from data values, *x_r*, for efficiency in computing the gradients of the ODE.

Non-stiff solver

```
array[,] real    integrate_ode_rk45(function ode, array[] real ini-
tial_state, real initial_time, array[] real times, array[] real
theta, array[] real x_r, array[] int x_i)
```

Solves the ODE system for the times provided using the Dormand-Prince algorithm, a 4th/5th order Runge-Kutta method.

Available since 2.10, deprecated in 2.24

```
array[,] real    integrate_ode_rk45(function ode, array[] real ini-
tial_state, real initial_time, array[] real times, array[] real
theta, array[] real x_r, array[] int x_i, real rel_tol, real
abs_tol, int max_num_steps)
```

Solves the ODE system for the times provided using the Dormand-Prince algorithm, a 4th/5th order Runge-Kutta method with additional control parameters for the solver.

Available since 2.10, deprecated in 2.24

```
array[,] real    integrate_ode(function ode, array[] real ini-
tial_state, real initial_time, array[] real times, array[] real
theta, array[] real x_r, array[] int x_i)
```

Solves the ODE system for the times provided using the Dormand-Prince algorithm, a 4th/5th order Runge-Kutta method.

Available since 2.10, deprecated in 2.24

```
array[,] real integrate_ode_adams(function ode, array[] real initial_state, real initial_time, array[] real times, array[] real theta, data array[] real x_r, data array[] int x_i)
```

Solves the ODE system for the times provided using the Adams-Moulton method.

Available since 2.23, deprecated in 2.24

```
array[,] real integrate_ode_adams(function ode, array[] real initial_state, real initial_time, array[] real times, array[] real theta, data array[] real x_r, data array[] int x_i, data real rel_tol, data real abs_tol, data int max_num_steps)
```

Solves the ODE system for the times provided using the Adams-Moulton method with additional control parameters for the solver.

Available since 2.23, deprecated in 2.24

Stiff solver

```
array[,] real integrate_ode_bdf(function ode, array[] real initial_state, real initial_time, array[] real times, array[] real theta, data array[] real x_r, data array[] int x_i)
```

Solves the ODE system for the times provided using the backward differentiation formula (BDF) method.

Available since 2.10, deprecated in 2.24

```
array[,] real integrate_ode_bdf(function ode, array[] real initial_state, real initial_time, array[] real times, array[] real theta, data array[] real x_r, data array[] int x_i, data real rel_tol, data real abs_tol, data int max_num_steps)
```

Solves the ODE system for the times provided using the backward differentiation formula (BDF) method with additional control parameters for the solver.

Available since 2.10, deprecated in 2.24

Arguments to the ODE solvers

The arguments to the ODE solvers in both the stiff and non-stiff cases are as follows.

- *ode*: function literal referring to a function specifying the system of differential equations with signature:

```
(real, array[] real, array[] real, data array[] real, data array[] int):array[] real
```

The arguments represent (1) time, (2) system state, (3) parameters, (4) real data, and (5) integer data, and the return value contains the derivatives with respect to time of the state,

- *initial_state*: initial state, type array[] real,
- *initial_time*: initial time, type int or real,
- *times*: solution times, type array[] real,
- *theta*: parameters, type array[] real,
- data *x_r*: real data, type array[] real, data only, and
- data *x_i*: integer data, type array[] int, data only.

For more fine-grained control of the ODE solvers, these parameters can also be provided:

- data *rel_tol*: relative tolerance for the ODE solver, type real, data only,
- data *abs_tol*: absolute tolerance for the ODE solver, type real, data only, and
- data *max_num_steps*: maximum number of steps to take in the ODE solver, type int, data only.

Return values

The return value for the ODE solvers is an array of type array[,] real, with values consisting of solutions at the specified times.

Sizes and parallel arrays

The sizes must match, and in particular, the following groups are of the same size:

- state variables passed into the system function, derivatives returned by the system function, initial state passed into the solver, and rows of the return value of the solver,
- solution times and number of rows of the return value of the solver,
- parameters, real data and integer data passed to the solver will be passed to the system function

12.3. algebra_solver, algebra_solver_newton algebraic solvers

These algebraic solver functions have been replaced by those described in [Algebraic Equation Solvers](#)..

Specifying an algebraic equation as a function

An algebraic system is specified as an ordinary function in Stan within the function block. The algebraic system function must have this signature:


```
vector algebra_system(vector y, vector theta,
                      data array[] real x_r, array[] int x_i)
```

The algebraic system function should return the value of the algebraic function which goes to 0, when we plug in the solution to the algebraic system.

The argument of this function are:

- y , the unknowns we wish to solve for
- θ , parameter values used to evaluate the algebraic system
- x_r , data values used to evaluate the algebraic system
- x_i , integer data used to evaluate the algebraic system

The algebraic system function separates parameter values, θ , from data values, x_r , for efficiency in propagating the derivatives through the algebraic system.

Call to the algebraic solver

```
vector algebra_solver(function algebra_system, vector y_guess, vec-
tor theta, data array[] real x_r, array[] int x_i)
```

Solves the algebraic system, given an initial guess, using the Powell hybrid algorithm.

Available since 2.17, deprecated in 2.31

```
vector algebra_solver(function algebra_system, vector y_guess,
vector theta, data array[] real x_r, array[] int x_i, data real
rel_tol, data real f_tol, int max_steps)
```

Solves the algebraic system, given an initial guess, using the Powell hybrid algorithm with additional control parameters for the solver.

Available since 2.17, deprecated in 2.31

Note: In future releases, the function `algebra_solver` will be deprecated and replaced with `algebra_solver_powell`.

```
vector algebra_solver_newton(function algebra_system, vector
y_guess, vector theta, data array[] real x_r, array[] int x_i)
```

Solves the algebraic system, given an initial guess, using Newton's method.

Available since 2.24, deprecated in 2.31

```
vector algebra_solver_newton(function algebra_system, vector
y_guess, vector theta, data array[] real x_r, array[] int x_i,
```

```
data real rel_tol, data real f_tol, int max_steps)
```

Solves the algebraic system, given an initial guess, using Newton's method with additional control parameters for the solver.

Available since 2.24, deprecated in 2.31

Arguments to the algebraic solver

The arguments to the algebraic solvers are as follows:

- *algebra_system*: function literal referring to a function specifying the system of algebraic equations with signature `(vector, vector, array[] real, array[] int):vector`. The arguments represent (1) unknowns, (2) parameters, (3) real data, and (4) integer data, and the return value contains the value of the algebraic function, which goes to 0 when we plug in the solution to the algebraic system,
- *y_guess*: initial guess for the solution, type `vector`,
- *theta*: parameters only, type `vector`,
- *x_r*: real data only, type `array[] real`, and
- *x_i*: integer data only, type `array[] int`.

For more fine-grained control of the algebraic solver, these parameters can also be provided:

- *rel_tol*: relative tolerance for the algebraic solver, type `real`, data only,
- *function_tol*: function tolerance for the algebraic solver, type `real`, data only,
- *max_num_steps*: maximum number of steps to take in the algebraic solver, type `int`, data only.

Return value

The return value for the algebraic solver is an object of type `vector`, with values which, when plugged in as y make the algebraic function go to 0.

Sizes and parallel arrays

Certain sizes have to be consistent. The initial guess, return value of the solver, and return value of the algebraic function must all be the same size.

The parameters, real data, and integer data will be passed from the solver directly to the system function.

13. Removed Functions

Functions which once existed in the Stan language and have since been replaced or removed are listed here.

13.1. `multiply_log` and `binomial_coefficient_log` functions

Removed: Currently two non-conforming functions ending in suffix `_log`.

Replacement: Replace `multiply_log(...)` with `lmultiply(...)`. Replace `binomial_coefficient_log(...)` with `lchoose(...)`.

Removed In: Stan 2.33

13.2. `get_lp()` function

Removed: The built-in no-argument function `get_lp()` is deprecated.

Replacement: Use the no-argument function `target()` instead.

Removed In: Stan 2.33

13.3. `fabs` function

Removed: The unary function `fabs` is deprecated.

Replacement: Use the unary function `abs` instead. Note that the return type for `abs` is different for integer overloads, but this replacement is safe due to Stan's type promotion rules.

Removed In: Stan 2.33

13.4. Exponentiated quadratic covariance functions

These covariance functions have been replaced by those described in [Gaussian Process Covariance Functions](#)

With magnitude α and length scale l , the exponentiated quadratic kernel is:

$$k(x_i, x_j) = \alpha^2 \exp\left(-\frac{1}{2\rho^2} \sum_{d=1}^D (x_{i,d} - x_{j,d})^2\right)$$

13.5. REAL ARGUMENTS TO LOGICAL OPERATORS `OPERATOR&&`, `OPERATOR||`, AND `OPERATOR!`

matrix `cov_exp_quad`(row_vectors x, real alpha, real rho)

The covariance matrix with an exponentiated quadratic kernel of x.

Available since 2.16, deprecated since 2.20, removed in in 2.33

matrix `cov_exp_quad`(vectors x, real alpha, real rho)

The covariance matrix with an exponentiated quadratic kernel of x.

Available since 2.16, deprecated since 2.20, removed in in 2.33

matrix `cov_exp_quad`(array[] real x, real alpha, real rho)

The covariance matrix with an exponentiated quadratic kernel of x.

Available since 2.16, deprecated since 2.20, removed in in 2.33

matrix `cov_exp_quad`(row_vectors x1, row_vectors x2, real alpha, real rho)

The covariance matrix with an exponentiated quadratic kernel of x1 and x2.

Available since 2.18, deprecated since 2.20, removed in in 2.33

matrix `cov_exp_quad`(vectors x1, vectors x2, real alpha, real rho)

The covariance matrix with an exponentiated quadratic kernel of x1 and x2.

Available since 2.18, deprecated since 2.20, removed in in 2.33

matrix `cov_exp_quad`(array[] real x1, array[] real x2, real alpha, real rho)

The covariance matrix with an exponentiated quadratic kernel of x1 and x2.

Available since 2.18, deprecated since 2.20, removed in in 2.33

13.5. Real arguments to logical operators `operator&&`, `operator||`, and `operator!`

Removed: A nonzero real number (even NaN) was interpreted as true and a zero was interpreted as false.

Replacement: Explicit `x != 0` comparison is preferred instead.

Removed In: Stan 2.34

14. Conventions for Probability Functions

Functions associated with distributions are set up to follow the same naming conventions for both built-in distributions and for user-defined distributions.

14.1. Suffix marks type of function

The suffix is determined by the type of function according to the following table.

function	outcome	suffix
log probability mass function	discrete	<code>_lpmf</code>
log probability density function	continuous	<code>_lpdf</code>
log cumulative distribution function	any	<code>_lcdf</code>
log complementary cumulative distribution function	any	<code>_lccdf</code>
random number generator	any	<code>_rng</code>

For example, `normal_lpdf` is the log of the normal probability density function (pdf) and `bernoulli_lpmf` is the log of the bernoulli probability mass function (pmf). The log of the corresponding cumulative distribution functions (cdf) use the same suffix, `normal_lcdf` and `bernoulli_lcdf`.

14.2. Argument order and the vertical bar

Each probability function has a specific outcome value and a number of parameters. Following conditional probability notation, probability density and mass functions use a vertical bar to separate the outcome from the parameters of the distribution. For example, `normal_lpdf(y | mu, sigma)` returns the value of mathematical formula $\log \text{Normal}(y | \mu, \sigma)$. Cumulative distribution functions separate the outcome from the parameters in the same way (e.g., `normal_lcdf(y_low | mu, sigma)`).

14.3. Sampling notation

The notation

```
y ~ normal(mu, sigma);
```

provides the same (proportional) contribution to the model log density as the explicit target density increment,

```
target += normal_lpdf(y | mu, sigma);
```

In both cases, the effect is to add terms to the target log density. The only difference is that the example with the sampling (\sim) notation drops all additive constants in the log density; the constants are not necessary for any of Stan's sampling, approximation, or optimization algorithms.

14.4. Finite inputs

All of the distribution functions are configured to throw exceptions (effectively rejecting samples or optimization steps) when they are supplied with non-finite arguments. The two cases of non-finite arguments are the infinite values and not-a-number value—these are standard in floating-point arithmetic.

14.5. Boundary conditions

Many distributions are defined with support or constraints on parameters forming an open interval. For example, the normal density function accepts a scale parameter $\sigma > 0$. If $\sigma = 0$, the probability function will throw an exception.

This is true even for (complementary) cumulative distribution functions, which will throw exceptions when given input that is out of the support.

14.6. Pseudorandom number generators

For most of the probability functions, there is a matching pseudorandom number generator (PRNG) with the suffix `_rng`. For example, the function `normal_rng(real, real)` accepts two real arguments, an unconstrained location μ and positive scale $\sigma > 0$, and returns an unconstrained pseudorandom value drawn from $\text{Normal}(\mu, \sigma)$. There are also vectorized forms of random number generators which return more than one random variate at a time.

Restricted to transformed data and generated quantities

Unlike regular functions, the PRNG functions may only be used in the transformed data or generated quantities blocks.

Limited vectorization

Unlike the probability functions, only some of the PRNG functions are vectorized.

14.7. Cumulative distribution functions

For most of the univariate probability functions, there is a corresponding cumulative distribution function, log cumulative distribution function, and log complementary

cumulative distribution function.

For a univariate random variable Y with probability function $p_Y(y | \theta)$, the cumulative distribution function (CDF) F_Y is defined by

$$F_Y(y) = \Pr[Y \leq y] = \int_{-\infty}^y p(y | \theta) dy.$$

The complementary cumulative distribution function (CCDF) is defined as

$$\Pr[Y > y] = 1 - F_Y(y).$$

The reason to use CCDFs instead of CDFs in floating-point arithmetic is that it is possible to represent numbers very close to 0 (the closest you can get is roughly 10^{-300}), but not numbers very close to 1 (the closest you can get is roughly $1 - 10^{-15}$).

In Stan, there is a cumulative distribution function for each probability function. For instance, `normal_cdf(y | mu, sigma)` is defined by

$$\int_{-\infty}^y \text{Normal}(y | \mu, \sigma) dy.$$

There are also log forms of the CDF and CCDF for most univariate distributions. For example, `normal_lcdf(y | mu, sigma)` is defined by

$$\log \left(\int_{-\infty}^y \text{Normal}(y | \mu, \sigma) dy \right)$$

and `normal_lccdf(y | mu, sigma)` is defined by

$$\log \left(1 - \int_{-\infty}^y \text{Normal}(y | \mu, \sigma) dy \right).$$

14.8. Vectorization

Stan's univariate log probability functions, including the log density functions, log mass functions, log CDFs, and log CCDFs, all support vectorized function application, with results defined to be the sum of the elementwise application of the function. Some of the PRNG functions support vectorization, see section [vectorized PRNG functions](#) for more details.

In all cases, matrix operations are at least as fast and usually faster than loops and vectorized log probability functions are faster than their equivalent form defined

with loops. This isn't because loops are slow in Stan, but because more efficient automatic differentiation can be used. The efficiency comes from the fact that a vectorized log probability function only introduces one new node into the expression graph, thus reducing the number of virtual function calls required to compute gradients in C++, as well as from allowing caching of repeated computations.

Stan also overloads the multivariate normal distribution, including the Cholesky-factor form, allowing arrays of row vectors or vectors for the variate and location parameter. This is a huge savings in speed because the work required to solve the linear system for the covariance matrix is only done once.

Stan also overloads some scalar functions, such as `log` and `exp`, to apply to vectors (arrays) and return vectors (arrays). These vectorizations are defined elementwise and unlike the probability functions, provide only minimal efficiency speedups over repeated application and assignment in a loop.

Vectorized function signatures

Vectorized scalar arguments

The normal probability function is specified with the signature

```
normal_lpdf(reals | reals, reals);
```

The pseudotype `reals` is used to indicate that an argument position may be vectorized. Argument positions declared as `reals` may be filled with a real, a one-dimensional array, a vector, or a row-vector. If there is more than one array or vector argument, their types can be anything but their size must match. For instance, it is legal to use `normal_lpdf(row_vector | vector, real)` as long as the vector and row vector have the same size.

Vectorized vector and row vector arguments

The multivariate normal distribution accepting vector or array of vector arguments is written as

```
multi_normal_lpdf(vectors | vectors, matrix);
```

These arguments may be row vectors, column vectors, or arrays of row vectors or column vectors.

Vectorized integer arguments

The pseudotype `ints` is used for vectorized integer arguments. Where it appears either an integer or array of integers may be used.

Evaluating vectorized log probability functions

The result of a vectorized log probability function is equivalent to the sum of the evaluations on each element. Any non-vector argument, namely `real` or `int`, is repeated. For instance, if `y` is a vector of size `N`, `mu` is a vector of size `N`, and `sigma` is a scalar, then

```
ll = normal_lpdf(y | mu, sigma);
```

is just a more efficient way to write

```
ll = 0;
for (n in 1:N) {
  ll = ll + normal_lpdf(y[n] | mu[n], sigma);
}
```

With the same arguments, the vectorized sampling statement

```
y ~ normal(mu, sigma);
```

has the same effect on the total log probability as

```
for (n in 1:N) {
  y[n] ~ normal(mu[n], sigma);
}
```

Evaluating vectorized PRNG functions

Some PRNG functions accept sequences as well as scalars as arguments. Such functions are indicated by argument pseudotypes `reals` or `ints`. In cases of sequence arguments, the output will also be a sequence. For example, the following is allowed in the transformed data and generated quantities blocks.

```
vector[3] mu = // ...
array[3] real x = normal_rng(mu, 3);
```

Argument types

In the case of PRNG functions, arguments marked `ints` may be integers or integer arrays, whereas arguments marked `reals` may be integers or reals, integer or real arrays, vectors, or row vectors.

pseudotype allowable PRNG arguments

<code>ints</code>	<code>int, array[]</code>	<code>int</code>
<code>reals</code>	<code>int, array[]</code>	<code>int, real, array[]</code>
		<code>real, vector, row_vector</code>

Dimension matching

In general, if there are multiple non-scalar arguments, they must all have the same dimensions, but need not have the same type. For example, the `normal_rng` function may be called with one vector argument and one real array argument as long as they have the same number of elements.

```
vector[3] mu = // ...
array[3] real sigma = // ...
array[3] real x = normal_rng(mu, sigma);
```

Return type

The result of a vectorized PRNG function depends on the size of the arguments and the distribution's support. If all arguments are scalars, then the return type is a scalar. For a continuous distribution, if there are any non-scalar arguments, the return type is a real array (`array[] real`) matching the size of any of the non-scalar arguments, as all non-scalar arguments must have matching size. Discrete distributions return `ints` and continuous distributions return `reals`, each of appropriate size. The symbol `R` denotes such a return type.

Part II

Discrete Distributions

15. Binary Distributions

Binary probability distributions have support on $\{0, 1\}$, where 1 represents the value true and 0 the value false.

15.1. Bernoulli distribution

Probability mass function

If $\theta \in [0, 1]$, then for $y \in \{0, 1\}$,

$$\text{Bernoulli}(y \mid \theta) = \begin{cases} \theta & \text{if } y = 1, \text{ and} \\ 1 - \theta & \text{if } y = 0. \end{cases}$$

Distribution statement

$y \sim \text{bernoulli}(\text{theta})$

Increment target log probability density with `bernoulli_lupmf(y | theta)`.

Available since 2.0

Stan Functions

`real bernoulli_lpmf(ints y | reals theta)`

The log Bernoulli probability mass of y given chance of success theta

Available since 2.12

`real bernoulli_lupmf(ints y | reals theta)`

The log Bernoulli probability mass of y given chance of success theta dropping constant additive terms

Available since 2.25

`real bernoulli_cdf(ints y | reals theta)`

The Bernoulli cumulative distribution function of y given chance of success theta

Available since 2.0

`real bernoulli_lcdf(ints y | reals theta)`

The log of the Bernoulli cumulative distribution function of y given chance of success theta

Available since 2.12

real **bernoulli_lccdf**(ints y | reals theta)

The log of the Bernoulli complementary cumulative distribution function of y given chance of success theta

Available since 2.12

ints **bernoulli_rng**(reals theta)

Generate a Bernoulli variate with chance of success theta or an array of Bernoulli variates given an array of thetas of the same dimensions; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

15.2. Bernoulli distribution, logit parameterization

Stan also supplies a direct parameterization in terms of a logit-transformed chance-of-success parameter. This parameterization is more numerically stable if the chance-of-success parameter is on the logit scale, as with the linear predictor in a logistic regression.

Probability mass function

If $\alpha \in \mathbb{R}$, then for $y \in \{0, 1\}$,

$$\text{BernoulliLogit}(y | \alpha) = \text{Bernoulli}(y | \text{logit}^{-1}(\alpha)) = \begin{cases} \text{logit}^{-1}(\alpha) & \text{if } y = 1, \text{ and} \\ 1 - \text{logit}^{-1}(\alpha) & \text{if } y = 0. \end{cases}$$

Distribution statement

$y \sim \text{bernoulli_logit}(\text{alpha})$

Increment target log probability density with `bernoulli_logit_lupmf(y | alpha)`.

Available since 2.0

Stan Functions

real **bernoulli_logit_lpmf**(ints y | reals alpha)

The log Bernoulli probability mass of y given chance of success `inv_logit(alpha)`

Available since 2.12

real **bernoulli_logit_lupmf**(ints y | reals alpha)

The log Bernoulli probability mass of y given chance of success `inv_logit(alpha)` dropping constant additive terms

Available since 2.25

R `bernoulli_logit_rng`(reals alpha)

Generate a Bernoulli variate with chance of success $\text{logit}^{-1}(\alpha)$; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

15.3. Bernoulli-logit generalized linear model (Logistic Regression)

Stan also supplies a single function for a generalized linear model with Bernoulli distribution and logit link function, i.e. a function for a logistic regression. This provides a more efficient implementation of logistic regression than a manually written regression in terms of a Bernoulli distribution and matrix multiplication.

Probability mass function

If $x \in \mathbb{R}^{n \cdot m}$, $\alpha \in \mathbb{R}^n$, $\beta \in \mathbb{R}^m$, then for $y \in \{0, 1\}^n$,

$$\begin{aligned} \text{BernoulliLogitGLM}(y \mid x, \alpha, \beta) &= \prod_{1 \leq i \leq n} \text{Bernoulli}(y_i \mid \text{logit}^{-1}(\alpha_i + x_i \cdot \beta)) \\ &= \prod_{1 \leq i \leq n} \begin{cases} \text{logit}^{-1}(\alpha_i + \sum_{1 \leq j \leq m} x_{ij} \cdot \beta_j) & \text{if } y_i = 1, \text{ and} \\ 1 - \text{logit}^{-1}(\alpha_i + \sum_{1 \leq j \leq m} x_{ij} \cdot \beta_j) & \text{if } y_i = 0. \end{cases} \end{aligned}$$

Distribution statement

$y \sim \text{bernoulli_logit_glm}(x, \text{alpha}, \text{beta})$

Increment target log probability density with `bernoulli_logit_glm_lupmf(y | x, alpha, beta)`.

Available since 2.25

Stan Functions

real `bernoulli_logit_glm_lpmf`(int y | matrix x, real alpha, vector beta)

The log Bernoulli probability mass of y given chance of success `inv_logit(alpha + x * beta)`.

Available since 2.23

real `bernoulli_logit_glm_lupmf`(int y | matrix x, real alpha, vector beta)

15.3. BERNOULLI-LOGIT GENERALIZED LINEAR MODEL (LOGISTIC REGRESSION)1

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \beta)$ dropping constant additive terms.

Available since 2.25

```
real bernoulli_logit_glm_lpmf(int y | matrix x, vector alpha, vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \beta)$.

Available since 2.23

```
real bernoulli_logit_glm_lupmf(int y | matrix x, vector alpha, vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \beta)$ dropping constant additive terms.

Available since 2.25

```
real bernoulli_logit_glm_lpmf(array[] int y | row_vector x, real alpha, vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \beta)$.

Available since 2.23

```
real bernoulli_logit_glm_lupmf(array[] int y | row_vector x, real alpha, vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \beta)$ dropping constant additive terms.

Available since 2.25

```
real bernoulli_logit_glm_lpmf(array[] int y | row_vector x, vector alpha, vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \beta)$.

Available since 2.23

```
real bernoulli_logit_glm_lupmf(array[] int y | row_vector x, vector alpha, vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \beta)$ dropping constant additive terms.

Available since 2.25


```
real bernoulli_logit_glm_lpmf(array[] int y | matrix x, real alpha,
vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \text{beta})$.

Available since 2.18

```
real bernoulli_logit_glm_lupmf(array[] int y | matrix x, real al-
pha, vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \text{beta})$ dropping constant additive terms.

Available since 2.25

```
real bernoulli_logit_glm_lpmf(array[] int y | matrix x, vector al-
pha, vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \text{beta})$.

Available since 2.18

```
real bernoulli_logit_glm_lupmf(array[] int y | matrix x, vector al-
pha, vector beta)
```

The log Bernoulli probability mass of y given chance of success $\text{inv_logit}(\alpha + x * \text{beta})$ dropping constant additive terms.

Available since 2.25

```
array[] int bernoulli_logit_glm_rng(matrix x, vector alpha, vector
beta)
```

Generate an array of Bernoulli variates with chances of success $\text{inv_logit}(\alpha + x * \text{beta})$; may only be used in transformed data and generated quantities blocks.

Available since 2.29

```
array[] int bernoulli_logit_glm_rng(row_vector x, vector alpha,
vector beta)
```

Generate an array of Bernoulli variates with chances of success $\text{inv_logit}(\alpha + x * \text{beta})$; may only be used in transformed data and generated quantities blocks.

Available since 2.29

16. Bounded Discrete Distributions

Bounded discrete probability functions have support on $\{0, \dots, N\}$ for some upper bound N .

16.1. Binomial distribution

Probability mass function

Suppose $N \in \mathbb{N}$ and $\theta \in [0, 1]$, and $n \in \{0, \dots, N\}$.

$$\text{Binomial}(n | N, \theta) = \binom{N}{n} \theta^n (1 - \theta)^{N-n}.$$

Log probability mass function

$$\begin{aligned} \log \text{Binomial}(n | N, \theta) &= \log \Gamma(N + 1) - \log \Gamma(n + 1) - \log \Gamma(N - n + 1) \\ &\quad + n \log \theta + (N - n) \log(1 - \theta), \end{aligned}$$

Gradient of log probability mass function

$$\frac{\partial}{\partial \theta} \log \text{Binomial}(n | N, \theta) = \frac{n}{\theta} - \frac{N - n}{1 - \theta}$$

Distribution statement

$n \sim \text{binomial}(N, \text{theta})$

Increment target log probability density with `binomial_lupmf(n | N, theta)`.

Available since 2.0

Stan functions

`real binomial_lpmf(ints n | ints N, reals theta)`

The log binomial probability mass of n successes in N trials given chance of success theta

Available since 2.12

real **binomial_lupmf**(ints n | ints N, reals theta)

The log binomial probability mass of n successes in N trials given chance of success theta dropping constant additive terms

Available since 2.25

real **binomial_cdf**(ints n | ints N, reals theta)

The binomial cumulative distribution function of n successes in N trials given chance of success theta

Available since 2.0

real **binomial_lcdf**(ints n | ints N, reals theta)

The log of the binomial cumulative distribution function of n successes in N trials given chance of success theta

Available since 2.12

real **binomial_lccdf**(ints n | ints N, reals theta)

The log of the binomial complementary cumulative distribution function of n successes in N trials given chance of success theta

Available since 2.12

R **binomial_rng**(ints N, reals theta)

Generate a binomial variate with N trials and chance of success theta; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

16.2. Binomial distribution, logit parameterization

Stan also provides a version of the binomial probability mass function distribution with the chance of success parameterized on the unconstrained logistic scale.

Probability mass function

Suppose $N \in \mathbb{N}$, $\alpha \in \mathbb{R}$, and $n \in \{0, \dots, N\}$. Then

$$\begin{aligned} \text{BinomialLogit}(n \mid N, \alpha) &= \text{Binomial}(n \mid N, \text{logit}^{-1}(\alpha)) \\ &= \binom{N}{n} \left(\text{logit}^{-1}(\alpha)\right)^n \left(1 - \text{logit}^{-1}(\alpha)\right)^{N-n}. \end{aligned}$$

Log probability mass function

$$\begin{aligned} \log \text{BinomialLogit}(n \mid N, \alpha) &= \log \Gamma(N + 1) - \log \Gamma(n + 1) - \log \Gamma(N - n + 1) \\ &\quad + n \log \text{logit}^{-1}(\alpha) + (N - n) \log \left(1 - \text{logit}^{-1}(\alpha)\right), \end{aligned}$$

Gradient of log probability mass function

$$\frac{\partial}{\partial \alpha} \log \text{BinomialLogit}(n \mid N, \alpha) = \frac{n}{\text{logit}^{-1}(\alpha)} - \frac{N - n}{\text{logit}^{-1}(\alpha)}$$

Distribution statement

`n` ~ **binomial_logit**(`N`, `alpha`)

Increment target log probability density with `binomial_logit_lupmf`(`n` | `N`, `alpha`).

Available since 2.0

Stan functions

`real binomial_logit_lpmf`(`ints n` | `ints N`, `reals alpha`)

The log binomial probability mass of `n` successes in `N` trials given logit-scaled chance of success `alpha`

Available since 2.12

`real binomial_logit_lupmf`(`ints n` | `ints N`, `reals alpha`)

The log binomial probability mass of `n` successes in `N` trials given logit-scaled chance of success `alpha` dropping constant additive terms

Available since 2.25

16.3. Binomial-logit generalized linear model (Logistic Regression)

Stan also supplies a single function for a generalized linear model with binomial distribution and logit link function, i.e., a function for logistic regression with aggregated outcomes. This provides a more efficient implementation of logistic regression than a manually written regression in terms of a binomial distribution and matrix multiplication.

Probability mass function

Suppose $N \in \mathbb{N}$, $x \in \mathbb{R}^{n \cdot m}$, $\alpha \in \mathbb{R}^n$, $\beta \in \mathbb{R}^m$, and $n \in \{0, \dots, N\}$. Then

$$\begin{aligned} \text{BinomialLogitGLM}(n \mid N, x, \alpha, \beta) &= \text{Binomial}(n \mid N, \text{logit}^{-1}(\alpha_i + x_i \cdot \beta)) \\ &= \binom{N}{n} \left(\text{logit}^{-1}(\alpha_i + \sum_{1 \leq j \leq m} x_{ij} \cdot \beta_j) \right)^n \left(1 - \text{logit}^{-1}(\alpha_i + \sum_{1 \leq j \leq m} x_{ij} \cdot \beta_j) \right)^{N-n}. \end{aligned}$$

Distribution statement

$n \sim \text{binomial_logit_glm}(N, x, \text{alpha}, \text{beta})$

Increment target log probability density with `binomial_logit_glm_lupmf(n | N, x, alpha, beta)`.

Available since 2.34

Stan Functions

real **binomial_logit_glm_lpmf**(int n | int N, matrix x, real alpha, vector beta)

The log binomial probability mass of n given N trials and chance of success `inv_logit(alpha + x * beta)`.

Available since 2.34

real **binomial_logit_glm_lupmf**(int n | int N, matrix x, real alpha, vector beta)

The log binomial probability mass of n given N trials and chance of success `inv_logit(alpha + x * beta)` dropping constant additive terms.

Available since 2.34

real **binomial_logit_glm_lpmf**(int n | int N, matrix x, vector alpha, vector beta)

The log binomial probability mass of n given N trials and chance of success `inv_logit(alpha + x * beta)`.

Available since 2.34

real **binomial_logit_glm_lupmf**(int n | int N, matrix x, vector alpha, vector beta)

The log binomial probability mass of n given N trials and chance of success `inv_logit(alpha + x * beta)` dropping constant additive terms.

Available since 2.34

16.3. BINOMIAL-LOGIT GENERALIZED LINEAR MODEL (LOGISTIC REGRESSION)18

```
real      binomial_logit_glm_lpmf(array[] int n | array[] int N,  
row_vector x, real alpha, vector beta)
```

The log binomial probability mass of n given N trials and chance of success $\text{inv_logit}(\alpha + x * \beta)$.

Available since 2.34

```
real      binomial_logit_glm_lupmf(array[] int n | array[] int N,  
row_vector x, real alpha, vector beta)
```

The log binomial probability mass of n given N trials and chance of success $\text{inv_logit}(\alpha + x * \beta)$ dropping constant additive terms.

Available since 2.34

```
real      binomial_logit_glm_lpmf(array[] int n | array[] int N,  
row_vector x, vector alpha, vector beta)
```

The log binomial probability mass of n given N trials and chance of success $\text{inv_logit}(\alpha + x * \beta)$.

Available since 2.34

```
real      binomial_logit_glm_lupmf(array[] int n | array[] int N,  
row_vector x, vector alpha, vector beta)
```

The log binomial probability mass of n given N trials and chance of success $\text{inv_logit}(\alpha + x * \beta)$ dropping constant additive terms.

Available since 2.34

```
real      binomial_logit_glm_lpmf(array[] int n | array[] int N, matrix  
x, real alpha, vector beta)
```

The log binomial probability mass of n given N trials and chance of success $\text{inv_logit}(\alpha + x * \beta)$.

Available since 2.34

```
real      binomial_logit_glm_lupmf(array[] int n | array[] int N, matrix  
x, real alpha, vector beta)
```

The log binomial probability mass of n given N trials and chance of success $\text{inv_logit}(\alpha + x * \beta)$ dropping constant additive terms.

Available since 2.34

```
real      binomial_logit_glm_lpmf(array[] int n | array[] int N, matrix  
x, vector alpha, vector beta)
```

The log binomial probability mass of n given N trials and chance of success `inv_logit(alpha + x * beta)`.

Available since 2.34

`real binomial_logit_glm_lupmf(array[] int n | array[] int N, matrix x, vector alpha, vector beta)`

The log binomial probability mass of n given N trials and chance of success `inv_logit(alpha + x * beta)` dropping constant additive terms.

Available since 2.34

16.4. Beta-binomial distribution

Probability mass function

If $N \in \mathbb{N}$, $\alpha \in \mathbb{R}^+$, and $\beta \in \mathbb{R}^+$, then for $n \in 0, \dots, N$,

$$\text{BetaBinomial}(n | N, \alpha, \beta) = \binom{N}{n} \frac{B(n + \alpha, N - n + \beta)}{B(\alpha, \beta)},$$

where the beta function $B(u, v)$ is defined for $u \in \mathbb{R}^+$ and $v \in \mathbb{R}^+$ by

$$B(u, v) = \frac{\Gamma(u) \Gamma(v)}{\Gamma(u + v)}.$$

Distribution statement

$n \sim \text{beta_binomial}(N, \text{alpha}, \text{beta})$

Increment target log probability density with `beta_binomial_lupmf(n | N, alpha, beta)`.

Available since 2.0

Stan functions

`real beta_binomial_lpmf(ints n | ints N, reals alpha, reals beta)`

The log beta-binomial probability mass of n successes in N trials given prior success count (plus one) of α and prior failure count (plus one) of β

Available since 2.12

`real beta_binomial_lupmf(ints n | ints N, reals alpha, reals beta)`

The log beta-binomial probability mass of n successes in N trials given prior success count (plus one) of α and prior failure count (plus one) of β dropping constant additive terms

Available since 2.25

real **beta_binomial_cdf**(ints n | ints N, reals alpha, reals beta)
 The beta-binomial cumulative distribution function of n successes in N trials given prior success count (plus one) of alpha and prior failure count (plus one) of beta

Available since 2.0

real **beta_binomial_lcdf**(ints n | ints N, reals alpha, reals beta)
 The log of the beta-binomial cumulative distribution function of n successes in N trials given prior success count (plus one) of alpha and prior failure count (plus one) of beta

Available since 2.12

real **beta_binomial_lccdf**(ints n | ints N, reals alpha, reals beta)
 The log of the beta-binomial complementary cumulative distribution function of n successes in N trials given prior success count (plus one) of alpha and prior failure count (plus one) of beta

Available since 2.12

R **beta_binomial_rng**(ints N, reals alpha, reals beta)
 Generate a beta-binomial variate with N trials, prior success count (plus one) of alpha, and prior failure count (plus one) of beta; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

16.5. Hypergeometric distribution

Probability mass function

If $a \in \mathbb{N}$, $b \in \mathbb{N}$, and $N \in \{0, \dots, a + b\}$, then for $n \in \{\max(0, N - b), \dots, \min(a, N)\}$,

$$\text{Hypergeometric}(n \mid N, a, b) = \frac{\binom{a}{n} \binom{b}{N-n}}{\binom{a+b}{N}}.$$

Distribution statement

$n \sim \text{hypergeometric}(N, a, b)$

Increment target log probability density with `hypergeometric_lupmf(n | N, a, b)`.

Available since 2.0

Stan functions

real **hypergeometric_lpmf**(int n | int N, int a, int b)

The log hypergeometric probability mass of n successes in N trials given total success count of a and total failure count of b

Available since 2.12

real **hypergeometric_lupmf**(int n | int N, int a, int b)

The log hypergeometric probability mass of n successes in N trials given total success count of a and total failure count of b dropping constant additive terms

Available since 2.25

int **hypergeometric_rng**(int N, int a, int b)

Generate a hypergeometric variate with N trials, total success count of a, and total failure count of b; may only be used in transformed data and generated quantities blocks

Available since 2.18

16.6. Categorical distribution

Probability mass functions

If $N \in \mathbb{N}$, $N > 0$, and if $\theta \in \mathbb{R}^N$ forms an N -simplex (i.e., has nonnegative entries summing to one), then for $y \in \{1, \dots, N\}$,

$$\text{Categorical}(y \mid \theta) = \theta_y.$$

In addition, Stan provides a log-odds scaled categorical distribution,

$$\text{CategoricalLogit}(y \mid \beta) = \text{Categorical}(y \mid \text{softmax}(\beta)).$$

See [the definition of softmax](#) for the definition of the softmax function.

Distribution statement

$y \sim \text{categorical}(\text{theta})$

Increment target log probability density with `categorical_lupmf(y | theta)` dropping constant additive terms.

Available since 2.0

Distribution statement

$y \sim \text{categorical_logit}(\text{beta})$

Increment target log probability density with `categorical_logit_lupmf(y | beta)`.

Available since 2.4

Stan functions

All of the categorical distributions are vectorized so that the outcome y can be a single integer (type `int`) or an array of integers (type `array[] int`).

real **categorical_lpmf**(ints y | vector θ)

The log categorical probability mass function with outcome(s) y in $1 : N$ given N -vector of outcome probabilities θ . The parameter θ must have non-negative entries that sum to one, but it need not be a variable declared as a simplex.

Available since 2.12

real **categorical_lupmf**(ints y | vector θ)

The log categorical probability mass function with outcome(s) y in $1 : N$ given N -vector of outcome probabilities θ dropping constant additive terms. The parameter θ must have non-negative entries that sum to one, but it need not be a variable declared as a simplex.

Available since 2.25

real **categorical_logit_lpmf**(ints y | vector β)

The log categorical probability mass function with outcome(s) y in $1 : N$ given log-odds of outcomes β .

Available since 2.12

real **categorical_logit_lupmf**(ints y | vector β)

The log categorical probability mass function with outcome(s) y in $1 : N$ given log-odds of outcomes β dropping constant additive terms.

Available since 2.25

int **categorical_rng**(vector θ)

Generate a categorical variate with N -simplex distribution parameter θ ; may only be used in transformed data and generated quantities blocks

Available since 2.0

int **categorical_logit_rng**(vector beta)

Generate a categorical variate with outcome in range $1 : N$ from log-odds vector beta; may only be used in transformed data and generated quantities blocks

Available since 2.16

16.7. Categorical logit generalized linear model (softmax regression)

Stan also supplies a single function for a generalized linear model with categorical distribution and logit link function, i.e. a function for a softmax regression. This provides a more efficient implementation of softmax regression than a manually written regression in terms of a categorical distribution and matrix multiplication.

Note that the implementation does not put any restrictions on the coefficient matrix β . It is up to the user to use a reference category, a suitable prior or some other means of identifiability. See Multi-logit in the [Stan User's Guide](#).

Probability mass functions

If $N, M, K \in \mathbb{N}$, $N, M, K > 0$, and if $x \in \mathbb{R}^{M \times K}$, $\alpha \in \mathbb{R}^N$, $\beta \in \mathbb{R}^{K \cdot N}$, then for $y \in \{1, \dots, N\}^M$,

$$\begin{aligned} \text{CategoricalLogitGLM}(y \mid x, \alpha, \beta) &= \prod_{1 \leq i \leq M} \text{CategoricalLogit}(y_i \mid \alpha + x_i \cdot \beta) \\ &= \prod_{1 \leq i \leq M} \text{Categorical}(y_i \mid \text{softmax}(\alpha + x_i \cdot \beta)). \end{aligned}$$

See [the definition of softmax](#) for the definition of the softmax function.

Distribution statement

$y \sim \text{categorical_logit_glm}(x, \text{alpha}, \text{beta})$

Increment target log probability density with `categorical_logit_glm_lupmf(y | x, alpha, beta)`.

Available since 2.23

Stan functions

real **categorical_logit_glm_lpmf**(int y | row_vector x, vector alpha, matrix beta)

The log categorical probability mass function with outcome y in $1 : N$ given N -vector of log-odds of outcomes $\text{alpha} + x * \text{beta}$.

Available since 2.23

16.7. CATEGORICAL LOGIT GENERALIZED LINEAR MODEL (SOFTMAX REGRESSION)

```
real categorical_logit_glm_lupmf(int y | row_vector x, vector alpha, matrix beta)
```

The log categorical probability mass function with outcome y in $1 : N$ given N -vector of log-odds of outcomes $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

```
real categorical_logit_glm_lpmf(int y | matrix x, vector alpha, matrix beta)
```

The log categorical probability mass function with outcomes y in $1 : N$ given N -vector of log-odds of outcomes $\alpha + x * \beta$.

Available since 2.23

```
real categorical_logit_glm_lupmf(int y | matrix x, vector alpha, matrix beta)
```

The log categorical probability mass function with outcomes y in $1 : N$ given N -vector of log-odds of outcomes $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

```
real categorical_logit_glm_lpmf(array[] int y | row_vector x, vector alpha, matrix beta)
```

The log categorical probability mass function with outcomes y in $1 : N$ given N -vector of log-odds of outcomes $\alpha + x * \beta$.

Available since 2.23

```
real categorical_logit_glm_lupmf(array[] int y | row_vector x, vector alpha, matrix beta)
```

The log categorical probability mass function with outcomes y in $1 : N$ given N -vector of log-odds of outcomes $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

```
real categorical_logit_glm_lpmf(array[] int y | matrix x, vector alpha, matrix beta)
```

The log categorical probability mass function with outcomes y in $1 : N$ given N -vector of log-odds of outcomes $\alpha + x * \beta$.

Available since 2.23

real **categorical_logit_glm_lupmf**(array[] int y | matrix x, vector alpha, matrix beta)

The log categorical probability mass function with outcomes y in $1 : N$ given N -vector of log-odds of outcomes $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

16.8. Discrete range distribution

Probability mass functions

If $l, u \in \mathbb{Z}$ are lower and upper bounds ($l \leq u$), then for any integer $y \in \{l, \dots, u\}$,

$$\text{DiscreteRange}(y | l, u) = \frac{1}{u - l + 1}.$$

Distribution statement

$y \sim \text{discrete_range}(l, u)$

Increment the target log probability density with `discrete_range_lupmf(y | l, u)` dropping constant additive terms.

Available since 2.26

Stan functions

All of the discrete range distributions are vectorized so that the outcome y and the bounds l, u can be a single integer (type `int`) or an array of integers (type `array[] int`).

real **discrete_range_lpmf**(ints y | ints l, ints u)

The log probability mass function with outcome(s) y in $l : u$.

Available since 2.26

real **discrete_range_lupmf**(ints y | ints l, ints u)

The log probability mass function with outcome(s) y in $l : u$ dropping constant additive terms.

Available since 2.26

real **discrete_range_cdf**(ints y | ints l, ints u)

The discrete range cumulative distribution function for the given y , lower and upper bounds.

Available since 2.26

real **discrete_range_lcdf**(ints y | ints l, ints u)

The log of the discrete range cumulative distribution function for the given y, lower and upper bounds.

Available since 2.26

real **discrete_range_lccdf**(ints y | ints l, ints u)

The log of the discrete range complementary cumulative distribution function for the given y, lower and upper bounds.

Available since 2.26

ints **discrete_range_rng**(ints l, ints u)

Generate a discrete variate between the given lower and upper bounds; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.26

16.9. Ordered logistic distribution

Probability mass function

If $K \in \mathbb{N}$ with $K > 2$, $c \in \mathbb{R}^{K-1}$ such that $c_k < c_{k+1}$ for $k \in \{1, \dots, K-2\}$, and $\eta \in \mathbb{R}$, then for $k \in \{1, \dots, K\}$,

$$\text{OrderedLogistic}(k | \eta, c) = \begin{cases} 1 - \text{logit}^{-1}(\eta - c_1) & \text{if } k = 1, \\ \text{logit}^{-1}(\eta - c_{k-1}) - \text{logit}^{-1}(\eta - c_k) & \text{if } 1 < k < K, \text{ and} \\ \text{logit}^{-1}(\eta - c_{K-1}) - 0 & \text{if } k = K. \end{cases}$$

The $k = K$ case is written with the redundant subtraction of zero to illustrate the parallelism of the cases; the $k = 1$ and $k = K$ edge cases can be subsumed into the general definition by setting $c_0 = -\infty$ and $c_K = +\infty$ with $\text{logit}^{-1}(-\infty) = 0$ and $\text{logit}^{-1}(\infty) = 1$.

Distribution statement

$k \sim \text{ordered_logistic}(\text{eta}, c)$

Increment target log probability density with `ordered_logistic_lupmf(k | eta, c)`.

Available since 2.0

Stan functions

real **ordered_logistic_lpmf**(ints k | vector eta, vectors c)

The log ordered logistic probability mass of k given linear predictors eta, and cutpoints c.

Available since 2.18

real **ordered_logistic_lupmf**(ints k | vector eta, vectors c)

The log ordered logistic probability mass of k given linear predictors eta, and cutpoints c dropping constant additive terms.

Available since 2.25

int **ordered_logistic_rng**(real eta, vector c)

Generate an ordered logistic variate with linear predictor eta and cutpoints c; may only be used in transformed data and generated quantities blocks

Available since 2.0

16.10. Ordered logistic generalized linear model (ordinal regression)

Probability mass function

If $N, M, K \in \mathbb{N}$ with $N, M > 0$, $K > 2$, $c \in \mathbb{R}^{K-1}$ such that $c_k < c_{k+1}$ for $k \in \{1, \dots, K-2\}$, and $x \in \mathbb{R}^{N \times M}$, $\beta \in \mathbb{R}^M$, then for $y \in \{1, \dots, K\}^N$,

$\text{OrderedLogisticGLM}(y \mid x, \beta, c)$

$$\begin{aligned}
 &= \prod_{1 \leq i \leq N} \text{OrderedLogistic}(y_i \mid x_i \cdot \beta, c) \\
 &= \prod_{1 \leq i \leq N} \begin{cases} 1 - \text{logit}^{-1}(x_i \cdot \beta - c_1) & \text{if } y = 1, \\ \text{logit}^{-1}(x_i \cdot \beta - c_{y-1}) - \text{logit}^{-1}(x_i \cdot \beta - c_y) & \text{if } 1 < y < K, \text{ and} \\ \text{logit}^{-1}(x_i \cdot \beta - c_{K-1}) - 0 & \text{if } y = K. \end{cases}
 \end{aligned}$$

The $k = K$ case is written with the redundant subtraction of zero to illustrate the parallelism of the cases; the $y = 1$ and $y = K$ edge cases can be subsumed into the general definition by setting $c_0 = -\infty$ and $c_K = +\infty$ with $\text{logit}^{-1}(-\infty) = 0$ and $\text{logit}^{-1}(\infty) = 1$.

Distribution statement

$y \sim \text{ordered_logistic_glm}(x, \text{beta}, c)$

16.10. ORDERED LOGISTIC GENERALIZED LINEAR MODEL (ORDINAL REGRESSION)

Increment target log probability density with `ordered_logistic_lupmf(y | x, beta, c)`.

Available since 2.23

Stan functions

```
real ordered_logistic_glm_lupmf(int y | row_vector x, vector beta, vector c)
```

The log ordered logistic probability mass of y , given linear predictors $x * \text{beta}$, and cutpoints c . The cutpoints c must be ordered.

Available since 2.23

```
real ordered_logistic_glm_lupmf(int y | row_vector x, vector beta, vector c)
```

The log ordered logistic probability mass of y , given linear predictors $x * \text{beta}$, and cutpoints c dropping constant additive terms. The cutpoints c must be ordered.

Available since 2.25

```
real ordered_logistic_glm_lupmf(int y | matrix x, vector beta, vector c)
```

The log ordered logistic probability mass of y , given linear predictors $x * \text{beta}$, and cutpoints c . The cutpoints c must be ordered.

Available since 2.23

```
real ordered_logistic_glm_lupmf(int y | matrix x, vector beta, vector c)
```

The log ordered logistic probability mass of y , given linear predictors $x * \text{beta}$, and cutpoints c dropping constant additive terms. The cutpoints c must be ordered.

Available since 2.25

```
real ordered_logistic_glm_lupmf(array[] int y | row_vector x, vector beta, vector c)
```

The log ordered logistic probability mass of y , given linear predictors $x * \text{beta}$, and cutpoints c . The cutpoints c must be ordered.

Available since 2.23

```
real ordered_logistic_glm_lupmf(array[] int y | row_vector x, vector beta, vector c)
```

The log ordered logistic probability mass of y , given linear predictors $x * \text{beta}$, and cutpoints c dropping constant additive terms. The cutpoints c must be ordered.

Available since 2.25

real **ordered_logistic_glm_lpmf**(array[] int y | matrix x, vector beta, vector c)

The log ordered logistic probability mass of y, given linear predictors x * beta, and cutpoints c. The cutpoints c must be ordered.

Available since 2.23

real **ordered_logistic_glm_lupmf**(array[] int y | matrix x, vector beta, vector c)

The log ordered logistic probability mass of y, given linear predictors x * beta, and cutpoints c dropping constant additive terms. The cutpoints c must be ordered.

Available since 2.25

16.11. Ordered probit distribution

Probability mass function

If $K \in \mathbb{N}$ with $K > 2$, $c \in \mathbb{R}^{K-1}$ such that $c_k < c_{k+1}$ for $k \in \{1, \dots, K-2\}$, and $\eta \in \mathbb{R}$, then for $k \in \{1, \dots, K\}$,

$$\text{OrderedProbit}(k \mid \eta, c) = \begin{cases} 1 - \Phi(\eta - c_1) & \text{if } k = 1, \\ \Phi(\eta - c_{k-1}) - \Phi(\eta - c_k) & \text{if } 1 < k < K, \text{ and} \\ \Phi(\eta - c_{K-1}) - 0 & \text{if } k = K. \end{cases}$$

The $k = K$ case is written with the redundant subtraction of zero to illustrate the parallelism of the cases; the $k = 1$ and $k = K$ edge cases can be subsumed into the general definition by setting $c_0 = -\infty$ and $c_K = +\infty$ with $\Phi(-\infty) = 0$ and $\Phi(\infty) = 1$.

Distribution statement

$k \sim \text{ordered_probit}(\text{eta}, c)$

Increment target log probability density with `ordered_probit_lupmf(k | eta, c)`.

Available since 2.19

Stan functions

real **ordered_probit_lpmf**(ints k | vector eta, vectors c)

The log ordered probit probability mass of k given linear predictors eta, and cutpoints c.

Available since 2.18

real **ordered_probit_lupmf**(ints k | vector eta, vectors c)

The log ordered probit probability mass of k given linear predictors eta, and cutpoints c dropping constant additive terms.

Available since 2.25

real **ordered_probit_lpmf**(ints k | real eta, vectors c)

The log ordered probit probability mass of k given linear predictor eta, and cutpoints c.

Available since 2.19

real **ordered_probit_lupmf**(ints k | real eta, vectors c)

The log ordered probit probability mass of k given linear predictor eta, and cutpoints c dropping constant additive terms.

Available since 2.19

int **ordered_probit_rng**(real eta, vector c)

Generate an ordered probit variate with linear predictor eta and cutpoints c; may only be used in transformed data and generated quantities blocks

Available since 2.18

17. Unbounded Discrete Distributions

The unbounded discrete distributions have support over the natural numbers (i.e., the non-negative integers).

17.1. Negative binomial distribution

For the negative binomial distribution Stan uses the parameterization described in Gelman et al. (2013). For alternative parameterizations, see section [negative binomial glm](#).

Probability mass function

If $\alpha \in \mathbb{R}^+$ and $\beta \in \mathbb{R}^+$, then for $n \in \mathbb{N}$,

$$\text{NegBinomial}(n \mid \alpha, \beta) = \binom{n + \alpha - 1}{\alpha - 1} \left(\frac{\beta}{\beta + 1}\right)^\alpha \left(\frac{1}{\beta + 1}\right)^n.$$

The mean and variance of a random variable $n \sim \text{NegBinomial}(\alpha, \beta)$ are given by

$$\mathbb{E}[n] = \frac{\alpha}{\beta} \quad \text{and} \quad \text{Var}[n] = \frac{\alpha}{\beta^2}(\beta + 1).$$

Distribution statement

$n \sim \text{neg_binomial}(\text{alpha}, \text{beta})$

Increment target log probability density with `neg_binomial_lupmf(n | alpha, beta)`.

Available since 2.0

Stan functions

real `neg_binomial_lpmf`(ints n | reals alpha, reals beta)

The log negative binomial probability mass of n given shape alpha and inverse scale beta

Available since 2.12

real `neg_binomial_lupmf`(ints n | reals alpha, reals beta)

The log negative binomial probability mass of n given shape alpha and inverse scale beta dropping constant additive terms

17.2. NEGATIVE BINOMIAL DISTRIBUTION (ALTERNATIVE PARAMETERIZATION)¹⁹

Available since 2.25

real **neg_binomial_cdf**(ints n | reals alpha, reals beta)

The negative binomial cumulative distribution function of n given shape alpha and inverse scale beta

Available since 2.0

real **neg_binomial_lcdf**(ints n | reals alpha, reals beta)

The log of the negative binomial cumulative distribution function of n given shape alpha and inverse scale beta

Available since 2.12

real **neg_binomial_lccdf**(ints n | reals alpha, reals beta)

The log of the negative binomial complementary cumulative distribution function of n given shape alpha and inverse scale beta

Available since 2.12

R **neg_binomial_rng**(reals alpha, reals beta)

Generate a negative binomial variate with shape alpha and inverse scale beta; may only be used in transformed data and generated quantities blocks. alpha / beta must be less than 2^{29} . For a description of argument and return types, see section [vectorized function signatures](#).

Available since 2.18

17.2. Negative binomial distribution (alternative parameterization)

Stan also provides an alternative parameterization of the negative binomial distribution directly using a mean (i.e., location) parameter and a parameter that controls overdispersion relative to the square of the mean. Section [combinatorial functions](#), below, provides a second alternative parameterization directly in terms of the log mean.

Probability mass function

The first parameterization is for $\mu \in \mathbb{R}^+$ and $\phi \in \mathbb{R}^+$, which for $n \in \mathbb{N}$ is defined as

$$\text{NegBinomial2}(n | \mu, \phi) = \binom{n + \phi - 1}{n} \left(\frac{\mu}{\mu + \phi} \right)^n \left(\frac{\phi}{\mu + \phi} \right)^\phi.$$

The mean and variance of a random variable $n \sim \text{NegBinomial2}(n \mid \mu, \phi)$ are

$$\mathbb{E}[n] = \mu \quad \text{and} \quad \text{Var}[n] = \mu + \frac{\mu^2}{\phi}.$$

Recall that $\text{Poisson}(\mu)$ has variance μ , so $\mu^2/\phi > 0$ is the additional variance of the negative binomial above that of the Poisson with mean μ . So the inverse of parameter ϕ controls the overdispersion, scaled by the square of the mean, μ^2 .

Distribution statement

$n \sim \text{neg_binomial_2}(\text{mu}, \text{phi})$

Increment target log probability density with `neg_binomial_2_lupmf(n | mu, phi)`.

Available since 2.3

Stan functions

`real neg_binomial_2_lpmf(ints n | reals mu, reals phi)`

The log negative binomial probability mass of n given location μ and precision ϕ .

Available since 2.20

`real neg_binomial_2_lupmf(ints n | reals mu, reals phi)`

The log negative binomial probability mass of n given location μ and precision ϕ dropping constant additive terms.

Available since 2.25

`real neg_binomial_2_cdf(ints n | reals mu, reals phi)`

The negative binomial cumulative distribution function of n given location μ and precision ϕ .

Available since 2.6

`real neg_binomial_2_lcdf(ints n | reals mu, reals phi)`

The log of the negative binomial cumulative distribution function of n given location μ and precision ϕ .

Available since 2.12

`real neg_binomial_2_lccdf(ints n | reals mu, reals phi)`

The log of the negative binomial complementary cumulative distribution function of n given location μ and precision ϕ .

Available since 2.12

`R neg_binomial_2_rng`(reals mu, reals phi)

Generate a negative binomial variate with location mu and precision phi; may only be used in transformed data and generated quantities blocks. mu must be less than 2^{29} . For a description of argument and return types, see section [vectorized function signatures](#).

Available since 2.18

17.3. Negative binomial distribution (log alternative parameterization)

Related to the parameterization in section [negative binomial, alternative parameterization](#), the following parameterization uses a log mean parameter $\eta = \log(\mu)$, defined for $\eta \in \mathbb{R}$, $\phi \in \mathbb{R}^+$, so that for $n \in \mathbb{N}$,

$$\text{NegBinomial2Log}(n \mid \eta, \phi) = \text{NegBinomial2}(n \mid \exp(\eta), \phi).$$

This alternative may be used for sampling, as a function, and for random number generation, but as of yet, there are no CDFs implemented for it. This is especially useful for log-linear negative binomial regressions.

Distribution statement

$n \sim \text{neg_binomial_2_log}(\text{eta}, \text{phi})$

Increment target log probability density with `neg_binomial_2_log_lupmf(n | eta, phi)`.

Available since 2.3

Stan functions

real `neg_binomial_2_log_lpmf`(ints n | reals eta, reals phi)

The log negative binomial probability mass of n given log-location eta and inverse overdispersion parameter phi.

Available since 2.20

real `neg_binomial_2_log_lupmf`(ints n | reals eta, reals phi)

The log negative binomial probability mass of n given log-location eta and inverse overdispersion parameter phi dropping constant additive terms.

Available since 2.25

`R neg_binomial_2_log_rng`(reals eta, reals phi)

Generate a negative binomial variate with log-location eta and inverse overdispersion

sion control `phi`; may only be used in transformed data and generated quantities blocks. `eta` must be less than $29 \log 2$. For a description of argument and return types, see section [vectorized function signatures](#).

Available since 2.18

17.4. Negative-binomial-2-log generalized linear model (negative binomial regression)

Stan also supplies a single function for a generalized linear model with negative binomial distribution and log link function, i.e. a function for a negative binomial regression. This provides a more efficient implementation of negative binomial regression than a manually written regression in terms of a negative binomial distribution and matrix multiplication.

Probability mass function

If $x \in \mathbb{R}^{n \times m}$, $\alpha \in \mathbb{R}^n$, $\beta \in \mathbb{R}^m$, $\phi \in \mathbb{R}^+$, then for $y \in \mathbb{N}^n$,

$$\text{NegBinomial2LogGLM}(y | x, \alpha, \beta, \phi) = \prod_{1 \leq i \leq n} \text{NegBinomial2}(y_i | \exp(\alpha_i + x_i \cdot \beta), \phi).$$

Distribution statement

$y \sim \text{neg_binomial_2_log_glm}(x, \text{alpha}, \text{beta}, \text{phi})$

Increment target log probability density with `neg_binomial_2_log_glm_lupmf(y | x, alpha, beta, phi)`.

Available since 2.19

Stan functions

real **neg_binomial_2_log_glm_lupmf**(int y | matrix x, real alpha, vector beta, real phi)

The log negative binomial probability mass of y given log-location $\text{alpha} + x * \text{beta}$ and inverse overdispersion parameter `phi`.

Available since 2.23

real **neg_binomial_2_log_glm_lupmf**(int y | matrix x, real alpha, vector beta, real phi)

The log negative binomial probability mass of y given log-location $\text{alpha} + x * \text{beta}$ and inverse overdispersion parameter `phi` dropping constant additive terms.

Available since 2.25

17.4. NEGATIVE-BINOMIAL-2-LOG GENERALIZED LINEAR MODEL (NEGATIVE BIN

```
real    neg_binomial_2_log_glm_lpmf(int y | matrix x, vector alpha,  
vector beta, real phi)
```

The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ .

Available since 2.23

```
real    neg_binomial_2_log_glm_lupmf(int y | matrix x, vector alpha,  
vector beta, real phi)
```

The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ dropping constant additive terms.

Available since 2.25

```
real    neg_binomial_2_log_glm_lpmf(array[] int y | row_vector x, real  
alpha, vector beta, real phi)
```

The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ .

Available since 2.23

```
real    neg_binomial_2_log_glm_lupmf(array[] int y | row_vector x,  
real alpha, vector beta, real phi)
```

The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ dropping constant additive terms.

Available since 2.25

```
real    neg_binomial_2_log_glm_lpmf(array[] int y | row_vector x, vec  
tor alpha, vector beta, real phi)
```

The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ .

Available since 2.23

```
real    neg_binomial_2_log_glm_lupmf(array[] int y | row_vector x,  
vector alpha, vector beta, real phi)
```

The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ dropping constant additive terms.

Available since 2.25

```
real    neg_binomial_2_log_glm_lpmf(array[] int y | matrix x, real al  
pha, vector beta, real phi)
```


The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ .

Available since 2.18

```
real neg_binomial_2_log_glm_lupmf(array[] int y | matrix x, real
alpha, vector beta, real phi)
```

The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ dropping constant additive terms.

Available since 2.25

```
real neg_binomial_2_log_glm_lpmf(array[] int y | matrix x, vector
alpha, vector beta, real phi)
```

The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ .

Available since 2.18

```
real neg_binomial_2_log_glm_lupmf(array[] int y | matrix x, vector
alpha, vector beta, real phi)
```

The log negative binomial probability mass of y given log-location $\alpha + x * \beta$ and inverse overdispersion parameter ϕ dropping constant additive terms.

Available since 2.25

17.5. Poisson distribution

Probability mass function

If $\lambda \in \mathbb{R}^+$, then for $n \in \mathbb{N}$,

$$\text{Poisson}(n|\lambda) = \frac{1}{n!} \lambda^n \exp(-\lambda).$$

Distribution statement

$n \sim \text{poisson}(\lambda)$

Increment target log probability density with `poisson_lupmf(n | lambda)`.

Available since 2.0

Stan functions

```
real poisson_lpmf(ints n | reals lambda)
```

The log Poisson probability mass of n given rate λ

Available since 2.12

real **poisson_lupmf**(ints n | reals lambda)

The log Poisson probability mass of n given rate lambda dropping constant additive terms

Available since 2.25

real **poisson_cdf**(ints n | reals lambda)

The Poisson cumulative distribution function of n given rate lambda

Available since 2.0

real **poisson_lcdf**(ints n | reals lambda)

The log of the Poisson cumulative distribution function of n given rate lambda

Available since 2.12

real **poisson_lccdf**(ints n | reals lambda)

The log of the Poisson complementary cumulative distribution function of n given rate lambda

Available since 2.12

R **poisson_rng**(reals lambda)

Generate a Poisson variate with rate lambda; may only be used in transformed data and generated quantities blocks. lambda must be less than 2^{30} . For a description of argument and return types, see section [vectorized function signatures](#).

Available since 2.18

17.6. Poisson distribution, log parameterization

Stan also provides a parameterization of the Poisson using the log rate $\alpha = \log \lambda$ as a parameter. This is useful for log-linear Poisson regressions so that the predictor does not need to be exponentiated and passed into the standard Poisson probability function.

Probability mass function

If $\alpha \in \mathbb{R}$, then for $n \in \mathbb{N}$,

$$\text{PoissonLog}(n|\alpha) = \frac{1}{n!} \exp(n\alpha - \exp(\alpha)).$$

Distribution statement

$n \sim \text{poisson_log}(\alpha)$

Increment target log probability density with `poisson_log_lupmf(n | alpha)`.

Available since 2.0

Stan functions

real **poisson_log_lpmf**(ints n | reals alpha)

The log Poisson probability mass of n given log rate alpha

Available since 2.12

real **poisson_log_lupmf**(ints n | reals alpha)

The log Poisson probability mass of n given log rate alpha dropping constant additive terms

Available since 2.25

R **poisson_log_rng**(reals alpha)

Generate a Poisson variate with log rate alpha; may only be used in transformed data and generated quantities blocks. alpha must be less than $30 \log 2$. For a description of argument and return types, see section [vectorized function signatures](#).

Available since 2.18

17.7. Poisson-log generalized linear model (Poisson regression)

Stan also supplies a single function for a generalized linear model with Poisson distribution and log link function, i.e. a function for a Poisson regression. This provides a more efficient implementation of Poisson regression than a manually written regression in terms of a Poisson distribution and matrix multiplication.

Probability mass function

If $x \in \mathbb{R}^{n \cdot m}$, $\alpha \in \mathbb{R}^n$, $\beta \in \mathbb{R}^m$, then for $y \in \mathbb{N}^n$,

$$\text{PoissonLogGLM}(y|x, \alpha, \beta) = \prod_{1 \leq i \leq n} \text{Poisson}(y_i | \exp(\alpha_i + x_i \cdot \beta)).$$

Distribution statement

$y \sim$ **poisson_log_glm**(x, alpha, beta)

Increment target log probability density with **poisson_log_glm_lupmf**(y | x, alpha, beta).

Available since 2.19

Stan functions

real **poisson_log_glm_lpmf**(int y | matrix x, real alpha, vector beta)

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$.

Available since 2.23

```
real    poisson_log_glm_lupmf(int y | matrix x, real alpha, vector
beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

```
real    poisson_log_glm_lpmf(int y | matrix x, vector alpha, vector
beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$.

Available since 2.23

```
real    poisson_log_glm_lupmf(int y | matrix x, vector alpha, vector
beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

```
real    poisson_log_glm_lpmf(array[] int y | row_vector x, real alpha,
vector beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$.

Available since 2.23

```
real    poisson_log_glm_lupmf(array[] int y | row_vector x, real al-
pha, vector beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

```
real    poisson_log_glm_lpmf(array[] int y | row_vector x, vector al-
pha, vector beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$.

Available since 2.23

```
real    poisson_log_glm_lupmf(array[] int y | row_vector x, vector al-
pha, vector beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

```
real    poisson_log_glm_lpmf(array[] int y | matrix x, real alpha,
vector beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$.

Available since 2.18

```
real    poisson_log_glm_lupmf(array[] int y | matrix x, real alpha,
vector beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

```
real    poisson_log_glm_lpmf(array[] int y | matrix x, vector alpha,
vector beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$.

Available since 2.18

```
real    poisson_log_glm_lupmf(array[] int y | matrix x, vector alpha,
vector beta)
```

The log Poisson probability mass of y given the log-rate $\alpha + x * \beta$ dropping constant additive terms.

Available since 2.25

17.8. Beta negative binomial distribution

Probability mass function

If $r \in \mathbb{R}^+$, $\alpha \in \mathbb{R}^+$, and $\beta \in \mathbb{R}^+$, then for $n \in \mathbb{N}$,

$$\text{BetaNegBinomial}(n|r, \alpha, \beta) = \frac{\Gamma(n+r)}{n! \Gamma(r)} \frac{B(\beta+n, \alpha+r)}{B(\beta, \alpha)}.$$

Distribution statement

$n \sim \text{beta_neg_binomial}(r, \alpha, \beta)$

Increment target log probability density with `beta_neg_binomial_lupmf(n | r, alpha, beta)`.

Available since 2.36

Stan functions

```
real beta_neg_binomial_lpmf(ints n | reals r, reals alpha, reals beta)
```

The log beta negative binomial probability mass of n given parameters r , α and β .

Available since 2.36

```
real beta_neg_binomial_lupmf(ints n | reals r, reals alpha, reals beta)
```

The log beta negative binomial probability mass of n given parameters r , α and β dropping constant additive terms.

Available since 2.36

```
real beta_neg_binomial_cdf(ints n | reals r, reals alpha, reals beta)
```

The beta negative binomial cumulative distribution function of n given parameters r , α and β .

Available since 2.36

```
real beta_neg_binomial_lcdf(ints n | reals r, reals alpha, reals beta)
```

The log of the beta negative binomial cumulative distribution function of n given parameters r , α and β .

Available since 2.36

```
real beta_neg_binomial_lccdf(ints n | reals r, reals alpha, reals beta)
```

The log of the beta negative binomial complementary cumulative distribution function of n given parameters r , α and β .

Available since 2.36

```
R beta_neg_binomial_rng(reals r, reals alpha, reals beta)
```

Generate a beta negative binomial variate with parameters r , α and β ; may only be used in transformed data and generated quantities blocks. $r \cdot \beta / (\alpha - 1)$ must be less than 2^{29} . For a description of argument and return types, see section [vectorized function signatures](#).

Available since 2.36

18. Multivariate Discrete Distributions

The multivariate discrete distributions are over multiple integer values, which are expressed in Stan as arrays.

18.1. Multinomial distribution

Probability mass function

If $K \in \mathbb{N}$, $N \in \mathbb{N}$, and $\theta \in K$ -simplex, then for $y \in \mathbb{N}^K$ such that $\sum_{k=1}^K y_k = N$,

$$\text{Multinomial}(y|\theta) = \binom{N}{y_1, \dots, y_K} \prod_{k=1}^K \theta_k^{y_k},$$

where the multinomial coefficient is defined by

$$\binom{N}{y_1, \dots, y_K} = \frac{N!}{\prod_{k=1}^K y_k!}.$$

Distribution statement

$y \sim \text{multinomial}(\text{theta})$

Increment target log probability density with `multinomial_lupmf(y | theta)`.

Available since 2.0

Stan functions

real `multinomial_lpmf`(array[] int y | vector theta)

The log multinomial probability mass function with outcome array y of size K given the K -simplex distribution parameter θ and (implicit) total count $N = \text{sum}(y)$

Available since 2.12

real `multinomial_lupmf`(array[] int y | vector theta)

The log multinomial probability mass function with outcome array y of size K given the K -simplex distribution parameter θ and (implicit) total count $N = \text{sum}(y)$ dropping constant additive terms

Available since 2.25

array[] int **multinomial_rng**(vector theta, int N)

Generate a multinomial variate with simplex distribution parameter theta and total count N ; may only be used in transformed data and generated quantities blocks

Available since 2.8

18.2. Multinomial distribution, logit parameterization

Stan also provides a version of the multinomial probability mass function distribution with the K -simplex for the event count probabilities per category given on the unconstrained logistic scale.

Probability mass function

If $K \in \mathbb{N}$, $N \in \mathbb{N}$, and $\text{softmax}(\theta) \in K\text{-simplex}$, then for $y \in \mathbb{N}^K$ such that $\sum_{k=1}^K y_k = N$,

$$\begin{aligned} \text{MultinomialLogit}(y \mid \gamma) &= \text{Multinomial}(y \mid \text{softmax}(\gamma)) \\ &= \binom{N}{y_1, \dots, y_K} \prod_{k=1}^K [\text{softmax}(\gamma_k)]^{y_k}, \end{aligned}$$

where the multinomial coefficient is defined by

$$\binom{N}{y_1, \dots, y_K} = \frac{N!}{\prod_{k=1}^K y_k!}.$$

Distribution statement

$y \sim \text{multinomial_logit}(\text{gamma})$

Increment target log probability density with `multinomial_logit_lupmf(y | gamma)`.

Available since 2.24

Stan functions

real **multinomial_logit_lpmf**(array[] int y | vector gamma)

The log multinomial probability mass function with outcome array y of size K given the log K -simplex distribution parameter γ and (implicit) total count $N = \text{sum}(y)$

Available since 2.24

real **multinomial_logit_lupmf**(array[] int y | vector gamma)

The log multinomial probability mass function with outcome array y of size K given

the log K -simplex distribution parameter γ and (implicit) total count $N = \text{sum}(y)$ dropping constant additive terms

Available since 2.25

array[] int **multinomial_logit_rng**(vector gamma, int N)
Generate a variate from a multinomial distribution with probabilities `softmax(gamma)` and total count N ; may only be used in transformed data and generated quantities blocks.

Available since 2.24

18.3. Dirichlet-multinomial distribution

Stan also provides the Dirichlet-multinomial distribution, which generalizes the Beta-binomial distribution to more than two categories. As such, it is an overdispersed version of the multinomial distribution.

Probability mass function

If $K \in \mathbb{N}$, $N \in \mathbb{N}$, and $\alpha \in \mathbb{R}_+^K$, then for $y \in \mathbb{N}^K$ such that $\sum_{k=1}^K y_k = N$, the PMF of the Dirichlet-multinomial distribution is defined as

$$\text{DirMult}(y|\theta) = \frac{\Gamma(\alpha_0)\Gamma(N+1)}{\Gamma(N+\alpha_0)} \prod_{k=1}^K \frac{\Gamma(y_k + \alpha_k)}{\Gamma(\alpha_k)\Gamma(y_k + 1)},$$

where α_0 is defined as $\alpha_0 = \sum_{k=1}^K \alpha_k$.

Distribution statement

$y \sim \text{dirichlet_multinomial}(\text{alpha})$

Increment target log probability density with `dirichlet_multinomial_lupmf(y | alpha)`.

Available since 2.34

Stan functions

real **dirichlet_multinomial_lpmf**(array[] int y | vector alpha)

The log multinomial probability mass function with outcome array y with K elements given the positive K -vector distribution parameter `alpha` and (implicit) total count $N = \text{sum}(y)$.

Available since 2.34

real **dirichlet_multinomial_lupmf**(array[] int y | vector alpha)

The log multinomial probability mass function with outcome array y with K ele-

ments, given the positive K -vector distribution parameter α and (implicit) total count $N = \text{sum}(y)$ dropping constant additive terms.

Available since 2.34

```
array[] int dirichlet_multinomial_rng(vector alpha, int N)
```

Generate a multinomial variate with positive vector distribution parameter α and total count N ; may only be used in transformed data and generated quantities blocks. This is equivalent to `multinomial_rng(dirichlet_rng(alpha), N)`.

Available since 2.34

Part III

Continuous Distributions

19. Unbounded Continuous Distributions

The unbounded univariate continuous probability distributions have support on all real numbers.

19.1. Normal distribution

Probability density function

If $\mu \in \mathbb{R}$ and $\sigma \in \mathbb{R}^+$, then for $y \in \mathbb{R}$,

$$\text{Normal}(y|\mu, \sigma) = \frac{1}{\sqrt{2\pi} \sigma} \exp\left(-\frac{1}{2} \left(\frac{y - \mu}{\sigma}\right)^2\right).$$

Distribution statement

$y \sim \text{normal}(\text{mu}, \text{sigma})$

Increment target log probability density with `normal_lupdf(y | mu, sigma)`.

Available since 2.0

Stan functions

`real normal_lpdf(reals y | reals mu, reals sigma)`

The log of the normal density of y given location μ and scale σ

Available since 2.12

`real normal_lupdf(reals y | reals mu, reals sigma)`

The log of the normal density of y given location μ and scale σ dropping constant additive terms.

Available since 2.25

`real normal_cdf(reals y | reals mu, reals sigma)`

The cumulative normal distribution of y given location μ and scale σ ; `normal_cdf` will underflow to 0 for $\frac{y-\mu}{\sigma}$ below -37.5 and overflow to 1 for $\frac{y-\mu}{\sigma}$ above 8.25; the function `Phi_approx` is more robust in the tails, but must be scaled and translated for anything other than a standard normal.

Available since 2.0

real **normal_lcdf**(reals y | reals mu, reals sigma)

The log of the cumulative normal distribution of y given location mu and scale sigma; normal_lcdf will underflow to $-\infty$ for $\frac{y-\mu}{\sigma}$ below -37.5 and overflow to 0 for $\frac{y-\mu}{\sigma}$ above 8.25; log(Phi_approx(...)) is more robust in the tails, but must be scaled and translated for anything other than a standard normal.

Available since 2.12

real **normal_lccdf**(reals y | reals mu, reals sigma)

The log of the complementary cumulative normal distribution of y given location mu and scale sigma; normal_lccdf will overflow to 0 for $\frac{y-\mu}{\sigma}$ below -37.5 and underflow to $-\infty$ for $\frac{y-\mu}{\sigma}$ above 8.25; log1m(Phi_approx(...)) is more robust in the tails, but must be scaled and translated for anything other than a standard normal.

Available since 2.15

R **normal_rng**(reals mu, reals sigma)

Generate a normal variate with location mu and scale sigma; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

Standard normal distribution

The standard normal distribution is so-called because its parameters are the units for their respective operations—the location (mean) is zero and the scale (standard deviation) one. The standard normal is parameter-free, and the unit parameters allow considerable simplification of the expression for the density.

$$\text{StdNormal}(y) = \text{Normal}(y \mid 0, 1) = \frac{1}{\sqrt{2\pi}} \exp\left(\frac{-y^2}{2}\right).$$

Up to a proportion on the log scale, where Stan computes,

$$\log \text{Normal}(y \mid 0, 1) = \frac{-y^2}{2} + \text{const.}$$

With no logarithm, no subtraction, and no division by a parameter, the standard normal log density is much more efficient to compute than the normal log density with constant location 0 and scale 1.

Distribution statement

$y \sim \text{std_normal}()$

Increment target log probability density with `std_normal_lupdf(y)`.

Available since 2.19

Stan functions

real **std_normal_lpdf**(reals y)

The standard normal (location zero, scale one) log probability density of y.

Available since 2.18

real **std_normal_lupdf**(reals y)

The standard normal (location zero, scale one) log probability density of y dropping constant additive terms.

Available since 2.25

real **std_normal_cdf**(reals y)

The cumulative standard normal distribution of y; `std_normal_cdf` will underflow to 0 for y below -37.5 and overflow to 1 for y above 8.25; the function `Phi_approx` is more robust in the tails.

Available since 2.21

real **std_normal_lcdf**(reals y)

The log of the cumulative standard normal distribution of y; `std_normal_lcdf` will underflow to $-\infty$ for y below -37.5 and overflow to 0 for y above 8.25; `log(Phi_approx(...))` is more robust in the tails.

Available since 2.21

real **std_normal_lccdf**(reals y)

The log of the complementary cumulative standard normal distribution of y; `std_normal_lccdf` will overflow to 0 for y below -37.5 and underflow to $-\infty$ for y above 8.25; `log1m(Phi_approx(...))` is more robust in the tails.

Available since 2.21

R **std_normal_qf**(T x)

Returns the value of the inverse standard normal cdf Φ^{-1} at the specified quantile x. The `std_normal_qf` is equivalent to the `inv_Phi` function.

Available since 2.31

R **std_normal_log_qf**(T x)

Return the value of the inverse standard normal cdf Φ^{-1} evaluated at the log of the specified quantile x. This function is equivalent to `std_normal_qf(exp(x))` but is more numerically stable.

Available since 2.31

real **std_normal_rng**()

Generate a normal variate with location zero and scale one; may only be used in transformed data and generated quantities blocks.

Available since 2.21

19.2. Normal-id generalized linear model (linear regression)

Stan also supplies a single function for a generalized linear model with normal distribution and identity link function, i.e. a function for a linear regression. This provides a more efficient implementation of linear regression than a manually written regression in terms of a normal distribution and matrix multiplication.

Probability distribution function

If $x \in \mathbb{R}^{n \cdot m}$, $\alpha \in \mathbb{R}^n$, $\beta \in \mathbb{R}^m$, $\sigma \in \mathbb{R}^+$, then for $y \in \mathbb{R}^n$,

$$\text{NormalIdGLM}(y|x, \alpha, \beta, \sigma) = \prod_{1 \leq i \leq n} \text{Normal}(y_i | \alpha_i + x_i \cdot \beta, \sigma).$$

Distribution statement

$y \sim \text{normal_id_glm}(x, \text{alpha}, \text{beta}, \text{sigma})$

Increment target log probability density with `normal_id_glm_lupdf(y | x, alpha, beta, sigma)`.

Available since 2.19

Stan functions

real **normal_id_glm_lpdf**(real y | matrix x, real alpha, vector beta, real sigma)

The log normal probability density of y given location $\text{alpha} + x * \text{beta}$ and scale sigma.

Available since 2.29

real **normal_id_glm_lupdf**(real y | matrix x, real alpha, vector beta, real sigma)

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.29

```
real    normal_id_glm_lpdf(real y | matrix x, vector alpha, vector
beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ .

Available since 2.29

```
real    normal_id_glm_lupdf(real y | matrix x, vector alpha, vector
beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.29

```
real    normal_id_glm_lpdf(real y | matrix x, real alpha, vector beta,
vector sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ .

Available since 2.23

```
real    normal_id_glm_lupdf(real y | matrix x, real alpha, vector
beta, vector sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.25

```
real    normal_id_glm_lpdf(real y | matrix x, vector alpha, vector
beta, vector sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ .

Available since 2.23

```
real    normal_id_glm_lupdf(real y | matrix x, vector alpha, vector
beta, vector sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.25

```
real normal_id_glm_lpdf(vector y | row_vector x, real alpha, vector
beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ .

Available since 2.29

```
real normal_id_glm_lupdf(vector y | row_vector x, real alpha, vec-
tor beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.29

```
real normal_id_glm_lpdf(vector y | row_vector x, vector alpha, vec-
tor beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ .

Available since 2.29

```
real normal_id_glm_lupdf(vector y | row_vector x, vector alpha,
vector beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.29

```
real normal_id_glm_lpdf(vector y | matrix x, real alpha, vector
beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ .

Available since 2.23

```
real normal_id_glm_lupdf(vector y | matrix x, real alpha, vector
beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.23

```
real normal_id_glm_lpdf(vector y | matrix x, vector alpha, vector
beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ .

Available since 2.23

```
real normal_id_glm_lupdf(vector y | matrix x, vector alpha, vector
beta, real sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.23

```
real normal_id_glm_lpdf(vector y | matrix x, real alpha, vector
beta, vector sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ .

Available since 2.30

```
real normal_id_glm_lupdf(vector y | matrix x, real alpha, vector
beta, vector sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.30

```
real normal_id_glm_lpdf(vector y | matrix x, vector alpha, vector
beta, vector sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ .

Available since 2.30

```
real normal_id_glm_lupdf(vector y | matrix x, vector alpha, vector
beta, vector sigma)
```

The log normal probability density of y given location $\alpha + x * \beta$ and scale σ dropping constant additive terms.

Available since 2.30

19.3. Exponentially modified normal distribution

Exponentially modified Gaussian describes the distribution of $Z = X + Y$ when X and Y are independent and X is normally distributed (with mean μ and standard deviation σ) and Y is exponentially distributed (with rate λ).

Probability density function

If $\mu \in \mathbb{R}$, $\sigma \in \mathbb{R}^+$, and $\lambda \in \mathbb{R}^+$, then for $y \in \mathbb{R}$,

$$\text{ExpModNormal}(y|\mu, \sigma, \lambda) = \frac{\lambda}{2} \exp\left(\frac{\lambda}{2} (2\mu + \lambda\sigma^2 - 2y)\right) \text{erfc}\left(\frac{\mu + \lambda\sigma^2 - y}{\sqrt{2}\sigma}\right).$$

Distribution statement

$y \sim \text{exp_mod_normal}(\text{mu}, \text{sigma}, \text{lambda})$

Increment target log probability density with `exp_mod_normal_lupdf(y | mu, sigma, lambda)`.

Available since 2.0

Stan functions

```
real    exp_mod_normal_lpdf(reals y | reals mu, reals sigma, reals
lambda)
```

The log of the exponentially modified normal density of y given location μ , scale σ , and rate λ

Available since 2.18

```
real    exp_mod_normal_lupdf(reals y | reals mu, reals sigma, reals
lambda)
```

The log of the exponentially modified normal density of y given location μ , scale σ , and rate λ dropping constant additive terms

Available since 2.25

```
real    exp_mod_normal_cdf(reals y | reals mu, reals sigma, reals
lambda)
```

The exponentially modified normal cumulative distribution function of y given location μ , scale σ , and rate λ

Available since 2.0

```
real    exp_mod_normal_lcdf(reals y | reals mu, reals sigma, reals
lambda)
```

The log of the exponentially modified normal cumulative distribution function of y given location μ , scale σ , and rate λ

Available since 2.18

```
real    exp_mod_normal_lccdf(reals y | reals mu, reals sigma, reals
lambda)
```

The log of the exponentially modified normal complementary cumulative distribution function of y given location μ , scale σ , and rate λ

Available since 2.18

R `exp_mod_normal_rng`(reals μ , reals σ , reals λ)

Generate an exponentially modified normal variate with location μ , scale σ , and rate λ ; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

19.4. Skew normal distribution

Probability density function

If $\xi \in \mathbb{R}$, $\omega \in \mathbb{R}^+$, and $\alpha \in \mathbb{R}$, then for $y \in \mathbb{R}$,

$$\text{SkewNormal}(y \mid \xi, \omega, \alpha) = \frac{1}{\omega\sqrt{2\pi}} \exp\left(-\frac{1}{2}\left(\frac{y-\xi}{\omega}\right)^2\right) \left(1 + \text{erf}\left(\alpha\left(\frac{y-\xi}{\omega\sqrt{2}}\right)\right)\right).$$

Distribution statement

$y \sim \text{skew_normal}(xi, \omega, \alpha)$

Increment target log probability density with `skew_normal_lupdf(y | xi, omega, alpha)`.

Available since 2.0

Stan functions

real **`skew_normal_lpdf`**(reals y | reals xi , reals ω , reals α)

The log of the skew normal density of y given location xi , scale ω , and shape α

Available since 2.16

real **`skew_normal_lupdf`**(reals y | reals xi , reals ω , reals α)

The log of the skew normal density of y given location xi , scale ω , and shape α dropping constant additive terms

Available since 2.25

real **skew_normal_cdf**(reals y | reals xi, reals omega, reals alpha)
 The skew normal distribution function of y given location xi, scale omega, and shape alpha

Available since 2.16

real **skew_normal_lcdf**(reals y | reals xi, reals omega, reals alpha)
 The log of the skew normal cumulative distribution function of y given location xi, scale omega, and shape alpha

Available since 2.18

real **skew_normal_lccdf**(reals y | reals xi, reals omega, reals alpha)
 The log of the skew normal complementary cumulative distribution function of y given location xi, scale omega, and shape alpha

Available since 2.18

R **skew_normal_rng**(reals xi, reals omega, real alpha)
 Generate a skew normal variate with location xi, scale omega, and shape alpha; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

19.5. Student-t distribution

Probability density function

If $\nu \in \mathbb{R}^+$, $\mu \in \mathbb{R}$, and $\sigma \in \mathbb{R}^+$, then for $y \in \mathbb{R}$,

$$\text{StudentT}(y|\nu, \mu, \sigma) = \frac{\Gamma((\nu+1)/2)}{\Gamma(\nu/2)} \frac{1}{\sqrt{\nu\pi}\sigma} \left(1 + \frac{1}{\nu} \left(\frac{y-\mu}{\sigma}\right)^2\right)^{-(\nu+1)/2}.$$

Distribution statement

$y \sim \text{student_t}(\text{nu}, \text{mu}, \text{sigma})$

Increment target log probability density with `student_t_lupdf(y | nu, mu, sigma)`.

Available since 2.0

Stan functions

real **student_t_lpdf**(reals y | reals nu, reals mu, reals sigma)

The log of the Student- t density of y given degrees of freedom ν , location μ , and scale σ

Available since 2.12

real **student_t_lupdf**(reals y | reals nu, reals mu, reals sigma)

The log of the Student- t density of y given degrees of freedom ν , location μ , and scale σ dropping constant additive terms

Available since 2.25

real **student_t_cdf**(reals y | reals nu, reals mu, reals sigma)

The Student- t cumulative distribution function of y given degrees of freedom ν , location μ , and scale σ

Available since 2.0

real **student_t_lcdf**(reals y | reals nu, reals mu, reals sigma)

The log of the Student- t cumulative distribution function of y given degrees of freedom ν , location μ , and scale σ

Available since 2.12

real **student_t_lccdf**(reals y | reals nu, reals mu, reals sigma)

The log of the Student- t complementary cumulative distribution function of y given degrees of freedom ν , location μ , and scale σ

Available since 2.12

R **student_t_rng**(reals nu, reals mu, reals sigma)

Generate a Student- t variate with degrees of freedom ν , location μ , and scale σ ; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

19.6. Cauchy distribution**Probability density function**

If $\mu \in \mathbb{R}$ and $\sigma \in \mathbb{R}^+$, then for $y \in \mathbb{R}$,

$$\text{Cauchy}(y|\mu, \sigma) = \frac{1}{\pi\sigma} \frac{1}{1 + ((y - \mu)/\sigma)^2}.$$

Distribution statement

$y \sim \text{cauchy}(\mu, \sigma)$

Increment target log probability density with `cauchy_lupdf(y | mu, sigma)`.

Available since 2.0

Stan functions

real **cauchy_lpdf**(reals y | reals mu, reals sigma)

The log of the Cauchy density of y given location mu and scale sigma

Available since 2.12

real **cauchy_lupdf**(reals y | reals mu, reals sigma)

The log of the Cauchy density of y given location mu and scale sigma dropping constant additive terms

Available since 2.25

real **cauchy_cdf**(reals y | reals mu, reals sigma)

The Cauchy cumulative distribution function of y given location mu and scale sigma

Available since 2.0

real **cauchy_lcdf**(reals y | reals mu, reals sigma)

The log of the Cauchy cumulative distribution function of y given location mu and scale sigma

Available since 2.12

real **cauchy_lccdf**(reals y | reals mu, reals sigma)

The log of the Cauchy complementary cumulative distribution function of y given location mu and scale sigma

Available since 2.12

R **cauchy_rng**(reals mu, reals sigma)

Generate a Cauchy variate with location mu and scale sigma; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

19.7. Double exponential (Laplace) distribution

Probability density function

If $\mu \in \mathbb{R}$ and $\sigma \in \mathbb{R}^+$, then for $y \in \mathbb{R}$,

$$\text{DoubleExponential}(y|\mu, \sigma) = \frac{1}{2\sigma} \exp\left(-\frac{|y - \mu|}{\sigma}\right).$$

Note that the double exponential distribution is parameterized in terms of the scale, in contrast to the exponential distribution (see section [exponential distribution](#)), which is parameterized in terms of inverse scale.

The double-exponential distribution can be defined as a compound exponential-normal distribution (Ding and Blitzstein 2018). Using the inverse scale parameterization for the exponential distribution, and the standard deviation parameterization for the normal distribution, one can write

$$\alpha \sim \text{Exponential}\left(\frac{1}{2\sigma^2}\right)$$

and

$$\beta \mid \alpha \sim \text{Normal}(\mu, \sqrt{\alpha}),$$

then

$$\beta \sim \text{DoubleExponential}(\mu, \sigma).$$

This may be used to code a non-centered parameterization by taking

$$\beta^{\text{raw}} \sim \text{Normal}(0, 1)$$

and defining

$$\beta = \mu + \sqrt{\alpha} \beta^{\text{raw}}.$$

Distribution statement

$y \sim \text{double_exponential}(\text{mu}, \text{sigma})$

Increment target log probability density with `double_exponential_lupdf(y | mu, sigma)`.

Available since 2.0

Stan functions

real **double_exponential_lpdf**(reals y | reals mu, reals sigma)

The log of the double exponential density of y given location mu and scale sigma

Available since 2.12

real **double_exponential_lupdf**(reals y | reals mu, reals sigma)

The log of the double exponential density of y given location mu and scale sigma dropping constant additive terms

Available since 2.25

real **double_exponential_cdf**(reals y | reals mu, reals sigma)

The double exponential cumulative distribution function of y given location mu and scale sigma

Available since 2.0

real **double_exponential_lcdf**(reals y | reals mu, reals sigma)

The log of the double exponential cumulative distribution function of y given location mu and scale sigma

Available since 2.12

real **double_exponential_lccdf**(reals y | reals mu, reals sigma)

The log of the double exponential complementary cumulative distribution function of y given location mu and scale sigma

Available since 2.12

R **double_exponential_rng**(reals mu, reals sigma)

Generate a double exponential variate with location mu and scale sigma; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

19.8. Logistic distribution**Probability density function**

If $\mu \in \mathbb{R}$ and $\sigma \in \mathbb{R}^+$, then for $y \in \mathbb{R}$,

$$\text{Logistic}(y|\mu, \sigma) = \frac{1}{\sigma} \exp\left(-\frac{y-\mu}{\sigma}\right) \left(1 + \exp\left(-\frac{y-\mu}{\sigma}\right)\right)^{-2}.$$

Distribution statement

$y \sim \mathbf{logistic}(\mu, \sigma)$

Increment target log probability density with `logistic_lupdf(y | mu, sigma)`.

Available since 2.0

Stan functions

`real logistic_lpdf(reals y | reals mu, reals sigma)`

The log of the logistic density of y given location μ and scale σ

Available since 2.12

`real logistic_lupdf(reals y | reals mu, reals sigma)`

The log of the logistic density of y given location μ and scale σ dropping constant additive terms

Available since 2.25

`real logistic_cdf(reals y | reals mu, reals sigma)`

The logistic cumulative distribution function of y given location μ and scale σ

Available since 2.0

`real logistic_lcdf(reals y | reals mu, reals sigma)`

The log of the logistic cumulative distribution function of y given location μ and scale σ

Available since 2.12

`real logistic_lccdf(reals y | reals mu, reals sigma)`

The log of the logistic complementary cumulative distribution function of y given location μ and scale σ

Available since 2.12

`R logistic_rng(reals mu, reals sigma)`

Generate a logistic variate with location μ and scale σ ; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

19.9. Gumbel distribution

Probability density function

If $\mu \in \mathbb{R}$ and $\beta \in \mathbb{R}^+$, then for $y \in \mathbb{R}$,

$$\text{Gumbel}(y|\mu, \beta) = \frac{1}{\beta} \exp\left(-\frac{y-\mu}{\beta} - \exp\left(-\frac{y-\mu}{\beta}\right)\right).$$

Distribution statement

$y \sim \mathbf{gumbel}(\mu, \text{beta})$

Increment target log probability density with `gumbel_lupdf(y | mu, beta)`.

Available since 2.0

Stan functions

`real gumbel_lpdf(reals y | reals mu, reals beta)`

The log of the gumbel density of y given location μ and scale beta

Available since 2.12

`real gumbel_lupdf(reals y | reals mu, reals beta)`

The log of the gumbel density of y given location μ and scale beta dropping constant additive terms

Available since 2.25

`real gumbel_cdf(reals y | reals mu, reals beta)`

The gumbel cumulative distribution function of y given location μ and scale beta

Available since 2.0

`real gumbel_lcdf(reals y | reals mu, reals beta)`

The log of the gumbel cumulative distribution function of y given location μ and scale beta

Available since 2.12

`real gumbel_lccdf(reals y | reals mu, reals beta)`

The log of the gumbel complementary cumulative distribution function of y given location μ and scale beta

Available since 2.12

`R gumbel_rng(reals mu, reals beta)`

Generate a gumbel variate with location μ and scale beta ; may only be used in

transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

19.10. Skew double exponential distribution

Probability density function

If $\mu \in \mathbb{R}$, $\sigma \in \mathbb{R}^+$ and $\tau \in [0, 1]$, then for $y \in \mathbb{R}$,

$$\text{SkewDoubleExponential}(y|\mu, \sigma, \tau) = \frac{2\tau(1-\tau)}{\sigma} \exp \left[-\frac{2}{\sigma} [(1-\tau) I(y < \mu)(\mu - y) + \tau I(y > \mu)(y - \mu)] \right]$$

Distribution statement

$y \sim \text{skew_double_exponential}(\text{mu}, \text{sigma}, \text{tau})$

Increment target log probability density with `skew_double_exponential(y | mu, sigma, tau)`

Available since 2.28

Stan functions

`real skew_double_exponential_lpdf(reals y | reals mu, reals sigma, reals tau)`

The log of the skew double exponential density of y given location μ , scale σ and skewness τ

Available since 2.28

`real skew_double_exponential_lupdf(reals y | reals mu, reals sigma, reals tau)`

The log of the skew double exponential density of y given location μ , scale σ and skewness τ dropping constant additive terms

Available since 2.28

`real skew_double_exponential_cdf(reals y | reals mu, reals sigma, reals tau)`

The skew double exponential cumulative distribution function of y given location μ , scale σ and skewness τ

Available since 2.28

```
real skew_double_exponential_lcdf(reals y | reals mu, reals sigma,  
reals tau)
```

The log of the skew double exponential cumulative distribution function of y given location μ , scale σ and skewness τ

Available since 2.28

```
real skew_double_exponential_lccdf(reals y | reals mu, reals sigma,  
reals tau)
```

The log of the skew double exponential complementary cumulative distribution function of y given location μ , scale σ and skewness τ

Available since 2.28

```
R skew_double_exponential_rng(reals mu, reals sigma, reals tau)
```

Generate a skew double exponential variate with location μ , scale σ and skewness τ ; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.28

20. Positive Continuous Distributions

The positive continuous probability functions have support on the positive real numbers.

20.1. Lognormal distribution

Probability density function

If $\mu \in \mathbb{R}$ and $\sigma \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$,

$$\text{LogNormal}(y|\mu, \sigma) = \frac{1}{\sqrt{2\pi} \sigma} \frac{1}{y} \exp\left(-\frac{1}{2} \left(\frac{\log y - \mu}{\sigma}\right)^2\right).$$

Distribution statement

$y \sim \text{lognormal}(\text{mu}, \text{sigma})$

Increment target log probability density with `lognormal_lupdf(y | mu, sigma)`.

Available since 2.0

Stan functions

`real lognormal_lpdf(reals y | reals mu, reals sigma)`

The log of the lognormal density of y given location μ and scale σ

Available since 2.12

`real lognormal_lupdf(reals y | reals mu, reals sigma)`

The log of the lognormal density of y given location μ and scale σ dropping constant additive terms

Available since 2.25

`real lognormal_cdf(reals y | reals mu, reals sigma)`

The cumulative lognormal distribution function of y given location μ and scale σ

Available since 2.0

`real lognormal_lcdf(reals y | reals mu, reals sigma)`

The log of the lognormal cumulative distribution function of y given location μ and scale σ

Available since 2.12

real **lognormal_lccdf**(reals y | reals mu, reals sigma)

The log of the lognormal complementary cumulative distribution function of y given location mu and scale sigma

Available since 2.12

R **lognormal_rng**(reals mu, reals sigma)

Generate a lognormal variate with location mu and scale sigma; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.22

20.2. Chi-square distribution

Probability density function

If $\nu \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$,

$$\text{ChiSquare}(y|\nu) = \frac{2^{-\nu/2}}{\Gamma(\nu/2)} y^{\nu/2-1} \exp\left(-\frac{1}{2}y\right).$$

Distribution statement

$y \sim \text{chi_square}(\text{nu})$

Increment target log probability density with `chi_square_lupdf(y | nu)`.

Available since 2.0

Stan functions

real **chi_square_lpdf**(reals y | reals nu)

The log of the Chi-square density of y given degrees of freedom nu

Available since 2.12

real **chi_square_lupdf**(reals y | reals nu)

The log of the Chi-square density of y given degrees of freedom nu dropping constant additive terms

Available since 2.25

real **chi_square_cdf**(reals y | reals nu)

The Chi-square cumulative distribution function of y given degrees of freedom nu

Available since 2.0

real **chi_square_lcdf**(reals y | reals nu)

The log of the Chi-square cumulative distribution function of y given degrees of freedom nu

Available since 2.12

real **chi_square_lccdf**(reals y | reals nu)

The log of the complementary Chi-square cumulative distribution function of y given degrees of freedom nu

Available since 2.12

R **chi_square_rng**(reals nu)

Generate a Chi-square variate with degrees of freedom nu; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

20.3. Inverse chi-square distribution

Probability density function

If $\nu \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$,

$$\text{InvChiSquare}(y | \nu) = \frac{2^{-\nu/2}}{\Gamma(\nu/2)} y^{-\nu/2-1} \exp\left(-\frac{1}{2} \frac{1}{y}\right).$$

Distribution statement

$y \sim \text{inv_chi_square}(\text{nu})$

Increment target log probability density with `inv_chi_square_lupdf(y | nu)`.

Available since 2.0

Stan functions

real **inv_chi_square_lpdf**(reals y | reals nu)

The log of the inverse Chi-square density of y given degrees of freedom nu

Available since 2.12

real **inv_chi_square_lupdf**(reals y | reals nu)

The log of the inverse Chi-square density of y given degrees of freedom nu dropping constant additive terms

Available since 2.25

real **inv_chi_square_cdf**(reals y | reals nu)

The inverse Chi-squared cumulative distribution function of y given degrees of freedom nu

Available since 2.0

real **inv_chi_square_lcdf**(reals y | reals nu)

The log of the inverse Chi-squared cumulative distribution function of y given degrees of freedom nu

Available since 2.12

real **inv_chi_square_lccdf**(reals y | reals nu)

The log of the inverse Chi-squared complementary cumulative distribution function of y given degrees of freedom nu

Available since 2.12

R **inv_chi_square_rng**(reals nu)

Generate an inverse Chi-squared variate with degrees of freedom nu; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

20.4. Scaled inverse chi-square distribution

Probability density function

If $\nu \in \mathbb{R}^+$ and $\sigma \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$,

$$\text{ScaledInvChiSquare}(y|\nu, \sigma) = \frac{(\nu/2)^{\nu/2}}{\Gamma(\nu/2)} \sigma^\nu y^{-(\nu/2+1)} \exp\left(-\frac{1}{2} \nu \sigma^2 \frac{1}{y}\right).$$

Distribution statement

$y \sim \text{scaled_inv_chi_square}(\text{nu}, \text{sigma})$

Increment target log probability density with `scaled_inv_chi_square_lupdf(y | nu, sigma)`.

Available since 2.0

Stan functions

real **scaled_inv_chi_square_lpdf**(reals y | reals nu, reals sigma)

The log of the scaled inverse Chi-square density of y given degrees of freedom nu and scale sigma

Available since 2.12

real **scaled_inv_chi_square_lupdf**(reals y | reals nu, reals sigma)
 The log of the scaled inverse Chi-square density of y given degrees of freedom nu and scale sigma dropping constant additive terms

Available since 2.25

real **scaled_inv_chi_square_cdf**(reals y | reals nu, reals sigma)
 The scaled inverse Chi-square cumulative distribution function of y given degrees of freedom nu and scale sigma

Available since 2.0

real **scaled_inv_chi_square_lcdf**(reals y | reals nu, reals sigma)
 The log of the scaled inverse Chi-square cumulative distribution function of y given degrees of freedom nu and scale sigma

Available since 2.12

real **scaled_inv_chi_square_lccdf**(reals y | reals nu, reals sigma)
 The log of the scaled inverse Chi-square complementary cumulative distribution function of y given degrees of freedom nu and scale sigma

Available since 2.12

R **scaled_inv_chi_square_rng**(reals nu, reals sigma)
 Generate a scaled inverse Chi-squared variate with degrees of freedom nu and scale sigma; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

20.5. Exponential distribution

Probability density function

If $\beta \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$,

$$\text{Exponential}(y|\beta) = \beta \exp(-\beta y).$$

Distribution statement

$y \sim \text{exponential}(\text{beta})$

Increment target log probability density with `exponential_lupdf(y | beta)`.

Available since 2.0

Stan functions

real **exponential_lpdf**(reals y | reals beta)

The log of the exponential density of y given inverse scale beta

Available since 2.12

real **exponential_lupdf**(reals y | reals beta)

The log of the exponential density of y given inverse scale beta dropping constant additive terms

Available since 2.25

real **exponential_cdf**(reals y | reals beta)

The exponential cumulative distribution function of y given inverse scale beta

Available since 2.0

real **exponential_lcdf**(reals y | reals beta)

The log of the exponential cumulative distribution function of y given inverse scale beta

Available since 2.12

real **exponential_lccdf**(reals y | reals beta)

The log of the exponential complementary cumulative distribution function of y given inverse scale beta

Available since 2.12

R **exponential_rng**(reals beta)

Generate an exponential variate with inverse scale beta; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

20.6. Gamma distribution**Probability density function**

If $\alpha \in \mathbb{R}^+$ and $\beta \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$,

$$\text{Gamma}(y|\alpha, \beta) = \frac{\beta^\alpha}{\Gamma(\alpha)} y^{\alpha-1} \exp(-\beta y).$$

Distribution statement

y ~ **gamma**(alpha, beta)

Increment target log probability density with `gamma_lupdf(y | alpha, beta)`.

Available since 2.0

Stan functions

real **gamma_lpdf**(reals y | reals alpha, reals beta)

The log of the gamma density of y given shape alpha and inverse scale beta

Available since 2.12

real **gamma_lupdf**(reals y | reals alpha, reals beta)

The log of the gamma density of y given shape alpha and inverse scale beta dropping constant additive terms

Available since 2.25

real **gamma_cdf**(reals y | reals alpha, reals beta)

The cumulative gamma distribution function of y given shape alpha and inverse scale beta

Available since 2.0

real **gamma_lcdf**(reals y | reals alpha, reals beta)

The log of the cumulative gamma distribution function of y given shape alpha and inverse scale beta

Available since 2.12

real **gamma_lccdf**(reals y | reals alpha, reals beta)

The log of the complementary cumulative gamma distribution function of y given shape alpha and inverse scale beta

Available since 2.12

R **gamma_rng**(reals alpha, reals beta)

Generate a gamma variate with shape alpha and inverse scale beta; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

20.7. Inverse gamma Distribution

Probability density function

If $\alpha \in \mathbb{R}^+$ and $\beta \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$,

$$\text{InvGamma}(y|\alpha, \beta) = \frac{\beta^\alpha}{\Gamma(\alpha)} y^{-(\alpha+1)} \exp\left(-\beta \frac{1}{y}\right).$$

Distribution statement

$y \sim \text{inv_gamma}(\text{alpha}, \text{beta})$

Increment target log probability density with `inv_gamma_lupdf(y | alpha, beta)`.

Available since 2.0

Stan functions

`real inv_gamma_lpdf(reals y | reals alpha, reals beta)`

The log of the inverse gamma density of y given shape α and scale β

Available since 2.12

`real inv_gamma_lupdf(reals y | reals alpha, reals beta)`

The log of the inverse gamma density of y given shape α and scale β dropping constant additive terms

Available since 2.25

`real inv_gamma_cdf(reals y | reals alpha, reals beta)`

The inverse gamma cumulative distribution function of y given shape α and scale β

Available since 2.0

`real inv_gamma_lcdf(reals y | reals alpha, reals beta)`

The log of the inverse gamma cumulative distribution function of y given shape α and scale β

Available since 2.12

`real inv_gamma_lccdf(reals y | reals alpha, reals beta)`

The log of the inverse gamma complementary cumulative distribution function of y given shape α and scale β

Available since 2.12

R `inv_gamma_rng`(reals alpha, reals beta)

Generate an inverse gamma variate with shape alpha and scale beta; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

20.8. Weibull distribution

Probability density function

If $\alpha \in \mathbb{R}^+$ and $\sigma \in \mathbb{R}^+$, then for $y \in [0, \infty)$,

$$\text{Weibull}(y|\alpha, \sigma) = \frac{\alpha}{\sigma} \left(\frac{y}{\sigma}\right)^{\alpha-1} \exp\left(-\left(\frac{y}{\sigma}\right)^\alpha\right).$$

Note that if $Y \propto \text{Weibull}(\alpha, \sigma)$, then $Y^{-1} \propto \text{Frechet}(\alpha, \sigma^{-1})$.

Distribution statement

$y \sim \text{weibull}(\text{alpha}, \text{sigma})$

Increment target log probability density with `weibull_lupdf(y | alpha, sigma)`.

Available since 2.0

Stan functions

real `weibull_lpdf`(reals y | reals alpha, reals sigma)

The log of the Weibull density of y given shape alpha and scale sigma

Available since 2.12

real `weibull_lupdf`(reals y | reals alpha, reals sigma)

The log of the Weibull density of y given shape alpha and scale sigma dropping constant additive terms

Available since 2.25

real `weibull_cdf`(reals y | reals alpha, reals sigma)

The Weibull cumulative distribution function of y given shape alpha and scale sigma

Available since 2.0

real `weibull_lcdf`(reals y | reals alpha, reals sigma)

The log of the Weibull cumulative distribution function of y given shape alpha and scale sigma

Available since 2.12

real **weibull_lccdf**(reals y | reals alpha, reals sigma)

The log of the Weibull complementary cumulative distribution function of y given shape alpha and scale sigma

Available since 2.12

R **weibull_rng**(reals alpha, reals sigma)

Generate a weibull variate with shape alpha and scale sigma; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

20.9. Frechet distribution

Probability density function

If $\alpha \in \mathbb{R}^+$ and $\sigma \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$,

$$\text{Frechet}(y|\alpha, \sigma) = \frac{\alpha}{\sigma} \left(\frac{y}{\sigma}\right)^{-\alpha-1} \exp\left(-\left(\frac{y}{\sigma}\right)^{-\alpha}\right).$$

Note that if $Y \propto \text{Frechet}(\alpha, \sigma)$, then $Y^{-1} \propto \text{Weibull}(\alpha, \sigma^{-1})$.

Distribution statement

$y \sim \text{frechet}(\text{alpha}, \text{sigma})$

Increment target log probability density with `frechet_lupdf(y | alpha, sigma)`.

Available since 2.5

Stan functions

real **frechet_lpdf**(reals y | reals alpha, reals sigma)

The log of the Frechet density of y given shape alpha and scale sigma

Available since 2.12

real **frechet_lupdf**(reals y | reals alpha, reals sigma)

The log of the Frechet density of y given shape alpha and scale sigma dropping constant additive terms

Available since 2.25

real **frechet_cdf**(reals y | reals alpha, reals sigma)

The Frechet cumulative distribution function of y given shape alpha and scale sigma

Available since 2.5

real **frechet_lcdf**(reals y | reals alpha, reals sigma)

The log of the Frechet cumulative distribution function of y given shape alpha and scale sigma

Available since 2.12

real **frechet_lccdf**(reals y | reals alpha, reals sigma)

The log of the Frechet complementary cumulative distribution function of y given shape alpha and scale sigma

Available since 2.12

R **frechet_rng**(reals alpha, reals sigma)

Generate a Frechet variate with shape alpha and scale sigma; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

20.10. Rayleigh distribution

Probability density function

If $\sigma \in \mathbb{R}^+$, then for $y \in [0, \infty)$,

$$\text{Rayleigh}(y|\sigma) = \frac{y}{\sigma^2} \exp(-y^2/2\sigma^2).$$

Distribution statement

$y \sim \text{rayleigh}(\text{sigma})$

Increment target log probability density with `rayleigh_lupdf(y | sigma)`.

Available since 2.0

Stan functions

real **rayleigh_lpdf**(reals y | reals sigma)

The log of the Rayleigh density of y given scale sigma

Available since 2.12

real **rayleigh_lupdf**(reals y | reals sigma)

The log of the Rayleigh density of y given scale sigma dropping constant additive terms

Available since 2.25

real **rayleigh_cdf**(real y | real sigma)

The Rayleigh cumulative distribution of y given scale sigma

Available since 2.0

real **rayleigh_lcdf**(real y | real sigma)

The log of the Rayleigh cumulative distribution of y given scale sigma

Available since 2.12

real **rayleigh_lccdf**(real y | real sigma)

The log of the Rayleigh complementary cumulative distribution of y given scale sigma

Available since 2.12

R **rayleigh_rng**(reals sigma)

Generate a Rayleigh variate with scale sigma; may only be used in generated quantities block. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

20.11. Log-logistic distribution

Probability density function

If $\alpha, \beta \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$,

$$\text{Log-Logistic}(y|\alpha, \beta) = \frac{\left(\frac{\beta}{\alpha}\right) \left(\frac{y}{\alpha}\right)^{\beta-1}}{\left(1 + \left(\frac{y}{\alpha}\right)^{\beta}\right)^2}.$$

Distribution statement

$y \sim \text{loglogistic}(\text{alpha}, \text{beta})$

Increment target log probability density with unnormalized version of `loglogistic_lpdf(y | alpha, beta)`

Available since 2.29

Stan functions

```
real loglogistic_lpdf(reals y | reals alpha, reals beta)
```

The log of the log-logistic density of y given scale α and shape β

Available since 2.29

```
real loglogistic_cdf(reals y | reals alpha, reals beta)
```

The log-logistic cumulative distribution function of y given scale α and shape β

Available since 2.29

```
R loglogistic_rng(reals alpha, reals beta)
```

Generate a log-logistic variate with scale α and shape β ; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.29

21. Positive Lower-Bounded Distributions

The positive lower-bounded probabilities have support on real values above some positive minimum value.

21.1. Pareto distribution

Probability density function

If $y_{\min} \in \mathbb{R}^+$ and $\alpha \in \mathbb{R}^+$, then for $y \in \mathbb{R}^+$ with $y \geq y_{\min}$,

$$\text{Pareto}(y|y_{\min}, \alpha) = \frac{\alpha y_{\min}^\alpha}{y^{\alpha+1}}.$$

Distribution statement

$y \sim \text{pareto}(y_{\min}, \text{alpha})$

Increment target log probability density with `pareto_lupdf(y | y_min, alpha)`.

Available since 2.0

Stan functions

`real pareto_lpdf(reals y | reals y_min, reals alpha)`

The log of the Pareto density of y given positive minimum value y_{\min} and shape α

Available since 2.12

`real pareto_lupdf(reals y | reals y_min, reals alpha)`

The log of the Pareto density of y given positive minimum value y_{\min} and shape α dropping constant additive terms

Available since 2.25

`real pareto_cdf(reals y | reals y_min, reals alpha)`

The Pareto cumulative distribution function of y given positive minimum value y_{\min} and shape α

Available since 2.0

`real pareto_lcdf(reals y | reals y_min, reals alpha)`

The log of the Pareto cumulative distribution function of y given positive minimum value y_{\min} and shape α

Available since 2.12

real **pareto_lccdf**(reals y | reals y_min, reals alpha)

The log of the Pareto complementary cumulative distribution function of y given positive minimum value y_min and shape alpha

Available since 2.12

R **pareto_rng**(reals y_min, reals alpha)

Generate a Pareto variate with positive minimum value y_min and shape alpha; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

21.2. Pareto type 2 distribution

Probability density function

If $\mu \in \mathbb{R}$, $\lambda \in \mathbb{R}^+$, and $\alpha \in \mathbb{R}^+$, then for $y \geq \mu$,

$$\text{Pareto_Type_2}(y|\mu, \lambda, \alpha) = \frac{\alpha}{\lambda} \left(1 + \frac{y - \mu}{\lambda}\right)^{-(\alpha+1)}.$$

Note that the Lomax distribution is a Pareto Type 2 distribution with $\mu = 0$.

Distribution statement

$y \sim \text{pareto_type_2}(\text{mu}, \text{lambda}, \text{alpha})$

Increment target log probability density with `pareto_type_2_lupdf(y | mu, lambda, alpha)`.

Available since 2.5

Stan functions

real **pareto_type_2_lpdf**(reals y | reals mu, reals lambda, reals alpha)

The log of the Pareto Type 2 density of y given location mu, scale lambda, and shape alpha

Available since 2.18

real **pareto_type_2_lupdf**(reals y | reals mu, reals lambda, reals alpha)

The log of the Pareto Type 2 density of y given location mu, scale lambda, and shape alpha dropping constant additive terms

Available since 2.25

real **pareto_type_2_cdf**(reals y | reals mu, reals lambda, reals alpha)

The Pareto Type 2 cumulative distribution function of y given location mu, scale lambda, and shape alpha

Available since 2.5

real **pareto_type_2_lcdf**(reals y | reals mu, reals lambda, reals alpha)

The log of the Pareto Type 2 cumulative distribution function of y given location mu, scale lambda, and shape alpha

Available since 2.18

real **pareto_type_2_lccdf**(reals y | reals mu, reals lambda, reals alpha)

The log of the Pareto Type 2 complementary cumulative distribution function of y given location mu, scale lambda, and shape alpha

Available since 2.18

R **pareto_type_2_rng**(reals mu, reals lambda, reals alpha)

Generate a Pareto Type 2 variate with location mu, scale lambda, and shape alpha; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

21.3. Wiener First Passage Time Distribution

Probability density function

If $\alpha \in \mathbb{R}^+$, $\tau \in \mathbb{R}^+$, $\beta \in (0, 1)$, $\delta \in \mathbb{R}$, $s_\delta \in \mathbb{R}^{\geq 0}$, $s_\beta \in [0, 1)$, and $s_\tau \in \mathbb{R}^{\geq 0}$ then for $y > \tau$,

$$\begin{aligned}
& \text{Wiener}(y \mid \alpha, \tau, \beta, \delta, s_\delta, s_\beta, s_\tau) = \\
& \frac{1}{s_\tau} \int_\tau^{\tau+s_\tau} \frac{1}{s_\beta} \int_{\beta-\frac{1}{2}s_\beta}^{\beta+\frac{1}{2}s_\beta} \int_{-\infty}^{\infty} p_3(y - \tau_0 \mid \alpha, \nu, \omega) \\
& \times \frac{1}{\sqrt{2\pi s_\delta^2}} \exp\left(-\frac{(\nu - \delta)^2}{2s_\delta^2}\right) d\nu d\omega d\tau_0 = \\
& \frac{1}{s_\tau} \int_\tau^{\tau+s_\tau} \frac{1}{s_\beta} \int_{\beta-\frac{1}{2}s_\beta}^{\beta+\frac{1}{2}s_\beta} M \times p_3(y - \tau_0 \mid \alpha, \nu, \omega) d\omega d\tau_0,
\end{aligned}$$

where $p(\cdot)$ denotes the density function, and M and $p_3(\cdot)$ are defined, by using $t := y - \tau_0$, as

$$M := \frac{1}{\sqrt{1 + s_\delta^2 t}} \exp\left(\alpha\delta\omega + \frac{\delta^2 t}{2} + \frac{s_\delta^2 \alpha^2 \omega^2 - 2\alpha\delta\omega - \delta^2 t}{2(1 + s_\delta^2 t)}\right) \text{ and}$$

$$p_3(t \mid \alpha, \delta, \beta) := \frac{1}{\alpha^2} \exp\left(-\alpha\delta\beta - \frac{\delta^2 t}{2}\right) f\left(\frac{t}{\alpha^2} \mid 0, 1, \beta\right),$$

where $f(t^* = \frac{t}{\alpha^2} \mid 0, 1, \beta)$ can be specified in two ways:

$$f_i(t^* \mid 0, 1, \beta) = \sum_{k=1}^{\infty} k\pi \exp\left(-\frac{k^2 \pi^2 t^*}{2}\right) \sin(k\pi\beta) \text{ and}$$

$$f_s(t^* \mid 0, 1, \beta) = \sum_{k=-\infty}^{\infty} \frac{1}{\sqrt{2\pi(t^*)^3}} (\beta + 2k) \exp\left(-\frac{(\beta + 2k)^2}{2t^*}\right).$$

Which of these is used in the computations depends on which expression requires the smaller number of components k to guarantee a pre-specified precision

In the case where $s_\delta, s_\beta,$ and s_τ are all 0, this simplifies to

$$\text{Wiener}(y \mid \alpha, \tau, \beta, \delta) = \frac{\alpha^3}{(y - \tau)^{3/2}} \exp\left(-\delta\alpha\beta - \frac{\delta^2(y - \tau)}{2}\right) \sum_{k=-\infty}^{\infty} (2k + \beta) \phi\left(\frac{2k\alpha + \beta}{\sqrt{y - \tau}}\right)$$

where $\phi(x)$ denotes the standard normal density function; see (Feller 1968), (Navarro and Fuss 2009).

Distribution statement

$y \sim \mathbf{wiener}(\alpha, \tau, \beta, \delta)$

Increment target log probability density with `wiener_lupdf(y | alpha, tau, beta, delta)`.

Available since 2.7

$y \sim \mathbf{wiener}(\alpha, \tau, \beta, \delta, \text{var_delta})$ Increment target log probability density with `wiener_lupdf(y | alpha, tau, beta, delta, var_delta)`.

Available since 2.35

$y \sim \mathbf{wiener}(\alpha, \tau, \beta, \delta, \text{var_delta}, \text{var_beta}, \text{var_tau})$ Increment target log probability density with `wiener_lupdf(y | alpha, tau, beta, delta, var_delta, var_beta, var_tau)`.

Available since 2.35

Stan functions

`real wiener_lpdf(reals y | reals alpha, reals tau, reals beta, reals delta)`

The log of the Wiener first passage time density of y given boundary separation α , non-decision time τ , a-priori bias β , and drift rate δ .

Available since 2.18

`real wiener_lpdf(real y | real alpha, real tau, real beta, real delta, real var_delta)`

The log of the Wiener first passage time density of y given boundary separation α , non-decision time τ , a-priori bias β , drift rate δ , and inter-trial drift rate variability var_delta .

Setting `var_delta` to 0 recovers the 4-parameter signature above.

Available since 2.35

`real wiener_lpdf(real y | real alpha, real tau, real beta, real delta, real var_delta, real var_beta, real var_tau)`

The log of the Wiener first passage time density of y given boundary separation α , non-decision time τ , a-priori bias β , drift rate δ , inter-trial drift rate variability var_delta , inter-trial variability of the starting point (bias) var_beta , and inter-trial variability of the non-decision time var_tau .

Setting `var_delta`, `var_beta`, and `var_tau` to 0 recovers the 4-parameter signature above.

Available since 2.35

```
real wiener_lupdf(reals y | reals alpha, reals tau, reals beta, reals delta)
```

The log of the Wiener first passage time density of y given boundary separation α , non-decision time τ , a-priori bias β , and drift rate δ , dropping constant additive terms

Available since 2.25

```
real wiener_lupdf(real y | real alpha, real tau, real beta, real delta, real var_delta)
```

The log of the Wiener first passage time density of y given boundary separation α , non-decision time τ , a-priori bias β , drift rate δ , and inter-trial drift rate variability `var_delta`, dropping constant additive terms.

Setting `var_delta` to 0 recovers the 4-parameter signature above.

Available since 2.35

```
real wiener_lupdf(real y | real alpha, real tau, real beta, real delta, real var_delta, real var_beta, real var_tau)
```

The log of the Wiener first passage time density of y given boundary separation α , non-decision time τ , a-priori bias β , drift rate δ , inter-trial drift rate variability `var_delta`, inter-trial variability of the starting point (bias) `var_beta`, and inter-trial variability of the non-decision time `var_tau`, dropping constant additive terms.

Setting `var_delta`, `var_beta`, and `var_tau` to 0 recovers the 4-parameter signature above.

Available since 2.35

Boundaries

`Stan` returns the first passage time of the accumulation process over the upper boundary only. To get the result for the lower boundary, use

$$\text{Wiener}(y|\alpha, \tau, 1 - \beta, -\delta)$$

For more details, see the appendix of Vandekerckhove and Wabersich (2014).

22. Continuous Distributions on [0, 1]

The continuous distributions with outcomes in the interval [0, 1] are used to characterize bounded quantities, including probabilities.

22.1. Beta distribution

Probability density function

If $\alpha \in \mathbb{R}^+$ and $\beta \in \mathbb{R}^+$, then for $\theta \in (0, 1)$,

$$\text{Beta}(\theta|\alpha, \beta) = \frac{1}{\text{B}(\alpha, \beta)} \theta^{\alpha-1} (1 - \theta)^{\beta-1},$$

where the beta function $\text{B}()$ is as defined in section [combinatorial functions](#).

Warning: If $\theta = 0$ or $\theta = 1$, then the probability is 0 and the log probability is $-\infty$. Similarly, the distribution requires strictly positive parameters, $\alpha, \beta > 0$.

Distribution statement

theta ~ **beta**(alpha, beta)

Increment target log probability density with `beta_lupdf(theta | alpha, beta)`.

Available since 2.0

Stan functions

real **beta_lpdf**(reals theta | reals alpha, reals beta)

The log of the beta density of theta in [0, 1] given positive prior successes (plus one) alpha and prior failures (plus one) beta

Available since 2.12

real **beta_lupdf**(reals theta | reals alpha, reals beta)

The log of the beta density of theta in [0, 1] given positive prior successes (plus one) alpha and prior failures (plus one) beta dropping constant additive terms

Available since 2.25

real **beta_cdf**(reals theta | reals alpha, reals beta)

The beta cumulative distribution function of theta in [0, 1] given positive prior successes (plus one) alpha and prior failures (plus one) beta

Available since 2.0

real **beta_lcdf**(reals theta | reals alpha, reals beta)

The log of the beta cumulative distribution function of theta in $[0, 1]$ given positive prior successes (plus one) alpha and prior failures (plus one) beta

Available since 2.12

real **beta_lccdf**(reals theta | reals alpha, reals beta)

The log of the beta complementary cumulative distribution function of theta in $[0, 1]$ given positive prior successes (plus one) alpha and prior failures (plus one) beta

Available since 2.12

R **beta_rng**(reals alpha, reals beta)

Generate a beta variate with positive prior successes (plus one) alpha and prior failures (plus one) beta; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

22.2. Beta proportion distribution

Probability density function

If $\mu \in (0, 1)$ and $\kappa \in \mathbb{R}^+$, then for $\theta \in (0, 1)$,

$$\text{Beta_Proportion}(\theta|\mu, \kappa) = \frac{1}{\text{B}(\mu\kappa, (1-\mu)\kappa)} \theta^{\mu\kappa-1} (1-\theta)^{(1-\mu)\kappa-1},$$

where the beta function $\text{B}()$ is as defined in section [combinatorial functions](#).

Warning: If $\theta = 0$ or $\theta = 1$, then the probability is 0 and the log probability is $-\infty$. Similarly, the distribution requires $\mu \in (0, 1)$ and strictly positive parameter, $\kappa > 0$.

Distribution statement

theta \sim **beta_proportion**(mu, kappa)

Increment target log probability density with `beta_proportion_lupdf(theta | mu, kappa)`.

Available since 2.19

Stan functions

real **beta_proportion_lpdf**(reals theta | reals mu, reals kappa)

The log of the beta_proportion density of theta in (0,1) given mean mu and precision kappa

Available since 2.19

real **beta_proportion_lupdf**(reals theta | reals mu, reals kappa)

The log of the beta_proportion density of theta in (0,1) given mean mu and precision kappa dropping constant additive terms

Available since 2.25

real **beta_proportion_lcdf**(reals theta | reals mu, reals kappa)

The log of the beta_proportion cumulative distribution function of theta in (0,1) given mean mu and precision kappa

Available since 2.18

real **beta_proportion_lccdf**(reals theta | reals mu, reals kappa)

The log of the beta_proportion complementary cumulative distribution function of theta in (0,1) given mean mu and precision kappa

Available since 2.18

R **beta_proportion_rng**(reals mu, reals kappa)

Generate a beta_proportion variate with mean mu and precision kappa; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

23. Circular Distributions

Circular distributions are defined for finite values y in any interval of length 2π .

23.1. Von Mises distribution

Probability density function

If $\mu \in \mathbb{R}$ and $\kappa \in \mathbb{R}^+$, then for $y \in \mathbb{R}$,

$$\text{VonMises}(y|\mu, \kappa) = \frac{\exp(\kappa \cos(y - \mu))}{2\pi I_0(\kappa)}.$$

In order for this density to properly normalize, y must be restricted to some interval $(c, c + 2\pi)$ of length 2π , because

$$\int_c^{c+2\pi} \text{VonMises}(y|\mu, \kappa) dy = 1.$$

Similarly, if μ is a parameter, it will typically be restricted to the same range as y .

If $\kappa > 0$, a von Mises distribution with its 2π interval of support centered around its location μ will have a single mode at μ ; for example, restricting y to $(-\pi, \pi)$ and taking $\mu = 0$ leads to a single local optimum at the mode μ . If the location μ is not in the center of the support, the density is circularly translated and there will be a second local maximum at the boundary furthest from the mode. Ideally, the parameterization and support will be set up so that the bulk of the probability mass is in a continuous interval around the mean μ .

For $\kappa = 0$, the Von Mises distribution corresponds to the circular uniform distribution with density $1/(2\pi)$ (independently of the values of y or μ).

Distribution statement

$y \sim \text{von_mises}(\text{mu}, \text{kappa})$

Increment target log probability density with `von_mises_lupdf(y | mu, kappa)`.

Available since 2.0

Stan functions

real `von_mises_lpdf`(reals y | reals mu , reals kappa)

The log of the von mises density of y given location mu and scale kappa .

Available since 2.18

real **von_mises_lupdf**(reals y | reals mu, reals kappa)

The log of the von mises density of y given location mu and scale kappa dropping constant additive terms.

Available since 2.25

real **von_mises_cdf**(reals y | reals mu, reals kappa)

The von mises cumulative distribution function of y given location mu and scale kappa.

Available since 2.29

real **von_mises_lcdf**(reals y | reals mu, reals kappa)

The log of the von mises cumulative distribution function of y given location mu and scale kappa.

Available since 2.29

real **von_mises_lccdf**(reals y | reals mu, reals kappa)

The log of the von mises complementary cumulative distribution function of y given location mu and scale kappa.

Available since 2.29

R **von_mises_rng**(reals mu, reals kappa)

Generate a Von Mises variate with location mu and scale kappa (i.e. returns values in the interval $[(\mu \bmod 2\pi) - \pi, (\mu \bmod 2\pi) + \pi]$); may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

Numerical stability

Evaluating the Von Mises distribution for $\kappa > 100$ is numerically unstable in the current implementation. Nathanael I. Lichti suggested the following workaround on the Stan users group, based on the fact that as $\kappa \rightarrow \infty$,

$$\text{VonMises}(y|\mu, \kappa) \rightarrow \text{Normal}(\mu, \sqrt{1/\kappa}).$$

The workaround is to replace $y \sim \text{von_mises}(\mu, \text{kappa})$ with

```
if (kappa < 100) {
  y ~ von_mises(mu, kappa);
} else {
```

```
y ~ normal(mu, sqrt(1 / kappa));  
}
```

24. Bounded Continuous Distributions

The bounded continuous probabilities have support on a finite interval of real numbers.

24.1. Uniform distribution

Probability density function

If $\alpha \in \mathbb{R}$ and $\beta \in (\alpha, \infty)$, then for $y \in [\alpha, \beta]$,

$$\text{Uniform}(y|\alpha, \beta) = \frac{1}{\beta - \alpha}.$$

Distribution statement

$y \sim \text{uniform}(\text{alpha}, \text{beta})$

Increment target log probability density with `uniform_lupdf(y | alpha, beta)`.

Available since 2.0

Stan functions

`real uniform_lpdf(reals y | reals alpha, reals beta)`

The log of the uniform density of y given lower bound α and upper bound β

Available since 2.12

`real uniform_lupdf(reals y | reals alpha, reals beta)`

The log of the uniform density of y given lower bound α and upper bound β dropping constant additive terms

Available since 2.25

`real uniform_cdf(reals y | reals alpha, reals beta)`

The uniform cumulative distribution function of y given lower bound α and upper bound β

Available since 2.0

`real uniform_lcdf(reals y | reals alpha, reals beta)`

The log of the uniform cumulative distribution function of y given lower bound α and upper bound β

Available since 2.12

real **uniform_lccdf**(reals y | reals alpha, reals beta)

The log of the uniform complementary cumulative distribution function of y given lower bound alpha and upper bound beta

Available since 2.12

R **uniform_rng**(reals alpha, reals beta)

Generate a uniform variate with lower bound alpha and upper bound beta; may only be used in transformed data and generated quantities blocks. For a description of argument and return types, see section [vectorized PRNG functions](#).

Available since 2.18

25. Distributions over Unbounded Vectors

The unbounded vector probability distributions have support on all of \mathbb{R}^K for some fixed K .

25.1. Multivariate normal distribution

Probability density function

If $K \in \mathbb{N}$, $\mu \in \mathbb{R}^K$, and $\Sigma \in \mathbb{R}^{K \times K}$ is symmetric and positive definite, then for $y \in \mathbb{R}^K$,

$$\text{MultiNormal}(y|\mu, \Sigma) = \frac{1}{(2\pi)^{K/2}} \frac{1}{\sqrt{|\Sigma|}} \exp\left(-\frac{1}{2}(y - \mu)^\top \Sigma^{-1} (y - \mu)\right),$$

where $|\Sigma|$ is the absolute determinant of Σ .

Distribution statement

$y \sim \text{multi_normal}(\mu, \text{Sigma})$

Increment target log probability density with `multi_normal_lupdf(y | mu, Sigma)`.

Available since 2.0

Stan functions

The multivariate normal probability function is overloaded to allow the variate vector y and location vector μ to be vectors or row vectors (or to mix the two types). The density function is also vectorized, so it allows arrays of row vectors or vectors as arguments; see section [vectorized function signatures](#) for a description of vectorization.

`real multi_normal_lpdf(vectors y | vectors mu, matrix Sigma)`

The log of the multivariate normal density of vector(s) y given location vector(s) μ and covariance matrix Sigma

Available since 2.12

`real multi_normal_lupdf(vectors y | vectors mu, matrix Sigma)`

The log of the multivariate normal density of vector(s) y given location vector(s) μ and covariance matrix Sigma dropping constant additive terms

Available since 2.25

```
real multi_normal_lpdf(vectors y | row_vectors mu, matrix Sigma)
```

The log of the multivariate normal density of vector(s) y given location row vector(s) μ and covariance matrix Σ

Available since 2.12

```
real multi_normal_lupdf(vectors y | row_vectors mu, matrix Sigma)
```

The log of the multivariate normal density of vector(s) y given location row vector(s) μ and covariance matrix Σ dropping constant additive terms

Available since 2.25

```
real multi_normal_lpdf(row_vectors y | vectors mu, matrix Sigma)
```

The log of the multivariate normal density of row vector(s) y given location vector(s) μ and covariance matrix Σ

Available since 2.12

```
real multi_normal_lupdf(row_vectors y | vectors mu, matrix Sigma)
```

The log of the multivariate normal density of row vector(s) y given location vector(s) μ and covariance matrix Σ dropping constant additive terms

Available since 2.25

```
real multi_normal_lpdf(row_vectors y | row_vectors mu, matrix Sigma)
```

The log of the multivariate normal density of row vector(s) y given location row vector(s) μ and covariance matrix Σ

Available since 2.12

```
real multi_normal_lupdf(row_vectors y | row_vectors mu, matrix Sigma)
```

The log of the multivariate normal density of row vector(s) y given location row vector(s) μ and covariance matrix Σ dropping constant additive terms

Available since 2.25

Although there is a direct multi-normal RNG function, if more than one result is required, it's much more efficient to Cholesky factor the covariance matrix and call `multi_normal_cholesky_rng`; see section [multi-variate normal, cholesky parameterization](#).

vector **multi_normal_rng**(vector mu, matrix Sigma)

Generate a multivariate normal variate with location mu and covariance matrix Sigma; may only be used in transformed data and generated quantities blocks

Available since 2.0

vector **multi_normal_rng**(row_vector mu, matrix Sigma)

Generate a multivariate normal variate with location mu and covariance matrix Sigma; may only be used in transformed data and generated quantities blocks

Available since 2.18

vectors **multi_normal_rng**(vectors mu, matrix Sigma)

Generate an array of multivariate normal variates with locations mu and covariance matrix Sigma; may only be used in transformed data and generated quantities blocks

Available since 2.18

vectors **multi_normal_rng**(row_vectors mu, matrix Sigma)

Generate an array of multivariate normal variates with locations mu and covariance matrix Sigma; may only be used in transformed data and generated quantities blocks

Available since 2.18

25.2. Multivariate normal distribution, precision parameterization

Probability density function

If $K \in \mathbb{N}$, $\mu \in \mathbb{R}^K$, and $\Omega \in \mathbb{R}^{K \times K}$ is symmetric and positive definite, then for $y \in \mathbb{R}^K$,

$$\text{MultiNormalPrecision}(y|\mu, \Omega) = \text{MultiNormal}(y|\mu, \Omega^{-1})$$

Distribution statement

$y \sim \text{multi_normal_prec}(\text{mu}, \text{Omega})$

Increment target log probability density with `multi_normal_prec_lupdf(y | mu, Omega)`.

Available since 2.3

Stan functions

real **multi_normal_prec_lpdf**(vectors y | vectors mu, matrix Omega)

The log of the multivariate normal density of vector(s) y given location vector(s)

mu and positive definite precision matrix Omega

Available since 2.18

real **multi_normal_prec_lupdf**(vectors y | vectors mu, matrix Omega)
 The log of the multivariate normal density of vector(s) y given location vector(s) mu and positive definite precision matrix Omega dropping constant additive terms

Available since 2.25

real **multi_normal_prec_lupdf**(vectors y | row_vectors mu, matrix Omega)

The log of the multivariate normal density of vector(s) y given location row vector(s) mu and positive definite precision matrix Omega

Available since 2.18

real **multi_normal_prec_lupdf**(vectors y | row_vectors mu, matrix Omega)

The log of the multivariate normal density of vector(s) y given location row vector(s) mu and positive definite precision matrix Omega dropping constant additive terms

Available since 2.25

real **multi_normal_prec_lupdf**(row_vectors y | vectors mu, matrix Omega)

The log of the multivariate normal density of row vector(s) y given location vector(s) mu and positive definite precision matrix Omega

Available since 2.18

real **multi_normal_prec_lupdf**(row_vectors y | vectors mu, matrix Omega)

The log of the multivariate normal density of row vector(s) y given location vector(s) mu and positive definite precision matrix Omega dropping constant additive terms

Available since 2.25

real **multi_normal_prec_lupdf**(row_vectors y | row_vectors mu, matrix Omega)

The log of the multivariate normal density of row vector(s) y given location row vector(s) mu and positive definite precision matrix Omega

Available since 2.18

real **multi_normal_prec_lupdf**(row_vectors y | row_vectors mu, matrix Omega)

The log of the multivariate normal density of row vector(s) y given location row vector(s) mu and positive definite precision matrix Omega dropping constant additive terms

Available since 2.25

25.3. Multivariate normal distribution, Cholesky parameterization

Probability density function

If $K \in \mathbb{N}$, $\mu \in \mathbb{R}^K$, and $L \in \mathbb{R}^{K \times K}$ is lower triangular and such that LL^\top is positive definite, then for $y \in \mathbb{R}^K$,

$$\text{MultiNormalCholesky}(y|\mu, L) = \text{MultiNormal}(y|\mu, LL^\top).$$

If L is lower triangular and LL^{top} is a $K \times K$ positive definite matrix, then $L_{k,k}$ must be strictly positive for $k \in 1:K$. If an L is provided that is not the Cholesky factor of a positive-definite matrix, the probability functions will raise errors.

Distribution statement

$y \sim \text{multi_normal_cholesky}(\text{mu}, L)$

Increment target log probability density with `multi_normal_cholesky_lupdf(y | mu, L)`.

Available since 2.0

Stan functions

real **multi_normal_cholesky_lpdf**(vectors y | vectors mu, matrix L)

The log of the multivariate normal density of vector(s) y given location vector(s) mu and lower-triangular Cholesky factor of the covariance matrix L

Available since 2.18

real **multi_normal_cholesky_lupdf**(vectors y | vectors mu, matrix L)

The log of the multivariate normal density of vector(s) y given location vector(s) mu and lower-triangular Cholesky factor of the covariance matrix L dropping constant additive terms

Available since 2.25

real **multi_normal_cholesky_lpdf**(vectors y | row_vectors mu, matrix L)

The log of the multivariate normal density of vector(s) y given location row vector(s) μ and lower-triangular Cholesky factor of the covariance matrix L

Available since 2.18

```
real multi_normal_cholesky_lupdf(vectors y | row_vectors mu, matrix L)
```

The log of the multivariate normal density of vector(s) y given location row vector(s) μ and lower-triangular Cholesky factor of the covariance matrix L dropping constant additive terms

Available since 2.25

```
real multi_normal_cholesky_lpdf(row_vectors y | vectors mu, matrix L)
```

The log of the multivariate normal density of row vector(s) y given location vector(s) μ and lower-triangular Cholesky factor of the covariance matrix L

Available since 2.18

```
real multi_normal_cholesky_lupdf(row_vectors y | vectors mu, matrix L)
```

The log of the multivariate normal density of row vector(s) y given location vector(s) μ and lower-triangular Cholesky factor of the covariance matrix L dropping constant additive terms

Available since 2.25

```
real multi_normal_cholesky_lpdf(row_vectors y | row_vectors mu, matrix L)
```

The log of the multivariate normal density of row vector(s) y given location row vector(s) μ and lower-triangular Cholesky factor of the covariance matrix L

Available since 2.18

```
real multi_normal_cholesky_lupdf(row_vectors y | row_vectors mu, matrix L)
```

The log of the multivariate normal density of row vector(s) y given location row vector(s) μ and lower-triangular Cholesky factor of the covariance matrix L dropping constant additive terms

Available since 2.25

```
vector multi_normal_cholesky_rng(vector mu, matrix L)
```

Generate a multivariate normal variate with location μ and lower-triangular

Cholesky factor of the covariance matrix L ; may only be used in transformed data and generated quantities blocks

Available since 2.3

vector **multi_normal_cholesky_rng**(row_vector mu, matrix L)

Generate a multivariate normal variate with location mu and lower-triangular Cholesky factor of the covariance matrix L ; may only be used in transformed data and generated quantities blocks

Available since 2.18

vectors **multi_normal_cholesky_rng**(vectors mu, matrix L)

Generate an array of multivariate normal variates with locations mu and lower-triangular Cholesky factor of the covariance matrix L ; may only be used in transformed data and generated quantities blocks

Available since 2.18

vectors **multi_normal_cholesky_rng**(row_vectors mu, matrix L)

Generate an array of multivariate normal variates with locations mu and lower-triangular Cholesky factor of the covariance matrix L ; may only be used in transformed data and generated quantities blocks

Available since 2.18

25.4. Multivariate Gaussian process distribution

Probability density function

If $K, N \in \mathbb{N}$, $\Sigma \in \mathbb{R}^{N \times N}$ is symmetric, positive definite kernel matrix and $w \in \mathbb{R}^K$ is a vector of positive inverse scales, then for $y \in \mathbb{R}^{K \times N}$,

$$\text{MultiGP}(y|\Sigma, w) = \prod_{i=1}^K \text{MultiNormal}(y_i|0, w_i^{-1}\Sigma),$$

where y_i is the i th row of y . This is used to efficiently handle Gaussian Processes with multi-variate outputs where only the output dimensions share a kernel function but vary based on their scale. Note that this function does not take into account the mean prediction.

Distribution statement

$y \sim \text{multi_gp}(\text{Sigma}, w)$

Increment target log probability density with `multi_gp_lupdf(y | Sigma, w)`.

Available since 2.3

Stan functions

real **multi_gp_lpdf**(matrix y | matrix Sigma, vector w)

The log of the multivariate GP density of matrix y given kernel matrix Sigma and inverses scales w

Available since 2.12

real **multi_gp_lupdf**(matrix y | matrix Sigma, vector w)

The log of the multivariate GP density of matrix y given kernel matrix Sigma and inverses scales w dropping constant additive terms

Available since 2.25

25.5. Multivariate Gaussian process distribution, Cholesky parameterization

Probability density function

If $K, N \in \mathbb{N}$, $L \in \mathbb{R}^{N \times N}$ is lower triangular and such that LL^\top is positive definite kernel matrix (implying $L_{n,n} > 0$ for $n \in 1:N$), and $w \in \mathbb{R}^K$ is a vector of positive inverse scales, then for $y \in \mathbb{R}^{K \times N}$,

$$\text{MultiGPCholesky}(y | L, w) = \prod_{i=1}^K \text{MultiNormal}(y_i | 0, w_i^{-1} LL^\top),$$

where y_i is the i th row of y . This is used to efficiently handle Gaussian Processes with multi-variate outputs where only the output dimensions share a kernel function but vary based on their scale. If the model allows parameterization in terms of Cholesky factor of the kernel matrix, this distribution is also more efficient than `MultiGP()`. Note that this function does not take into account the mean prediction.

Distribution statement

$y \sim \text{multi_gp_cholesky}(L, w)$

Increment target log probability density with `multi_gp_cholesky_lupdf(y | L, w)`.

Available since 2.5

Stan functions

real **multi_gp_cholesky_lpdf**(matrix y | matrix L, vector w)

The log of the multivariate GP density of matrix y given lower-triangular Cholesky factor of the kernel matrix L and inverses scales w

Available since 2.12

real **multi_gp_cholesky_lupdf**(matrix y | matrix L, vector w)

The log of the multivariate GP density of matrix y given lower-triangular Cholesky factor of the kernel matrix L and inverses scales w dropping constant additive terms

Available since 2.25

25.6. Multivariate Student-t distribution

Probability density function

If $K \in \mathbb{N}$, $\nu \in \mathbb{R}^+$, $\mu \in \mathbb{R}^K$, and $\Sigma \in \mathbb{R}^{K \times K}$ is symmetric and positive definite, then for $y \in \mathbb{R}^K$,

$$\begin{aligned} & \text{MultiStudentT}(y | \nu, \mu, \Sigma) \\ &= \frac{1}{\pi^{K/2}} \frac{1}{\nu^{K/2}} \frac{\Gamma((\nu+K)/2)}{\Gamma(\nu/2)} \frac{1}{\sqrt{|\Sigma|}} \left(1 + \frac{1}{\nu} (y - \mu)^\top \Sigma^{-1} (y - \mu) \right)^{-(\nu+K)/2}. \end{aligned}$$

Distribution statement

$y \sim \text{multi_student_t}(\text{nu}, \text{mu}, \text{Sigma})$

Increment target log probability density with `multi_student_t_lupdf(y | nu, mu, Sigma)`.

Available since 2.0

Stan functions

real **multi_student_t_lpdf**(vectors y | real nu, vectors mu, matrix Sigma)

The log of the multivariate Student-*t* density of vector(s) y given degrees of freedom nu, location vector(s) mu, and scale matrix Sigma

Available since 2.18

real **multi_student_t_lupdf**(vectors y | real nu, vectors mu, matrix Sigma)

The log of the multivariate Student-*t* density of vector(s) y given degrees of freedom nu, location vector(s) mu, and scale matrix Sigma dropping constant additive terms

Available since 2.25

real **multi_student_t_lpdf**(vectors y | real nu, row_vectors mu, matrix Sigma)

The log of the multivariate Student- t density of vector(s) y given degrees of freedom nu , location row vector(s) mu , and scale matrix $Sigma$

Available since 2.18

```
real multi_student_t_lupdf(vectors y | real nu, row_vectors mu, matrix Sigma)
```

The log of the multivariate Student- t density of vector(s) y given degrees of freedom nu , location row vector(s) mu , and scale matrix $Sigma$ dropping constant additive terms

Available since 2.25

```
real multi_student_t_lpdf(row_vectors y | real nu, vectors mu, matrix Sigma)
```

The log of the multivariate Student- t density of row vector(s) y given degrees of freedom nu , location vector(s) mu , and scale matrix $Sigma$

Available since 2.18

```
real multi_student_t_lupdf(row_vectors y | real nu, vectors mu, matrix Sigma)
```

The log of the multivariate Student- t density of row vector(s) y given degrees of freedom nu , location vector(s) mu , and scale matrix $Sigma$ dropping constant additive terms

Available since 2.25

```
real multi_student_t_lpdf(row_vectors y | real nu, row_vectors mu, matrix Sigma)
```

The log of the multivariate Student- t density of row vector(s) y given degrees of freedom nu , location row vector(s) mu , and scale matrix $Sigma$

Available since 2.18

```
real multi_student_t_lupdf(row_vectors y | real nu, row_vectors mu, matrix Sigma)
```

The log of the multivariate Student- t density of row vector(s) y given degrees of freedom nu , location row vector(s) mu , and scale matrix $Sigma$ dropping constant additive terms

Available since 2.25

```
vector multi_student_t_rng(real nu, vector mu, matrix Sigma)
```

Generate a multivariate Student- t variate with degrees of freedom nu , location

`mu`, and scale matrix `Sigma`; may only be used in transformed data and generated quantities blocks

Available since 2.0

vector `multi_student_t_rng`(real `nu`, row_vector `mu`, matrix `Sigma`)
 Generate a multivariate Student-*t* variate with degrees of freedom `nu`, location `mu`, and scale matrix `Sigma`; may only be used in transformed data and generated quantities blocks

Available since 2.18

vectors `multi_student_t_rng`(real `nu`, vectors `mu`, matrix `Sigma`)
 Generate an array of multivariate Student-*t* variates with degrees of freedom `nu`, locations `mu`, and scale matrix `Sigma`; may only be used in transformed data and generated quantities blocks

Available since 2.18

vectors `multi_student_t_rng`(real `nu`, row_vectors `mu`, matrix `Sigma`)
 Generate an array of multivariate Student-*t* variates with degrees of freedom `nu`, locations `mu`, and scale matrix `Sigma`; may only be used in transformed data and generated quantities blocks

Available since 2.18

25.7. Multivariate Student-t distribution, Cholesky parameterization

Probability density function

Let $K \in \mathbb{N}$, $\nu \in \mathbb{R}^+$, $\mu \in \mathbb{R}^K$, and L a $K \times K$ lower-triangular matrix with strictly positive, finite diagonal then

$$\begin{aligned} & \text{MultiStudentTCholesky}(y \mid \nu, \mu, L) \\ &= \frac{1}{\pi^{K/2}} \frac{1}{\nu^{K/2}} \frac{\Gamma((\nu+K)/2)}{\Gamma(\nu/2)} \frac{1}{|L|} \left(1 + \frac{1}{\nu} (y - \mu)^\top L^{-T} L^{-1} (y - \mu) \right)^{-(\nu+K)/2}. \end{aligned}$$

Distribution statement

$y \sim \text{multi_student_t_cholesky}(\text{nu}, \text{mu}, L)$

Increment target log probability density with
`multi_student_t_cholesky_lupdf(y | nu, mu, L).`

Available since 2.30

Stan functions

real **multi_student_t_cholesky_lpdf**(vectors y | real nu, vectors mu, matrix L)

The log of the multivariate Student-*t* density of vector or array of vectors y given degrees of freedom nu, location vector or array of vectors mu, and Cholesky factor of the scale matrix L. For a definition of the arguments compatible with the vectors type, see the [probability vectorization section](#).

Available since 2.30

real **multi_student_t_cholesky_lupdf**(vectors y | real nu, vectors mu, matrix L)

The log of the multivariate Student-*t* density of vector or vector array y given degrees of freedom nu, location vector or vector array mu, and Cholesky factor of the scale matrix L, dropping constant additive terms. For a definition of arguments compatible with the vectors type, see the [probability vectorization section](#).

Available since 2.30

vector **multi_student_t_cholesky_rng**(real nu, vector mu, matrix L)

Generate a multivariate Student-*t* variate with degrees of freedom nu, location mu, and Cholesky factor of the scale matrix L; may only be used in transformed data and generated quantities blocks.

Available since 2.30

array[] vector **multi_student_t_cholesky_rng**(real nu, array[] vector mu, matrix L)

Generate a multivariate Student-*t* variate with degrees of freedom nu, location array mu, and Cholesky factor of the scale matrix L; may only be used in transformed data and generated quantities blocks.

Available since 2.30

array[] vector **multi_student_t_cholesky_rng**(real nu, array[] row_vector mu, matrix L)

Generate an array of multivariate Student-*t* variate with degrees of freedom nu, location array mu, and Cholesky factor of the scale matrix L; may only be used in transformed data and generated quantities blocks.

Available since 2.30

25.8. Gaussian dynamic linear models

A Gaussian Dynamic Linear model is defined as follows, For $t \in 1, \dots, T$,

$$\begin{aligned}y_t &\sim N(F'\theta_t, V) \\ \theta_t &\sim N(G\theta_{t-1}, W) \\ \theta_0 &\sim N(m_0, C_0)\end{aligned}$$

where y is $n \times T$ matrix where rows are variables and columns are observations. These functions calculate the log-density of the observations marginalizing over the latent states ($p(y|F, G, V, W, m_0, C_0)$). This log-density is a system that is calculated using the Kalman Filter. If V is diagonal, then a more efficient algorithm which sequentially processes observations and avoids a matrix inversions can be used (Durbin and Koopman 2001, sec. 6.4).

Distribution statement

$y \sim \text{gaussian_dlm_obs}(F, G, V, W, m_0, C_0)$

Increment target log probability density with `gaussian_dlm_obs_lupdf(y | F, G, V, W, m0, C0)`.

Available since 2.0

Stan functions

The following two functions differ in the type of their V , the first taking a full observation covariance matrix V and the second a vector V representing the diagonal of the observation covariance matrix. The sampling statement defined in the previous section works with either type of observation V .

```
real gaussian_dlm_obs_lpdf(matrix y | matrix F, matrix G, matrix V,
matrix W, vector m0, matrix C0)
```

The log of the density of the Gaussian Dynamic Linear model with observation matrix y in which rows are variables and columns are observations, design matrix F , transition matrix G , observation covariance matrix V , system covariance matrix W , and the initial state is distributed normal with mean m_0 and covariance C_0 .

Available since 2.12

```
real gaussian_dlm_obs_lupdf(matrix y | matrix F, matrix G, matrix
V, matrix W, vector m0, matrix C0)
```

The log of the density of the Gaussian Dynamic Linear model with observation matrix y in which rows are variables and columns are observations, design matrix F , transition matrix G , observation covariance matrix V , system covariance matrix

W , and the initial state is distributed normal with mean m_0 and covariance C_0 . This function drops constant additive terms.

Available since 2.25

```
real gaussian_dlm_obs_lpdf(matrix y | matrix F, matrix G, vector V,  
matrix W, vector m0, matrix C0)
```

The log of the density of the Gaussian Dynamic Linear model with observation matrix y in which rows are variables and columns are observations, design matrix F , transition matrix G , observation covariance matrix with diagonal V , system covariance matrix W , and the initial state is distributed normal with mean m_0 and covariance C_0 .

Available since 2.12

```
real gaussian_dlm_obs_lupdf(matrix y | matrix F, matrix G, vector  
V, matrix W, vector m0, matrix C0)
```

The log of the density of the Gaussian Dynamic Linear model with observation matrix y in which rows are variables and columns are observations, design matrix F , transition matrix G , observation covariance matrix with diagonal V , system covariance matrix W , and the initial state is distributed normal with mean m_0 and covariance C_0 . This function drops constant additive terms.

Available since 2.25

26. Simplex Distributions

The simplex probabilities have support on the unit K -simplex for a specified K . A K -dimensional vector θ is a unit K -simplex if $\theta_k \geq 0$ for $k \in \{1, \dots, K\}$ and $\sum_{k=1}^K \theta_k = 1$.

26.1. Dirichlet distribution

Probability density function

If $K \in \mathbb{N}$ and $\alpha \in (\mathbb{R}^+)^K$, then for $\theta \in K$ -simplex,

$$\text{Dirichlet}(\theta|\alpha) = \frac{\Gamma\left(\sum_{k=1}^K \alpha_k\right)}{\prod_{k=1}^K \Gamma(\alpha_k)} \prod_{k=1}^K \theta_k^{\alpha_k-1}$$

Warning: If any of the components of θ satisfies $\theta_i = 0$ or $\theta_i = 1$, then the probability is 0 and the log probability is $-\infty$. Similarly, the distribution requires strictly positive parameters, with $\alpha_i > 0$ for each i .

Meaning of Dirichlet parameters

A symmetric Dirichlet prior is $[\alpha, \dots, \alpha]^\top$. To code this in Stan,

```
data {  
  int<lower=1> K;  
  real<lower=0> alpha;  
}  
generated quantities {  
  vector[K] theta = dirichlet_rng(rep_vector(alpha, K));  
}
```

Taking $K = 10$, here are the first five draws for $\alpha = 1$. For $\alpha = 1$, the distribution is uniform over simplexes.

```
1) 0.17 0.05 0.07 0.17 0.03 0.13 0.03 0.03 0.27 0.05  
2) 0.08 0.02 0.12 0.07 0.52 0.01 0.07 0.04 0.01 0.06  
3) 0.02 0.03 0.22 0.29 0.17 0.10 0.09 0.00 0.05 0.03  
4) 0.04 0.03 0.21 0.13 0.04 0.01 0.10 0.04 0.22 0.18  
5) 0.11 0.22 0.02 0.01 0.06 0.18 0.33 0.04 0.01 0.01
```


That does not mean it's uniform over the marginal probabilities of each element. As the size of the simplex grows, the marginal draws become more and more concentrated below (not around) $1/K$. When one component of the simplex is large, the others must all be relatively small to compensate. For example, in a uniform distribution on 10-simplexes, the probability that a component is greater than the mean of $1/10$ is only 39%. Most of the posterior marginal probability mass for each component is in the interval $(0, 0.1)$.

When the α value is small, the draws gravitate to the corners of the simplex. Here are the first five draws for $\alpha = 0.001$.

```
1) 3e-203 0e+00 2e-298 9e-106 1e+000 0e+00 0e+000 1e-047 0e+00 4e-279
2) 1e+000 0e+00 5e-279 2e-014 1e-275 0e+00 3e-285 9e-147 0e+00 0e+000
3) 1e-308 0e+00 1e-213 0e+000 0e+000 8e-75 0e+000 1e+000 4e-58 7e-112
4) 6e-166 5e-65 3e-068 3e-147 0e+000 1e+00 3e-249 0e+000 0e+00 0e+000
5) 2e-091 0e+00 0e+000 0e+000 1e-060 0e+00 4e-312 1e+000 0e+00 0e+000
```

Each row denotes a draw. Each draw has a single value that rounds to one and other values that are very close to zero or rounded down to zero.

As α increases, the draws become increasingly uniform. For $\alpha = 1000$,

```
1) 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10
2) 0.10 0.10 0.09 0.10 0.10 0.10 0.11 0.10 0.10 0.10
3) 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10
4) 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10
5) 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10
```

Distribution statement

theta ~ **dirichlet**(alpha)

Increment target log probability density with `dirichlet_lupdf(theta | alpha)`.

Available since 2.0

Stan functions

The Dirichlet probability functions are overloaded to allow the simplex θ and prior counts (plus one) α to be vectors or row vectors (or to mix the two types). The density functions are also vectorized, so they allow arrays of row vectors or vectors as arguments; see section [vectorized function signatures](#) for a description of vectorization.

real **dirichlet_lpdf**(vectors theta | vectors alpha)

The log of the Dirichlet density for simplex(es) theta given prior counts (plus one) alpha

Available since 2.12, vectorized in 2.21

real **dirichlet_lupdf**(vectors theta | vectors alpha)

The log of the Dirichlet density for simplex(es) theta given prior counts (plus one) alpha dropping constant additive terms

Available since 2.25

vector **dirichlet_rng**(vector alpha)

Generate a Dirichlet variate with prior counts (plus one) alpha; may only be used in transformed data and generated quantities blocks

Available since 2.0

27. Correlation Matrix Distributions

The correlation matrix distributions have support on the (Cholesky factors of) correlation matrices. A Cholesky factor L for a $K \times K$ correlation matrix Σ of dimension K has rows of unit length so that the diagonal of LL^\top is the unit K -vector. Even though models are usually conceptualized in terms of correlation matrices, it is better to operationalize them in terms of their Cholesky factors. If you are interested in the posterior distribution of the correlations, you can recover them in the generated quantities block via

```
generated quantities {  
  corr_matrix[K] Sigma;  
  Sigma = multiply_lower_tri_self_transpose(L);  
}
```

27.1. LKJ correlation distribution

Probability density function

For $\eta > 0$, if Σ a positive-definite, symmetric matrix with unit diagonal (i.e., a correlation matrix), then

$$\text{LkjCorr}(\Sigma|\eta) \propto \det(\Sigma)^{(\eta-1)}.$$

The expectation is the identity matrix for any positive value of the shape parameter η , which can be interpreted like the shape parameter of a symmetric beta distribution:

- if $\eta = 1$, then the density is uniform over correlation matrices of order K ;
- if $\eta > 1$, the identity matrix is the modal correlation matrix, with a sharper peak in the density at the identity matrix for larger η ; and
- for $0 < \eta < 1$, the density has a trough at the identity matrix.
- if η were an unknown parameter, the Jeffreys prior is proportional to $\sqrt{2 \sum_{k=1}^{K-1} \left(\psi_1 \left(\eta + \frac{K-k-1}{2} \right) - 2\psi_1(2\eta + K - k - 1) \right)}$, where $\psi_1(\cdot)$ is the trigamma function

See (Lewandowski, Kurowicka, and Joe 2009) for definitions. However, it is much

better computationally to work directly with the Cholesky factor of Σ , so this distribution should never be explicitly used in practice.

Distribution statement

$y \sim \text{lkj_corr}(\eta)$

Increment target log probability density with `lkj_corr_lupdf(y | eta)`.

Available since 2.3

Stan functions

`real lkj_corr_lpdf(matrix y | real eta)`

The log of the LKJ density for the correlation matrix y given nonnegative shape η . `lkj_corr_cholesky_lpdf` is faster, more numerically stable, uses less memory, and should be preferred to this.

Available since 2.12

`real lkj_corr_lupdf(matrix y | real eta)`

The log of the LKJ density for the correlation matrix y given nonnegative shape η dropping constant additive terms. `lkj_corr_cholesky_lupdf` is faster, more numerically stable, uses less memory, and should be preferred to this.

Available since 2.25

`matrix lkj_corr_rng(int K, real eta)`

Generate a LKJ random correlation matrix of order K with shape η ; may only be used in transformed data and generated quantities blocks

Available since 2.0

27.2. Cholesky LKJ correlation distribution

Stan provides an implicit parameterization of the LKJ correlation matrix density in terms of its Cholesky factor, which you should use rather than the explicit parameterization in the previous section. For example, if L is a Cholesky factor of a correlation matrix, then

```
L ~ lkj_corr_cholesky(2.0); # implies L * L' ~ lkj_corr(2.0);
```

Because Stan requires models to have support on all valid constrained parameters, L will almost always¹ be a parameter declared with the type of a Cholesky factor for a correlation matrix; for example,

¹It is possible to build up a valid L within Stan, but that would then require Jacobian adjustments to imply the intended posterior.

parameters { `cholesky_factor_corr`[K] L; # rather than `corr_matrix`[K]

Probability density function

For $\eta > 0$, if L is a $K \times K$ lower-triangular Cholesky factor of a symmetric positive-definite matrix with unit diagonal (i.e., a correlation matrix), then

$$\text{LkjCholesky}(L|\eta) \propto |J| \det(LL^\top)^{(\eta-1)} = \prod_{k=2}^K L_{kk}^{K-k+2\eta-2}.$$

See the previous section for details on interpreting the shape parameter η . Note that even if $\eta = 1$, it is still essential to evaluate the density function because the density of L is not constant, regardless of the value of η , even though the density of LL^\top is constant iff $\eta = 1$.

A lower triangular L is a Cholesky factor for a correlation matrix if and only if $L_{k,k} > 0$ for $k \in 1:K$ and each row L_k has unit Euclidean length.

Distribution statement

$L \sim \text{lkj_corr_cholesky}(\text{eta})$

Increment target log probability density with `lkj_corr_cholesky_lupdf(L | eta)`.

Available since 2.4

Stan functions

real `lkj_corr_cholesky_lpdf`(matrix L | real eta)

The log of the LKJ density for the lower-triangular Cholesky factor L of a correlation matrix given shape eta

Available since 2.12

real `lkj_corr_cholesky_lupdf`(matrix L | real eta)

The log of the LKJ density for the lower-triangular Cholesky factor L of a correlation matrix given shape eta dropping constant additive terms

Available since 2.25

matrix `lkj_corr_cholesky_rng`(int K, real eta)

Generate a random Cholesky factor of a correlation matrix of order K that is distributed LKJ with shape eta ; may only be used in transformed data and generated quantities blocks

Available since 2.4

28. Covariance Matrix Distributions

The covariance matrix distributions have support on symmetric, positive-definite $K \times K$ matrices or their Cholesky factors (square, lower triangular matrices with positive diagonal elements).

28.1. Wishart distribution

Probability density function

If $K \in \mathbb{N}$, $\nu \in (K - 1, \infty)$, and $S \in \mathbb{R}^{K \times K}$ is symmetric and positive definite, then for symmetric and positive-definite $W \in \mathbb{R}^{K \times K}$,

$$\text{Wishart}(W \mid \nu, S) = \frac{1}{2^{\nu K/2}} \frac{1}{\Gamma_K\left(\frac{\nu}{2}\right)} |S|^{-\nu/2} |W|^{(\nu-K-1)/2} \exp\left(-\frac{1}{2} \text{tr}(S^{-1}W)\right),$$

where $\text{tr}()$ is the matrix trace function, and $\Gamma_K()$ is the multivariate Gamma function,

$$\Gamma_K(x) = \frac{1}{\pi^{K(K-1)/4}} \prod_{k=1}^K \Gamma\left(x + \frac{1-k}{2}\right).$$

Distribution statement

$W \sim \text{wishart}(\text{nu}, \text{Sigma})$

Increment target log probability density with `wishart_lupdf(W | nu, Sigma)`.

Available since 2.0

Stan functions

`real wishart_lpdf(matrix W | real nu, matrix Sigma)`

Return the log of the Wishart density for symmetric and positive-definite matrix W given degrees of freedom nu and symmetric and positive-definite scale matrix Sigma .

Available since 2.12

`real wishart_lupdf(matrix W | real nu, matrix Sigma)`

Return the log of the Wishart density for symmetric and positive-definite matrix W given degrees of freedom nu and symmetric and positive-definite scale matrix Sigma dropping constant additive terms.

Available since 2.25

matrix `wishart_rng`(real nu, matrix Sigma)

Generate a Wishart variate with degrees of freedom nu and symmetric and positive-definite scale matrix Sigma; may only be used in transformed data and generated quantities blocks.

Available since 2.0

28.2. Wishart distribution, Cholesky Parameterization

The Cholesky parameterization of the Wishart distribution uses a Cholesky factor for both the variate and the parameter. If S and W are positive definite matrices with Cholesky factors L_S and L_W (i.e., $S = L_S L_S^\top$ and $W = L_W L_W^\top$), then the Cholesky parameterization is defined so that

$$L_W \sim \text{WishartCholesky}(\nu, L_S)$$

if and only if

$$W \sim \text{Wishart}(\nu, S).$$

Probability density function

If $K \in \mathbb{N}$, $\nu \in (K - 1, \infty)$, and $L_S, L_W \in \mathbb{R}^{K \times K}$ are lower triangular matrixes with positive diagonal elements, then the Cholesky parameterized Wishart density is

$$\text{WishartCholesky}(L_W \mid \nu, L_S) = \text{Wishart}(L_W L_W^\top \mid \nu, L_S L_S^\top) \left| J_{f^{-1}} \right|,$$

where $J_{f^{-1}}$ is the Jacobian of the (inverse) transform of the variate, $f^{-1}(L_W) = L_W L_W^\top$. The log absolute determinant is

$$\log \left| J_{f^{-1}} \right| = K \log(2) + \sum_{k=1}^K (K - k + 1) \log (L_W)_{k,k}.$$

The probability functions will raise errors if $\nu \leq K - 1$ or if L_S and L_W are not Cholesky factors (square, lower-triangular matrices with positive diagonal elements) of the same size.

Stan functions

real `wishart_cholesky_lpdf`(matrix L_W | real nu, matrix L_S)

Return the log of the Wishart density for lower-triangular Cholesky factor L_W given degrees of freedom nu and lower-triangular Cholesky factor of the scale matrix L_S.

Available since 2.30

real **wishart_cholesky_lupdf**(matrix L_W | real nu, matrix L_S)
Return the log of the Wishart density for lower-triangular Cholesky factor of L_W given degrees of freedom nu and lower-triangular Cholesky factor of the scale matrix L_S dropping constant additive terms.

Available since 2.30

matrix **wishart_cholesky_rng**(real nu, matrix L_S)
Generate the Cholesky factor of a Wishart variate with degrees of freedom nu and lower-triangular Cholesky factor of the scale matrix L_S; may only be used in transformed data and generated quantities blocks

Available since 2.30

28.3. Inverse Wishart distribution

Probability density function

If $K \in \mathbb{N}$, $\nu \in (K - 1, \infty)$, and $S \in \mathbb{R}^{K \times K}$ is symmetric and positive definite, then for symmetric and positive-definite $W \in \mathbb{R}^{K \times K}$,

$$\text{InvWishart}(W \mid \nu, S) = \frac{1}{2^{\nu K/2}} \frac{1}{\Gamma_K(\frac{\nu}{2})} |S|^{\nu/2} |W|^{-(\nu+K+1)/2} \exp\left(-\frac{1}{2} \text{tr}(SW^{-1})\right).$$

Distribution statement

$W \sim \text{inv_wishart}(\text{nu}, \text{Sigma})$

Increment target log probability density with `inv_wishart_lupdf(W | nu, Sigma)`.

Available since 2.0

Stan functions

real **inv_wishart_lpdf**(matrix W | real nu, matrix Sigma)
Return the log of the inverse Wishart density for symmetric and positive-definite matrix W given degrees of freedom nu and symmetric and positive-definite scale matrix Sigma.

Available since 2.12

real **inv_wishart_lupdf**(matrix W | real nu, matrix Sigma)
Return the log of the inverse Wishart density for symmetric and positive-definite

matrix W given degrees of freedom ν and symmetric and positive-definite scale matrix Σ dropping constant additive terms.

Available since 2.25

matrix `inv_wishart_rng`(real ν , matrix Σ)

Generate an inverse Wishart variate with degrees of freedom ν and symmetric and positive-definite scale matrix Σ ; may only be used in transformed data and generated quantities blocks.

Available since 2.0

28.4. Inverse Wishart distribution, Cholesky Parameterization

The Cholesky parameterization of the inverse Wishart distribution uses a Cholesky factor for both the variate and the parameter. If S and W are positive definite matrices with Cholesky factors L_S and L_W (i.e., $S = L_S L_S^\top$ and $W = L_W L_W^\top$), then the Cholesky parameterization is defined so that

$$L_W \sim \text{InvWishartCholesky}(\nu, L_S)$$

if and only if

$$W \sim \text{InvWishart}(\nu, S).$$

Probability density function

If $K \in \mathbb{N}$, $\nu \in (K - 1, \infty)$, and $L_S, L_W \in \mathbb{R}^{K \times K}$ are lower triangular matrixes with positive diagonal elements, then the Cholesky parameterized inverse Wishart density is

$$\text{InvWishartCholesky}(L_W \mid \nu, L_S) = \text{InvWishart}(L_W L_W^\top \mid \nu, L_S L_S^\top) \left| J_{f^{-1}} \right|,$$

where $J_{f^{-1}}$ is the Jacobian of the (inverse) transform of the variate, $f^{-1}(L_W) = L_W L_W^\top$. The log absolute determinant is

$$\log \left| J_{f^{-1}} \right| = K \log(2) + \sum_{k=1}^K (K - k + 1) \log (L_W)_{k,k}.$$

The probability functions will raise errors if $\nu \leq K - 1$ or if L_S and L_W are not Cholesky factors (square, lower-triangular matrices with positive diagonal elements) of the same size.

Stan functions

real **inv_wishart_cholesky_lpdf**(matrix L_W | real nu, matrix L_S)

Return the log of the inverse Wishart density for lower-triangular Cholesky factor L_W given degrees of freedom nu and lower-triangular Cholesky factor of the scale matrix L_S.

Available since 2.30

real **inv_wishart_cholesky_lupdf**(matrix L_W | real nu, matrix L_S)

Return the log of the inverse Wishart density for lower-triangular Cholesky factor of L_W given degrees of freedom nu and lower-triangular Cholesky factor of the scale matrix L_S dropping constant additive terms.

Available since 2.30

matrix **inv_wishart_cholesky_rng**(real nu, matrix L_S)

Generate the Cholesky factor of an inverse Wishart variate with degrees of freedom nu and lower-triangular Cholesky factor of the scale matrix L_S; may only be used in transformed data and generated quantities blocks.

Available since 2.30

Part IV

Additional Distributions

29. Hidden Markov Models

An elementary first-order Hidden Markov model is a probabilistic model over N observations, y_n , and N hidden states, x_n , which can be fully defined by the conditional distributions $p(y_n | x_n, \phi)$ and $p(x_n | x_{n-1}, \phi)$. Here we make the dependency on additional model parameters, ϕ , explicit. When x is continuous, the user can explicitly encode these distributions in Stan and use Markov chain Monte Carlo to integrate x out.

When each state x takes a value over a discrete and finite set, say $\{1, 2, \dots, K\}$, we can take advantage of the dependency structure to marginalize x and compute $p(y | \phi)$. We start by defining the conditional observational distribution, stored in a $K \times N$ matrix ω with

$$\omega_{kn} = p(y_n | x_n = k, \phi).$$

Next, we introduce the $K \times K$ transition matrix, Γ , with

$$\Gamma_{ij} = p(x_n = j | x_{n-1} = i, \phi).$$

Each row defines a probability distribution and must therefore be a simplex (i.e. its components must add to 1). Currently, Stan only supports stationary transitions where a single transition matrix is used for all transitions. Finally we define the initial state K -vector ρ , with

$$\rho_k = p(x_0 = k | \phi).$$

The Stan functions that support this type of model are special in that the user does not explicitly pass y and ϕ as arguments. Instead, the user passes $\log \omega$, Γ , and ρ , which in turn depend on y and ϕ .

29.1. Stan functions

`real hmm_marginal(matrix log_omega, matrix Gamma, vector rho)`

Returns the log probability density of y , with x_n integrated out at each iteration.

Available since 2.24

The arguments represent (1) the log density of each output, (2) the transition matrix, and (3) the initial state vector.

- `log_omega`: $\log \omega_{kn} = \log p(y_n | x_n = k, \phi)$, log density of each output,

- *Gamma*: $\Gamma_{ij} = p(x_n = j | x_{n-1} = i, \phi)$, the transition matrix,
- *rho*: $\rho_k = p(x_0 = k | \phi)$, the initial state probability.

array[] int **hmm_latent_rng**(matrix log_omega, matrix Gamma, vector rho)

Returns a length N array of integers over $\{1, \dots, K\}$, sampled from the joint posterior distribution of the hidden states, $p(x | \phi, y)$. May be only used in transformed data and generated quantities.

Available since 2.24

matrix **hmm_hidden_state_prob**(matrix log_omega, matrix Gamma, vector rho)

Returns the matrix of marginal posterior probabilities of each hidden state value. This will be a $K \times N$ matrix. The n^{th} column is a simplex of probabilities for the n^{th} variable. Moreover, let A be the output. Then $A_{ij} = p(x_j = i | \phi, y)$. This function may only be used in transformed data and generated quantities.

Available since 2.24

Part V

Appendix

30. Mathematical Functions

This appendix provides the definition of several mathematical functions used throughout the manual.

30.1. Beta

The beta function, $B(a, b)$, computes the normalizing constant for the beta distribution, and is defined for $a > 0$ and $b > 0$ by

$$B(a, b) = \int_0^1 u^{a-1} (1-u)^{b-1} du = \frac{\Gamma(a)\Gamma(b)}{\Gamma(a+b)},$$

where $\Gamma(x)$ is the [Gamma function](#).

30.2. Incomplete beta

The incomplete beta function, $B(x; a, b)$, is defined for $x \in [0, 1]$ and $a, b \geq 0$ such that $a + b \neq 0$ by

$$B(x; a, b) = \int_0^x u^{a-1} (1-u)^{b-1} du,$$

where $B(a, b)$ is the beta function defined in [appendix](#). If $x = 1$, the incomplete beta function reduces to the beta function, $B(1; a, b) = B(a, b)$.

The regularized incomplete beta function divides the incomplete beta function by the beta function,

$$I_x(a, b) = \frac{B(x; a, b)}{B(a, b)}.$$

30.3. Gamma

The gamma function, $\Gamma(x)$, is the generalization of the factorial function to continuous variables, defined so that for positive integers n ,

$$\Gamma(n+1) = n!$$

Generalizing to all positive numbers and non-integer negative numbers,

$$\Gamma(x) = \int_0^\infty u^{x-1} \exp(-u) du.$$

30.4. Digamma

The digamma function Ψ is the derivative of the $\log \Gamma$ function,

$$\Psi(u) = \frac{d}{du} \log \Gamma(u) = \frac{1}{\Gamma(u)} \frac{d}{du} \Gamma(u).$$

References

- Bailey, David H., Karthik Jeyabalan, and Xiaoye S. Li. 2005. "A Comparison of Three High-Precision Quadrature Schemes." *Experiment. Math.* 14 (3): 317–29. <https://projecteuclid.org:443/euclid.em/1128371757>.
- Bowling, Shannon R., Mohammad T. Khasawneh, Sittichai Kaewkuekool, and Byung Rae Cho. 2009. "A Logistic Approximation to the Cumulative Normal Distribution." *Journal of Industrial Engineering and Management* 2 (1): 114–27.
- Ding, Peng, and Joseph K. Blitzstein. 2018. "On the Gaussian Mixture Representation of the Laplace Distribution." *The American Statistician* 72 (2): 172–74. <https://doi.org/10.1080/00031305.2017.1291448>.
- Durbin, J., and S. J. Koopman. 2001. *Time Series Analysis by State Space Methods*. New York: Oxford University Press.
- Feller, William. 1968. *An Introduction to Probability Theory and Its Applications*. Vol. 1. 3. Wiley, New York.
- Gaebler, Johann D. 2021. "Autodiff for Implicit Functions in Stan." <https://www.jg.aeb.com/2021/09/13/implicit-autodiff.html#fn:7>.
- Gelman, Andrew, J. B. Carlin, Hal S. Stern, David B. Dunson, Aki Vehtari, and Donald B. Rubin. 2013. *Bayesian Data Analysis*. Third Edition. London: Chapman & Hall / CRC Press.
- Golub, G. H., and V. Pereyra. 1973. "The Differentiation of Pseudo-Inverses and Nonlinear Least Squares Problems Whose Variables Separate." *SIAM Journal on Numerical Analysis* 10 (2): 413–32. <https://doi.org/10.1137/0710036>.
- Guennebaud, Gaël, Benoît Jacob, et al. 2010. "Eigen V3." <http://eigen.tuxfamily.org>.
- Hindmarsh, Alan C, Peter N Brown, Keith E Grant, Steven L Lee, Radu Serban, Dan E Shumaker, and Carol S Woodward. 2005. "SUNDIALS: Suite of Nonlinear and Differential/Algebraic Equation Solvers." *ACM Transactions on Mathematical Software (TOMS)* 31 (3): 363–96.
- Jorge J. More, Kenneth E. Hillstrom, Burton S. Garbow. 1980. *User Guide for MINPACK-1*. 9700 South Cass Avenue, Argonne, Illinois 60439: Argonne National Laboratory.
- Lewandowski, Daniel, Dorota Kurowicka, and Harry Joe. 2009. "Generating Random Correlation Matrices Based on Vines and Extended Onion Method." *Journal of Multivariate Analysis* 100: 1989–2001.
- Margossian, Charles C, and Michael Betancourt. 2022. "Efficient Automatic Differ-

- entiation of Implicit Functions." *Preprint. arXiv:2112.14217*.
- Mori, Masatake. 1978. "An IMT-Type Double Exponential Formula for Numerical Integration." *Publications of the Research Institute for Mathematical Sciences* 14 (3): 713–29. <https://doi.org/10.2977/prims/1195188835>.
- Navarro, Danielle J, and Ian G Fuss. 2009. "Fast and Accurate Calculations for First-Passage Times in Wiener Diffusion Models." *Journal of Mathematical Psychology* 53 (4): 222–30.
- Powell, Michael J. D. 1970. "A Hybrid Method for Nonlinear Equations." In *Numerical Methods for Nonlinear Algebraic Equations*, edited by P. Rabinowitz. Gordon; Breach.
- Serban, Radu, Cosmin Petra, Alan C. Hindmarsh, Cody J. Balos, David J. Gardner, Daniel R. Reynolds, and Carol S. Woodward. 2021. "User Documentation for IDAS V5.0.0." Lawrence Livermore National Laboratory.
- Takahasi, Hidetosi, and Masatake Mori. 1974. "Double Exponential Formulas for Numerical Integration." *Publications of the Research Institute for Mathematical Sciences* 9 (3): 721–41. <https://doi.org/10.2977/prims/1195192451>.
- Tanaka, Ken'ichiro, Masaaki Sugihara, Kazuo Murota, and Masatake Mori. 2009. "Function Classes for Double Exponential Integration Formulas." *Numerische Mathematik* 111 (4): 631–55. <https://doi.org/10.1007/s00211-008-0195-1>.
- Vandekerckhove, Joachim, and Dominik Wabersich. 2014. "The RWiener Package: An R Package Providing Distribution Functions for the Wiener Diffusion Model." *The R Journal* 6/1. <http://journal.r-project.org/archive/2014-1/vandekerckhove-wabersich.pdf>.
- Wichura, Michael J. 1988. "Algorithm AS 241: The Percentage Points of the Normal Distribution." *Journal of the Royal Statistical Society. Series C (Applied Statistics)* 37 (3): 477–84. <http://www.jstor.org/stable/2347330>.

Index

abs

(T x): T, 8, 24
(complex z): real, 46

acos

(T x): R, 28
(complex z): complex, 49

acosh

(T x): R, 29
(complex z): complex, 50

add_diag

(complex_matrix m, complex d):
complex_matrix, 117
(complex_matrix m, complex_row_vector d): complex_matrix, 117
(complex_matrix m, complex_vector d): complex_matrix, 117
(matrix m, real d): matrix, 78
(matrix m, row_vector d): matrix, 78
(matrix m, vector d): matrix, 78

algebra_solver

(function algebra_system, vector y_guess, vector theta, data array[] real x_r, array[] int x_i, data real rel_tol, data real f_tol, int max_steps): vector, 160

algebra_solver_newton

(function algebra_system, vector y_guess, vector theta, data array[] real x_r, array[] int x_i): vector, 160
(function algebra_system, vector y_guess, vector theta, data array[] real x_r, array[] int x_i, data real rel_tol, data real f_tol, int max_steps): vector, 160

append_array

(T x, T y): T, 59

append_col

(complex x, complex_row_vector y): complex_row_vector, 119
(complex_matrix x, complex_matrix y): complex_matrix, 119
(complex_matrix x, complex_vector

y): complex_matrix, 119
(complex_row_vector x, complex y): complex_row_vector, 120
(complex_row_vector x, complex_row_vector y): complex_row_vector, 119
(complex_vector x, complex_matrix y): complex_matrix, 119
(complex_vector x, complex_vector y): complex_matrix, 119
(matrix x, matrix y): matrix, 83
(matrix x, vector y): matrix, 83
(real x, row_vector y): row_vector, 84
(row_vector x, real y): row_vector, 84
(row_vector x, row_vector y): row_vector, 84
(vector x, matrix y): matrix, 83
(vector x, vector y): matrix, 83

append_row

(complex x, complex_vector y): complex_vector, 120
(complex_matrix x, complex_matrix y): complex_matrix, 120
(complex_matrix x, complex_row_vector y): complex_matrix, 120
(complex_row_vector x, complex_matrix y): complex_matrix, 120
(complex_row_vector x, complex_row_vector y): complex_matrix, 120
(complex_vector x, complex y): complex_vector, 120
(complex_vector x, complex_vector y): complex_vector, 120
(matrix x, matrix y): matrix, 84
(matrix x, row_vector y): matrix, 84
(real x, vector y): vector, 85
(row_vector x, matrix y): matrix, 84
(row_vector x, row_vector y): matrix, 84
(vector x, real y): vector, 85
(vector x, vector y): vector, 84

arg
(complex z): real, [47](#)

asin
(T x): R, [28](#)
(complex z): complex, [49](#)

asinh
(T x): R, [29](#)
(complex z): complex, [51](#)

atan
(T x): R, [28](#)
(complex z): complex, [50](#)

atan2
(T y, T x): R, [28](#)

atanh
(T x): R, [29](#)
(complex z): complex, [51](#)

bernoulli
sampling statement, [172](#)

bernoulli_cdf
(ints y | reals theta): real, [172](#)

bernoulli_lccdf
(ints y | reals theta): real, [172](#)

bernoulli_lcdf
(ints y | reals theta): real, [172](#)

bernoulli_logit
sampling statement, [173](#)

bernoulli_logit_glm
sampling statement, [174](#)

bernoulli_logit_glm_lpmf
(array[] int y | matrix x, real alpha, vector beta): real, [175](#)
(array[] int y | matrix x, vector alpha, vector beta): real, [176](#)
(array[] int y | row_vector x, real alpha, vector beta): real, [175](#)
(array[] int y | row_vector x, vector alpha, vector beta): real, [175](#)
(int y | matrix x, real alpha, vector beta): real, [174](#)
(int y | matrix x, vector alpha, vector beta): real, [175](#)

bernoulli_logit_glm_lupmf
(array[] int y | matrix x, real alpha, vector beta): real, [176](#)
(array[] int y | matrix x, vector alpha, vector beta): real, [176](#)
(array[] int y | row_vector x, real alpha, vector beta): real, [175](#)

(array[] int y | row_vector x, vector alpha, vector beta): real, [175](#)
(int y | matrix x, real alpha, vector beta): real, [174](#)
(int y | matrix x, vector alpha, vector beta): real, [174](#)

bernoulli_logit_glm_rng
(matrix x, vector alpha, vector beta): array[] int, [176](#)
(row_vector x, vector alpha, vector beta): array[] int, [176](#)

bernoulli_logit_lpmf
(ints y | reals alpha): real, [173](#)

bernoulli_logit_lupmf
(ints y | reals alpha): real, [173](#)

bernoulli_logit_rng
(reals alpha): R, [174](#)

bernoulli_lpmf
(ints y | reals theta): real, [172](#)

bernoulli_lupmf
(ints y | reals theta): real, [172](#)

bernoulli_rng
(reals theta): R, [173](#)

bessel_first_kind
(T1 x, T2 y): R, [34](#)
(int v, real x): real, [34](#)

bessel_second_kind
(T1 x, T2 y): R, [35](#)
(int v, real x): real, [35](#)

beta
(T1 x, T2 y): R, [31](#)
(real alpha, real beta): real, [31](#)
sampling statement, [249](#)

beta_binomial
sampling statement, [182](#)

beta_binomial_cdf
(ints n | ints N, reals alpha, reals beta): real, [183](#)

beta_binomial_lccdf
(ints n | ints N, reals alpha, reals beta): real, [183](#)

beta_binomial_lcdf
(ints n | ints N, reals alpha, reals beta): real, [183](#)

beta_binomial_lpmf
(ints n | ints N, reals alpha, reals beta): real, [182](#)

beta_binomial_lupmf

(ints n | ints N, reals alpha, reals beta): real, 182

beta_binomial_rng
(ints N, reals alpha, reals beta): R, 183

beta_cdf
(reals theta | reals alpha, reals beta): real, 249

beta_lccdf
(reals theta | reals alpha, reals beta): real, 250

beta_lcdf
(reals theta | reals alpha, reals beta): real, 250

beta_lpdf
(reals theta | reals alpha, reals beta): real, 249

beta_lupdf
(reals theta | reals alpha, reals beta): real, 249

beta_neg_binomial
sampling statement, 204

beta_neg_binomial_cdf
(ints n | reals r, reals alpha, reals beta): real, 205

beta_neg_binomial_lccdf
(ints n | reals r, reals alpha, reals beta): real, 205

beta_neg_binomial_lcdf
(ints n | reals r, reals alpha, reals beta): real, 205

beta_neg_binomial_lpmf
(ints n | reals r, reals alpha, reals beta): real, 205

beta_neg_binomial_lupmf
(ints n | reals r, reals alpha, reals beta): real, 205

beta_neg_binomial_rng
(reals r, reals alpha, reals beta): R, 205

beta_proportion
sampling statement, 250

beta_proportion_lccdf
(reals theta | reals mu, reals kappa): real, 251

beta_proportion_lcdf
(reals theta | reals mu, reals kappa): real, 251

beta_proportion_lpdf
(reals theta | reals mu, reals kappa): real, 251

beta_proportion_lupdf
(reals theta | reals mu, reals kappa): real, 251

beta_proportion_rng
(reals mu, reals kappa): R, 251

beta_rng
(reals alpha, reals beta): R, 250

binary_log_loss
(T1 x, T2 y): R, 31
(int y, real y_hat): real, 31

binomia_cdf
(ints n | ints N, reals theta): real, 178

binomia_lccdf
(ints n | ints N, reals theta): real, 178

binomia_lcdf
(ints n | ints N, reals theta): real, 178

binomia_lpmf
(ints n | ints N, reals theta): real, 177

binomia_lupmf
(ints n | ints N, reals theta): real, 177

binomial
sampling statement, 177

binomial_logit
sampling statement, 179

binomial_logit_glm
sampling statement, 180

binomial_logit_glm_lpmf
(array[] int n | array[] int N, matrix x, real alpha, vector beta): real, 181
(array[] int n | array[] int N, matrix x, vector alpha, vector beta): real, 181
(array[] int n | array[] int N, row_vector x, real alpha, vector beta): real, 180
(array[] int n | array[] int N, row_vector x, vector alpha, vector beta): real, 181
(int n | int N, matrix x, real alpha, vector beta): real, 180
(int n | int N, matrix x, vector

alpha, vector beta): real,180

binomial_logit_glm_lupmf
(array[] int n | array[] int N,
matrix x, real alpha, vector
beta): real,181
(array[] int n | array[] int N,
matrix x, vector alpha, vector
beta): real,182
(array[] int n | array[] int N,
row_vector x, real alpha, vec-
tor beta): real,181
(array[] int n | array[] int N,
row_vector x, vector alpha,
vector beta): real,181
(int n | int N, matrix x, real
alpha, vector beta): real,180
(int n | int N, matrix x, vector
alpha, vector beta): real,180

binomial_logit_lpmf
(ints n | ints N, reals alpha):
real,179

binomial_logit_lupmf
(ints n | ints N, reals alpha):
real,179

binomial_rng
(ints N, reals theta): R,178

block
(complex_matrix x, int i, int j,
int n_rows, int n_cols): com-
plex_matrix,118
(matrix x, int i, int j, int n_rows,
int n_cols): matrix,81

categorical
sampling statement, 184

categorical_logit
sampling statement, 185

categorical_logit_glm
sampling statement, 186

categorical_logit_glm_lupmf
(array[] int y | matrix x, vector
alpha, matrix beta): real,187
(array[] int y | row_vector x, vec-
tor alpha, matrix beta): real,
187
(int y | matrix x, vector alpha,
matrix beta): real,187
(int y | row_vector x, vector alpha,
matrix beta): real,186

categorical_logit_glm_lupmf
(array[] int y | matrix x, vector
alpha, matrix beta): real,187
(array[] int y | row_vector x, vec-
tor alpha, matrix beta): real,
187
(int y | matrix x, vector alpha,
matrix beta): real,187
(int y | row_vector x, vector alpha,
matrix beta): real,186

categorical_logit_lupmf
(ints y | vector beta): real,185

categorical_logit_rng
(vector beta): int,185

categorical_lupmf
(ints y | vector theta): real,185

categorical_lupmf
(ints y | vector theta): real,185

categorical_rng
(vector theta): int,185

cauchy
sampling statement, 223

cauchy_cdf
(reals y | reals mu, reals sigma):
real,223

cauchy_lccdf
(reals y | reals mu, reals sigma):
real,223

cauchy_lcdf
(reals y | reals mu, reals sigma):
real,223

cauchy_lpdf
(reals y | reals mu, reals sigma):
real,223

cauchy_lupdf
(reals y | reals mu, reals sigma):
real,223

cauchy_rng
(reals mu, reals sigma): R,223

cbrt
(T x): R,26

ceil
(T x): R,26

chi_square
sampling statement, 231

chi_square_cdf
(reals y | reals nu): real,231

chi_square_lccdf

(reals y | reals nu): real, 232

chi_square_lcdf
(reals y | reals nu): real, 231

chi_square_lpdf
(reals y | reals nu): real, 231

chi_square_lupdf
(reals y | reals nu): real, 231

chi_square_rng
(reals nu): R, 232

chol2inv
(matrix L): matrix, 97

cholesky_decompose
(matrix A): matrix, 100

choose
(T1 x, T2 y): R, 34
(int x, int y): int, 34

col
(complex_matrix x, int n): complex_vector, 117
(matrix x, int n): vector, 81

cols
(complex_matrix x): int, 105
(complex_row_vector x): int, 104
(complex_vector x): int, 104
(matrix x): int, 62
(row_vector x): int, 62
(vector x): int, 62

columns_dot_product
(complex_matrix x, complex_matrix y): complex_row_vector, 112
(complex_row_vector x, complex_row_vector y): complex_row_vector, 112
(complex_vector x, complex_vector y): complex_row_vector, 112
(matrix x, matrix y): row_vector, 70
(row_vector x, row_vector y): row_vector, 70
(vector x, vector y): row_vector, 70

columns_dot_self
(complex_matrix x): complex_row_vector, 113
(complex_row_vector x): complex_row_vector, 113
(complex_vector x): complex_row_vector, 113
(matrix x): row_vector, 71
(row_vector x): row_vector, 71
(vector x): row_vector, 71

complex_schur_decompose
(complex_matrix A): tuple(complex_matrix, complex_matrix), 126
(matrix A): tuple(complex_matrix, complex_matrix), 125

complex_schur_decompose_t
(complex_matrix A): complex_matrix, 125
(matrix A): complex_matrix, 125

complex_schur_decompose_u
(complex_matrix A): complex_matrix, 125
(matrix A): complex_matrix, 125

conj
(Z z): Z, 47
(complex z): complex, 47

cos
(T x): R, 28
(complex z): complex, 49

cosh
(T x): R, 29
(complex z): complex, 50

cov_exp_quad
(array[] real x, real alpha, real rho): matrix, 163
(array[] real x1, array[] real x2, real alpha, real rho): matrix, 163
(row_vectors x, real alpha, real rho): matrix, 162
(row_vectors x1, row_vectors x2, real alpha, real rho): matrix, 163
(vectors x, real alpha, real rho): matrix, 163
(vectors x1, vectors x2, real alpha, real rho): matrix, 163

crossprod
(matrix x): matrix, 71

csr_extract
(matrix a): tuple(vector, array[] int, array[] int), 128

csr_extract_u
(matrix a): array[] int, 128

csr_extract_v
(matrix a): array[] int, 128

csr_extract_w
(matrix a): vector, 128

csr_matrix_times_vector

(int m, int n, vector w, array[] int v, array[] int u, vector b): vector, [129](#)

csr_to_dense_matrix

(int m, int n, vector w, array[] int v, array[] int u): matrix, [129](#)

cumulative_sum

(array[] complex x): array[] real, [122](#)

(array[] int x): array[] int, [86](#)

(array[] real x): array[] real, [86](#)

(complex_row_vector rv): complex_row_vector, [122](#)

(complex_vector v): complex_vector, [122](#)

(row_vector rv): row_vector, [86](#)

(vector v): vector, [86](#)

dae

(function residual, vector initial_state, vector initial_state_derivative, data real initial_time, data array[] real times, ...): array[] vector, [148](#)

dae_tol

(function residual, vector initial_state, vector initial_state_derivative, data real initial_time, data array[] real times, data real rel_tol, data real abs_tol, int max_num_steps, ...): array[] vector, [148](#)

determinant

(matrix A): real, [96](#)

diag_matrix

(complex_vector x): complex_matrix, [117](#)

(vector x): matrix, [78](#)

diag_post_multiply

(complex_matrix m, complex_row_vector v): complex_matrix, [114](#)

(complex_matrix m, complex_vector v): complex_matrix, [114](#)

(matrix m, row_vector rv): matrix, [73](#)

(matrix m, vector v): matrix, [73](#)

diag_pre_multiply

(complex_row_vector v, complex_matrix m): complex_matrix, [114](#)

(complex_vector v, complex_matrix m): complex_matrix, [114](#)

(row_vector rv, matrix m): matrix, [73](#)

(vector v, matrix m): matrix, [73](#)

diagonal

(complex_matrix x): complex_vector, [117](#)

(matrix x): vector, [78](#)

digamma

(T x): R, [32](#)

dims

(T x): array[] int, [57](#)

dirichlet

sampling statement, [272](#)

dirichlet_lpdf

(vectors theta | vectors alpha): real, [272](#)

dirichlet_lupdf

(vectors theta | vectors alpha): real, [273](#)

dirichlet_multinomial

sampling statement, [208](#)

dirichlet_multinomial_lpmf

(array[] int y | vector alpha): real, [208](#)

dirichlet_multinomial_lupmf

(array[] int y | vector alpha): real, [208](#)

dirichlet_multinomial_rng

(vector alpha, int N): array[] int, [209](#)

dirichlet_rng

(vector alpha): vector, [273](#)

discrete_range

sampling statement, [188](#)

discrete_range_cdf

(ints n | ints N, reals theta): real, [188](#)

discrete_range_lccdf

(ints n | ints N, reals theta): real, [189](#)

discrete_range_lcdf

(ints n | ints N, reals theta): real, [188](#)

discrete_range_lpmf
 (ints y | ints l, ints u): real, 188

discrete_range_lupmf
 (ints y | ints l, ints u): real, 188

discrete_range_rng
 (ints l, ints u): ints, 189

distance
 (row_vector x, row_vector y): real, 55
 (row_vector x, vector y): real, 55
 (vector x, row_vector y): real, 55
 (vector x, vector y): real, 55

dot_product
 (complex_row_vector x, complex_row_vector y): complex, 112
 (complex_row_vector x, complex_vector y): complex, 112
 (complex_vector x, complex_row_vector y): complex, 112
 (complex_vector x, complex_vector y): complex, 112
 (row_vector x, row_vector y): real, 70
 (row_vector x, vector y): real, 70
 (vector x, row_vector y): real, 70
 (vector x, vector y): real, 70

dot_self
 (complex_row_vector x): complex, 113
 (complex_vector x): complex, 113
 (row_vector x): real, 71
 (vector x): real, 71

double_exponential
 sampling statement, 224

double_exponential_cdf
 (reals y | reals mu, reals sigma): real, 225

double_exponential_lccdf
 (reals y | reals mu, reals sigma): real, 225

double_exponential_lcdf
 (reals y | reals mu, reals sigma): real, 225

double_exponential_lpdf
 (reals y | reals mu, reals sigma): real, 225

double_exponential_lupdf
 (reals y | reals mu, reals sigma): real, 225

double_exponential_rng
 (reals mu, reals sigma): R, 225

e
 (): real, 16

eigendecompose
 (complex_matrix A): tuple(complex_matrix, complex_vector), 123
 (matrix A): tuple(complex_matrix, complex_vector), 98

eigendecompose_sym
 (complex_matrix A): tuple(complex_matrix, complex_vector), 123
 (matrix A): tuple(matrix, vector), 98

eigenvalues
 (complex_matrix A): complex_vector, 123
 (matrix A): complex_vector, 98

eigenvalues_sym
 (complex_matrix A): complex_vector, 123
 (matrix A): vector, 98

eigenvectors
 (complex_matrix A): complex_matrix, 123
 (matrix A): complex_matrix, 98

eigenvectors_sym
 (complex_matrix A): complex_matrix, 123
 (matrix A): matrix, 98

erf
 (T x): R, 30

erfc
 (T x): R, 30

exp
 (T x): R, 26
 (complex z): complex, 48

exp2
 (T x): R, 26

exp_mod_normal
 sampling statement, 219

exp_mod_normal_cdf
 (reals y | reals mu, reals sigma, reals lambda): real, 219

exp_mod_normal_lccdf
 (reals y | reals mu, reals sigma, reals lambda): real, 219

exp_mod_normal_lcdf
 (reals y | reals mu, reals sigma,
 reals lambda): real, 219

exp_mod_normal_lpdf
 (reals y | reals mu, reals sigma,
 reals lambda): real, 219

exp_mod_normal_lupdf
 (reals y | reals mu, reals sigma,
 reals lambda): real, 219

exp_mod_normal_rng
 (reals mu, reals sigma, reals
 lambda): R, 220

expm1
 (T x): R, 38

exponential
 sampling statement, 234

exponential_cdf
 (reals y | reals beta): real, 235

exponential_lccdf
 (reals y | reals beta): real, 235

exponential_lcdf
 (reals y | reals beta): real, 235

exponential_lpdf
 (reals y | reals beta): real, 235

exponential_lupdf
 (reals y | reals beta): real, 235

exponential_rng
 (reals beta): R, 235

falling_factorial
 (T1 x, T2 y): R, 36
 (real x, real n): real, 36

fatal_error
 (T1 x1, ..., TN xN): void, 5

fdim
 (T1 x, T2 y): R, 24
 (real x, real y): real, 24

fft
 (complex_vector v): complex_vector,
 121

fft2
 (complex_matrix m): complex_matrix,
 121

floor
 (T x): R, 25

fma
 (real x, real y, real z): real, 38

fmax
 (T1 x, T2 y): R, 25
 (real x, real y): real, 25

fmin
 (T1 x, T2 y): R, 24
 (real x, real y): real, 24

fmod
 (T1 x, T2 y): R, 25
 (real x, real y): real, 25

frechet
 sampling statement, 239

frechet_cdf
 (reals y | reals alpha, reals
 sigma): real, 239

frechet_lccdf
 (reals y | reals alpha, reals
 sigma): real, 240

frechet_lcdf
 (reals y | reals alpha, reals
 sigma): real, 240

frechet_lpdf
 (reals y | reals alpha, reals
 sigma): real, 239

frechet_lupdf
 (reals y | reals alpha, reals
 sigma): real, 239

frechet_rng
 (reals alpha, reals sigma): R, 240

gamma
 sampling statement, 236

gamma_cdf
 (reals y | reals alpha, reals beta):
 real, 236

gamma_lccdf
 (reals y | reals alpha, reals beta):
 real, 236

gamma_lcdf
 (reals y | reals alpha, reals beta):
 real, 236

gamma_lpdf
 (reals y | reals alpha, reals beta):
 real, 236

gamma_lupdf
 (reals y | reals alpha, reals beta):
 real, 236

gamma_p
 (T1 x, T2 y): R, 33
 (real a, real z): real, 33

gamma_q
 (T1 x, T2 y): R, 34
 (real a, real z): real, 33

gamma_rng

(reals alpha, reals beta): R,236

gaussian_dlm_obs
sampling statement,269

gaussian_dlm_obs_lpdf
(matrix y | matrix F, matrix G,
matrix V, matrix W, vector m0,
matrix C0): real,269
(matrix y | matrix F, matrix G,
vector V, matrix W, vector m0,
matrix C0): real,270

gaussian_dlm_obs_lupdf
(matrix y | matrix F, matrix G,
matrix V, matrix W, vector m0,
matrix C0): real,269
(matrix y | matrix F, matrix G,
vector V, matrix W, vector m0,
matrix C0): real,270

generalized_inverse
(matrix A): matrix,98

get_imag
(T x): T_demoted,116
(complex z): real,43

get_real
(T x): T_demoted,116
(complex z): real,43

gp_dot_prod_cov
(array[] real x, real sigma): ma-
trix,88
(array[] real x1, array[] real x2,
real sigma): matrix,88
(vectors x, real sigma): matrix,88
(vectors x1, vectors x2, real
sigma): matrix,88

gp_exp_quad_cov
(array[] real x, real sigma, real
length_scale): matrix,87
(array[] real x1, array[] real x2,
real sigma, real length_scale):
matrix,87
(vectors x, real sigma, array[] real
length_scale): matrix,87
(vectors x, real sigma, real
length_scale): matrix,87
(vectors x1, vectors x2, real sigma,
array[] real length_scale):
matrix,87
(vectors x1, vectors x2, real sigma,
real length_scale): matrix,87

gp_exponential_cov
(array[] real x, real sigma, real
length_scale): matrix,89
(array[] real x1, array[] real x2,
real sigma, real length_scale):
matrix,89
(vectors x, real sigma, array[] real
length_scale): matrix,89
(vectors x, real sigma, real
length_scale): matrix,89
(vectors x1, vectors x2, real sigma,
array[] real length_scale):
matrix,90
(vectors x1, vectors x2, real sigma,
real length_scale): matrix,89

gp_matern32_cov
(array[] real x, real sigma, real
length_scale): matrix,90
(array[] real x1, array[] real x2,
real sigma, real length_scale):
matrix,90
(vectors x, real sigma, array[] real
length_scale): matrix,90
(vectors x, real sigma, real
length_scale): matrix,90
(vectors x1, vectors x2, real sigma,
array[] real length_scale):
matrix,91
(vectors x1, vectors x2, real sigma,
real length_scale): matrix,91

gp_matern52_cov
(array[] real x, real sigma, real
length_scale): matrix,91
(array[] real x1, array[] real x2,
real sigma, real length_scale):
matrix,91
(vectors x, real sigma, array[] real
length_scale): matrix,92
(vectors x, real sigma, real
length_scale): matrix,91
(vectors x1, vectors x2, real sigma,
array[] real length_scale):
matrix,92
(vectors x1, vectors x2, real sigma,
real length_scale): matrix,92

gp_periodic_cov
(array[] real x, real sigma, real
length_scale, real period):
matrix,92
(array[] real x1, array[] real x2,

```

        real sigma, real length_scale,
        real period): matrix,93
(vectors x, real sigma, real
    length_scale, real period):
    matrix,93
(vectors x1, vectors x2, real sigma,
    real length_scale, real pe-
    riod): matrix,93
gumbel
    sampling statement, 227
gumbel_cdf
    (reals y | reals mu, reals beta):
        real,227
gumbel_lccdf
    (reals y | reals mu, reals beta):
        real,227
gumbel_lcdf
    (reals y | reals mu, reals beta):
        real,227
gumbel_lpdf
    (reals y | reals mu, reals beta):
        real,227
gumbel_lupdf
    (reals y | reals mu, reals beta):
        real,227
gumbel_rng
    (reals mu, reals beta): R,227
head
    (array[] T sv, int n): array[] T,82
    (complex_row_vector rv, int n):
        complex_row_vector,118
    (complex_vector v, int n): com-
        plex_vector,118
    (row_vector rv, int n): row_vector,
        82
    (vector v, int n): vector,82
hmm_hidden_state_prob
    (matrix log_omega, matrix Gamma,
        vector rho): matrix,285
hmm_latent_rng
    (matrix log_omega, matrix Gamma,
        vector rho): array[] int,285
hmm_marginal
    (matrix log_omega, matrix Gamma,
        vector rho): real,284
hypergeometric
    sampling statement, 184
hypergeometric_lpmf
    (int n | int N, int a, int b):
        real,184
hypergeometric_lupmf
    (int n | int N, int a, int b):
        real,184
hypergeometric_rng
    (int N, int a, int2 b): int,184
hypot
    (T1 x, T2 y): R,28
    (real x, real y): real,28
identity_matrix_matrix
    (int k): matrix,79
inc_beta
    (real alpha, real beta, real x):
        real,32
int_step
    (int x): int,8
    (real x): int,8
integrate_1d
    (function integrand, real a, real
        b, array[] real theta, array[]
        real x_r, array[] int x_i):
        real,151
    (function integrand, real a, real
        b, array[] real theta, array[]
        real x_r, array[] int x_i, real
        relative_tolerance): real,151
integrate_ode
    (function ode, array[] real ini-
        tial_state, real initial_time,
        array[] real times, array[]
        real theta, array[] real x_r,
        array[] int x_i): array[, ]
        real,157
integrate_ode_adams
    (function ode, array[] real ini-
        tial_state, real initial_time,
        array[] real times, array[]
        real theta, data array[] real
        x_r, data array[] int x_i):
        array[, ] real,157
    (function ode, array[] real ini-
        tial_state, real initial_time,
        array[] real times, array[]
        real theta, data array[]
        real x_r, data array[] int
        x_i, data real rel_tol,
        data real abs_tol, data int
        max_num_steps): array[, ] real,
        158

```

integrate_ode_bdf
(function ode, array[] real initial_state, real initial_time, array[] real times, array[] real theta, data array[] real x_r, data array[] int x_i): array[,] real, 158
(function ode, array[] real initial_state, real initial_time, array[] real times, array[] real theta, data array[] real x_r, data array[] int x_i, data real rel_tol, data real abs_tol, data int max_num_steps): array[,] real, 158

integrate_ode_rk45
(function ode, array[] real initial_state, real initial_time, array[] real times, array[] real theta, array[] real x_r, array[] int x_i): array[,] real, 157
(function ode, array[] real initial_state, real initial_time, array[] real times, array[] real theta, array[] real x_r, array[] int x_i, real rel_tol, real abs_tol, int max_num_steps): array[,] real, 157

inv
(T x): R, 27

inv_chi_square
sampling statement, 232

inv_chi_square_cdf
(real y | reals nu): real, 232

inv_chi_square_lccdf
(real y | reals nu): real, 233

inv_chi_square_lcdf
(real y | reals nu): real, 233

inv_chi_square_lpdf
(real y | reals nu): real, 232

inv_chi_square_lupdf
(real y | reals nu): real, 232

inv_chi_square_rng
(real y | reals nu): R, 233

inv_cloglog
(T x): R, 30

inv_erfc
(T x): R, 30

inv_fft
(complex_vector u): complex_vector, 121

inv_fftf
(complex_matrix m): complex_matrix, 122

inv_gamma
sampling statement, 237

inv_gamma_cdf
(real y | reals alpha, reals beta): real, 237

inv_gamma_lccdf
(real y | reals alpha, reals beta): real, 237

inv_gamma_lcdf
(real y | reals alpha, reals beta): real, 237

inv_gamma_lpdf
(real y | reals alpha, reals beta): real, 237

inv_gamma_lupdf
(real y | reals alpha, reals beta): real, 237

inv_gamma_rng
(real alpha, reals beta): R, 237

inv_inc_beta
(real alpha, real beta, real p): real, 32

inv_logit
(T x): R, 30

inv_phi
(T x): R, 30

inv_sqrt
(T x): R, 27

inv_square
(T x): R, 27

inv_wishart
sampling statement, 279

inv_wishart_cholesky_lpdf
(matrix L_W | real nu, matrix L_S): real, 281

inv_wishart_lpdf
(matrix W | real nu, matrix Sigma): real, 279

inv_wishart_lupdf
(matrix L_W | real nu, matrix L_S): real, 281

(matrix W | real nu, matrix Sigma):
 real, 279

inv_wishart_rng
 (real nu, matrix L_S): matrix, 281
 (real nu, matrix Sigma): matrix, 280

inverse
 (matrix A): matrix, 97

inverse_spd
 (matrix A): matrix, 97

is_inf
 (real x): int, 22

is_nan
 (real x): int, 22

lambert_w0
 (T x): R, 41

lambert_wm1
 (T x): R, 41

lbeta
 (T1 x, T2 y): R, 32
 (real alpha, real beta): real, 32

lchoose
 (T1 x, T2 y): R, 37
 (real x, real y): real, 36

ldexp
 (T1 x, T2 y): R, 38
 (real x, int y): real, 38

lgamma
 (T x): R, 32

linspace_array
 (int n, data real lower, data real
 upper): array[] real, 79

linspace_int_array
 (int n, int lower, int upper):
 array[] real, 79

linspace_row_vector
 (int n, data real lower, data real
 upper): row_vector, 79

linspace_vector
 (int n, data real lower, data real
 upper): vector, 79

lkj_corr
 sampling statement, 275

lkj_corr_cholesky
 sampling statement, 276

lkj_corr_cholesky_lpdf
 (matrix L | real eta): real, 276

lkj_corr_cholesky_lupdf
 (matrix L | real eta): real, 276

lkj_corr_cholesky_rng
 (int K, real eta): matrix, 276

lkj_corr_lpdf
 (matrix y | real eta): real, 275

lkj_corr_lupdf
 (matrix y | real eta): real, 275

lkj_corr_rng
 (int K, real eta): matrix, 275

lmgamma
 (T1 x, T2 y): R, 33
 (int n, real x): real, 33

lmultiply
 (T1 x, T2 y): R, 38
 (real x, real y): real, 38

log
 (T x): R, 26
 (complex z): complex, 48

log10
 (): real, 16
 (T x): R, 27
 (complex z): complex, 48

log1m
 (T x): R, 39

log1m_exp
 (T x): R, 39

log1m_inv_logit
 (T x): R, 40

log1p
 (T x): R, 38

log1p_exp
 (T x): R, 39

log2
 (): real, 16
 (T x): R, 27

log_determinant
 (matrix A): real, 96

log_diff_exp
 (T1 x, T2 y): R, 39
 (real x, real y): real, 39

log_falling_factorial
 (real x, real n): real, 37

log_inv_logit
 (T x): R, 40

log_inv_logit_diff
 (T1 x, T2 y): R, 40

log_mix
 (T1 thetas, T2 lps): real, 40
 (real theta, real lp1, real lp2):
 real, 39

log_modified_bessel_first_kind

(T1 x, T2 y): R, 35
(real v, real z): real, 35

log_rising_factorial
(T1 x, T2 y): R, 37
(real x, real n): real, 37

log_softmax
(vector x): vector, 85

log_sum_exp
(T1 x, T2 y): R, 40
(array[] real x): real, 53
(matrix x): real, 74
(row_vector x): real, 73
(vector x): real, 73

logistic
sampling statement, 226

logistic_cdf
(reals y | reals mu, reals sigma):
real, 226

logistic_lccdf
(reals y | reals mu, reals sigma):
real, 226

logistic_lcdf
(reals y | reals mu, reals sigma):
real, 226

logistic_lpdf
(reals y | reals mu, reals sigma):
real, 226

logistic_lupdf
(reals y | reals mu, reals sigma):
real, 226

logistic_rng
(reals mu, reals sigma): R, 226

logit
(T x): R, 29

loglogistic
sampling statement, 241

loglogistic_cdf
(reals y | reals alpha, reals beta):
real, 242

loglogistic_lpdf
(reals y | reals alpha, reals beta):
real, 242

loglogistic_rng
(reals alpha, reals beta): R, 242

lognormal
sampling statement, 230

lognormal_cdf
(reals y | reals mu, reals sigma):
real, 230

lognormal_lccdf
(reals y | reals mu, reals sigma):
real, 231

lognormal_lcdf
(reals y | reals mu, reals sigma):
real, 230

lognormal_lpdf
(reals y | reals mu, reals sigma):
real, 230

lognormal_lupdf
(reals y | reals mu, reals sigma):
real, 230

lognormal_rng
(reals mu, reals sigma): R, 231

machine_precision
(): real, 17

map_rect
(F f, vector phi, array[] vector
theta, data array[,] real x_r,
data array[,] int x_i): vector,
155

matrix_exp
(matrix A): matrix, 95

matrix_exp_multiply
(matrix A, matrix B): matrix, 95

matrix_power
(matrix A, int B): matrix, 96

max
(array[] int x): int, 52
(array[] real x): real, 52
(int x, int y): int, 9
(matrix x): real, 74
(row_vector x): real, 74
(vector x): real, 74

mdivide_left_spd
(matrix A, matrix B): vector, 95
(matrix A, vector b): matrix, 95

mdivide_left_tri_low
(matrix A, matrix B): matrix, 94
(matrix A, vector b): vector, 94

mdivide_right_spd
(matrix B, matrix A): matrix, 95
(row_vector b, matrix A):
row_vector, 95

mdivide_right_tri_low
(matrix B, matrix A): matrix, 94
(row_vector b, matrix A):
row_vector, 94

mean

(array[] real x): real, [53](#)
 (matrix x): real, [75](#)
 (row_vector x): real, [75](#)
 (vector x): real, [75](#)

min

(array[] int x): int, [52](#)
 (array[] real x): real, [52](#)
 (int x, int y): int, [9](#)
 (matrix x): real, [74](#)
 (row_vector x): real, [74](#)
 (vector x): real, [74](#)

modified_bessel_first_kind

(T1 x, T2 y): R, [35](#)
 (int v, real z): real, [35](#)

modified_bessel_second_kind

(T1 x, T2 y): R, [36](#)
 (int v, real z): real, [36](#)

multi_gp

sampling statement, [264](#)

multi_gp_cholesky

sampling statement, [264](#)

multi_gp_cholesky_lpdf

(matrix y | matrix L, vector w):
real, [264](#)

multi_gp_cholesky_lupdf

(matrix y | matrix L, vector w):
real, [265](#)

multi_gp_lpdf

(matrix y | matrix Sigma, vector w):
real, [264](#)

multi_gp_lupdf

(matrix y | matrix Sigma, vector w):
real, [264](#)

multi_normal

sampling statement, [257](#)

multi_normal_cholesky

sampling statement, [261](#)

multi_normal_cholesky_lpdf

(row_vectors y | row_vectors mu,
matrix L): real, [262](#)

(row_vectors y | vectors mu, matrix
L): real, [262](#)

(vectors y | row_vectors mu, matrix
L): real, [261](#)

(vectors y | vectors mu, matrix L):
real, [261](#)

multi_normal_cholesky_lupdf

(row_vectors y | row_vectors mu,
matrix L): real, [262](#)

(row_vectors y | vectors mu, matrix
L): real, [262](#)

(vectors y | row_vectors mu, matrix
L): real, [261](#)

(vectors y | vectors mu, matrix L):
real, [261](#)

(row_vectors y | vectors mu, matrix
L): real, [262](#)

(vectors y | vectors mu, matrix L):
real, [262](#)

(vectors y | vectors mu, matrix L):
real, [261](#)

(vectors y | vectors mu, matrix L):
real, [263](#)

(vectors y | vectors mu, matrix L):
real, [261](#)

(vectors y | vectors mu, matrix L):
real, [263](#)

(vector mu, matrix L): vector, [262](#)

(vectors mu, matrix L): vectors, [263](#)

multi_normal_lpdf

(row_vectors y | row_vectors mu,
matrix Sigma): real, [258](#)

(row_vectors y | vectors mu, matrix
Sigma): real, [258](#)

(vectors y | row_vectors mu, matrix
Sigma): real, [258](#)

(vectors y | vectors mu, matrix
Sigma): real, [257](#)

multi_normal_lupdf

(row_vectors y | row_vectors mu,
matrix Sigma): real, [258](#)

(row_vectors y | vectors mu, matrix
Sigma): real, [258](#)

(vectors y | row_vectors mu, matrix
Sigma): real, [258](#)

(vectors y | vectors mu, matrix
Sigma): real, [257](#)

multi_normal_prec

sampling statement, [259](#)

multi_normal_prec_lpdf

(row_vectors y | row_vectors mu,
matrix Omega): real, [260](#)

(row_vectors y | vectors mu, matrix
Omega): real, [260](#)

(vectors y | row_vectors mu, matrix
Omega): real, [260](#)

(vectors y | vectors mu, matrix
Omega): real, [259](#)

multi_normal_prec_lupdf

(row_vectors y | row_vectors mu,
matrix Omega): real, [260](#)

(row_vectors y | vectors mu, matrix
Omega): real, [260](#)

(vectors y | row_vectors mu, matrix
Omega): real, [260](#)

(vectors y | vectors mu, matrix
Omega): real, [260](#)

(vectors y | vectors μ , matrix Ω): real, [260](#)

multi_normal_rng
 (row_vector μ , matrix Σ): vector, [259](#)
 (row_vectors μ , matrix Σ): vectors, [259](#)
 (vector μ , matrix Σ): vector, [258](#)
 (vectors μ , matrix Σ): vectors, [259](#)

multi_student_t
 sampling statement, [265](#)

multi_student_t_cholesky
 sampling statement, [267](#)

multi_student_t_cholesky_lpdf
 (vectors y | real ν , vectors μ , matrix L): real, [268](#)

multi_student_t_cholesky_lupdf
 (vectors y | real ν , vectors μ , matrix L): real, [268](#)

multi_student_t_cholesky_rng
 (real ν , row_vectors μ , matrix L): vector, [268](#)
 (real ν , vector μ , matrix L): vector, [268](#)

multi_student_t_lpdf
 (row_vectors y | real ν , row_vectors μ , matrix Σ): real, [266](#)
 (row_vectors y | real ν , vectors μ , matrix Σ): real, [266](#)
 (vectors y | real ν , row_vectors μ , matrix Σ): real, [265](#)
 (vectors y | real ν , vectors μ , matrix Σ): real, [265](#)

multi_student_t_lupdf
 (row_vectors y | real ν , row_vectors μ , matrix Σ): real, [266](#)
 (row_vectors y | real ν , vectors μ , matrix Σ): real, [266](#)
 (vectors y | real ν , row_vectors μ , matrix Σ): real, [266](#)
 (vectors y | real ν , vectors μ , matrix Σ): real, [265](#)

multi_student_t_rng
 (real ν , row_vector μ , matrix Σ): vector, [267](#)
 (real ν , row_vectors μ , matrix Σ): vectors, [267](#)
 (real ν , vector μ , matrix Σ): vector, [266](#)
 (real ν , vectors μ , matrix Σ): vectors, [267](#)

multinomial
 sampling statement, [206](#)

multinomial_logit
 sampling statement, [207](#)

multinomial_logit_lpmf
 (array[] int y | vector γ): real, [207](#)

multinomial_logit_lupmf
 (array[] int y | vector γ): real, [207](#)

multinomial_logit_rng
 (vector γ , int N): array[] int, [208](#)

multinomial_lpmf
 (array[] int y | vector θ): real, [206](#)

multinomial_lupmf
 (array[] int y | vector θ): real, [206](#)

multinomial_rng
 (vector θ , int N): array[] int, [206](#)

multiply_lower_tri_self_transpose
 (matrix x): matrix, [73](#)

neg_binomial
 sampling statement, [194](#)

neg_binomial_2
 sampling statement, [196](#)

neg_binomial_2_cdf
 (ints n | reals μ , reals ϕ): real, [196](#)

neg_binomial_2_lccdf
 (ints n | reals μ , reals ϕ): real, [196](#)

neg_binomial_2_lcdf
 (ints n | reals μ , reals ϕ): real, [196](#)

neg_binomial_2_log
 sampling statement, [197](#)

neg_binomial_2_log_glm
 sampling statement, [198](#)

neg_binomial_2_log_glm_lpmf
 (array[] int y | matrix x , real

alpha, vector beta, real phi):
 real, [199](#)
 (array[] int y | matrix x, vector
 alpha, vector beta, real phi):
 real, [200](#)
 (array[] int y | row_vector x, real
 alpha, vector beta, real phi):
 real, [199](#)
 (array[] int y | row_vector x, vec-
 tor alpha, vector beta, real
 phi): real, [199](#)
 (int y | matrix x, real alpha, vec-
 tor beta, real phi): real,
[198](#)
 (int y | matrix x, vector alpha,
 vector beta, real phi): real,
[198](#)
neg_binomial_2_log_glm_lupmf
 (array[] int y | matrix x, real
 alpha, vector beta, real phi):
 real, [200](#)
 (array[] int y | matrix x, vector
 alpha, vector beta, real phi):
 real, [200](#)
 (array[] int y | row_vector x, real
 alpha, vector beta, real phi):
 real, [199](#)
 (array[] int y | row_vector x, vec-
 tor alpha, vector beta, real
 phi): real, [199](#)
 (int y | matrix x, real alpha, vec-
 tor beta, real phi): real,
[198](#)
 (int y | matrix x, vector alpha,
 vector beta, real phi): real,
[199](#)
neg_binomial_2_log_lpmf
 (ints n | reals eta, reals phi):
 real, [197](#)
neg_binomial_2_log_lupmf
 (ints n | reals eta, reals phi):
 real, [197](#)
neg_binomial_2_log_rng
 (reals eta, reals phi): R, [197](#)
neg_binomial_2_lpmf
 (ints n | reals mu, reals phi):
 real, [196](#)
neg_binomial_2_lupmf
 (ints n | reals mu, reals phi):
 real, [196](#)
neg_binomial_2_rng
 (reals mu, reals phi): R, [197](#)
neg_binomial_cdf
 (ints n | reals alpha, reals beta):
 real, [195](#)
neg_binomial_lccdf
 (ints n | reals alpha, reals beta):
 real, [195](#)
neg_binomial_lcdf
 (ints n | reals alpha, reals beta):
 real, [195](#)
neg_binomial_lpmf
 (ints n | reals alpha, reals beta):
 real, [194](#)
neg_binomial_lupmf
 (ints n | reals alpha, reals beta):
 real, [194](#)
neg_binomial_rng
 (reals alpha, reals beta): R, [195](#)
negative_infinity
 (): real, [17](#)
norm
 (complex z): real, [47](#)
norm1
 (array[] real x): real, [54](#)
 (row_vector x): real, [54](#)
 (vector x): real, [54](#)
norm2
 (array[] real x): real, [55](#)
 (row_vector x): real, [55](#)
 (vector x): real, [54](#)
normal
 sampling statement, [212](#)
normal_cdf
 (reals y | reals mu, reals sigma):
 real, [212](#)
normal_id_glm
 sampling statement, [215](#)
normal_id_glm_lpdf
 (real y | matrix x, real alpha,
 vector beta, real sigma): real,
[215](#)
 (real y | matrix x, real alpha, vec-
 tor beta, vector sigma): real,
[216](#)
 (real y | matrix x, vector alpha,
 vector beta, real sigma): real,
[216](#)

```

(real y | matrix x, vector alpha,
  vector beta, vector sigma):
  real,216
(vector y | matrix x, real alpha,
  vector beta, real sigma): real,
  217
(vector y | matrix x, real alpha,
  vector beta, vector sigma):
  real,218
(vector y | matrix x, vector alpha,
  vector beta, real sigma): real,
  217
(vector y | matrix x, vector alpha,
  vector beta, vector sigma):
  real,218
(vector y | row_vector x, real al-
  pha, vector beta, real sigma):
  real,216
(vector y | row_vector x, vector al-
  pha, vector beta, real sigma):
  real,217
normal_id_glm_lupdf
(real y | matrix x, real alpha,
  vector beta, real sigma): real,
  215
(real y | matrix x, real alpha, vec-
  tor beta, vector sigma): real,
  216
(real y | matrix x, vector alpha,
  vector beta, real sigma): real,
  216
(real y | matrix x, vector alpha,
  vector beta, vector sigma):
  real,216
(vector y | matrix x, real alpha,
  vector beta, real sigma): real,
  217
(vector y | matrix x, real alpha,
  vector beta, vector sigma):
  real,218
(vector y | matrix x, vector alpha,
  vector beta, real sigma): real,
  218
(vector y | matrix x, vector alpha,
  vector beta, vector sigma):
  real,218
(vector y | row_vector x, real al-
  pha, vector beta, real sigma):
  real,217
(vector y | row_vector x, vector al-
  pha, vector beta, real sigma):
  real,217
normal_lccdf
(reals y | reals mu, reals sigma):
  real,213
normal_lcdf
(reals y | reals mu, reals sigma):
  real,212
normal_lpdf
(reals y | reals mu, reals sigma):
  real,212
normal_lupdf
(reals y | reals mu, reals sigma):
  real,212
normal_rng
(reals mu, reals sigma): R,213
not_a_number
(): real,17
num_elements
(array[] T x): int,57
(complex_matrix x): int,104
(complex_row_vector x): int,104
(complex_vector x): int,104
(matrix x): int,62
(row_vector x): int,62
(vector x): int,62
ode_adams
(function ode, vector initial_state,
  real initial_time, array[] real
  times, ...): array[] vector,
  144
ode_adams_tol
(function ode, vector initial_state,
  real initial_time, array[]
  real times, data real rel_tol,
  data real abs_tol, data int
  max_num_steps, ...): array[]
  vector,144
ode_bdf
(function ode, vector initial_state,
  real initial_time, array[] real
  times, ...): array[] vector,
  144
ode_bdf_tol
(function ode, vector initial_state,
  real initial_time, ar-
  ray[] real times, data real
  rel_tol, data real abs_tol, int

```

max_num_steps, ...): array[]
 vector, [144](#)

(function ode, vector initial_state,
 real initial_time, ar-
 ray[] real times, data real
 rel_tol_forward, data vector
 abs_tol_forward, data real
 rel_tol_backward, data vec-
 tor abs_tol_backward, data
 real rel_tol_quadrature, data
 real abs_tol_quadrature,
 int max_num_steps, int
 num_steps_between_checkpoints,
 int interpolation_polynomial,
 int solver_forward, int
 solver_backward, ...): ar-
 ray[] vector, [145](#)

ode_ckrk
 (function ode, array[] real ini-
 tial_state, real initial_time,
 array[] real times, ...): ar-
 ray[] vector, [143](#)

ode_ckrk_tol
 (function ode, vector initial_state,
 real initial_time, ar-
 ray[] real times, data real
 rel_tol, data real abs_tol, int
 max_num_steps, ...): array[]
 vector, [144](#)

ode_rk45
 (function ode, array[] real ini-
 tial_state, real initial_time,
 array[] real times, ...): ar-
 ray[] vector, [143](#)

ode_rk45_tol
 (function ode, vector initial_state,
 real initial_time, ar-
 ray[] real times, data real
 rel_tol, data real abs_tol, int
 max_num_steps, ...): array[]
 vector, [143](#)

one_hot_array
 (int n, int k): array[] real, [80](#)

one_hot_int_array
 (int n, int k): array[] int, [79](#)

one_hot_row_vector
 (int n, int k): row_vector, [80](#)

one_hot_vector
 (int n, int k): vector, [80](#)

ones_array
 (int n): array[] real, [80](#)

ones_int_array
 (int n): array[] int, [80](#)

ones_row_vector
 (int n): row_vector, [80](#)

ones_vector
 (int n): vector, [80](#)

operator/
 (complex_matrix B, complex_matrix
 A): complex_matrix, [123](#)
 (complex_row_vector b, com-
 plex_matrix A): com-
 plex_row_vector, [122](#)

operator_add
 (complex x, complex y): complex, [44](#)
 (complex x, complex_matrix y):
 complex_matrix, [108](#)
 (complex x, complex_vector y):
 complex_vector, [108](#)
 (complex x, row_complex_vector y):
 row_complex_vector, [108](#)
 (complex_matrix x, complex y):
 complex_matrix, [108](#)
 (complex_matrix x, complex_matrix
 y): complex_matrix, [106](#)
 (complex_vector x, complex y):
 complex_vector, [108](#)
 (complex_vector x, complex_vector
 y): complex_vector, [106](#)
 (int x): int, [8](#)
 (int x, int y): int, [7](#)
 (matrix x, matrix y): matrix, [64](#)
 (matrix x, real y): matrix, [66](#)
 (real x): real, [23](#)
 (real x, matrix y): matrix, [66](#)
 (real x, real y): real, [22](#)
 (real x, row_vector y): row_vector,
[66](#)
 (real x, vector y): vector, [65](#)
 (row_complex_vector x, complex y):
 row_complex_vector, [108](#)
 (row_complex_vector x,
 row_complex_vector y):
 row_complex_vector, [106](#)
 (row_vector x, real y): row_vector,
[65](#)
 (row_vector x, row_vector y):
 row_vector, [64](#)

(vector x, real y): vector, 65
 (vector x, vector y): vector, 64

operator_add
 (complex z): complex, 44

operator_assign
 (complex x, complex y): void, 46

operator_compound_add
 (T x, U y): void, 138
 (complex x, complex y): void, 46

operator_compound_divide
 (T x, U y): void, 139
 (complex x, complex y): void, 46

operator_compound_elt_divide
 (T x, U y): void, 139

operator_compound_elt_multiply
 (T x, U y): void, 139

operator_compound_multiply
 (T x, U y): void, 138

operator_compound_multiply
 (complex x, complex y): void, 46

operator_compound_subtract
 (T x, U y): void, 138
 (complex x, complex y): void, 46

operator_divide
 (complex x, complex y): complex, 44
 (complex_matrix x, complex y):
 complex_matrix, 109
 (complex_vector x, complex y):
 complex_vector, 109
 (int x, int y): int, 7
 (matrix B, matrix A): matrix, 93
 (matrix x, real y): matrix, 67
 (real x, real y): real, 23
 (row_complex_vector x, complex y):
 row_complex_vector, 109
 (row_vector b, matrix A):
 row_vector, 93
 (row_vector x, real y): row_vector,
 67
 (vector x, real y): vector, 66

operator_elt_divide
 (complex x, complex_matrix y):
 complex_matrix, 111
 (complex x, complex_row_vector y):
 complex_row_vector, 110
 (complex x, complex_vector y):
 complex_vector, 110
 (complex_matrix x, complex y):
 complex_matrix, 111

(complex_matrix x, complex_matrix
 y): complex_matrix, 111
 (complex_row_vector x, complex y):
 complex_row_vector, 110
 (complex_row_vector x, com-
 plex_row_vector y): com-
 plex_row_vector, 110
 (complex_vector x, complex y):
 complex_vector, 110
 (complex_vector x, complex_vector
 y): complex_vector, 110
 (matrix x, matrix y): matrix, 68
 (real x, matrix y): matrix, 68
 (real x, row_vector y): row_vector,
 68
 (real x, vector y): vector, 68
 (row_vector x, real y): row_vector,
 68
 (row_vector x, row_vector y):
 row_vector, 68
 (vector x, real y): vector, 68
 (vector x, vector y): vector, 68

operator_elt_multiply
 (complex_matrix x, complex_matrix
 y): complex_matrix, 110
 (complex_row_vector x, com-
 plex_row_vector y): com-
 plex_row_vector, 110
 (complex_vector x, complex_vector
 y): complex_vector, 110
 (matrix x, matrix y): matrix, 68
 (row_vector x, row_vector y):
 row_vector, 67
 (vector x, vector y): vector, 67

operator_elt_pow
 (complex_matrix x, complex y):
 matrix, 112
 (complex_matrix x, complex_matrix
 y): matrix, 111
 (complex x, complex_matrix y):
 matrix, 112
 (complex x, complex_row_vector y):
 complex_row_vector, 111
 (complex x, complex_vector y):
 vector, 111
 (complex_row_vector x, complex y):
 complex_row_vector, 111
 (complex_row_vector x, com-

plex_row_vector y): complex_row_vector, 111
 (complex_vector x, complex y): vector, 111
 (complex_vector x, complex_vector y): vector, 111
 (matrix x, matrix y): matrix, 69
 (matrix x, real y): matrix, 69
 (real x, matrix y): matrix, 69
 (real x, row_vector y): row_vector, 69
 (real x, vector y): vector, 69
 (row_vector x, real y): row_vector, 69
 (row_vector x, row_vector y): row_vector, 69
 (vector x, real y): vector, 69
 (vector x, vector y): vector, 69

operator_int_divide
 (int x, int y): int, 7

operator_left_div
 (matrix A, matrix B): matrix, 94
 (matrix A, vector b): vector, 93

operator_logical_and
 (int x, int y): int, 20
 (real x, real y): int, 20

operator_logical_equal
 (complex x, complex y): int, 45
 (int x, int y): int, 19
 (real x, real y): int, 19

operator_logical_greater_than
 (int x, int y): int, 18
 (real x, real y): int, 18

operator_logical_greater_than_equal
 (int x, int y): int, 19
 (real x, real y): int, 19

operator_logical_less_than
 (int x, int y): int, 18
 (real x, real y): int, 18

operator_logical_less_than_equal
 (int x, int y): int, 18
 (real x, real y): int, 18

operator_logical_not_equal
 (complex x, complex y): int, 45
 (int x, int y): int, 19
 (real x, real y): int, 19

operator_logical_or
 (int x, int y): int, 21
 (real x, real y): int, 21

operator_mod
 (int x, int y): int, 8

operator_multiply
 (complex x, complex y): complex, 44
 (complex x, complex_matrix y): complex_matrix, 106
 (complex x, complex_vector y): complex_vector, 106
 (complex x, row_complex_vector y): row_complex_vector, 106
 (complex_matrix x, complex y): complex_matrix, 107
 (complex_matrix x, complex_matrix y): complex_matrix, 107
 (complex_matrix x, complex_vector y): complex_vector, 107
 (complex_vector x, complex y): complex_vector, 107
 (complex_vector x, row_complex_vector y): complex_vector, 107
 (int x, int y): int, 7
 (matrix x, matrix y): matrix, 65
 (matrix x, real y): matrix, 65
 (matrix x, vector y): vector, 65
 (real x, matrix y): matrix, 64
 (real x, real y): real, 22
 (real x, row_vector y): row_vector, 64
 (real x, vector y): vector, 64
 (row_complex_vector x, complex y): row_complex_vector, 107
 (row_complex_vector x, complex_matrix y): row_complex_vector, 107
 (row_complex_vector x, complex_vector y): complex_vector, 107
 (row_vector x, matrix y): row_vector, 65
 (row_vector x, real y): row_vector, 65
 (row_vector x, vector y): real, 65
 (vector x, real y): vector, 64
 (vector x, row_vector y): matrix, 65

operator_negation
 (int x): int, 20
 (real x): int, 20

operator_pow
 (complex x, complex y): complex, 45

(real x, real y): real, 23

operator_subtract

(T x): T, 8, 23, 44, 63, 105

(complex x, complex y): complex, 44

(complex x, complex_matrix y):
complex_matrix, 109

(complex x, complex_vector y):
complex_vector, 108

(complex x, row_complex_vector y):
row_complex_vector, 108

(complex_matrix x): complex_matrix,
105

(complex_matrix x, complex y):
complex_matrix, 109

(complex_matrix x, complex_matrix
y): complex_matrix, 106

(complex_vector x): complex_vector,
105

(complex_vector x, complex y):
complex_vector, 108

(complex_vector x, complex_vector
y): complex_vector, 106

(int x): int, 8

(int x, int y): int, 7

(matrix x): matrix, 63

(matrix x, matrix y): matrix, 64

(matrix x, real y): matrix, 66

(real x): real, 23

(real x, matrix y): matrix, 66

(real x, real y): real, 22

(real x, row_vector y): row_vector,
66

(real x, vector y): vector, 66

(row_complex_vector x):
row_complex_vector, 105

(row_complex_vector x, complex y):
row_complex_vector, 108

(row_complex_vector x,
row_complex_vector y):
row_complex_vector, 106

(row_vector x): row_vector, 63

(row_vector x, real y): row_vector,
66

(row_vector x, row_vector y):
row_vector, 64

(vector x): vector, 63

(vector x, real y): vector, 66

(vector x, vector y): vector, 64

operator_subtract

(complex z): complex, 44

operator_transpose

(complex_matrix x): complex_matrix,
109

(complex_vector x):
row_complex_vector, 109

(matrix x): matrix, 67

(row_complex_vector x): com-
plex_vector, 109

(row_vector x): vector, 67

(vector x): row_vector, 67

ordered_logistic
sampling statement, 189

ordered_logistic_glm
sampling statement, 191

ordered_logistic_glm_lpmf

(array[] int y | matrix x, vector
beta, vector c): real, 192

(array[] int y | row_vector x, vec-
tor beta, vector c): real,
191

(int y | matrix x, vector beta,
vector c): real, 191

(int y | row_vector x, vector beta,
vector c): real, 191

ordered_logistic_glm_lupmf

(array[] int y | matrix x, vector
beta, vector c): real, 192

(array[] int y | row_vector x, vec-
tor beta, vector c): real,
191

(int y | matrix x, vector beta,
vector c): real, 191

(int y | row_vector x, vector beta,
vector c): real, 191

ordered_logistic_lpmf
(ints k | vector eta, vectors c):
real, 190

ordered_logistic_lupmf
(ints k | vector eta, vectors c):
real, 190

ordered_logistic_rng
(real eta, vector c): int, 190

ordered_probit
sampling statement, 192

ordered_probit_lpmf
(ints k | real eta, vectors c):
real, 193

(ints k | vector eta, vectors c):

```

        real, 192
ordered_probit_lupmf
    (ints k | real eta, vectors c):
        real, 193
    (ints k | vector eta, vectors c):
        real, 193
ordered_probit_rng
    (real eta, vector c): int, 193
owens_t
    (T1 x, T2 y): R, 31
    (real h, real a): real, 31
pareto
    sampling statement, 243
pareto_cdf
    (reals y | reals y_min, reals al-
        pha): real, 243
pareto_lccdf
    (reals y | reals y_min, reals al-
        pha): real, 244
pareto_lcdf
    (reals y | reals y_min, reals al-
        pha): real, 243
pareto_lpdf
    (reals y | reals y_min, reals al-
        pha): real, 243
pareto_lupdf
    (reals y | reals y_min, reals al-
        pha): real, 243
pareto_rng
    (reals y_min, reals alpha): R, 244
pareto_type_2
    sampling statement, 244
pareto_type_2_cdf
    (reals y | reals mu, reals lambda,
        reals alpha): real, 245
pareto_type_2_lccdf
    (reals y | reals mu, reals lambda,
        reals alpha): real, 245
pareto_type_2_lcdf
    (reals y | reals mu, reals lambda,
        reals alpha): real, 245
pareto_type_2_lpdf
    (reals y | reals mu, reals lambda,
        reals alpha): real, 244
pareto_type_2_lupdf
    (reals y | reals mu, reals lambda,
        reals alpha): real, 244
pareto_type_2_rng
    (reals mu, reals lambda, reals
        alpha): R, 245
phi
    (T x): R, 30
phi_approx
    (T x): R, 30
pi
    (): real, 16
poisson
    sampling statement, 200
poisson_cdf
    (ints n | reals lambda): real, 201
poisson_lccdf
    (ints n | reals lambda): real, 201
poisson_lcdf
    (ints n | reals lambda): real, 201
poisson_log
    sampling statement, 202
poisson_log_glm
    sampling statement, 202
poisson_log_glm_lupmf
    (array[] int y | matrix x, real
        alpha, vector beta): real, 204
    (array[] int y | matrix x, vector
        alpha, vector beta): real, 204
    (array[] int y | row_vector x, real
        alpha, vector beta): real, 203
    (array[] int y | row_vector x, vec-
        tor alpha, vector beta): real,
        203
    (int y | matrix x, real alpha,
        vector beta): real, 202
    (int y | matrix x, vector alpha,
        vector beta): real, 203
poisson_log_glm_lupmf
    (array[] int y | matrix x, real
        alpha, vector beta): real, 204
    (array[] int y | matrix x, vector
        alpha, vector beta): real, 204
    (array[] int y | row_vector x, real
        alpha, vector beta): real, 203
    (array[] int y | row_vector x, vec-
        tor alpha, vector beta): real,
        203
    (int y | matrix x, real alpha,
        vector beta): real, 203
    (int y | matrix x, vector alpha,
        vector beta): real, 203
poisson_log_lupmf
    (ints n | reals alpha): real, 202

```

poisson_log_lupmf (ints n | reals alpha): real, 202
poisson_log_rng (reals alpha): R, 202
poisson_lpmf (ints n | reals lambda): real, 200
poisson_lupmf (ints n | reals lambda): real, 200
poisson_rng (reals lambda): R, 201
polar (real r, real theta): complex, 48
positive_infinity (): real, 17
pow (T1 x, T2 y): R, 27
(T1 x, T2 y): Z, 48
(complex x, complex y): complex, 48
(real x, real y): real, 27
print (T1 x1, ..., TN xN): void, 4
prod (array[] int x): real, 53
(array[] real x): real, 53
(complex_matrix x): complex, 115
(complex_row_vector x): complex, 115
(complex_vector x): complex, 115
(matrix x): real, 75
(row_vector x): real, 75
(vector x): real, 75
proj (complex z): complex, 47
qr (matrix A): tuple(matrix, matrix), 100
qr_q (matrix A): matrix, 99
qr_r (matrix A): matrix, 99
qr_thin (matrix A): tuple(matrix, matrix), 99
qr_thin_q (matrix A): matrix, 99
qr_thin_r (matrix A): matrix, 99
quad_form (matrix A, matrix B): matrix, 72
(matrix A, vector B): real, 72
quad_form_diag (matrix m, row_vector rv): matrix, 72
(matrix m, vector v): matrix, 72
quad_form_sym (matrix A, matrix B): matrix, 72
(matrix A, vector B): real, 72
quantile (data array[] real x, data array[] real p): real, 56
(data array[] real x, data real p): real, 56
(data row_vector x, data array[] real p): real, 77
(data row_vector x, data real p): real, 76
(data vector x, data array[] real p): real, 76
(data vector x, data real p): real, 76
rank (array[] int v, int s): int, 60
(array[] real v, int s): int, 60
(row_vector v, int s): int, 102
(vector v, int s): int, 102
rayleigh sampling statement, 240
rayleigh_cdf (real y | real sigma): real, 241
rayleigh_lccdf (real y | real sigma): real, 241
rayleigh_lcdf (real y | real sigma): real, 241
rayleigh_lpdf (reals y | reals sigma): real, 240
rayleigh_lupdf (reals y | reals sigma): real, 240
rayleigh_rng (reals sigma): R, 241
reduce_sum (F f, array[] T x, int grainsize, T1 s1, T2 s2, ...): real, 153
reject (T1 x1, ..., TN xN): void, 4
rep_array (T x, int k, int m, int n): array[,], T, 58
(T x, int m, int n): array[,], T, 57
(T x, int n): array[] T, 57
rep_matrix

```

    (complex z, int m, int n): complex_matrix, 116
    (complex_row_vector rv, int m): complex_matrix, 116
    (complex_vector v, int n): complex_matrix, 116
    (real x, int m, int n): matrix, 77
    (row_vector rv, int m): matrix, 77
    (vector v, int n): matrix, 77
rep_row_vector
    (complex z, int n): complex_row_vector, 116
    (real x, int n): row_vector, 77
rep_vector
    (complex z, int m): complex_vector, 116
    (real x, int m): vector, 77
reverse
    (array[] T v): array[] T, 61
    (complex_row_vector v): complex_row_vector, 126
    (complex_vector v): complex_vector, 126
    (row_vector v): row_vector, 102
    (vector v): vector, 102
rising_factorial
    (T1 x, T2 y): R, 37
    (real x, int n): real, 37
round
    (T x): R, 26
row
    (complex_matrix x, int m): complex_row_vector, 117
    (matrix x, int m): row_vector, 81
rows
    (complex_matrix x): int, 104
    (complex_row_vector x): int, 104
    (complex_vector x): int, 104
    (matrix x): int, 62
    (row_vector x): int, 62
    (vector x): int, 62
rows_dot_product
    (complex_matrix x, complex_matrix y): complex_vector, 113
    (complex_row_vector x, complex_row_vector y): complex_vector, 113
    (complex_vector x, complex_vector y): complex_vector, 113
    (matrix x, matrix y): vector, 70
    (row_vector x, row_vector y): vector, 70
    (vector x, vector y): vector, 70
rows_dot_self
    (complex_matrix x): complex_vector, 114
    (complex_row_vector x): complex_vector, 113
    (complex_vector x): complex_vector, 113
    (matrix x): vector, 71
    (row_vector x): vector, 71
    (vector x): vector, 71
scale_matrix_exp_multiply
    (real t, matrix A, matrix B): matrix, 96
scaled_inv_chi_square
    sampling statement, 233
scaled_inv_chi_square_cdf
    (reals y | reals nu, reals sigma): real, 234
scaled_inv_chi_square_lccdf
    (reals y | reals nu, reals sigma): real, 234
scaled_inv_chi_square_lcdf
    (reals y | reals nu, reals sigma): real, 234
scaled_inv_chi_square_lpdf
    (reals y | reals nu, reals sigma): real, 233
scaled_inv_chi_square_lupdf
    (reals y | reals nu, reals sigma): real, 234
scaled_inv_chi_square_rng
    (reals nu, reals sigma): R, 234
sd
    (array[] real x): real, 54
    (matrix x): real, 76
    (row_vector x): real, 76
    (vector x): real, 76
segment
    (array[] T sv, int i, int n): array[] T, 83
    (complex_row_vector rv, int i, int n): complex_row_vector, 119
    (complex_vector v, int i, int n): complex_vector, 118
    (row_vector rv, int i, int n):

```

row_vector, [83](#)
 (vector v, int i, int n): vector, [83](#)

sin
 (T x): R, [28](#)
 (complex z): complex, [49](#)

singular_values
 (complex_matrix A): vector, [124](#)
 (matrix A): vector, [100](#)

sinh
 (T x): R, [29](#)
 (complex z): complex, [50](#)

size
 (array[] T x): int, [57](#)
 (complex_matrix x): int, [105](#)
 (complex_row_vector x): int, [105](#)
 (complex_vector x): int, [105](#)
 (int x): int, [9](#)
 (matrix x): int, [63](#)
 (real x): int, [9](#)
 (row_vector x): int, [63](#)
 (vector x): int, [63](#)

skew_double_exponential
 sampling statement, [228](#)

skew_double_exponential_cdf
 (reals y | reals mu, reals sigma,
 reals tau): real, [228](#)

skew_double_exponential_lcdf
 (reals y | reals mu, reals sigma,
 reals tau): real, [229](#)

skew_double_exponential_lpdf
 (reals y | reals mu, reals sigma,
 reals tau): real, [228](#)

skew_double_exponential_lupdf
 (reals y | reals mu, reals sigma,
 reals tau): real, [228](#)

skew_double_exponential_rng
 (reals mu, reals sigma, reals tau):
 R, [229](#)

skew_normal
 sampling statement, [220](#)

skew_normal_cdf
 (reals y | reals xi, reals omega,
 reals alpha): real, [220](#)

skew_normal_lcdf
 (reals y | reals xi, reals omega,
 reals alpha): real, [221](#)

skew_normal_lpdf
 (reals y | reals xi, reals omega,
 reals alpha): real, [220](#)

skew_normal_lupdf
 (reals y | reals xi, reals omega,
 reals alpha): real, [220](#)

skew_normal_rng
 (reals xi, reals omega, real alpha):
 R, [221](#)

softmax
 (vector x): vector, [85](#)

sort_asc
 (array[] int v): array[] int, [60](#)
 (array[] real v): array[] real, [60](#)
 (row_vector v): row_vector, [101](#)
 (vector v): vector, [101](#)

sort_desc
 (array[] int v): array[] int, [60](#)
 (array[] real v): array[] real, [60](#)
 (row_vector v): row_vector, [101](#)
 (vector v): vector, [101](#)

sort_indices_asc
 (array[] int v): array[] int, [60](#)
 (array[] real v): array[] int, [60](#)
 (row_vector v): array[] int, [102](#)
 (vector v): array[] int, [101](#)

sort_indices_desc
 (array[] int v): array[] int, [60](#)
 (array[] real v): array[] int, [60](#)
 (row_vector v): array[] int, [102](#)
 (vector v): array[] int, [102](#)

sqrt
 (T x): R, [26](#)
 (complex x): complex, [49](#)

sqrt2
 (): real, [16](#)

square
 (T x): R, [26](#)

squared_distance
 (row_vector x, row_vector y): real,
[56](#)
 (row_vector x, vector y): real, [56](#)
 (vector x, row_vector y): real, [56](#)
 (vector x, vector y): real, [55](#)

std_normal
 sampling statement, [214](#)

std_normal_cdf
 (reals y): real, 214

std_normal_lccdf
 (reals y): real, 214

std_normal_lcdf
 (reals y): real, 214

std_normal_log_qf
 (T x): R, 214

std_normal_lpdf
 (reals y): real, 214

std_normal_lupdf
 (reals y): real, 214

std_normal_qf
 (T x): R, 214

std_normal_rng
 (): real, 215

step
 (real x): real, 21

student_t
 sampling statement, 221

student_t_cdf
 (reals y | reals nu, reals mu, reals sigma): real, 222

student_t_lccdf
 (reals y | reals nu, reals mu, reals sigma): real, 222

student_t_lcdf
 (reals y | reals nu, reals mu, reals sigma): real, 222

student_t_lpdf
 (reals y | reals nu, reals mu, reals sigma): real, 222

student_t_lupdf
 (reals y | reals nu, reals mu, reals sigma): real, 222

student_t_rng
 (reals nu, reals mu, reals sigma): R, 222

sub_col
 (complex_matrix x, int i, int j, int n_rows): complex_vector, 118
 (matrix x, int i, int j, int n_rows): vector, 82

sub_row
 (complex_matrix x, int i, int j, int n_cols): complex_row_vector, 118
 (matrix x, int i, int j, int n_cols): row_vector, 82

sum
 (array[] complex x): complex, 52
 (array[] int x): int, 52
 (array[] real x): real, 52
 (complex_matrix x): complex, 115
 (complex_row_vector x): complex, 114
 (complex_vector x): complex, 114
 (matrix x): real, 75
 (row_vector x): real, 74
 (vector x): real, 74

svd
 (complex_matrix A): tuple(complex_matrix, vector, complex_matrix), 124
 (matrix A): tuple(matrix, vector, matrix), 101

svd_U
 (complex_matrix A): complex_matrix, 124
 (matrix A): matrix, 101

svd_V
 (complex_matrix A): complex_matrix, 124
 (matrix A): matrix, 101

symmetrize_from_lower_tri
 (complex_matrix A): complex_matrix, 117
 (matrix A): matrix, 78

tail
 (array[] T sv, int n): array[] T, 82
 (complex_row_vector rv, int n): complex_row_vector, 118
 (complex_vector v, int n): complex_vector, 118
 (row_vector rv, int n): row_vector, 82
 (vector v, int n): vector, 82

tan
 (T x): R, 28
 (complex z): complex, 49

tanh
 (T x): R, 29
 (complex z): complex, 50

target
 (): real, 17

tcrossprod
 (matrix x): matrix, 71

tgamma
 (T x): R, 32

to_array_1d
(array[...] complex a): array[] complex, 136
(array[...] int a): array[] int, 136
(array[...] real a): array[] real, 136
(complex_matrix m): array[] complex, 136
(complex_row_vector v): array[] complex, 136
(complex_vector v): array[] complex, 136
(matrix m): array[] real, 136
(row_vector v): array[] real, 136
(vector v): array[] real, 136

to_array_2d
(complex_matrix m): array[,] complex, 135
(matrix m): array[,] real, 135

to_complex
(): complex, 43
(T1 re, T2 im): Z, 43
(real re): complex, 43
(real re, real im): complex, 43

to_int
(data R x): I, 10
(data real x): int, 10

to_matrix
(array[,] complex a): complex_matrix, 133
(array[,] int a): matrix, 133
(array[,] real a): matrix, 133
(array[] complex a, int m, int n): complex_matrix, 132
(array[] complex a, int m, int n, int col_major): complex_matrix, 133
(array[] complex_row_vector vs): complex_matrix, 133
(array[] int a, int m, int n): matrix, 132
(array[] int a, int m, int n, int col_major): matrix, 132
(array[] real a, int m, int n): matrix, 132
(array[] real a, int m, int n, int col_major): matrix, 132
(array[] row_vector vs): matrix, 133

(complex_matrix A, int m, int n, int col_major): complex_matrix, 131
(complex_matrix M, int m, int n): complex_matrix, 130
(complex_matrix m): complex_matrix, 130
(complex_row_vector v): complex_matrix, 130
(complex_row_vector v, int m, int n): complex_matrix, 131
(complex_row_vector v, int m, int n, int col_major): complex_matrix, 132
(complex_vector v): complex_matrix, 130
(complex_vector v, int m, int n): complex_matrix, 131
(complex_vector v, int m, int n, int col_major): complex_matrix, 131
(matrix A, int m, int n, int col_major): matrix, 131
(matrix M, int m, int n): matrix, 130
(matrix m): matrix, 130
(row_vector v): matrix, 130
(row_vector v, int m, int n): matrix, 131
(row_vector v, int m, int n, int col_major): matrix, 132
(vector v): matrix, 130
(vector v, int m, int n): matrix, 131
(vector v, int m, int n, int col_major): matrix, 131

to_row_vector
(array[] complex a): complex_row_vector, 135
(array[] int a): row_vector, 135
(array[] real a): row_vector, 135
(complex_matrix m): complex_row_vector, 134
(complex_row_vector v): complex_row_vector, 135
(complex_vector v): complex_row_vector, 135
(matrix m): row_vector, 134
(row_vector v): row_vector, 135
(vector v): row_vector, 135

to_vector

(array[] complex a): complex_vector, [134](#)
 (array[] int a): vector, [134](#)
 (array[] real a): vector, [134](#)
 (complex_matrix m): complex_vector, [134](#)
 (complex_row_vector v): complex_vector, [134](#)
 (complex_vector v): complex_vector, [134](#)
 (matrix m): vector, [133](#)
 (row_vector v): vector, [134](#)
 (vector v): vector, [134](#)

trace
 (complex_matrix A): complex, [123](#)
 (matrix A): real, [96](#)

trace_gen_quad_form
 (matrix D, matrix A, matrix B): real, [72](#)

trace_quad_form
 (matrix A, matrix B): real, [72](#)

trigamma
 (T x): R, [33](#)

trunc
 (T x): R, [26](#)

uniform
 sampling statement, [255](#)

uniform_cdf
 (reals y | reals alpha, reals beta): real, [255](#)

uniform_lccdf
 (reals y | reals alpha, reals beta): real, [256](#)

uniform_lcdf
 (reals y | reals alpha, reals beta): real, [255](#)

uniform_lpdf
 (reals y | reals alpha, reals beta): real, [255](#)

uniform_lupdf
 (reals y | reals alpha, reals beta): real, [255](#)

uniform_rng
 (reals alpha, reals beta): R, [256](#)

uniform_simplex
 (int n): vector, [81](#)

variance
 (array[] real x): real, [53](#)
 (matrix x): real, [76](#)
 (row_vector x): real, [75](#)
 (vector x): real, [75](#)

von_mises
 sampling statement, [252](#)

von_mises_cdf
 (reals y | reals mu, reals kappa): real, [253](#)

von_mises_lcdf
 (reals y | reals mu, reals kappa): real, [253](#)

von_mises_lpdf
 (reals y | reals mu, reals kappa): real, [252](#)

von_mises_lupdf
 (reals y | reals mu, reals kappa): real, [253](#)

von_mises_rng
 (reals mu, reals kappa): R, [253](#)

weibull
 sampling statement, [238](#)

weibull_cdf
 (reals y | reals alpha, reals sigma): real, [238](#)

weibull_lccdf
 (reals y | reals alpha, reals sigma): real, [239](#)

weibull_lcdf
 (reals y | reals alpha, reals sigma): real, [238](#)

weibull_lpdf
 (reals y | reals alpha, reals sigma): real, [238](#)

weibull_lupdf
 (reals y | reals alpha, reals sigma): real, [238](#)

weibull_rng
 (reals alpha, reals sigma): R, [239](#)

wiener
 sampling statement, [247](#)

wiener_lpdf
 (real y | real alpha, real tau, real beta, real delta, real var_delta): real, [247](#)
 (real y | real alpha, real tau, real beta, real delta, real var_delta, real var_beta, real var_tau): real, [247](#)
 (reals y | reals alpha, reals tau, reals beta, reals delta): real,

247

wiener_lupdf

(real y | real alpha, real tau,
real beta, real delta, real
var_delta): real,248
(real y | real alpha, real tau,
real beta, real delta, real
var_delta, real var_beta, real
var_tau): real,248
(reals y | reals alpha, reals tau,
reals beta, reals delta): real,
248

wishart

sampling statement,277

wishart_cholesky_lpdf

(matrix L_W | real nu, matrix L_S):
real,278

wishart_lpdf

(matrix W | real nu, matrix Sigma):
real,277

wishart_lupdf

(matrix L_W | real nu, matrix L_S):
real,279
(matrix W | real nu, matrix Sigma):
real,277

wishart_rng

(real nu, matrix L_S): matrix,279
(real nu, matrix Sigma): matrix,278

zeros_array

(int n): array[] real,80

zeros_int_array

(int n): array[] int,80

zeros_row_vector

(int n): row_vector,81

zeros_vector

(int n): vector,80